

Resumo

CESEP -2011 – 4th International conference on carbon for energy storage conversion environment protection, “Microporosity evaluation of active carbon from polish lignite by the use of ethanol” from 25 – 29 September 2011, Vichy – France. A. Albiniak, E. Broniek, M. Jasieńko-Hałat, P.J.M. Carrott, I.P.P. Cansado, P.A.M. Mourão.

Microporous activated carbons prepared by KOH chemical activation or steam activation from lignite were characterised by adsorption of N₂ at 77 K and CO₂ at 298 K. Subsequently, the adsorption of ethanol was carried out and complemented by adsorption of benzene and cyclohexane. The isotherm analysis included application of the *as* method using ethanol reference data obtained here by also studying non-porous carbon blacks. The work confirmed that ethanol is an experimentally convenient adsorptive to use and leads to results in overall agreement with those obtained using other probe molecules. Of particular interest was the observation that ethanol can gain access to the whole microporosity even in the case of samples containing constricted micropore entrances. It was also possible to show that certain furnace carbon blacks contain intrinsic microporosity which is more difficult to unambiguously detect by adsorption of N₂ at 77 K. On the other hand, the results also suggested that the exact shape of the ethanol adsorption isotherm on a nonporous surface is more sensitive to the nature of the surface than has previously been found with other adsorptives.