



EPDIC 15

The European
Powder Diffraction
Conference

Bari, Italy, 12-15 June 2016
The Nicolaus Hotel

BOOK OF ABSTRACTS



[1] H. Sowa, H. Ahsbahs *Acta Cryst.*, 1998, B54, 578. [2] S. K. Wolff, D. J. Grimwood, J. J. McKinnon, M. J. Turner, D. Jayatilaka, M. A. Spackman, CrystalExplorer 3.0, University of Western Australia, 2012.

Keywords: high-pressure diffraction, compression mechanism

MS12-P03 Applications of synchrotron x-ray powder diffraction in hydrated cements: high-resolution and high-pressure studies

A. Cuesta^a, A. G. De la Torre^b, I. Santacruz^b, C. Popescu^a, M. A. G. Aranda^{a,b}

^aALBA synchrotron, Carrer de la Llum, 2-26, E-08290 Cerdanyola del Vallés, Barcelona, Spain

^bDepartamento de Química Inorgánica, Cristalografía y Mineralogía, Universidad de Málaga, 29071-Málaga, Spain

E-mail: acuesta@cells.es

The main aim of this study is to apply synchrotron radiation techniques for the study of hydrated cement pastes. In particular, the tetracalcium aluminoferrite phase, C₄AF in cement nomenclature, is the major iron-containing phase in Ordinary Portland Cement (OPC) and in iron rich belite calcium sulfoaluminate cements.

In a first study, the hydration mechanism of pure tetracalcium aluminoferrite phase with water-to-solid ratio of 1.0 has been investigated by HR-SXRPD (high resolution synchrotron X-ray powder diffraction). C₄AF in the presence of water hydrates to form mainly an iron-containing hydrogarnet-type (katoite) phase, C₃A_{0.84}F_{0.16}H₆, as single crystalline phase. Its crystal structure and stoichiometry were determined by the Rietveld method and the final disagreement factors were R_{wp}=8.1% and R_f=4.8% [1]. As the iron content in the product is lower than that in C₄AF, it is assumed that part of the iron also goes to an amorphous iron rich gel, like the hydrated alumina-type gel, as hydration proceeds. Further results from the high-resolution study will be discussed.

In a second study, the behavior of pure and iron-containing katoites (C₃AH₆ and C₃A_{0.84}F_{0.16}H₆) under pressure have been analyzed by SXRPD using a diamond anvil cell (DAC) and then their bulk moduli were determined. The role of the pressure transmitting medium (PTM) has also been studied. In this case, silicone oil as well as methanol/ethanol mixtures have been used as PTM. Some “new peaks” were detected in the pattern for C₃A_{0.84}F_{0.16}H₆ as pressure increases, when using ethanol/methanol as PTM. These new peaks were still present at ambient pressure after releasing the applied pressure. They may correspond to crystalline nordstrandite or doyleite from the crystallization of amorphous aluminium hydroxide. The results from the high-pressure study will also be discussed.

[1] Cuesta A., Santacruz I., Sanfélix S.G., Fauth F., Aranda M.A.G. and De la Torre A.G. *Constr Build Mater*, 2015, 101, 818.

Keywords: Synchrotron radiation, hydrated cements, high-pressure, bulk moduli

MS12-P04 Mechanical Properties of the isostructural Gallium and Aluminum Fumarate Metal-Organic Frameworks: A Joint Experimental-Modelling Exploration

P. Ramaswamy^a, P. G. Yot^a, L. Vanduyfhuys^b, P. Fabry^c, E. Alvarez^c, T. Devic^c, C. Serre^c, V. Van Speybroeck^b, G. Maurin^a

^aICGM, Université de Montpellier, CC15005, Pl. E. Bataillon, F-34095 Montpellier cedex05, France.

^bCentre for Molecular Modeling, Ghent University, Technologiepark 903, B-9052, Zwijnaarde, Belgium

^cInstitut Lavoisier Versailles, Université de Versailles St-Quentin, 45, av. des Etats-Unis, F-78035, Versailles cedex, France

E-mail: padmini.ramaswamy@umontpellier.fr

Metal-organic frameworks (MOFs) are a relatively new class of hybrid materials consisting of crystalline networks formed by metal ions or metal clusters connected *via* organic ligands. Their porous frameworks exhibit a wide range of properties of great promises for diverse societally relevant applications in the fields of environment, energy and biomedicine [1]. In this context, there have been very few studies on the thermo-mechanical properties of MOFs [2]. Recently, we showed that the commercialized Aluminium Fumarate MOF, MIL53(Al)-FA, undergoes a reversible structural contraction under an applied pressure above 100MPa, with an associated work energy of 60 J.g⁻¹, which is among the highest values reported for porous solids [3]. As part of our ongoing investigations into related flexible,

Bøjesen; 194
Boldyreva; 200
Bolshakov; 143
Bombardi; 180
Bonevich; 122
Bortolotti; 80
Bosnar; 182
Boudar; 60
Boughzala; 95
Boullay; 77
Bowron; 29
Bozin; 32; 172; 173
Braga; 196
Brant; 149
Bräunig; 58
Braz Fernandes; 140; 187
Bremholm; 179
Brezesinski; 141
Bristowe; 180
Brückel; 107
Brunelli; 28; 37
Buckley; 92; 144
Bulavchenko; 146
Buršik; 163
Buscaglia; 163
Bushmarinov; 42
Bytchkov; 66

C

Calatayud; 128
Calderon; 79
Caliandro; 180
Callear; 170
Calvo; 98
Camargo; 75
Campbell; 49
Canossa; 47
Canu; 163
Čapek; 108
Cappelletto; 211
Cappuccino; 67
Carlsson; 144
Casas; 55
Casas-Cabanas; 89
Casati; 145; 147; 200
Casini; 37
Cedervall; 190
Ceola; 29
Cerhová; 184
Cernik; 77; 85
Černý; 147; 179
Cervellino; 25; 156; 164; 215
Chahine; 192
Chang; 54
Chapman; 17; 35
Chater; 104
Checchia; 37
Cheda; 53

Cheng; 18
Cheong; 180
Cherepanova; 146; 162
Chernikov; 81
Chinga Carrasco; 159
Chizhov; 113
Cho; 54
Chráška; 159
Christensen; 169; 194
Christopoulou; 69
Cinert; 159
Ciomaga Hatnean; 172
Ciriaco; 52
Cliffe; 27
Cline; 112; 122
Coates; 29
Cockcroft; 219
Coduri; 37
Coelho; 33
Colombo; 55
Comboni; 202
Confalonieri; 141; 163
Connelly; 85
Conrad; 107
Cooper; 29
Cordon; 97
Correll; 136
Corriero; 50; 52
Costa; 46; 59; 212
Coutard; 69
Crawford; 18
Crespi; 48
Crichton; 199
Cruciani; 19
Cuesta; 114; 203
Cuocci; 50; 52; 180
Czech; 188
Czerwinski; 174

D

da Silva; 46
Dadivanyan; 37
Daemen; 32
Damay; 175
Daniš; 184
Dapiaggi; 29; 141; 154; 157; 163; 164
David; 15; 41
Day; 103
De Baerdemaeker; 48
De la Torre; 114; 139; 203
De Pascalis; 78
De Riccardis; 69; 70; 71
De Vos; 48
Degen; 65; 67; 69; 209
Delevoye; 135
Dennis; 134
Dercz; 189
Devic; 200; 203