

## Coalgebras and Higher-Order Computation: a Gol Approach\*

## Ichiro Hasuo

Department of Computer Science, University of Tokyo, Japan ichiro@is.s.u-tokyo.ac.jp

## Abstract

Girard's geometry of interaction (GoI) [3] can be seen – in one practical aspect of it – as a compositional compilation method from functional programs to sequential machines (see e.g. [8, 2). There tokens move around and express interactions between (parts of) programs. Intrigued by the combination of abstract structures and concrete dynamics in GoI, our line of work [4, 5, 10, 11, 6, 9] has aimed at exploiting, in GoI, results from the theory of coalgebra – a categorical abstraction of state-based transition systems that has found its use principally in concurrency theory. Such reinforced connection between higher-order computation and state-based dynamics is made possible thanks to an elegant categorical axiomatization of GoI by Abramsky, Haghverdi and Scott [1], where traced monoidal categories [7] are identified to be the essential structure behind. In the talk I shall lay out these basic ideas, together with some of our results on: GoI semantics for a quantum programming language [4, 5]; and our "memoryful" extension of GoI [10, 11, 6, 9] with algebraic effects [12].

The talk is based on my joint work with my colleague Naohiko Hoshino (RIMS, Kyoto University) and my (former) students Koko Muroya (University of Birmingham) and Toshiki Kataoka (University of Tokyo), to whom I owe special thanks.

1998 ACM Subject Classification D.3.1 [Formal Definitions and Theory] Semantics, F.3.2 [Semantics of Programming Languages Algebraic approaches to semantics

**Keywords and phrases** functional programming, geometry of interaction, categorical semantics, coalgebra

Digital Object Identifier 10.4230/LIPIcs.FSCD.2016.2

Category Invited Talk

## - References

- S. Abramsky, E. Haghverdi and P. Scott. Geometry of interaction and linear combinatory algebras. Math. Struct. in Comp. Sci., 12(5):625–665, 2002.
- D.R. Ghica, A.I. Smith and S. Singh. Geometry of synthesis IV: compiling affine recursion into static hardware. In M.M.T. Chakravarty, Z. Hu and O. Danvy, editors, ICFP, pp. 221–233. ACM, 2011.
- J.Y. Girard. Geometry of interaction I: Interpretation of system F. In R. Ferro et al., editors, Logic Colloquium 1988, pp. 221–260. North-Holland, 1989.
- I. Hasuo and N. Hoshino. Semantics of higher-order quantum computation via geometry of interaction. In LICS, pp. 237–246. IEEE Computer Society, 2011.

Supported by Grants-in-Aid No. 24680001, 15K11984 & 15KT0012, JSPS; by the JSPS-INRIA Bilateral Joint Research Project "CRECOGI"; and by Aihara Innovative Mathematical Modelling Project, FIRST Program, JSPS/CSTP.

- 5 I. Hasuo and N. Hoshino. Semantics of higher-order quantum computation via geometry of interaction, 2016. Extended version of [Hasuo & Hoshino, LICS 2011], to appear in *Ann. Pure & Appl. Logic*. Preprint available at arXiv.
- N. Hoshino, K. Muroya and I. Hasuo. Memoryful geometry of interaction: from coalgebraic components to algebraic effects. In T.A. Henzinger and D. Miller, editors, Joint Meeting of the Twenty-Third EACSL Annual Conference on Computer Science Logic (CSL) and the Twenty-Ninth Annual ACM/IEEE Symposium on Logic in Computer Science (LICS), CSL-LICS'14, Vienna, Austria, July 14 18, 2014, page 52. ACM, 2014.
- 7 A. Joyal, R. Street and D. Verity. Traced monoidal categories. *Math. Proc. Cambridge Phil. Soc.*, 119(3):425–446, 1996.
- 8 I. Mackie. The geometry of interaction machine. In POPL'95: Proceedings of the 22nd ACM SIGPLAN-SIGACT symposium on Principles of programming languages, pp. 198–208. ACM, New York, NY, USA, 1995.
- 9 K. Muroya, N. Hoshino and I. Hasuo. Memoryful GoI with recursion. In *International Workshop on Syntax and Semantics of Low-Level Language (LOLA 2015)*. 2015.
- 10 K. Muroya, N. Hoshino and I. Hasuo. Memoryful geometry of interaction II: recursion and adequacy. In R. Bodik and R. Majumdar, editors, Proceedings of the 43rd Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL 2016, St. Petersburg, FL, USA, January 20 22, 2016, pp. 748-760. ACM, 2016.
- 11 K. Muroya, T. Kataoka, I. Hasuo and N. Hoshino. Compiling effectful terms to transducers: Prototype implementation of memoryful geometry of interaction. In *International Workshop on Syntax and Semantics of Low-Level Language (LOLA 2014)*. 2014.
- 12 G.D. Plotkin and J. Power. Adequacy for algebraic effects. In F. Honsell and M. Miculan, editors, FoSsaCS, vol. 2030 of Lecture Notes in Computer Science, pp. 1–24. Springer, 2001.