




Fundamental power couplers for the ERL prototype SRF gun at BNL



*Sergey Belomestnykh and Wencan Xu
Collider-Accelerator Department, BNL*

October 20, 2011

BROOKHAVEN
NATIONAL LABORATORY

a passion for discovery



U.S. DEPARTMENT OF
ENERGY

Office of
Science

ERL 2011 Workshop
KEK • October 16-21, 2011

Acknowledgements


Below is a (incomplete) list of colleagues I would like to thank for contributing to SRF development at BNL.

BNL: Z. Altinbas, I. Ben-Zvi, S. Deonarine, J. Jamilkowski, D. Gassner, D. Kayran, P. Kankiya, N. Laloudakis, G. McIntyre, L. Masi Jr, D. Pate, D. Philips, T. Seda, A. Steszyn, T. Tellerico, R. Todd, D. Weiss, A. Zaltsman


AES: M. Cole, G. White

SLAC: Liling Xiao, Lixin Ge, Kwok Ko


FPC for the prototype ERL SRF gun





- 500-kW coaxial fundamental power (FPC) coupler belongs to the family of TRISTAN/KEKB/SNS couplers.
- Two couplers will provide up to 1 MW of RF power to the R&D ERL SRF gun.
- FPC has a planar berillia window.
- Inside the cryostat the copper-plated stainless steel outer conductor is cooled by helium gas.
- Copper inner conductor is cooled by water.
- Air-side inner and outer conductors are cooled by water.
- Window assembly has ports for vacuum gauges and arc detectors.
- Doorknob transition to WR1500.
- Pringle-shaped tip of the antenna to enhance coupling (similar to that of Cornell ERL injector).
- Designed by AES, manufactured by CPI/Beverly.




Conflat gasket with RF seal



- A custom Conflat gasket with RF seal is used between the FPC and the SRF gun cavity.
- We have found that the original gasket was difficult to seal as the flanges had to crush the gasket in two places, which required very high force.
- A modification was proposed to alleviate the problem. It is used now on the SRF gun cavity/FPC interface.
- We may use similar gaskets in the future for beam pipe seals.




Simulations of multipacting with Track3P





- The simulations were carried out for the FPC conditioning setup: standing wave, full reflection at different phases .
- MP was found in the coaxial line, but not at the window → MP zones are not sensitive to the RF pahse of reflecting wave.
- MP is predicted at RF power levels about 4 kW, 16 kW, 25 kW, 80 kW and 160 kW.
- Zones are not sensitive to the RF frequency. However, the strength of multipacting varies with the frequency change.

MP simulation at different reflection phase:
red - 0, black - $\pi/9$, blue - $\pi/6$





More simulations results


Left - vacuum side coaxial line, right – window



Simulations at different frequencies: left - 703.9 MHz, right - 703.75 MHz



FPC conditioning set up




FPCs for conditioning set up: 1 - waveguide connecting to 1 MW klystron, 2 - two FPCs, 3 - cooling hoses, 4 - waveguide phase shifter and a short plate.

- The FPC conditioning cart and FPCs were assembled at AES.
- All components were cleaned in an ultrasonic bath and dried with dust-free nitrogen gas.
- The window assemblies were also rinsed with DI water to reduce concentration of dust particles and contaminants trapped in the window.
- The assembly of vacuum components was carried out in a class 10 clean room at AES.



- The first thing after the cart arrival at BNL was vacuum bake at 200°C for about 20 hours.
- With a thermal-insulation box, it takes 7 hours to ramp the temperature up to 200°C (RF window temperature). The stand stays at this temperature for 20 hours. Then the temperature is ramped down at a rate of 15°C/hr. The vacuum reached 7.3E-9 Torr immediately after baking and to 3E-9 Torr after several days of pumping.
- The S-parameters were measured.
- Finally, the FPCs were connected to the klystron output at one end, and the phase shifter terminated by a short plate at the other end.

FPC conditioning





- Conditioning is performed in standing wave mode.
- It begins in various pulse modes, from 100 μ s/10 ms to 2 ms/10 ms pulse length/period, followed by the CW mode with gradual increase of RF power to the maximum value.
- The phase shifting up to 45 degrees is performed via the remotely controlled phase shifter.
- The output of the klystron is controlled by a computer program with feedback on vacuum.
- RF power was limited to 125 kW in CW mode to keep local field levels at standing wave maximum the same as they would be at 500 kW.
- RF power in pulse mode was up to 250 kW (limited by the klystron collector).





FPC conditioning: MP zones



(a) MP at 4-6 kW





(b) MP at 16-18 kW





(c) MP at 25 kW

(d) MP at 40 kW



FPC conditioning: MP zones (2)





(e) MP at 80 kW



(f) MP at 100 kW




(g) MP and outgassing at 160 kW



(h) outgassing at higher input power

Comparison with simulations



- Simulations predicted multipacting at RF power levels about 4 kW, 16 kW, 25 kW, 80 kW, and 160 kW.
- A lot of electron activity is predicted above 100 kW, which can be responsible for outgassing.
- These is exactly what was observed in the experiment.

Summary

- We have successfully tested 500-kW FPCs for the R&D ERL SRF gun.
- The test was in a standing wave mode with full reflection.
- Maximum power was set to 250 kW in pulse mode (limited by klystron collector) and 125 kW in CW (administrative limit).
- Observed MP barriers were in very good agreement with those predicted by simulations with Track3P.
- A modified Conflat gasket with RF contact was designed and may be useful for beam pipe seals.