



LAWRENCE
LIVERMORE
NATIONAL
LABORATORY

Amplification of 1 ps Pulse Length Beam by Stimulated Raman Scattering of a 1 ns Beam in a Low Density Plasma

E. Dewald, R. K. Kirkwood, C. Niemann, N. Meezan, S.
C. Wilks, L. Divol, R. L. Berger, O. L. Landen, J.
Wurtele, A. E. Charman, Min Sup Hur, R. Lindberg, N.
Fisch, V. M. Malkin

June 22, 2005

IEEE International Conference on Plasma Science
Monterey, CA, United States
June 20, 2005 through June 24, 2005


Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

Amplification of a 1 ps Pulse Length Beam by Stimulated Raman Scattering of a 1 ns Beam in a Low Density Plasma

NIF

The National Ignition Facility



**E. Dewald, R. K. Kirkwood, C. Niemann, N. Meezan, S. C. Wilks,
L. Divol, R. L. Berger, O.L. Landen
LLNL**

**J. Wurtele, A. E. Charman, Min Sup Hur, R. Lindberg,
UC Berkeley/LBL**

N. J. Fisch, V. M. Malkin, Princeton University

Introduction



The National Ignition Facility

The compression of a laser pulse by amplification of an ultra short pulse beam which seeds the stimulated Raman scatter of the first beam has been long been discussed in the context of solid and gas media.

We investigate the possibility of using intersecting beams in a *plasma* to compress nanosecond pulses to picosecond duration by scattering from driven electron waves.


Recent theoretical studies have shown the possibility of efficient compression with large amplitude, non-linear Langmuir waves driven either by SRS [1] or non-resonantly [2].

We describe experiments in which a plasma suitable for pulse compression is created , and amplification of an ultra short pulse beam is demonstrated.

[1] V. M. Malkin G. Shvets, and N. J. Fisch, PRL 82, 4448 (1999).

[2] G. Shvets, N. J. Fisch, A. Pukhov, and J. Meyer-ter-Vehn, PRL 81, 4879 (1998).

Two Beams in a Plasma Will Stimulate Plasma Waves That Scatter Energy Between the Beams



A beat intensity profile is produced by two beams that have spatial and temporal frequency component determined by the difference in the two beams.

$$k_{\text{plasma}} = k_1 - k_2$$
$$W_{\text{plasma}} = W_1 - W_2$$

With the right plasma conditions the wave is resonant and grows to large amplitude

The plasma wave forms a 3D Bragg cell grating that scatters power from one beam to the other.


Counter Propagating Beams, Amplified by Stimulated Raman Scattering, Can Deplete the Pump



The National Ignition Facility

Counter propagating beams allow an ultra short pulse to extract all the energy of a long pulse beam, causing pulse compression when SRS gain is high.

The interaction distance and plasma size are given by $x = (1/2) c t_{\text{long pulse}}$ or $\sim 15 \text{ cm of plasma}$ per ns of compressed pulse.



From Malkin et. al.

Critical Issues for Pulse Compression by SRS in a Plasma



The National Ignition Facility

1) The ponderomotive force of the two beams must be able to drive a large enough wave amplitude to scatter nearly 100% of the pump power.

- a) The strongly non-linear wave response should be verified by proof of principle experiments.
- b) The necessary coherence of the scattered light must also be verified by experiments.

2) Desirable plasma properties include:

- a) be hot enough to *minimize inverse bremsstrahlung* absorption of the beams and the collisional damping of the Langmuir waves.
- b) be cold and dense enough to *allow weak Landau damping*.

Our Experiment tests 1) under conditions determined by 2)


Optimization of Plasma Conditions for Compressing 1 ns Pulses into 1 ps Pulses with 1 micron Wave Lengths



The National Ignition Facility

The minimum plasma density fluctuation to scatter 100% of the pump power into the probe indicates average plasma densities of $\geq \sim 2-3 \times 10^{18}$ are needed.

Langmuir wave growth requires low $k\lambda_D$ while good beam transmission requires low inverse bremsstrahlung, which leads to greatest effects at lowest densities.




Our experiments begin with 2.5×10^{18} and 1×10^{19} cm^{-3} As the resonant density

An Single Beam Produces a Uniform Density Plasma, Simulations Confirm Little Time Variation During 1 ns




The National Ignition Facility

527 nm Interferometer
(2 ns gate)




Interferometric measurements with a single (unsmoothed) beams Have confirmed uniform initial gas and plasma density over the range of parameters.




Hydra simulations of RPP smoothed beam confirm little variation of density plateau during the 1 ns pulse, and low temperatures at $2.5 \times 10^{18}/\text{cm}^3$ density.

PIC Simulations of Experimental Conditions Show Substantial Amplification Under These Conditions



Power Amplification
Vs. Density




PIC simulations confirm *significant amplification* of a 1ps pulse under these Conditions, and show the *amplified pulse length* $\sim 1ps$, and the maximum Amplification is at the *resonant value of density*.

Experiments with Janus/Comet Laser Systems Test USP Pulse Amplification in a Plasma Suitable for 1ns Pulse Compression



The National Ignition Facility

- Experiments with Janus/Comet Beams may show amplification of the 1ps Comet beam by the 1ns Janus beam.
- A gas jet produces a He plasma about 1-3 mm wide.
- High intensity interaction across the entire plasma could deplete 10-20 ps slice of pump beam and demonstrate pulse compression
- Available intensities ($< 1.1 \times 10^{15}/\text{cm}^2$) are well above what is needed if plasma response is linear, so the non-linear response has been studied.



The back scatter geometry has the beams nearly parallel.
(beams perpendicular to jet)


The 1ps beam is converted to 1124 nm and 1200 nm by a H_2 gas Raman Cell

Maximum energy is Exchanged between beams when density is adjusted to resonant value.

Unseeded (single beam) SRS spectra from Low Density He Plasmas Shows Rapid Increase of Scattering, and the Expected Increase of Wavelength, with Plasma Density (or Gas Pressure)



The National Ignition Facility



SRS is seen to be
Much more intense and
At longer wavelength
As plasma density is
Increased, as expected.

Interferometer measurements
show plateau plasma density
is consistent with the SRS
Spectral peak.


Additional measurements
At low beam intensity
Show little change in
SRS reflectivity,
Consistent with strongly
Saturated waves.

Seeding the high density plasma with a 1ps pulse at the resonant wavelength of 1200 nm produced a large amplification showing high density is favorable as expected.



The National Ignition Facility

$$I_{\text{pump}} = 3.5 \times 10^{14} \text{ W/cm}^2$$
$$n_e = 1.0 \times 10^{19} \text{ cm}^{-3}$$



The observed amplification of the transmission of the seed pulse is consistent with weak damping and saturation of the scattering Langmuir waves at this density.

(However this high density may significant absorption of energy if used for pulse compression of a 1 ns pulse)


Seeding the high density plasma with a 1ps pulse at the resonant wavelength of 1200 nm at Increased Intensity produced ?? Amplification showing Scaling with Intensity.



The National Ignition Facility

$$I_{\text{pump}} = 1.1 \times 10^{15} \text{ W/cm}^2$$
$$n_e = 1.0 \times 10^{19} \text{ cm}^{-3}$$


The observed scaling of the amplification of the transmission of the seed pulse with intensity is will allow a pulse compression experiment to be designed.



Attenuation of Non-Resonant Light (1124 nm) Shows 4x Attenuation Due to Plasma Absorption and Beam Spreading, Indicating The Real Amplification at 1200 nm is Even Greater



The National Ignition Facility



The 1124 nm transmission is Measured on the same shots, With the same timing and plasma conditions and indicate 4x attenuation of ‘Non-resonant’ light at the time of the Interaction

Attenuation is due to both inverse bremsstrahlung absorption and spreading of the beam outside the collection optics.

This increases measured gain following

$$\text{Amp.} = \frac{(\text{‘Pump+seed’} - \text{‘Pump only’})}{(\text{‘seed only’})}$$

~ 10x

Seeding the low density plasma with a 1ps pulse at the resonant wavelength of 1124 nm produced less amplification than at high density




The National Ignition Facility

The 'pump+seed' waveform is Only slightly larger than the sum of the 'pump only' and 'seed only' cases at early time

Pump only SRS is weak and varying adding to un-certainty of amplification.

Little attenuation of seed is seen, Or expected at this density, so Amplification is compared to Vacuum seed transmission to Give: Amp. $\sim 1.75x$



The small amplification of the transmitted seed pulse relative to its vacuum value is consistent with strongly damped or saturated Langmuir waves at this density

Summary



The National Ignition Facility

Low density and low temperature plasmas have been recognized as desirable for efficient compression of a 1 ns pulse by Stimulated Raman Scattering in a Plasma.


Experiments to demonstrate and study the scaling of the amplification of a 1 ps pulse in a such a plasma in the presence of a 1ns pulse have demonstrated $\sim 10x$ amplification of a pulse with $1.0 \times 10^{19}/\text{cm}^{-3}$ electron density and showed reduced amplification at $2.5 \times 10^{18}/\text{cm}^{-3}$.

Single beam near backscatter measurements under these conditions show scattering increasing rapidly with plasma density in the density range studied, with weaker dependence on beam intensity.

Both Comet Only and Janus Only Data Showed Good Reproducibility, Supporting the Amplification Result



Comet Only measurements



Five 'Comet Only' shots (shown) Before and after the amplification Experiment show little variability.

The two Janus shots with no Comet Interaction showed similar Scattering results


Further, calorimeter measurements showed 456 mJ on the amplification shot and ~ 200 mJ (trig.level) on all other shots.

These results indicate that the large signal on the Janus +Comet shot was due to plasma Amplification (not laser fluctuation).

469 nm Hell Line Indicates T - ~25 eV Near Resonant Density




The National Ignition Facility



469 nm
(Hell)

532 nm
(probe
laser)




Line to continuum ratio at 85psi jet pressure consistent with ~ 25eV electron temperature (un inverted). Spatial imaging indicates localization to beam.

He Line to Continuum Ratio Gives T_e vs. Position



The National Ignition Facility




85psi jet pressure

Interferometer Measurements Show Peak Density Approximately Tracks Gas Jet Pressure, as Expected



The National Ignition Facility



Error bars indicate
Fringed reading
uncertainty

4mm dia. nozzle


Even with varying profiles, peak fringed shift on interferometer approximately follows the gas jet pressure.

(pressure may be best indication of average density)


Thermal SRS Observed at higher Plasma Densities Have Appropriate Wavelengths for Measured Density Profiles



SRS Spectrum



Measured Fringe Profile




Operation of jet at higher pressure allows high density plasma to be produced and thermal SRS spectrum (un seeded) is observed.

SBS Was Found to be Very Large Even with Defocused (Low Intensity) Beams at High Density




The National Ignition Facility



Further SBS studies in this plasma in a later talk by D. Froula

Demonstration of Efficient Raman Conversion of a 1 ps Beam to 1124 nm Has Been an Essential Step




An H₂ gas Raman Cell (500 psi, 1 m length) allows the 1054 nm Comet line to be converted to 1124 nm with ~ 15% efficiency.

Short pulse Transmission Measurement in Small Scale Plasma Gave Some Evidence of Amplification Near the Resonant Density



The National Ignition Facility



Plasma waves
Amplitudes at
'trapping threshold'
($dn/n \ll 10^{-3}$)
would produce
 $\ll 2x$ amplification

Maximum amplification observed with small scale plasma is $\ll 1.2x$