

§28. Effects of Metal Wall and Electric Field on Density Profile in Large Area Plasma Source

Shinohara, S., Itagaki, N., Ichiki, R. (Interdis. Grad. Sch. Eng. Sci., Kyushu Univ.), Kaneko, O., Tsumori, K.

In the high power neutral beam injection system (NBI) utilizing negative ions developed in NIFS, improvement of spatial homogeneity of the large area plasma production is crucial. The inhomogeneity is supposed to be partly due to the magnetic field and electric field induced by the plasma potential. Nevertheless, the effect of the electric field on the plasma performance has not been investigated in detail. Here, we examined how the plasma density and bulk plasma flow changed in a magnetized plasma by applying a voltage on the metal plate in order to develop to a future large area ion source.

The experiment was performed using Ar gas plasma (45 cm in diameter and 170 cm in axial length), produced by RF using a four-turn antenna, with a pressure of $P = 0.3 - 3$ mTorr and the axial magnetic field $B = 500$ G [1,2]. Typical electron density n_e and temperature T_e were $< 10^{10}$ cm $^{-3}$, 3 - 8 eV, respectively. A voltage biased plate was made of stainless steel (20 cm \times 20 cm, with 0.1 cm thickness) with an insulator plate on one side. Near the bias plate, semi-circular earthed metal plate was also located to see the boundary effects. Plasma parameters were measured by the Langmuir probes including the Mach probe for the plasma flow measurement.




Fig. 1. Radial profiles of ion saturation current

Dependences of n_e , plasma flow (x direction, which is parallel (perpendicular) to the plate surface (magnetic field)) and floating potential V_f on the biased voltage V_b were investigated. Figure 1 shows a typical example of radial profiles of ion saturation current I_s . For the positively (negatively) biased case, plasma density moved to the positive (negative) x direction. This asymmetry became weaker with increasing a distance (y direction) from the plate. With the increase in the magnetic field and/or the decrease in the pressure, this tendency became stronger. In addition, the density distribution was inverted by changing a polarity of the magnetic field.

Figure 2 shows distributions of (a) floating potential V_f and (b) R , the ratio of I_s collected from two opposite directions, measured by the Mach probe. If R is larger (smaller) than 1, the plasma flows to the positive (negative) x direction. Applying the positively (negatively) biased voltage with the magnetic field along the positive z direction, the plasma flowed to the positive (negative) x direction. This flow velocity was larger with the lower pressure and higher magnetic field and also near the plate. The effect of the earthed plate was found to be small.

In conclusion, magnetized plasma distribution was investigated by applying a biased voltage on the metal plate. The obtained results could be understood by the $E \times B$ drift based on the normalized Larmor radius and collision time. In order to develop a large area ion source, we must consider the electric field near the boundary.




Fig. 2. Radial profiles of (a) floating potential and (b) current density ratio.

Reference

- 1) Matsuyama, S., Shinohara, S. and Kaneko, O.: Trans. Fusion Technol. **39** (2001) 362.
- 2) Shinohara, S., Matsuyama, S., and Kaneko, O.: Thin Solid Films **407** (2002) 209.