

COMMISSION OF THE EUROPEAN COMMUNITIES

COM(83) 206 final

Brussels, 15 April 1983

Draft for a
COUNCIL REGULATION (EEC)

temporarily suspending the autonomous Common Customs Tariff
duties on certain industrial products

(submitted to the Council by the Commission)

EXPLANATORY MEMORANDUM

1. The subject of the following draft regulation is the temporary suspension of duties in the Common Customs Tariff for a number of industrial items, as requested by the Member States.
It is partly a prolongation and partly a new measure.

2. It seems appropriate to the Commission that a duty suspension is justified for the goods listed in the annex to this regulation. The Commission proposes a total suspension for those products for which Community production does not exist or is minimal. A partial suspension is proposed in cases where the Community production covers only a part of the requirements. The rate of the partially suspended duty depends on the extent of the possible Community supply to the Community users. The Commission is also always looking for the right balance between the interests of the suppliers, users and the consumers in the Community.
It also takes into account the need to protect employment.

3. The proposed measures are confined to six or twelve months because of the difficulties of estimating the evolution of the basic factors.

4. For a number of items for which the Member States also requested duty suspensions the Commission does not propose a tariff measure because the necessary conditions are not fulfilled. This concerns the following items :

CCT heading No	Description
ex 28.04 C III	Tellurium in powder or granulated form
ex 29.02 C and ex 30.03 A II	Mitotane (INN)
ex 29.01 D VII	Tricyclo[8.2.2.2 ^{4,7}]hexadeca-1(12),4,6,10,13,15-hexaene
ex 29.02 A III	Methyl Bromide of 99 % purity plus 1 % Chloropicrine
ex 29.05 B II	2,2'- <u>p</u> -phenylenedipropan-2-ol
ex 29.16 A I	<u>DL</u> -Lactic acid, synthetic
ex 29.24 B	Diallyldimethylammonium chloride
ex 29.27	Isophthalonitri c e for the manufacture of tetrachloroisophthalonitri c e (u)
ex 29.35 Q	Tetrahydrofuran, containing not more than 40 mg/L in total of tetrahydro-2-methylfuran and tetrahydro-3-methylfuran
ex 29.35 Q	3,6-dichloropyridine-2-carboxylic acid
ex 29.41 D	Ivermectin (INN)
ex 29.44 C	Gentamicin (INN) and its salts
ex 29.44 C	Ceftizoxime sodium (INNM)
ex 30.03 A II b)	Naloxone hydrochloride (INNM)
ex 38.19 G	Catalysts, in the form of rodlets, having a diameter of not less than 1.5 mm and not more than 9.5 mm, containing not less than 60 % by weight of diiron trioxide, not less than 8 % by weight of dipotassium oxide and not less than 0.5 % by weight of dichromium trioxide
ex 38.19 G	Catalysts consisting of a mixture of oxides on a silicon dioxide support and containing by weight: — not less than 25 % and not more than 40 % of antimony — not less than 5 % and not more than 10 % of iron — not less than 0.2 % and not more than 1.5 % of molybdenum — not less than 0.8 % and not more than 4.0 % of tellurium

CCT heading No	Description
ex 38.19 G	Catalysts, in the form of rodlets, having a diameter of not less than 1 mm and not more than 3 mm, containing not less than 5 % and not more than 10 % by weight of a mixture of nickel and tungsten, supported on a carrier of aluminium oxide and silicon dioxide
ex 38.19 G	Catalysts in the form of tablets or discs, having a diameter of not less than 3 mm and not more than 6 mm, and a thickness of not less than 3 mm and not more than 6 mm, or in the form of rodlets, having a diameter of not less than 1.5 mm and not more than 6 mm consisting of a mixture of aluminium oxide and silicon dioxide, and containing by weight : a) not less than 40% and not more than 50% of nickel b) not less than 3% and not more than 10% of cobalt c) not less than 3% and not more than 8% of copper
ex 38.19 G	Catalysts in the form of tablets or discs having a diameter of not less than 3 mm and not more than 6 mm, and a thickness of not less than 3 mm and not more than 6 mm, or in the form of rodlets, having a diameter of not less than 1.5 mm and not more than 6 mm, consisting of a mixture of oxides supported on a carrier of aluminium oxide and silicon dioxide and containing by weight : a) not less than 40% and not more than 60% of nickel b) not less than 3% and not more than 8% of copper
ex 38.19 X	Reaction products of dibutyl dihydrogendiphosphate and 1,2-epoxypropane
ex 38.19 G	Alkenylsuccinic anhydride, with a branched alkenylchain of not less than 15 and not more than 20 carbon atoms
ex 39.01 C III a)	Polyethylene-terephthalate film, in rolls, of a thickness not less than 13 micrometres for the manufacture of magnetic tapes for video recorders (a)

CCT heading No	Description
ex 39.01 C VII	<i>alpha</i> -4-Hydroxybutyl- <i>omega</i> -hydroxypoly(oxytetramethylene)
ex 39.05 B	Chlorinated rubber containing not less than 63 % and not more than 69 % by weight of chlorine and with an average molecular weight of not less than 200,000
ex 40.11 A	Cushion tyres having a diameter not greater than 300 mm
ex 48.07 C	Bleached paper impregnated with acrylic resin and coated with poly(vinylidene chloride) having a thickness of not less than 200 micrometres and not more than 255 micrometres and of a weight per square metre of not less than 165 grams and not more than 180 grams
ex 48.07 D	Coloured paper impregnated with acrylic resin and coated with poly(vinylidene chloride) having a thickness of not less than 200 micrometres and not more than 255 micrometres and of a weight per square metre of not less than 165 grams and not more than 180 grams
ex 48.07 D	Paper bleached or unbleached impregnated with an agent, the principal component of which is ammonium bis[2[N-ethyl(perfluoro-octane)-1-sulfonylamido] ethyl]orthophosphate, which imparts resistance to penetration of grease and oil to the paper
ex 68.02 B	Artificially coloured granules and chippings
ex 70.20 B	Spun roving of not less than 7 000 tex with a core of not less than 600 tex and not more than 1 500 tex, made from continuous glass fibre, coated with epoxy resin
ex 70.20 B	Yarns obtained from continuous spun glass filaments having a diameter of not less than 12.5 micrometres and not more than 13.5 micrometres treated with resorcinol formaldehyde, of not less than 340 tex and not more than 680 tex
ex 70.20 B	Yarns, spun from continuous glass filaments having a diameter of not less than 5.8 micrometres and not more than 6.4 micrometres of 33 or 34 tex or a multiple thereof and containing not more than 0.8 % by weight of dressing
ex 84.18 C II b)	Parts of equipment for the filtration and purification of liquids, consisting of a bundle of hollow fibres of artificial plastic material with permeable walls, embedded in a block of artificial plastic material at one end and passing through a block of artificial plastic material at the other end, the whole being enclosed in an artificial plastic container
ex 85.18 A	Oil filled capacitor contained in a metal box, whose exterior dimensions do not exceed 200 x 400 x 700 mm excluding terminals, whose temperature does not exceed 70 ° C at a potential difference of 50 KV when increased by a pulse with a potential difference of 60 KV at a frequency of 200 Hz and a duration of 125 microseconds

CCT heading No	Description
ex 85.19 A	<p>Thermal relays contained in a hermetically sealed glass cartridge not exceeding 35 mm in length excluding wires, with a maximum leakage rate of 10^{-6} cm³ He/sec at 1 bar in the temperature range 0-160 °C</p>
ex 85.21 D II	<p>Dynamic random access memories, operating from a single +5 V power supply, of N-MOS technology (N-MOS single +5 V power supply D-RAMS) with a storage capacity of 16 K bits in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 9 x 24 mm, with no more than 16 connecting pins or 18 contact areas and bearing:</p> <ul style="list-style-type: none"> — an identification marking either consisting of one of the following combinations of figures or including one of those combinations: <p style="margin-left: 40px;">2118 4517 4816 5295 8117 8118</p> <ul style="list-style-type: none"> OR — other identification markings relating to N-MOS D-RAMS complying with the abovementioned description
ex 85.21 D II	<p>Single-chip microcomputer in the form of a monolithic integrated circuit, consisting of an arithmetical logic unit with a capacity of 8 bits, not more than two timers each with a capacity of not more than 16 bits, an internal clock, an electronic programmable read only memory (EPROM) UV erasable with a storage capacity of not less than 8 K bits and not more than 32 K bits and a random access memory (RAM) with a storage capacity of not less than 512 bits and not more than 4 K bits, with not less than 13 and not more than 32 input/output lines and contained in a housing whose exterior dimensions do not exceed 17 x 54 mm with not more than 40 connecting pins, with a quartz window on the upper surface and bearing:</p> <ul style="list-style-type: none"> — an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: <p style="margin-left: 40px;">68701 68705 8741 A 8748 8749 8750 8751</p> <p style="margin-left: 40px;">or</p> <ul style="list-style-type: none"> — other identification markings relating to single-chip microcomputers complying with the abovementioned description
ex 85.21 D II	<p>Static random access memories of N-MOS technology (N-MOS Static RAMS) with a storage capacity of 1 K x 4 bits and an access time of not more than 85 ns, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 9 x 24 mm, with not more than 20 connecting pins, and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations :

CCT heading No	Description								
ex 85.21 D II	<p>2148 H 2149 H</p> <p>or</p> <ul style="list-style-type: none">- other identification markings relating to N-MOS Static RAMS complying with the above-mentioned description <p>Single-chip microcomputer in the form of a monolithic integrated circuit, consisting of an arithmetical logic unit with a capacity of 8 bits, not more than 2 timers each with a capacity of not more than 16 bits an internal clock, a read only memory (ROM) with a capacity of not less than 8 K-bits and not more than 32 K-bits and a random access memory (RAM) with a capacity of not less than 512 bits and not more than 4 K-bits, with less than 13 and not more than 32 input/output lines and contained in a housing whose exterior dimensions do not exceed 17 x 54 mm, with not more than 40 connecting pins and bearing :</p> <ul style="list-style-type: none">- an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations : <table data-bbox="824 1145 1232 1236"><tr><td>TMP 80 C 22</td><td>TMP 80 C 50</td></tr><tr><td>TMP 80 C 48</td><td>TMP 80 C 51</td></tr><tr><td>TMP 80 C 49</td><td></td></tr></table>- other identification markings relating to single-chip microcomputers complying with the above-mentioned description	TMP 80 C 22	TMP 80 C 50	TMP 80 C 48	TMP 80 C 51	TMP 80 C 49			
TMP 80 C 22	TMP 80 C 50								
TMP 80 C 48	TMP 80 C 51								
TMP 80 C 49									
ex 85.21 D II	<p>Single-chip microcomputer in the form of a monolithic integrated circuit, consisting of an arithmetical logic unit with a capacity of 8 bits, not more than 2 timers each with a capacity of not more than 16 bits, an internal clock, and a random access memory (RAM) with storage capacity of not less than 512 bits and not more than 4 K-bits, with not less than 27 and not more than 32 input/output lines and contained in a housing whose exterior dimensions do not exceed 17 x 54 mm, with not more than 40 connecting pins and bearing :</p> <ul style="list-style-type: none">- an identification marking either consisting of one of the following combinations of figures of figures and letters or including one of those combinations : <table data-bbox="476 1893 793 2018"><tr><td>80 C 31</td><td>8031</td></tr><tr><td>80 C 35</td><td>8035</td></tr><tr><td>80 C 39</td><td>8039</td></tr><tr><td>80 C 40</td><td>8040</td></tr></table>- other identification markings relating to single-chip microcomputers complying with the above-mentioned description	80 C 31	8031	80 C 35	8035	80 C 39	8039	80 C 40	8040
80 C 31	8031								
80 C 35	8035								
80 C 39	8039								
80 C 40	8040								

CCT heading No	Description
ex 85.21 D II	<p>N-MOS Programmable Communication Interface (N-MOS PCI), in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with not more than 28 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures and letters or including this combination <p style="margin-left: 40px;">8251 A</p> <p style="margin-left: 40px;">or</p> <ul style="list-style-type: none"> - other identification markings relating to N-MOS PCIs complying with the abovementioned description
ex 85.21 D II	<p>N-MOS Programmable Peripheral Interface (N-MOS PPI), in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 16 x 54 mm, with not more than 40 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures and letters or including this combination <p style="margin-left: 40px;">8255 A</p> <p style="margin-left: 40px;">or</p> <ul style="list-style-type: none"> - other identification markings relating to N-MOS PPIs, complying with the abovementioned description
ex 85.21 D II	<p>4-Channel N-MOS Direct Memory Access Controller (N-MOS-DMA-Controller), in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 16 x 54 mm, with not more than 40 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or including this combination <p style="margin-left: 40px;">8257</p> <p style="margin-left: 40px;">or</p> <ul style="list-style-type: none"> - other identification markings relating to N-MOS-DMA-Controller, complying with the abovementioned description
ex 85.21 D II	<p>Programmable Interval Timers (PITs) of N-MOS-technology, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm with not more than 24 connecting pins, and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or

CCT heading No	Description
	including this combination 8253 or - other identification markings relating to PITs complying with the abovementioned description
ex 85. 21 D II	Monolithic integrated circuit consisting of a static random access memory (S-RAM) with a storage capacity of 256 bits <i>superimposed</i> bit-for-bit on a reprogrammable electrically erasable read only memory (E ² -PROM), contained in a housing whose exterior dimensions do not exceed 8 x 23 mm, with 18 connecting pins and bearing : - the identification marking X 2210 or - other identification markings relating to S-RAMS <i>superimposed</i> on E ² -PROMS complying with the abovementioned description
ex 85.21 D II	Semi custom logic array (Gate array), of C-MOS technology, in the form of a monolithic integrated circuit with not less than 8,000 2-input NAND functions, contained in a housing whose exterior dimensions do not exceed 39 x 39 mm with not less than 179 connecting pins and bearing : - an identification marking either consisting of the following combination of figures and letters or including this combination M866000VH or - other identification markings relating to C-MOS logic arrays complying with the abovementioned description
ex 90.19 A III	Vascular prostheses of which the largest opening has an internal diameter exceeding 8 mm

5. Attention is drawn to the fact that the Council Resolution of 27.6.1974 simplifying the task of the customs administrations (OJ C 79/74) requires the publication of the attached Regulation at least six weeks before its entry into force.

Draft for a

COUNCIL REGULATION (EEC)

temporarily suspending the autonomous Common Customs Tariff duties on certain industrial products

THE COUNCIL OF THE EUROPEAN COMMUNITIES,

Having regard to the Treaty establishing the European Economic Community, and in particular Article 28 thereof,

Having regard to the draft Regulation submitted by the Commission,

Whereas production of the products referred to in this Regulation is at present inadequate or non-existent within the Community and producers are thus unable to meet the needs of user industries in the Community;

Whereas it is in the Community's interest to suspend the autonomous Common Customs Tariff duties only partially in certain cases, due particularly to the existence of Community production, and to suspend them completely in other cases;

Whereas, taking account of the difficulties involved in accurately assessing the development of the economic situation in the sectors concerned in the near future,

these suspension measures should be taken only temporarily with their term of validity fixed to coincide with the interests of Community production,

HAS ADOPTED THIS REGULATION:

Article 1

The autonomous Common Customs Tariff duties for the products listed in the tables annexed to this Regulation shall be suspended at the level indicated in respect of each of them.

These suspensions shall be valid:

- from 1 July to 31 December 1983 for the products listed in Table I,
- from 1 July 1983 to 30 June 1984 for the products listed in Table II.

Article 2

This Regulation shall enter into force on 1 July 1983.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg,

*For the Council
The President*

CCT heading No	Description	Rate of autonomous duty (%)
ex 13.03 A V	Extract of dewaxed pyrethrum	0
ex 29.08 A III c)	2-Bromo-6-methoxynaphthalene	0
ex 29.04 A III a)	2-Methylpropan-2-ol(<i>tert</i> -butyl alcohol), with a purity of not less than 90 % but not more than 96 % by weight	0
ex 29.08 B I	3,3'-oxydi(propylene glycol)	0
ex 29.23 C	Ketamine hydrochloride (INN)	0
ex 29.16 D	Methyl 5-(2,4-dichlorophenoxy)-2-nitrobenzoate	0
ex 29.29	2,4,6-Trichlorophenylhydrazine	0
ex 29.35 Q	Isonicotinonitrile	0
ex 29.35 Q	6-Hydroxy-2-phenylpyridazin-3(2H)-one	0
ex 29.35 Q and ex 30.03 A II b)	Bucindolol (INN)	0
ex 29.35 Q	Adenosine phosphate (INN)	4.5
ex 29.35 Q and ex 30.03 A II b)	Tegafur (INN)	0
ex 29.35 Q	2-Hydroxyethylammonium 3,6-dichloropyridine-2-carboxylate	5
29.42 C I	Caffeine and its salts	6
ex 29.44 C	Fumagillin dicyclohexylammonium (INN)	0
ex 30.03 B II b)	Purified collagen dispersed in a phosphate physiological saline solution whether or not containing lidocaine (INN)	0
ex 32.01 A IV	Tanning extracts derived from gambier and myrobalan fruits	0
ex 32.01 A IV	Tanning extracts of eucalyptus	3.2
ex 35.07	Lipoamide dehydrogenase	0
ex 35.07	<u>sn</u> -Glycerol-3-phosphate : oxygen oxidoreductase (EC.1.1.3.)	
ex 38.03 B	Acid activated montmorillonite which, when examined by X-ray powder diffraction, shows four principal lines corresponding to crystal interplane spacing (d values) of 0.44, 0.40, 0.33 and 0.25 nm the line corresponding to 0.40 nm being the most intense, for the manufacture of self-copy paper (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
38.07 A	Gum spirits of turpentine	1.6
38.07 B	Spirits of sulphate turpentine; crude dipentene	0
38.07 C	Spirits of wood turpentine; terpenic solvents produced by the distillation or other treatment of coniferous woods; sulphite turpentine; pine oil (excluding 'pine oils' not rich in terpineol)	1.7
ex 38.19 G	Catalysts, in the form of granules or rings, having a diameter of not less than 3 mm and not more than 10 mm, consisting of silver supported on aluminium oxide, the silver content being not less than 10 % and not more than 20 % by weight	0
ex 38.19 X	Grains, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight not less than 70 % and not more than 78 % dialuminium trioxide and not less than 19 % and not more than 26 % zirconium dioxide	6.4
ex 38.19 X	Grains, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight not less than 54 % and not more than 62 % dialuminium trioxide and not less than 36 % and not more than 44 % zirconium dioxide	6.4
ex 38.19 X	Ivermectin (INN) dissolved in toluene	0
ex 38.19 X	Magnesium bromide 2-oxoperhydroazepin-1-ide dissolved in <u>epsilon</u> -caprolactam to a concentration of not less than 20 % and not more than 25 % by weight	5.5
ex 39.01 C III a)	Reflecting films, tinted in the mass or metallized, containing substances opaque to ultra-violet rays, made up of two layers of polyethylene terephthalate glued to each other and a film of polypropylene glued on one surface, whether or not in rolls	0
ex 39.02 A	Membrane, consisting of a copolymer of tetra=fluoroethylene and trifluoroethylene having perfluorinated alkoxy side chains ending in carboxylic acid groups in the ester form, coated on each side with a metallic inorganic compound, whether or not in rolls	0
ex 39.02 A	Membrane, consisting of a copolymer of tetra=fluoroethylene and trifluoroethylene having perfluorinated alkoxy side chains ending in carboxylic acid or sulphonic acid end groups in the potassium salt form, coated on each side with a metallic inorganic compound, whether or not in rolls	0
ex 39.02 A	Membrane, consisting of a copolymer of tetra=fluoroethylene and trifluoroethylene having perfluorinated alkoxy side chains ending in carboxylic acid end groups in the ester form, containing a woven poly(tetrafluoroethylene) fibre fabric support and coated on each side with a metallic inorganic compound, whether or not in rolls	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 39.02 C I a)	Polyethylene, in one of the forms mentioned in Note 3 (b) to Chapter 39, having a density of not less than 0.954 g/cm ³ and not more than 0.958 g/cm ³ for the manufacture of typewriter ribbon or similar ribbon (a)	0
ex 39.02 C I b)	Transparent polyethylene film which will split longitudinally when stretched at right angles to its length, and having a density of not less than 0.925 gm/cc and yielding not less than 7 g/m ² and not more than 19 g/m ² , for the manufacture of typewriter ribbon or similar ribbon (a)	0
ex 39.02 (I a)	Synthetic paper pulp in the form of moist sheets made from unconnected finely branched, polyethylene, fibrils whether or not blended with cellulose fibres in a quantity not exceeding 15%, containing polyvinyl alcohol dissolved in water as the moistening agent	0
ex 39.02 C II	Microporous polytetrafluoroethylene film, not less than 30 cm in width and weighing not more than 22.4 g/m ² , whether or not in rolls	0
ex 39.02 C IV	Moist sheets made from finely branched fibrils of a mixture of polypropylene and polypropylene modified by an organic acid, whether or not blended with cellulose fibres in a quantity not exceeding 15%, containing polyvinyl alcohol dissolved in water as the moistening agent	0
ex 39.02 C IV	Moist sheets made from finely branched polypropylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15%, containing polyvinyl alcohol dissolved in water as the moistening agent	0
ex 39.02 C VI a)	Copolymer entirely of maleic anhydride and styrene, whether or not containing a styrene-butadiene block copolymer in one of the forms mentioned in Note 3 (b) to Chapter 39	0
ex 39.02 C VI b)	Plates made of a copolymer consisting of maleic anhydride and styrene, also containing styrene-block copolymer, covered on both sides with a sheet of the abovementioned copolymer, modified with butadiene or pigmented	0
ex 39.02 C XIV a)	Polimerization products of acrylic acid with small quantities of a polyunsaturated monomer for use as a thickener in textile pigment printing passes or in the manufacture of products falling within heading 30.03 (a)	0
ex 39.02 C XIV a)	Terpolymer of ethylene, methyl acrylate and a monomer containing a non-terminal carboxy group as a substituent, compounded with silica	12.5

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ex 39.02 C XIV a)	Copolymer of a poly(oxyalkylene) ester of a polycarboxylic acid and <u>epsilon</u> -caprolactam	7.3
ex 39.07 B V d)	Reflecting sheeting or tape consisting of a facing strip of polyvinyl chloride embossed in a regular pyramidal pattern, heat sealed, in parallel lines or a grid pattern to a backing strip of plastic material, or of knitted or woven fabric covered on one side with plastic material, whether or not in rolls	0
ex 44.28 C	Match splints manufactured from aspen (<i>Populus tremuloides</i>) for the manufacture of matches not requiring a specific striking surface (so called 'strike-anywhere' matches) (a)	0
ex 49.11 B	Artists' screen prints (commonly described as serigraphs), signed by the artist and numbered from 1 to 200	0
ex 51.01 A	Yarn of synthetic textile fibres, exclusively of aromatic polyamides obtained by the polycondensation of <u>m</u> -phenylenediamine and isophthalic acid.	0
ex 51.01 A	Polyamide yarn, not textured, untwisted or with not more than 22 turns per metre, of crimpable bicomponent filaments consisting of poly(hexamethylene adipamide) and a copolyamide for the manufacture of knee-length stockings, falling within subheading 60.03 B I; women's stockings, falling within subheading 60.03 B II a) or panty hose (tights) falling within subheading 60.04 B III a) 1 (a)	0
ex 54.03 B I a)	Unbleached linen yarn (excluding yarn of flax tow), measuring per kg 30 000 m or less, for the manufacture of multiple or cabled yarns for the footwear industry or for whipping cables (a)	0
ex 56.01 A	Textile fibres containing not less than 85 % by weight of fibres of aromatic polyamides obtained by the polycondensation of <u>m</u> -phenylenediamine and isophthalic acid and not less than 1 % and not more than 15 % by weight of fibres of poly(<u>p</u> -phenyleneterephthalamide)	6
ex 56.01 A	Acetalized, multicomponent spun fibres with a matrix fibril structure, consisting of emulsion polymerized poly(vinyl alcohol) and vinylchloride	0
ex 59.08	Woven poly(tetrafluoroethylene) fibre fabric coated on one side with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side chains ending in carboxylic acid or sulphonic acid groups in the potassium salt form, whether or not in rolls	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
62.03 A I	Sacks and bags, of a kind used for the packing of goods, used, of jute or of other textile bast fibres of heading No 57.03	0
62.03 B I a)	Sacks and bags of the kind used for the packing of goods, used, of flax or of sisal	0
ex 70.20 A	Mats of non-textile glass fibres of a weight per square metre of not more than 100 grams and a fibre diameter of not more than seven micrometres	0
ex 74.05 B	Non-rigid sheets and plates of polytetrafluoroethylene, with aluminium oxide or titanium dioxide as a filler or reinforced with glass-fibre fabric, laminated on both sides with copper foil	0
ex 81.04 K I	Waste and scrap titanium	0
ex 81.04 K I	Titanium sponge	0
ex 84.31 A	Suction roll shells, not drilled, being alloy steel tubes with a length of not less than 5 207 mm and an outside diameter of not less than 754 mm for use in machinery for making paper or paperboard (a)	0
ex 84.51 A	Typewriters with Braille characters	0
ex 84.51 A	Electronic pocket communicators for handicapped persons which, by means of push buttons and printing thermic head, print and issue text on tape	0
ex 84.51 A	Portable machine for reading and writing Braille with tactile read-out and magnetic tape cassette recording systems, microphone and speaker, equipped with a standard electro-mechanical Braille typewriter keyboard and an electro-mechanical Braille read-out unit with 20 characters, all contained in a case measuring 24 x 36 x 11 cm	0
ex 84.55 C	Opto-electric encoder for electronic typewriters consisting of electronic circuits, a light-emitting diode (LED), a rotating disc with radial openings, a fixed mask and a single chip photovoltaic cell, contained in two plastic shells forming a housing of a size not exceeding 60 x 48 x 16 mm	0
ex 84.55 C	Winchester technology magnetic heads for disc file peripherals, capable of recording to a density of 35.4 tracks per mm	0
ex 84.55 C	<p>Assemblies for automatic data processing machines consisting of 2 stacked substrate layers each with 2 static random access memories of N-MOS technology (N-MOS-S-RAMS) in the form of monolithic integrated circuits each with a storage capacity of 2 K bits and with a total storage capacity of either 8 K x 1 bit or 4 K x 2 bits contained in a housing whose exterior <i>do</i> not exceed 13 x 13 mm with 23 connecting pins and bearing :</p> <p>- an identification marking either consisting of one of the following combination of figures or including one of those combinations :</p>	

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ex 84.55 C (suite)	<p>4598601 5121843 5121850 5121934 5121935 5122148 5123005 5123058 5123059 5123120 5123128 5123129 5123334 5123336 5123337 5123338 5123339 5123341</p> <p>or</p> <p>- other identification markings relating to assemblies complying with the abovementioned description</p>	0
ex 84.55 C	<p>Assemblies for automatic data processing machines consisting of 2 stacked substrate layers each with 2 Random Access Memories, of N-MOS technology other than dynamic, (N-MOS RAMs other than dynamic) in the form of monolithic integrated circuits each with a storage capacity of 4 Kbits and with a total storage capacity of either 16 K x 1 bit or 8 K x 2 bits contained in a housing whose exterior dimensions of not exceed 13 x 13 mm and with 24 connecting pins and bearing :</p> <p>- an identification marking either consisting of one of the following combinations of figures or including one of those combinations :</p> <p>4599766 4599767 4599768 4599769 4599770 4599771 4599772 4599773 4599774 4599893</p> <p>or</p> <p>- other identification markings relating to assemblies complying with the abovementioned description</p>	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 84.55 C	Dot matrix displays whose external dimensions do not exceed 14 x 37 x 169 mm excluding cables and connectors, consisting of a layer of liquid crystals between two sheets or plates with 2560 <i>Characters</i> (arranged in 16 lines and 160 columns) mounted on a printed circuit board comprising electronic components providing drive and control functions, with 10 or 20-core cable with connector	0
ex 84.59 B	Integrally forged, rough-turned components with unit weights of more than 200 tonnes, for reactor pressure vessels	0
ex 85.01 B II	Pulse transformers with maximum dimensions of 400 x 500 x 700 mm and weighing not more than 300 kg for the transforming of voltage from 4 KV to 60 KV at a frequency of 200 Hz with a duration of 125 microseconds	0
ex 85.03	Dry zinc/carbon batteries of a voltage of not less than 5.5 and not more than 6.5 and of a size not exceeding 110 x 90 x 5 mm, for incorporation in film cassettes for instant pictures (a)	0
ex 85.21 A V	Colour cathode-ray tubes, using shadow mask, in-line technology in which images are displayed on a screen with a usable surface not exceeding 165 x 165 mm for use in electronic flight instrument, warning and systems displays (a)	0
ex 85.21 A V	Digital displays in the form of a tube consisting of a glass housing mounted on a board whose dimensions do not exceed 350 x 300 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallized base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0
ex 85.21 D II	<p>Static random access memories of N-MOS technology (N-MOS S-RAMS) in the form of a monolithic integrated circuit consisting of 2 stacked substrate layers, each with two chips each having a storage capacity of 2 K bits and with a total storage capacity of 8 K x 1 bit or 4 K x 2 bits, contained in a housing whose exterior dimensions do not exceed 13 x 13 mm, with 23 connecting pins and bearing :</p> <p>- an identification marking either consisting of one of the following combinations of figures or including one of those combinations :</p>	

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II (suite)	4598601 5121843 5121850 5121934 5121935 5122148 5123005 5123058 5123059 5123120 5123128 5123129 5123334 5123336 5123337 5123338 5123339 5123341	
	or - other identification markings relating to N-MOS S-RAMS complying with the above-mentioned descriptions	0
ex 85.21 D II	"Quasi-static" random access memories of N-MOS technology (N-MOS Quasi static RAMS) in the form of a monolithic integrated circuit consisting of two stacked substrate layers each with 2 chips each having a storage capacity of 4 K bits and with a total storage capacity of 16 K x 1 bit or K K x 2 bits contained in a housing whose exterior dimensions do not exceed 13 x 13 mm and with 24 connecting pins and bearing : - an identification marking consisting of one of the undermentioned numerical combinations or containing one of these combinations as constituent part : 4599766 4599767 4599768 4599769 4599770 4599771 4599772 4599773 4599774 4599893	
	or - other identification markings relating to Quasi-static RAMS complying with the above-mentioned description	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	Digital displays of a size not exceeding 25 x 35 mm, consisting of a printed circuit board on which are mounted, under a transparent plastic cover, up to 22 light-emitting diodes manufactured from gallium-based semi-conductor compounds. Each display consists of a single character with or without a plus or minus sign and/or one or two dots	0
ex 85.21 D II	Digital displays, consisting of a printed circuit board of a size not exceeding 35 X 90 mm with a single line of characters not less than three in number comprising light-emitting diodes made from gallium-based semi-conductor compounds mounted thereon. Each character is composed of up to eight segments and the line of characters has a protective cover of transparent plastic	0
ex 85.21 D II	Digital displays, consisting of a printed circuit board of a size not exceeding 35 x 90 mm, with a single line of digits, not less than three in number, comprising light-emitting diodes manufactured from gallium-based semi-conductor compounds mounted thereon. Each digit is composed of seven segments plus a decimal point and the line of digits has a protective cover of transparent plastic	0

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Programmable, non-erasable, read only memories (PROMS) of Schottky TTL technology, with a storage capacity of 1 K bit, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 9 × 23 mm, with 16 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>14 S 10 24 S 10 24 SA 10 247 A 10 27 S 20 27 S 21 29760 29761 38510 5300 5301 53 S 140 53 S 141 54 S 287 54 S 387 54700 5603 5623 6300 6301 63 S 140 63 S 141 7052 7057 74 S 287 74 S 387 7610 7611 82 S 126 82 S 129 8520 8521 93417 93427</p> <p>or</p> <p>— other identification markings relating to PROMS complying with the abovementioned description</p>	11.5

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Programmable, non-erasable, read only memories (PROMS) of Schottky TTL technology, with a storage capacity of 2 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with not more than 24 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>27 S 12 27 S 13 28 L 22 28 LA 22 29613 29770 29771 38510 5305 5306 5308 5309 53 S 240 53 S 241 54 S 570 54 S 571 5604 5624 6305 6306 6308 6309 63 S 240 63 S 241 6335 6336 7053 7058 74 S 570 74 S 571 76 LS 03 7620 7621 82 S 114 82 S 130 82 S 131 93436 93446</p> <p>or</p> <p>— other identification markings relating to PROMS complying with the abovementioned description</p>	11.5

CCT heading No	Description	Rate of autonomous duty (%)																																																																																																																																																						
ex 85.21 D II	<p>Programmable, non-erasable, read only memories (PROMS), with a storage capacity of 4 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with not more than 24 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <table data-bbox="465 532 975 1882"> <tr><td>18 S 42</td><td>38510</td><td>7121</td></tr> <tr><td>18 S 46</td><td></td><td>7122</td></tr> <tr><td>18 SA 42</td><td></td><td>7123 ← 7124</td></tr> <tr><td>18 SA 46</td><td>5340</td><td>7125</td></tr> <tr><td></td><td>5341</td><td>7126</td></tr> <tr><td></td><td>53 S 440</td><td></td></tr> <tr><td>24 S 41</td><td>53 RA 441</td><td></td></tr> <tr><td>24 SA 41</td><td>53 RS 441</td><td>74 S 472</td></tr> <tr><td></td><td>53 S 441</td><td>74 S 473</td></tr> <tr><td></td><td>5348</td><td>74 S 474</td></tr> <tr><td>27 S 15</td><td>5349</td><td>74 S 475</td></tr> <tr><td>27 S 26</td><td>5350</td><td>74 S 476</td></tr> <tr><td>27 S 27</td><td>5351</td><td>74 S 477</td></tr> <tr><td>27 S 28</td><td>5352</td><td>74 S 572</td></tr> <tr><td>27 S 29</td><td>5353</td><td>74 S 573</td></tr> <tr><td>27 S 30</td><td></td><td></td></tr> <tr><td>27 S 31</td><td></td><td></td></tr> <tr><td>27 S 32</td><td>54 S 472</td><td>7640</td></tr> <tr><td>27 S 33</td><td>54 S 473</td><td>7641</td></tr> <tr><td></td><td>54 S 474</td><td>7642</td></tr> <tr><td></td><td>54 S 475</td><td>7643</td></tr> <tr><td>28 L 42</td><td>54 S 476</td><td>7644</td></tr> <tr><td>28 L 45</td><td>54 S 477</td><td>7645</td></tr> <tr><td>28 P 42</td><td>54 S 572</td><td>7647</td></tr> <tr><td>28 P 45</td><td>54 S 573</td><td>7648</td></tr> <tr><td>28 R 45</td><td>54740</td><td>7649</td></tr> <tr><td></td><td>54741</td><td></td></tr> <tr><td>28 SA 41</td><td></td><td>82 HS 137</td></tr> <tr><td>28 S 42</td><td>5605</td><td>82 HS 147</td></tr> <tr><td>28 SA 42</td><td>5625</td><td></td></tr> <tr><td>28 S 45</td><td></td><td></td></tr> <tr><td>28 S 46</td><td></td><td>82 S 115</td></tr> <tr><td>28 SA 46</td><td>6340</td><td>82 S 136</td></tr> <tr><td></td><td>6341</td><td>82 S 137</td></tr> <tr><td></td><td>63 S 440</td><td>82 S 140</td></tr> <tr><td>29620</td><td>63 RA 441</td><td>82 S 141</td></tr> <tr><td>29621</td><td>63 RS 441</td><td>82 S 142</td></tr> <tr><td>29622</td><td>63 S 441</td><td>82 S 146</td></tr> <tr><td>29623</td><td>6348</td><td>82 S 147</td></tr> <tr><td>29624</td><td>6349</td><td></td></tr> <tr><td>29625</td><td>6350</td><td></td></tr> <tr><td>29626</td><td>6351</td><td>93438</td></tr> <tr><td>29627</td><td>6352</td><td>93448</td></tr> <tr><td></td><td>6353</td><td>93452</td></tr> <tr><td></td><td></td><td>93453</td></tr> <tr><td>3604</td><td></td><td></td></tr> <tr><td>3624</td><td>HM 6641</td><td></td></tr> <tr><td>3625</td><td></td><td></td></tr> <tr><td></td><td>7054</td><td></td></tr> <tr><td></td><td>7059</td><td></td></tr> </table> <p>or</p> <p>— other identification markings relating to PROMS complying with the abovementioned description</p>	18 S 42	38510	7121	18 S 46		7122	18 SA 42		7123 ← 7124	18 SA 46	5340	7125		5341	7126		53 S 440		24 S 41	53 RA 441		24 SA 41	53 RS 441	74 S 472		53 S 441	74 S 473		5348	74 S 474	27 S 15	5349	74 S 475	27 S 26	5350	74 S 476	27 S 27	5351	74 S 477	27 S 28	5352	74 S 572	27 S 29	5353	74 S 573	27 S 30			27 S 31			27 S 32	54 S 472	7640	27 S 33	54 S 473	7641		54 S 474	7642		54 S 475	7643	28 L 42	54 S 476	7644	28 L 45	54 S 477	7645	28 P 42	54 S 572	7647	28 P 45	54 S 573	7648	28 R 45	54740	7649		54741		28 SA 41		82 HS 137	28 S 42	5605	82 HS 147	28 SA 42	5625		28 S 45			28 S 46		82 S 115	28 SA 46	6340	82 S 136		6341	82 S 137		63 S 440	82 S 140	29620	63 RA 441	82 S 141	29621	63 RS 441	82 S 142	29622	63 S 441	82 S 146	29623	6348	82 S 147	29624	6349		29625	6350		29626	6351	93438	29627	6352	93448		6353	93452			93453	3604			3624	HM 6641		3625				7054			7059		0
18 S 42	38510	7121																																																																																																																																																						
18 S 46		7122																																																																																																																																																						
18 SA 42		7123 ← 7124																																																																																																																																																						
18 SA 46	5340	7125																																																																																																																																																						
	5341	7126																																																																																																																																																						
	53 S 440																																																																																																																																																							
24 S 41	53 RA 441																																																																																																																																																							
24 SA 41	53 RS 441	74 S 472																																																																																																																																																						
	53 S 441	74 S 473																																																																																																																																																						
	5348	74 S 474																																																																																																																																																						
27 S 15	5349	74 S 475																																																																																																																																																						
27 S 26	5350	74 S 476																																																																																																																																																						
27 S 27	5351	74 S 477																																																																																																																																																						
27 S 28	5352	74 S 572																																																																																																																																																						
27 S 29	5353	74 S 573																																																																																																																																																						
27 S 30																																																																																																																																																								
27 S 31																																																																																																																																																								
27 S 32	54 S 472	7640																																																																																																																																																						
27 S 33	54 S 473	7641																																																																																																																																																						
	54 S 474	7642																																																																																																																																																						
	54 S 475	7643																																																																																																																																																						
28 L 42	54 S 476	7644																																																																																																																																																						
28 L 45	54 S 477	7645																																																																																																																																																						
28 P 42	54 S 572	7647																																																																																																																																																						
28 P 45	54 S 573	7648																																																																																																																																																						
28 R 45	54740	7649																																																																																																																																																						
	54741																																																																																																																																																							
28 SA 41		82 HS 137																																																																																																																																																						
28 S 42	5605	82 HS 147																																																																																																																																																						
28 SA 42	5625																																																																																																																																																							
28 S 45																																																																																																																																																								
28 S 46		82 S 115																																																																																																																																																						
28 SA 46	6340	82 S 136																																																																																																																																																						
	6341	82 S 137																																																																																																																																																						
	63 S 440	82 S 140																																																																																																																																																						
29620	63 RA 441	82 S 141																																																																																																																																																						
29621	63 RS 441	82 S 142																																																																																																																																																						
29622	63 S 441	82 S 146																																																																																																																																																						
29623	6348	82 S 147																																																																																																																																																						
29624	6349																																																																																																																																																							
29625	6350																																																																																																																																																							
29626	6351	93438																																																																																																																																																						
29627	6352	93448																																																																																																																																																						
	6353	93452																																																																																																																																																						
		93453																																																																																																																																																						
3604																																																																																																																																																								
3624	HM 6641																																																																																																																																																							
3625																																																																																																																																																								
	7054																																																																																																																																																							
	7059																																																																																																																																																							

CCT heading No	Description	Rate of autonomous duty (%)																																																																																																																																																																																																				
ex 85.21 D II	<p>Programmable, non-erasable, read only memories (PROMS), with a storage capacity of 8 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with not more than 24 connecting pins or 28 contact areas, and bearing:</p>																																																																																																																																																																																																					
	<p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p>																																																																																																																																																																																																					
	<table border="0"> <tr> <td>24 S 81</td> <td>6380</td> <td>82707</td> <td></td> </tr> <tr> <td>24 SA 81</td> <td>6381</td> <td>82708</td> <td>82 HS 185</td> </tr> <tr> <td>24 S 86</td> <td>6388</td> <td>82 LS 180</td> <td></td> </tr> <tr> <td></td> <td>6389</td> <td>82 LS 181</td> <td></td> </tr> <tr> <td></td> <td>63 S 840</td> <td>82 S 180</td> <td></td> </tr> <tr> <td>27 S 180</td> <td>63 S 841</td> <td>82 S 181</td> <td></td> </tr> <tr> <td>27 S 181</td> <td></td> <td>82 S 182</td> <td></td> </tr> <tr> <td>27 S 185</td> <td></td> <td>82 S 183</td> <td></td> </tr> <tr> <td></td> <td>7050</td> <td>82 S 184</td> <td></td> </tr> <tr> <td>28 L 85</td> <td>7055</td> <td>82 S 185</td> <td></td> </tr> <tr> <td>28 L 86</td> <td>7060</td> <td>82 S 2708</td> <td></td> </tr> <tr> <td>28 P 85</td> <td>7127</td> <td></td> <td></td> </tr> <tr> <td>28 R 85</td> <td>7128</td> <td>87 S 180</td> <td></td> </tr> <tr> <td>28 S 2708</td> <td>7129</td> <td>87 S 181</td> <td></td> </tr> <tr> <td>28 S 85</td> <td>7130</td> <td>87 S 184</td> <td></td> </tr> <tr> <td>28 S 86</td> <td>7131</td> <td>87 S 185</td> <td></td> </tr> <tr> <td>28 SA 86</td> <td>7132</td> <td>87 S 186</td> <td></td> </tr> <tr> <td>28 R 35</td> <td></td> <td>87 S 187</td> <td></td> </tr> <tr> <td>28 SS 35</td> <td></td> <td></td> <td></td> </tr> <tr> <td>29623</td> <td>74 LS 478</td> <td></td> <td></td> </tr> <tr> <td>29630</td> <td>74 S 2708</td> <td>93450</td> <td></td> </tr> <tr> <td>29631</td> <td>74 S 454</td> <td>93451</td> <td></td> </tr> <tr> <td>29632</td> <td>74 S 455</td> <td>93460</td> <td></td> </tr> <tr> <td>29633</td> <td>74 S 478</td> <td>93461</td> <td></td> </tr> <tr> <td>29634</td> <td>74 S 479</td> <td>93465</td> <td></td> </tr> <tr> <td>29635</td> <td></td> <td>93466</td> <td></td> </tr> <tr> <td>29636</td> <td></td> <td>93 L 450</td> <td></td> </tr> <tr> <td>29637</td> <td>7608</td> <td>93 L 451</td> <td></td> </tr> <tr> <td>29650</td> <td>7680</td> <td></td> <td></td> </tr> <tr> <td>29651</td> <td>7681</td> <td></td> <td></td> </tr> <tr> <td>29652</td> <td>7684</td> <td>9460</td> <td></td> </tr> <tr> <td>29653</td> <td>7685</td> <td></td> <td></td> </tr> <tr> <td></td> <td>7686</td> <td></td> <td></td> </tr> <tr> <td></td> <td>7687</td> <td></td> <td></td> </tr> <tr> <td>3628</td> <td>7688</td> <td></td> <td></td> </tr> <tr> <td></td> <td>7689</td> <td></td> <td></td> </tr> <tr> <td>5380</td> <td></td> <td></td> <td></td> </tr> <tr> <td>5381</td> <td>77 S 180</td> <td></td> <td></td> </tr> <tr> <td>5388</td> <td>77 S 181</td> <td></td> <td></td> </tr> <tr> <td>5389</td> <td>77 S 184</td> <td></td> <td></td> </tr> <tr> <td>53 S 840</td> <td>77 S 185</td> <td></td> <td></td> </tr> <tr> <td>53 S 841</td> <td>77 S 186</td> <td></td> <td></td> </tr> <tr> <td></td> <td>77 S 187</td> <td></td> <td></td> </tr> <tr> <td>54 LS 478</td> <td></td> <td></td> <td></td> </tr> <tr> <td>54 S 2708</td> <td>TBPS 81 M</td> <td></td> <td></td> </tr> <tr> <td>54 S 454</td> <td></td> <td></td> <td></td> </tr> <tr> <td>54 S 455</td> <td></td> <td></td> <td></td> </tr> <tr> <td>54 S 478</td> <td></td> <td></td> <td></td> </tr> <tr> <td>54 S 479</td> <td></td> <td></td> <td></td> </tr> </table>	24 S 81	6380	82707		24 SA 81	6381	82708	82 HS 185	24 S 86	6388	82 LS 180			6389	82 LS 181			63 S 840	82 S 180		27 S 180	63 S 841	82 S 181		27 S 181		82 S 182		27 S 185		82 S 183			7050	82 S 184		28 L 85	7055	82 S 185		28 L 86	7060	82 S 2708		28 P 85	7127			28 R 85	7128	87 S 180		28 S 2708	7129	87 S 181		28 S 85	7130	87 S 184		28 S 86	7131	87 S 185		28 SA 86	7132	87 S 186		28 R 35		87 S 187		28 SS 35				29623	74 LS 478			29630	74 S 2708	93450		29631	74 S 454	93451		29632	74 S 455	93460		29633	74 S 478	93461		29634	74 S 479	93465		29635		93466		29636		93 L 450		29637	7608	93 L 451		29650	7680			29651	7681			29652	7684	9460		29653	7685				7686				7687			3628	7688				7689			5380				5381	77 S 180			5388	77 S 181			5389	77 S 184			53 S 840	77 S 185			53 S 841	77 S 186				77 S 187			54 LS 478				54 S 2708	TBPS 81 M			54 S 454				54 S 455				54 S 478				54 S 479				
24 S 81	6380	82707																																																																																																																																																																																																				
24 SA 81	6381	82708	82 HS 185																																																																																																																																																																																																			
24 S 86	6388	82 LS 180																																																																																																																																																																																																				
	6389	82 LS 181																																																																																																																																																																																																				
	63 S 840	82 S 180																																																																																																																																																																																																				
27 S 180	63 S 841	82 S 181																																																																																																																																																																																																				
27 S 181		82 S 182																																																																																																																																																																																																				
27 S 185		82 S 183																																																																																																																																																																																																				
	7050	82 S 184																																																																																																																																																																																																				
28 L 85	7055	82 S 185																																																																																																																																																																																																				
28 L 86	7060	82 S 2708																																																																																																																																																																																																				
28 P 85	7127																																																																																																																																																																																																					
28 R 85	7128	87 S 180																																																																																																																																																																																																				
28 S 2708	7129	87 S 181																																																																																																																																																																																																				
28 S 85	7130	87 S 184																																																																																																																																																																																																				
28 S 86	7131	87 S 185																																																																																																																																																																																																				
28 SA 86	7132	87 S 186																																																																																																																																																																																																				
28 R 35		87 S 187																																																																																																																																																																																																				
28 SS 35																																																																																																																																																																																																						
29623	74 LS 478																																																																																																																																																																																																					
29630	74 S 2708	93450																																																																																																																																																																																																				
29631	74 S 454	93451																																																																																																																																																																																																				
29632	74 S 455	93460																																																																																																																																																																																																				
29633	74 S 478	93461																																																																																																																																																																																																				
29634	74 S 479	93465																																																																																																																																																																																																				
29635		93466																																																																																																																																																																																																				
29636		93 L 450																																																																																																																																																																																																				
29637	7608	93 L 451																																																																																																																																																																																																				
29650	7680																																																																																																																																																																																																					
29651	7681																																																																																																																																																																																																					
29652	7684	9460																																																																																																																																																																																																				
29653	7685																																																																																																																																																																																																					
	7686																																																																																																																																																																																																					
	7687																																																																																																																																																																																																					
3628	7688																																																																																																																																																																																																					
	7689																																																																																																																																																																																																					
5380																																																																																																																																																																																																						
5381	77 S 180																																																																																																																																																																																																					
5388	77 S 181																																																																																																																																																																																																					
5389	77 S 184																																																																																																																																																																																																					
53 S 840	77 S 185																																																																																																																																																																																																					
53 S 841	77 S 186																																																																																																																																																																																																					
	77 S 187																																																																																																																																																																																																					
54 LS 478																																																																																																																																																																																																						
54 S 2708	TBPS 81 M																																																																																																																																																																																																					
54 S 454																																																																																																																																																																																																						
54 S 455																																																																																																																																																																																																						
54 S 478																																																																																																																																																																																																						
54 S 479																																																																																																																																																																																																						
	or																																																																																																																																																																																																					
	<p>— other identification markings relating to PROMS complying with the abovementioned description</p>																																																																																																																																																																																																					

CCT heading No	Description	Rate of autonomous duty (%)																																								
ex 85.21 D II	<p>Programmable, non-erasable, read only memories (PROMS), with a storage capacity of 16 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with not more than 24 connecting pins or 28 contact areas, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <table data-bbox="458 619 783 1084"> <tr><td>TBP 28 L 166</td><td>HM 76 16-5</td></tr> <tr><td>TBP 28 P 166</td><td>DM 77 S 190</td></tr> <tr><td>TBP 28 R 166</td><td>DM 77 S 191</td></tr> <tr><td>TBP 28 S 166</td><td>MM 82 S 191</td></tr> <tr><td>29681</td><td>SM 82 S 190</td></tr> <tr><td>29681 A</td><td>S 82 S 190</td></tr> <tr><td>29683</td><td>MM 82 S 191</td></tr> <tr><td>29683 A</td><td>SM 82 S 191</td></tr> <tr><td>3636</td><td>N 82 S 191</td></tr> <tr><td>3636-1</td><td>S 82 S 191</td></tr> <tr><td>M 36 36</td><td>DM 87 S 190</td></tr> <tr><td></td><td>DM 87 S 191</td></tr> <tr><td>53 S 1641</td><td>93 510 C</td></tr> <tr><td>53 LS 1681</td><td>93 510 M</td></tr> <tr><td>53 PS 1681</td><td>93 511 C</td></tr> <tr><td>53 S 1681</td><td>93 511 M</td></tr> <tr><td>63 S 1641</td><td></td></tr> <tr><td>63 LS 1681</td><td></td></tr> <tr><td>63 PS 1681</td><td></td></tr> <tr><td>63 S 1681</td><td></td></tr> </table> <p>7134 7136 7137 7138 HM 76 160-2 HM 76 160-5 HM 76 161-2 HM 76 161-5 HM 76 16-2</p> <p>or</p> <p>— other identification marking relating to PROMS complying with the abovementioned description</p>	TBP 28 L 166	HM 76 16-5	TBP 28 P 166	DM 77 S 190	TBP 28 R 166	DM 77 S 191	TBP 28 S 166	MM 82 S 191	29681	SM 82 S 190	29681 A	S 82 S 190	29683	MM 82 S 191	29683 A	SM 82 S 191	3636	N 82 S 191	3636-1	S 82 S 191	M 36 36	DM 87 S 190		DM 87 S 191	53 S 1641	93 510 C	53 LS 1681	93 510 M	53 PS 1681	93 511 C	53 S 1681	93 511 M	63 S 1641		63 LS 1681		63 PS 1681		63 S 1681		4
TBP 28 L 166	HM 76 16-5																																									
TBP 28 P 166	DM 77 S 190																																									
TBP 28 R 166	DM 77 S 191																																									
TBP 28 S 166	MM 82 S 191																																									
29681	SM 82 S 190																																									
29681 A	S 82 S 190																																									
29683	MM 82 S 191																																									
29683 A	SM 82 S 191																																									
3636	N 82 S 191																																									
3636-1	S 82 S 191																																									
M 36 36	DM 87 S 190																																									
	DM 87 S 191																																									
53 S 1641	93 510 C																																									
53 LS 1681	93 510 M																																									
53 PS 1681	93 511 C																																									
53 S 1681	93 511 M																																									
63 S 1641																																										
63 LS 1681																																										
63 PS 1681																																										
63 S 1681																																										
ex 85.21 D II	<p>Electronic, programmable, read only memories (EPROMS) UV erasable, with a storage capacity of 2 K bits in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with a quartz window on the upper surface, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures and letters or including one of those combinations:</p> <p>B 1702 A AMI 702 ADC 82140 PP</p> <p>or</p> <p>— other identification markings relating to EPROMS complying with the abovementioned description</p>	0																																								

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Electronic, programmable, read only memories (EPROMS) UV erasable, with a storage capacity of 32 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with a quartz window on the upper surface, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>2532 25 A 32 25 L 32</p> <p>2732</p> <p>68732 68 L 732</p> <p>or</p> <p>— other identification markings relating to EPROMS complying with the abovementioned description</p>	8.5
ex 85.21 D II	<p>Electronic, programmable, read only memories (EPROMS) UV erasable, with a storage capacity of 64 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with a quartz window on the upper surface, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p>2564 2764</p> <p>68 L 64 68764 68 A 764 68 L 764 68766</p> <p>or</p> <p>— other identification markings relating to EPROMS complying with the abovementioned description</p>	11.5

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Dynamic random access memories (D-RAMS) with a storage capacity of 16 K × 4 bits, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 9 × 24 mm with 18 connecting pins, and bearing:</p> <ul style="list-style-type: none"> — an identification marking either consisting of one of the following combinations of figures and letters or including one of those combinations: IMS 2620. TMS 4416 or — other identification markings relating to D-RAMS complying with the above-mentioned description 	12
ex 85.21 D II	<p>Static random access memories of N-MOS technology (N-MOS S-RAMS), with a storage capacity of 256 × 4 bits in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with not more than 24 connecting pins, and bearing:</p> <ul style="list-style-type: none"> — an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: M 120 8101 2101 8111 21 H 01 2102 9101 2111 91 L 01 21 H 11 9111 2112 91 L 11 21 H 12 9112 91 L 12 or — other identification markings relating to N-MOS S-RAMS complying with the abovementioned descriptions 	0
ex 85.21 D II	<p>Static random access memories of N-MOS technology (N-MOS S-RAMS), with a storage capacity of 8 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with not more than 24 connecting pins, and bearing:</p> <ul style="list-style-type: none"> — an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: 4008 8104 4118 8108 PD 421 8112 4801 8114 8185 or — Other identification markings relating to N-MOS-RAMS complying with the abovementioned description 	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Static random access memories of N-MOS technology (N-MOS S-RAMS), with a storage capacity of 2 K × 8 bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with 24 connecting pins or not more than 32 contact areas and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <p style="margin-left: 40px;">MCM 2016 TMM 2016 2128 3528 TMS 4016 4802 58725 8128</p> <p style="margin-left: 40px;">or</p> <p>— other identification markings relating to N-MOS S-RAMS complying with the abovementioned description</p>	8.5
ex 85.21 D II	<p>Static random access memories of C-MOS technology (C-MOS S-RAMS) with a storage capacity of 64 K bits in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 18 × 39 mm, with not more than 28 connecting pins and bearing :</p> <p>- an identification marking, consisting of the following combination of figures and letters or including this combination :</p> <p style="margin-left: 40px;">TC 5564 TC 5565 HM 6264P-15 MB 8464</p> <p style="margin-left: 40px;">or</p> <p>- other identification markings relating to C-MOS S-RAMS complying with the abovementioned description</p>	0

CCT heading No	Description	Rate of autonomous duty (%)																						
ex 85.21 D II	<p>Static random access memory of TTL technology (TTL-S-RAM), with a storage capacity of 1 K bit, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 16 × 30 mm, with not more than 22 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:</p> <table data-bbox="439 607 716 864"> <tr><td>2205</td><td>93412</td></tr> <tr><td>2510</td><td>93 L 412</td></tr> <tr><td>2511</td><td>93415</td></tr> <tr><td>74 LS 214</td><td>93 L 415</td></tr> <tr><td>74 LS 215</td><td>93422</td></tr> <tr><td>74 LS 314</td><td>93 L 422</td></tr> <tr><td>74 LS 315</td><td>93425</td></tr> <tr><td>74 S 207</td><td>93 F 425</td></tr> <tr><td>74 S 208</td><td>93 L 425</td></tr> <tr><td>74 S 214</td><td></td></tr> <tr><td>74 S 314</td><td></td></tr> </table> <p>or</p> <p>— other identification markings relating to TTL-S-RAMS complying with the abovementioned description</p>	2205	93412	2510	93 L 412	2511	93415	74 LS 214	93 L 415	74 LS 215	93422	74 LS 314	93 L 422	74 LS 315	93425	74 S 207	93 F 425	74 S 208	93 L 425	74 S 214		74 S 314		0
2205	93412																							
2510	93 L 412																							
2511	93415																							
74 LS 214	93 L 415																							
74 LS 215	93422																							
74 LS 314	93 L 422																							
74 LS 315	93425																							
74 S 207	93 F 425																							
74 S 208	93 L 425																							
74 S 214																								
74 S 314																								
ex 85.21 D II	<p>Single-chip microcomputer, in the form of a monolithic integrated circuit, consisting of an arithmetical unit with a capacity of 4 bits plus a read only memory (ROM) with a capacity of not less than 18 K bits and not more than 65 K bits and a random access memory (RAM) with a capacity of not less than 512 bits and not more than 4 K bits, contained in a housing whose exterior dimensions do not exceed 16 × 54 mm, with not more than 42 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures and letters or including one of those combinations:</p> <table data-bbox="439 1390 916 1510"> <tr><td>CD 3200 to 3299</td><td>TMC 1980 to 1999</td></tr> <tr><td>TMC 0270 to 0279</td><td>TP 0310 to 03299</td></tr> <tr><td>TMC 0500 to 0599</td><td>TP 0450 to 04599</td></tr> <tr><td>TMC 0980 to 0989</td><td>TP 0480 to 04899</td></tr> <tr><td>TMC 1500 to 1599</td><td>TP 0500 to 05999</td></tr> </table> <p>or</p> <p>— other identification markings relating to single-chip microcomputers complying with the abovementioned description</p>	CD 3200 to 3299	TMC 1980 to 1999	TMC 0270 to 0279	TP 0310 to 03299	TMC 0500 to 0599	TP 0450 to 04599	TMC 0980 to 0989	TP 0480 to 04899	TMC 1500 to 1599	TP 0500 to 05999	0												
CD 3200 to 3299	TMC 1980 to 1999																							
TMC 0270 to 0279	TP 0310 to 03299																							
TMC 0500 to 0599	TP 0450 to 04599																							
TMC 0980 to 0989	TP 0480 to 04899																							
TMC 1500 to 1599	TP 0500 to 05999																							
ex 85.21 D II	<p>Single-chip microcomputer, in the form of a monolithic integrated circuit, consisting of an arithmetical unit with a capacity of 8 bits, a 12 bit timer, an internal clock, a read only memory (ROM) with a capacity of 32 K bits and a random access memory (RAM) with a capacity of 1 K bit, with 48 input/output gates and contained in a housing whose exterior dimensions do not exceed 16.5 × 42 mm, with 64 connecting pins, and bearing:</p>																							

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>P-MOS 12/24-hour clock circuit, incorporating an elapsed time facility, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 53 × 14 mm, with 40 connecting pins, for the manufacture of instrument panel clocks and clocks of a similar type for motor vehicles (a), and bearing:</p> <p>— an identification marking either consisting of the following combination of figures and letters or including this combination:</p> <p style="padding-left: 40px;">MM 53124</p> <p style="padding-left: 40px;">or</p> <p>— other identification markings relating to clock circuits complying with the abovementioned description</p>	0
ex 85.21 D II	<p>C-MOS clock circuits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 16 × 54 mm, with not more than 42 connecting pins, for the production of automatic time-switches, instrument panel clocks and clocks of a similar type for motor vehicles (a).</p> <p>The case bears:</p> <p>— an identification marking either consisting of one of the following combinations of figures and letters or including one of these combinations:</p> <p style="padding-left: 40px;">HI 2060 HI 2065 T 3605</p> <p style="padding-left: 40px;">or</p> <p>— other identification markings relating to clock circuits complying with the abovementioned description</p>	0
ex 85.21 D II	<p>C-MOS clock circuits, operating from a single 1.55 V power supply, with a liquid crystal display (LCD) driver, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 15 X 21 mm, with not more than 56 connecting pins and bearing :</p> <p>- an identification marking either consisting of one of the following combinations of figures and letters or including one of these combinations :</p> <p style="padding-left: 40px;">TC 8219 AF</p> <p>or</p> <p>- other identification markings relating to clock circuits complying with the abovementioned description</p>	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)																		
ex 85.21 D II	<p>Monolithic integrated circuit, consisting of eight independent elements capable of controlling the eight segments and/or characters of fluorescent or gas discharge displays, contained in a housing whose exterior dimensions do not exceed 7 x 23 mm, with 18 connecting pins, and bearing:</p> <p>— an identification marking either consisting of one of the following combinations of figures or including one of those combinations:</p> <p>513 514 534 594 6118 6128 6138</p> <p>or</p> <p>— other identification markings relating to circuits complying with the abovementioned description</p>	0																		
ex 85.21 D II	<p>Programmable, non-erasable, logic circuit (Field Programmable Logic Array) of TTL Schottky technology, with max. 48 AND functions and max eight OR functions and max. 16 inputs, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with max. 28 connecting pins and bearing :</p> <p>- an identification marking consisting of one of the following combinations of figures or figures and letters</p> <table data-bbox="374 1401 982 1596"> <tr> <td>82 S 100</td> <td>EP 54 AS 899</td> <td>FP 74 AS 839</td> </tr> <tr> <td>82 S 101</td> <td>FP 54 AS 840</td> <td>FP 74 AS 840</td> </tr> <tr> <td>93 458</td> <td>SN 54 LS 333</td> <td>SN 74 LS 333</td> </tr> <tr> <td>93 459</td> <td>SN 54 LS 334</td> <td>SN 74 LS 334</td> </tr> <tr> <td></td> <td>SN 54 LS 335</td> <td>SN 74 LS 335</td> </tr> <tr> <td></td> <td>SN 54 LS 336</td> <td>SN 74 LS 336</td> </tr> </table> <p>or</p> <p>- other identification markings relating to programmable logic arrays complying with the abovementioned description</p>	82 S 100	EP 54 AS 899	FP 74 AS 839	82 S 101	FP 54 AS 840	FP 74 AS 840	93 458	SN 54 LS 333	SN 74 LS 333	93 459	SN 54 LS 334	SN 74 LS 334		SN 54 LS 335	SN 74 LS 335		SN 54 LS 336	SN 74 LS 336	5
82 S 100	EP 54 AS 899	FP 74 AS 839																		
82 S 101	FP 54 AS 840	FP 74 AS 840																		
93 458	SN 54 LS 333	SN 74 LS 333																		
93 459	SN 54 LS 334	SN 74 LS 334																		
	SN 54 LS 335	SN 74 LS 335																		
	SN 54 LS 336	SN 74 LS 336																		

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Arithmetic-logic unit of H-MOS technology, in the form of a monolithic integrated circuit, consisting of one 32 bit register, one 24 bit register, one 4 bit register, twelve 1 bit registers, two 16 × 24 bit service memories, one logic network performing arithmetic and logic operations, decodifying logic, an error detection and management logic, one 8 bit counter, and a timing network, contained in a housing whose exterior dimensions do not exceed 23 × 82 mm, with 64 connecting pins, and bearing:</p> <ul style="list-style-type: none"> — the identification marking ALU 0486 or — other identification markings relating to arithmetic-logic units complying with the abovementioned description 	0
ex 85.21 D II	<p>Sequence control circuit of H-MOS technology, in the form of a monolithic integrated circuit, consisting of one 32 bit register, three 16 bit registers, one 16 × 16 bit service memory, one 7 × 17 bit last in first out (LIFO) memory, one adder circuit, decodifying logic, priority logic, error detection and management logic, one 16 bit multiplexer, one 8 bit counter and a timing network, contained in a housing whose exterior dimensions do not exceed 23 × 82 mm, with 64 connecting pins, and bearing:</p> <ul style="list-style-type: none"> — the identification marking CSS 0484 or — other identification markings relating to sequence control circuits complying with the abovementioned description 	0
ex 85.21 D II	<p>Logic control circuit of H-MOS technology in the form of a monolithic integrated circuit consisting of one 7 bit register, three timers, one multiplexer, sequential and combining networks intended to perform control operations, decodifying logic, error detection and management logic and a timing network, contained in a housing whose exterior dimensions do not exceed 23 × 82 mm, with 64 connecting pins, and bearing:</p> <ul style="list-style-type: none"> — the identification marking MIC 0482 or — other identification markings relating to logic control circuits complying with the abovementioned description 	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Amplifier, in the form of a monolithic integrated analogue circuit, contained in a housing whose dimensions do not exceed 1.65 × 3.56 × 3.56 mm with not more than 10 connecting pins for use in products falling within subheading 90.19 B I (a), and bearing:</p> <ul style="list-style-type: none"> — an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: V 35 C 05 or — other identification markings relating to amplifiers complying with the abovementioned description 	0
ex 85.21 D II	<p>Direct access memory controllers of N-MOS technology (N-MOS DMA controller) in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 14 × 53 mm, with not more than 40 connecting pins, and bearing:</p> <ul style="list-style-type: none"> — an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: AM 9517 A 8237 or — other identification markings relating to N-MOS DMA controllers complying with the abovementioned description 	11.5
ex 85.21 D II	<p>Enhanced programmable communications interface (EPCI) in the form of a monolithic integrated circuit contained in a housing whose external dimensions do not exceed 37 × 15 mm, with not more than 28 connecting pins, and bearing:</p> <ul style="list-style-type: none"> — an identification marking either consisting of the following combination of figures or including that combination: 2661 or — other identification markings relating to EPCIs complying with the above description 	0
ex 85.21 D II	<p>Image sensor consisting of not less less than 128 and not more than 3 456 photosensitive areas, of a matrix linked to shift registers, amplification circuits and control circuits, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 16 × 46 mm, with a glass window on the upper surface and with not more than 24 connecting pins and bearing:</p> <ul style="list-style-type: none"> — one of the following identification markings: TC 101 TC 102 TC 103 TC 104 or — other identification markings relating to linear image sensors complying with the abovementioned description 	11.5

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Random access memories in ECL-technology (ECL-RAMs) with a storage capacity of 1 K x 4 bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 10 x 10 mm, with not more than 28 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or figures and letters <p>PB 10474</p> <p>or</p> <ul style="list-style-type: none"> - other identification markings relating to ECL-RAMs complying with the above-mentioned description 	0
ex 85.21 D II	<p>Programmable read-only memories (PROMs) with a storage capacity of 32 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with not more than 28 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or figures and letters or including one of those combinations : <p>TMS 25 P 32, TMS 27 P 32</p> <p>or</p> <ul style="list-style-type: none"> - other identification markings relating to PROMs, complying with the above-mentioned description 	0
ex 85.21 D II	<p>Read-only memories (ROMs), in the form of a monolithic integrated circuit, with a storage capacity of 16 K bits x 8, with read-register and output control, contained in a housing whose exterior dimensions do not exceed 50 x 16 mm, with not more than 40 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of one of the following combinations of figures or including one of those combinations : <p>from 62 000 to 62 999</p> <p>or</p> <ul style="list-style-type: none"> - other identification marking relating to ROMs complying with the above-mentioned description 	8,5

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Programmable read-only memories (PROMs), with a storage capacity of 64 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with not more than 28 connecting pins, and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations : TMS 25 P 64, TMS 27 P 64 or - other identification marking relating to PROMs complying with the above-mentioned description 	0
ex 85.21 D II	<p>Electronic control circuit of N-MOS technology (N-MOS ECLs) in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 53 mm, with not more than 40 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or figures and letters TMS 4500, 8203, 8207 or - other identification markings relating to N-MOS ECLs, complying with the above-mentioned description 	0
ex 85.21 D II	<p>Static random access memory in H-MOS technology (H-MOS S-RAM), with a storage capacity of 1 K x 4 bits, and access time not exceeding 70 ns, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 8 x 23 mm, with not more than 18 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or figures and letters : SY 2149 H AM 2149 TMS 2149 NEC UDP 2149 or - other identification markings relating to H-MOS S-RAMs, complying with the above-mentioned description 	8,5

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Electronic, programmable UV-erasable read-only-memory (EPROM) with a storage capacity of 128 K (16 K x 8) bits in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 16 x 36 mm, with not more than 28 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or figures 27128 or - other identification markings relating to EPROMs complying with the above-mentioned description 	0
ex 85.21 D II	<p>Electronic, programmable UV-erasable UV-erasable read-only-memory in the form of a monolithic integrated circuit ("EPROM"), with a storage capacity of 4 K x 8 bits, having an access time not exceeding 300 ns, contained in a housing whose exterior dimensions do not exceed 12 x 36 mm, a quartz window in the upper surface and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination or including this combination : 2732 A-3 or - other identification markings relating to EPROMs complying with the abovenmentioned description 	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Interface logic circuit (FSL) between floppy disc control (FDC) and the control circuit (drive) with data-recovery and precompensation logic functions in N-MOS technology in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 8.5 x 26.5 mm, with not more than 20 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or figures and letters <p style="margin-left: 40px;">W D 1691</p> <p style="margin-left: 40px;">or</p> <ul style="list-style-type: none"> - other identification markings relating to Interface logic circuits (FSLs) complying with the above-mentioned description 	0
ex 85.21 D II	<p>Dynamic random access memories of N-MOS technology (N-MOS DRAMS) with a storage capacity of 256K bits, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 17 x 34 mm with not more than 20 connecting pins, and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or figures and letters <p style="margin-left: 40px;">41245</p> <p style="margin-left: 40px;">UPD 41256 D</p> <p style="margin-left: 40px;">TMM 41257</p> <p style="margin-left: 40px;">MCM 4256 S</p> <p style="margin-left: 40px;">TMM 4256 AP</p> <p style="margin-left: 40px;">TMM 4256 P</p> <p style="margin-left: 40px;">MCM 4257 S</p> <p style="margin-left: 40px;">HM 50257</p> <p style="margin-left: 40px;">MCM 6256</p> <p style="margin-left: 40px;">82256</p> <p style="margin-left: 40px;">or</p> <ul style="list-style-type: none"> - other identification markings relating to N-MOS DRAMS complying with the above-mentioned description 	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Static Random Access Memory of Complementary MOS technology (C-MOS Static RAM) with a storage capacity of 4 K x 1 bits, a maximum access time not exceeding 70 ns and a standby mode supply current of less than 1 mA, in the form of a monolithic integrated circuit in a housing whose dimensions do not exceed 9 x 26 mm with 18 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or <i>including one of those combinations.</i> 6147 or - other identification markings relating to C-MOS Static RAMS complying with the above-mentioned description 	4
ex 85.21 D II	<p>Contention resolving Local Area Network Controller in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 51 x 16 mm with not more than 48 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or figures and letters 82586 AM 7990 or - other identification markings relating to Contention resolving Local Area Network Controllers complying with the above-mentioned description 	0

CCT heading No	Description	Rate of autonomous duty (%)																											
ex 85.21 D II	<p>Serial interface capable of implementing the data stream encoding, decoding and associated control functions for a Local Area Network, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 28 x 9 mm with not more than 24 connecting pins and bearing :</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or figures and letters <ul style="list-style-type: none"> 82501 AM 7991 or - other identification markings relating to Serial Interface devices complying with the above-mentioned description 	0																											
ex 85.21 D II	<p>Field Programmable Array Logic (PAL) of bipolar technology in the form of a monolithic integrated circuit, with fusible links, a programmable AND array, fixed OR array, not more than 20 inputs and not more than 10 outputs, whether or not with registers, contained in a housing whose dimensions do not exceed 17 x 39 mm with not more than 28 connecting pins and bearing</p> <ul style="list-style-type: none"> - an identification marking either consisting of the following combination of figures or figures and letters <table data-bbox="480 1397 908 1680" style="margin-left: 40px;"> <tbody> <tr> <td>10H8</td> <td>16L8</td> <td>18L4</td> </tr> <tr> <td>12H6</td> <td>16R8</td> <td>20L2</td> </tr> <tr> <td>14H4</td> <td>16R6</td> <td>20C1</td> </tr> <tr> <td>16H2</td> <td>16R4</td> <td>20L10</td> </tr> <tr> <td>16C1</td> <td>16X4</td> <td>20X10</td> </tr> <tr> <td>10L8</td> <td>16A4</td> <td>20X8</td> </tr> <tr> <td>12L6</td> <td>12L10</td> <td>20X4</td> </tr> <tr> <td>14L4</td> <td>14L8</td> <td></td> </tr> <tr> <td>16L2</td> <td>16L6</td> <td></td> </tr> </tbody> </table> or - other identification markings relating with PALs complying with the above-mentioned description 	10H8	16L8	18L4	12H6	16R8	20L2	14H4	16R6	20C1	16H2	16R4	20L10	16C1	16X4	20X10	10L8	16A4	20X8	12L6	12L10	20X4	14L4	14L8		16L2	16L6		5
10H8	16L8	18L4																											
12H6	16R8	20L2																											
14H4	16R6	20C1																											
16H2	16R4	20L10																											
16C1	16X4	20X10																											
10L8	16A4	20X8																											
12L6	12L10	20X4																											
14L4	14L8																												
16L2	16L6																												

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.22 C II	Electromagnetic display, consisting of seven electromagnetic coils which by means of the residual magnetism in the stators provide indefinite memory, seven pivoting light-reflecting segments each of which is attached to a bar magnet. The display is contained in a housing whose dimensions do not exceed 28 x 36 x 50 mm	0
ex 85.23 B	Hyperfrequency coaxial cables with a diameter of not less than 3 mm and not more than 12 mm, with a nominal weight of not less than 20 g/m and not more than 300 g/m	0
ex 90.02	Image reverser made up from an assembly of optical <i>filmes</i> .	0
ex 90.13	Liquid Crystals Displays consisting of a layer of liquid crystals between 2 glass sheets or plates, with a minimum of 8 and a maximum of 31 figures or letters, contained in a housing whose exterior dimensions do not exceed 25 x 154 mm, with not more than 192 contact areas and bearing : <ul style="list-style-type: none"> - an identification marking either consisting of one of the following combinatings of figures or including one of those combinations : from 1 000 000-001 to 9999999-9999 or - other identification marking relating to LCDS complying with the above-mentioned description 	0
ex 90.19 A III	Vascular prostheses of which the largest opening has an internal diameter not exceeding 8 mm	0
ex 90.19 A III	Artificial heart valves	0
ex 90.19 A III	Bioprosthetic heart valves	0
ex 90.19 B I	Receivers for hearing aids, contained in a housing whose external dimensions, including correcting points, do not exceed 3.2 x 6.5 x 4.5 mm	0
ex 90.19 B II	Reading appliances for the blind, in which a miniature camera using photo-transistors transmits letters onto a scanning board with piezo-electric pencils, and their parts and accessories	0
ex 90.20	Apparatus for the irradiation of biological samples incorporating permanently shielded caesium 137 radioactive sources, an exposure chamber whose volume does not exceed 930 cubic centimetres, an electrically driven turntable and a digital timer	0
ex 98.04 A II	Non-fibrous plastic pen-tips with an internal channel	0

- 39 -
TABLE II

CCT heading No	Description	Rate of autonomous duty (%)
ex 27.07 A I	Crude light oils containing by weight: — not less than 10 % of vinyltoluenes — not less than 10 % of indene — not less than 1 % and not more than 5 % of naphthalene	0
ex 27.13 B II	Synthetic paraffin wax having a molecular weight of not less than 460 and not more than 1 560	0
ex 27.10 B III	Mineral oil, consisting of 85 % or more of linear paraffins by weight with a chain length of 8-16 carbon atoms, and of not more than 13 % of <i>alkyl</i> benzenes by weight with a linear chain of 10-12 carbon atoms	0
ex 28.04 B	Helium	0
ex 28.13 IJ	Tellurium dioxide	0
ex 28.14 B	Iodine pentafluoride	0
ex 28.21	Chromium dioxide	0
ex 28.31 C	Lithium hypochlorite	0
ex 28.38 C	Potassium hydrogenperoxomonosulphate	0
ex 28.39 A	Potassium nitrite for the manufacture of cooling and cutting fluids used in the working of metal or metal carbides (a)	0
ex 28.40 B II	pentaCalcium hydroxide tris(orthophosphate) for use in non-ferrous metallurgy (a)	0
ex 28.42 A VI	Lithium carbonates not corresponding to the following specifications: — In the form of white powder — Containing 98.5 % or more of Li_2CO_3 and: — Less than 2 ppm of arsenic — Less than 200 ppm of calcium — Less than 200 ppm of chlorides — Less than 20 ppm of iron — Less than 150 ppm of magnesium — Less than 20 ppm of heavy metals — Less than 300 ppm of potassium — Less than 300 ppm of sodium — Less than 200 ppm of sulphates	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
28.46 A I b)	Sodium borates, anhydrous	0
ex 28.47 C	Potassium permanganate	0
ex 28.47 F	Calcium wolframate, for the manufacture of ferro-alloys or deca-ammonium 41-oxododecawolframate (ammonium paratungstate) (a)	0
ex 28.48 B III	Hydrotalcite (INN)	0
ex 28.48 B III	<i>tetra</i> -Aluminium nonamagnesium dicarbonate hexacosahydroxide hepta hydrate	0
28.51 A	Deuterium, deuterium oxide (heavy water) and other compounds of deuterium; hydrogen and compounds thereof, enriched in deuterium, mixtures and solutions containing these products (<i>EURATOM</i>)	0
ex 28.52 B	Lanthanum bromide oxide	0
ex 28.55 A	Phosphides of iron (ferro-phosphorus) containing by weight: — not less than 68 % and not more than 72 % of iron, — not less than 22 % and not more than 26 % of phosphorus, — not more than 3.5 % of silicon, of which not less than 99 % by weight is of a particle size of less than 20 micrometres; for the manufacture of varnishes or paints (a)	0
ex 28.57 A	Silane (silicon hydride)	0
ex 28.57 B	Manganese nitride containing not more than 8 % of nitrogen by weight	0
ex 29.01 C I	<i>beta</i> -Pinene	0
ex 29.01 D VII	Vinyltoluenes	0
ex 29.01 D VII	1,3-Diisopropylbenzene with a purity of not less than 94 % by weight	0
ex 29.02 A I	Carbon tetrafluoride (tetrafluoromethane)	0
ex 29.02 A II b)	1,2,3-Trichloropropenes	0
ex 29.02 A III	Vinyl bromide	0
ex 29.02 A III	1,2-Dibromoethane	4
ex 29.02 A V	Bromochloromethane	0
ex 29.02 B	1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo[12.2.1.1. ^{6,9} .0 ^{2,13} .0 ^{5,10}]octadeca-7,15-diene, for use in the manufacture of polyamide (a)	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.02 C	Di- or tetrachlorotricyclo[8.2.2.2 ^{4,7}]hexadeca-1(12),4,6,10,13,15-hexaene, mixed isomers	0
ex 29.03 A	Methanesulphonic acid	0
ex 29.03 B II	Nitromethane	0
ex 29.03 B II	1-Nitropropane	0
ex 29.03 B II	2-Nitropropane	0
ex 29.03 B II	Nitroethane	0
ex 29.03 C I	Methanesulphonyl chloride	0
ex 29.04 C I	Butane-1,3-diol	0
ex 29.04 C I	2,4,7,9-Tetramethyldec-5-yne-4,7-diol	0
ex 29.04 C V	2,2-Bis(bromomethyl)propanediol	0
ex 29.05 A II	(+)Menthol	0
ex 29.06 A IV	2-Isopropylphenol	0
ex 29.06 B V	4,4'-(2,3-Dimethyltetramethylene)dipyrocatechol, not less than 98 % pure	0
ex 29.06 B V	6,6',6"-Tri- <i>tert</i> -butyl-4,4',4"-((1-methylpropan-1-yl-3-ylidene)tri- <i>m</i> -cresol, whether or not containing toluene of crystallization	0
ex 29.06 B V	2,5-Di(<i>tert</i> -pentyl)hydroquinone	0
ex 29.07 C III	2,4-Dinitro-6-octylphenol	0
ex 29.08 A III c)	Bis(phenoxyphenoxy)benzene, mixed isomers	0
ex 29.08 A III c)	Sodium 4-(2-methylallyloxy)benzenesulphonate	0
ex 29.09 B	1,2-Epoxybutane	7
ex 29.13 A I	5-Methylhexan-2-one	0
ex 29.13 A I	3,3-Dimethylbutanone	0
ex 29.13 B I b)	Refined natural bornan-2-one(camphor)	0
ex 29.13 D I b)	3- <i>beta</i> -Hydroxy-16- <i>alpha</i> -methylpregn-5-en-20-one	6
ex 29.13 D I b)	11- <i>alpha</i> ,17,21-Trihydroxy-16- <i>beta</i> -methylpregna-1,4-diene-3,20-dione	0
ex 29.13 E	4-Methoxy-4-methylpentan-2-one	0
ex 29.13 F	1,4-Naphtoquinone	0
ex 29.13 G II	1-Chloro-3,3-dimethylbutanone	0
ex 29.14 A II c) 4	16- <i>alpha</i> ,17- <i>alpha</i> -Epoxy-20-oxopregn-5-en-3- <i>beta</i> -yl acetate	6

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.14 A II c) 4	20-Oxopregna-5,16-dien-3- <i>beta</i> -yl acetate	0
ex 29.14 A XI	2,2'-Ethylenedioxydiethyl-2-ethylbutyrate)	0
ex 29.14 B IV b)	Butyl perchlorocrotonate	0
29.15 A IV a)	Azelaic acid and sebacic acid	0
ex 29.15 B	1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride (chlorendic anhydride)	0
ex 29.15 C III	Benzene-1,2,4-tricarboxylic acid	0
ex 29.15 C III	Benzene-1,2,4-tricarboxylic acid 1,2-anhydride	0
ex 29.15 C III	Tetrachlorophthalic anhydride	0
ex 29.15 C III	Benzyl 3-isobutyryloxy-1-isopropyl-2,2-dimethylpropyl phthalate	0
ex 29.15 C III	Tetrabromophthalic anhydride	0
ex 29.16 A II	Malic acid and its salts, with an L isomer of not less than 94 %	0
ex 29.16 A VIII a)	2,2-Bis(hydroxymethyl)propionic acid	0
ex 29.16 B VI	Octadecyl 3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate	0
ex 29.16 B VI	Pentaerythritol tetrakis[3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate]	0
ex 29.16 D	Dinoprostone (INN)	0
ex 29.16 D	Alprostadil (INN)	0
ex 29.19 C	2,2-Bis(chloromethyl)trimethylene tetrakis(2-chloroethyl) phosphate)	5
ex 29.21 B II	0,0-Dioctadecyl pentaerythritol bis(phosphite)	0
ex 29.21 B II	1,1'-Dimethyl-2,2'-oxydiethylene tetraphenyl bis(phosphite)	0
ex 29.22 A III	<i>tert</i> -Butylamine	0
ex 29.22 A III	1,1,3,3-Tetramethylbutylamine	0
ex 29.22 A III	1,1-Dimethylprop-2-ynylamine	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.22 B II	<i>N,N,N',N'</i> -Tetrabutylhexamethylenediamine	0
ex 29.22 D VII	<i>N</i> -(1-Ethylpropyl)-2,6 dinitro-3,4-xylidine	7
ex 29.22 E II	1,8-Naphthylenediamine	0
ex 29.22 E II	<i>m</i> -Phenylenebis(methylamine)	0
ex 29.23 A II	Dinoprost(INN), Trometamol (INN) <i>salt.</i>	0
ex 29.23 A II	(+) -4-Dimethylamino-3-methyl-1,2-diphenylbutan-2-ol	0
ex 29.23 A II	1-Deoxy-1-(octylamino)- <u>D</u> -glucitol	0
ex 29.23 B II	Dobutamine (INN) and its salts	0
ex 29.23 D V	Tranexamic acid (INN)	0
ex 29.23 D V	<i>beta</i> -Alanine	0
ex 29.23 E	4-(2-Hydroxy-3-isopropylaminopropoxy)-2,3,6-trimethylphenyl <i>acetate</i>	0
ex 29.23 E	Methyl dopa (INN)	0
ex 29.23 E	Diethyl-1,3-benzodioxol-5-ylaminomethylenemalonate	0
ex 29.23 E	6-Acetyl 1,3-benzodioxol-5-ylammonium chloride	0
ex 29.23 E	Levodopa (INN)	0
ex 29.23 E	Nadolol (INN)	0
ex 29.25 A II	<i>N</i> -Acetyl- <u>DL</u> -valine	0
ex 29.25 A II	(3-Methacrylamidopropyl)trimethylammonium chloride	0
ex 29.25 A II	2-Acrylamido-2-methylpropanesulphonic acid	0
29.25 B II a)	Phenobarbital (INN) and its salts	11
ex 29.25 B II c)	Barbituric acid	0
ex 29.25 B III b)	2'-Benzoyl-4'-chloro- <i>N</i> -(2-hydroxypropyl)glycinanilide	0
ex 29.25 B III b)	Bendiocarb (ISO)	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.25 B III b)	3,5-Dichloro- <i>N</i> -(1,1-dimethylprop-2-ynyl)benzamide	0
ex 29.27	(-)- <u><i>N</i></u> -(<u>alpha</u> -Cyano-4-hydroxy-3-methoxy- <u>alpha</u> -methylphenethyl)acetamide	0
ex 29.27	2-(3-Phenoxyphenyl)propionitrile	0
ex 29.27	Octocrilene (INN)	0
ex 29.29	20-Hydroxyiminopregna-5,16-dien-3-yl acetate	0
ex 29.29	Carbidopa (INN)	0
ex 29.29	Robenidine hydrochloride (INN)	0
ex 29.29	<i>N,N</i> -Diethylhydroxylamine	0
ex 29.29	3,3'- <i>Bis</i> (3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)- <i>N,N'</i> -bipropionamide	0
ex 29.30	<i>O,O</i> - <i>Bis</i> (4- <i>tert</i> -butylphenyl)- <i>N</i> -cyclohexylphosphoramidothioate	0
ex 29.30	Methyl isocyanate	9
ex 29.30	Methylenedicyclohexyl di-isocyanate, mixed isomers	0
ex 29.31 B	2-Methyl-2-(methylthio)propionaldehyde oxime	0
ex 29.31 B	Thiophenol	0
ex 29.31 B	Tolnaftate (INN)	0
ex 29.31 B	2,2'-Thiodiethyl bis[3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate]	0
ex 29.31 B and ex 38.19 X	Biosynthetic peptide having the structure of the 'A' chain of human insulin, in the form of a salt of the <i>S</i> -sulphonate derivative	0
ex 29.31 B	4,4'-Sulphonyldiphenol with a purity of not less than 99.5 % by weight	0
ex 29.34 C	Crystalline dimethyltin dichloride in the form of powder, for the production of goods falling within Chapter 70 (a)	0
ex 29.34 C	2-Chloroethylphosphonic acid	7.6
ex 29.34 C	2-Diphenylphosphinobenzoic acid	0
ex 29.35 Q	2-Benzotriazol-2-yl-4-(1,1,3,3-tetramethylbutyl)phenol	0
ex 29.35 Q	2-Benzotriazol-2-yl- <i>p</i> -cresol	0
ex 29.35 Q	2,6-Di- <i>tert</i> -butyl-4-[4,6-bis(octylthio)-1,3,5-triazin-2-yl-amino]phenol	0
ex 29.35 Q and ex 30.03 A II b)	Butorphanol (INN) and its salts	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.35 Q	2,3-Dihydro-2,2-dimethylbenzofuran-7-ol	0
ex 29.35 Q	1-Ethyl-1,4-dihydro-4-oxo[1,3]dioxolo[4,5-g]cinnoline-3-carbonitrile	0
ex 29.35 Q	Diphemanil metilsulphate (INN)	0
ex 29.35 Q	Orazamide (INN)	0
ex 29.35 Q	(25 <i>R</i>)-Spirost-5-en-3- ^{SPACE} <i>beta</i> -ol (diosgenin) and its esters	0
ex 29.35 Q	Azatadine dimaleate (INN)	0
ex 29.35 Q	Amprolium hydrochloride (INN)	0
ex 29.35 Q	2-(4-Pyridyl)ethanesulphonic acid	0
ex 29.35 Q	Prifinium bromide (INN)	0
ex 29.35 Q	Glucuro lactone (INN)	0
ex 29.35 Q	2-Chlorodibenz[<i>b,f</i>][1,4]oxazepin-11(10 <i>H</i>)-one	0
ex 29.35 Q	2,3,5,6-Tetrachloropyridine	0
ex 29.35 Q	Diltiazem hydrochloride (INN)	0
ex 29.35 Q	(6 <i>R</i> ,7 <i>R</i>)-3-Acetoxyethyl-7-[(<i>R</i>)-2-formyloxy-2-phenylacetamido]-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid and its salts and esters	0
ex 29.35 Q and ex 30.03 A II b)	Buspirone hydrochloride (INN)	0
ex 29.35 Q and ex 30.03 A II b)	Encainide hydrochloride (INN)	0
ex 29.35 Q	5-Bromopyrimidine	0
ex 29.35 Q	Minoxidil (INN)	0
ex 29.35 Q	Triazolam (INN)	0
ex 29.35 Q	Diazoxide (INN)	0
ex 29.35 Q	(6 <i>R</i> ,7 <i>R</i>)-7-Amino-3-(5-methyl-1,3,4-thiadiazol-2-ylthiomethyl)-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid and its salts	0
ex 29.35 Q	Captopril (INN)	0
ex 29.35 Q	Flunixin meglumine (INN)	0
ex 29.35 Q	L-Tryptophan	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.35 Q	2-Chloro-5-trifluoromethylpyridine	0
ex 29.35 Q	Alprazolam (INN)	4.5
ex 29.35 Q	Norfloxacin (INN)	0
ex 29.35 Q	Lasalocid sodium (INN)	0
ex 29.35 Q	1-Hydroxy-4- <u>1</u> -(4-hydroxy-3-methoxycarbonyl-1-naphthyl)-3-oxo-1H,3H-benzo[de]isochromen-1-yl-6-octadecyloxy-2-nephthoic acid	0
ex 29.36	3- <u>1</u> -(7-Hexadecane-1-sulphonamidoindol-3-yl)-3-oxo-1H,3H-benzo[de]isochromen-1-ylindole-7-carboxylic acid	0
ex 29.36	Quinethazone (INN)	0
ex 29.36	Sulfaguanidine (INN)	0
ex 29.36	Sulfathiazole (INN)	0
ex 29.36	4-Chloro-5-sulphamoylanthranil- <i>o</i> -toluidide	0
ex 29.38 A	Nicotinic acid (INN)	0
ex 29.38 B II	Panthenol (INN)	0
ex 29.38 B III	Folic acid (INN)	0
ex 29.38 B V	Nicotinamide (INN)	0
ex 29.39 C I	Serum gonadotrophin (INN)	0
ex 29.39 D II	Betamethasone 17,21-dipropionate (INN)	0
ex 29.39 D II	Triamcinolone hexacetonide (INN)	6.6
ex 29.39 D II	Diflorasone di(acetate) (INN)	0
ex 29.39 E	Calcitonin (INN), salmon-type and its salts	0
ex 29.39 E	Prasterone (INN)	0
ex 29.39 E	Calcitonin (INN), porcine	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.42 C VII	(22R,25R)-Tomat-5-enin-3-beta-ol (Solasodine)	0
ex 29.42 C VII and ex 30.03 A II b)	Vindesine sulphate (INN)	0
ex 29.43 B	Ribose	0
ex 29.43 B	Sucralfate (INN)	0
ex 29.44 A	Epicillin (INN)	0
ex 29.44 A	Piperacillin (INN)	0
ex 29.44 A and ex 30.03 A II a) 1	Piperacillin sodium (INN)	0
ex 29.44 C and ex 30.03 A II b)	Amikacin (INN) and its salts	0
ex 29.44 C and ex 30.03 A II b)	Mitomycin (INN)	0
ex 29.44 C	Amphotericin B (INN)	0
ex 29.44 C	Minocycline <i>mono</i> -hydrochloride (dihydrate) (INN), ↓	0
ex 29.44 C	Clindamycin (INN) and its salts and esters	0
ex 29.44 C	Spectinomycin dihydrochloride (pentahydrate) (INN), ↓	0
ex 29.44 C	Nystatin (INN)	0
ex 29.44 C and ex 30.03 A II b)	Bleomycin sulphate (INN)	0
ex 29.44 C	Sisomicin sulphate (INN)	0
ex 29.44 C	Spectinomycin sulphate (INN)	0
ex 29.44 C	Tobramycin (INN) and its salts	0
ex 29.44 C	Lincomycin (INN) and its salts and esters, for the manufacture of products falling within heading No 30.03 (a)	0
ex 29.44 C	Monensin (INN) and its salts	0
ex 29.44 C	Cefaclor (INN) and its hydrates, salts and esters	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.44 C	Netilmicin sulphate (INNM)	0
ex 29.44 C	Dibekacin sulphate (INNM)	0
ex 29.44 C	Cefoxitin sodium (INNM)	0
ex 29.44 C	Céfradine (INN)	0
ex 29.44 C	Cefamandole (INN) and its salts and esters	0
ex 29.44 C	Cefazolin (INN) and its salts	0
ex 29.44 C	(6 <i>R</i> ,7 <i>R</i>)-7-[2-Carboxy-2-(4-hydroxyphenyl)acetamido]-7-methoxy-3-(1-methyl-1 <i>H</i> -tetrazol-5-ylthiomethyl)-8-oxo-5-oxa-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid and its salts and esters	0
ex 29.44 C	Josamycin (INN)	0
ex 29.44 C	Josamycin propionate (INNM)	0
ex 29.44 C	Aclarubicine hydrochloride (INNM)	0
ex 29.44 C	Ribostamycin sulphate (INNM)	0
ex 29.45	Potassium <i>tert</i> -butoxide	0
ex 30.01 B II	Extracts of suprarenal glands	0
ex 30.02 A	Tetanus immunoglobulin	0
ex 30.02 A	Anti-tetanus immunoplasma	0
ex 30.02 A	German measles immunoplasma	0
ex 30.02 A	Mumps immunoplasma	0
ex 30.02 A	Whooping-cough immunoplasma	0
ex 30.02 A	Rabies immunoplasma	0
ex 30.03 A II b) and B II b)	Human albumin, whether or not in solution	0
ex 30.03 A II b) and B II b)	Human fibrinogen	0
ex 30.03 A II b) and B II b)	Preserved serum prepared on a basis of human blood	0
ex 30.03 A II b) and B II b)	Anti-haemophilic globulin and anti-P(D)-globulin derived from human blood	0
ex 30.03 A II b)	Mixture of oestrogens of equine origin, in powder form	0
ex 30.03 A II b)	Mitomycin (INN)	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 30.03 B II b)	Gamma-globulin, in solution, derived from human blood	0
ex 30.03 B II b)	Lyophilized gamma-globulin derived from human blood	0
32.01 A I	Tanning extracts of wattle (mimosa)	0
ex 32.07 B	Inorganic colouring matter preparations mentioned in Note 3 to Chapter 32, in hollow polyurethane spheres having a diameter of less than 200 micrometres	0
ex 32.08 D	Glass in the form of flakes of a length not less than 0.1 mm and not more than 3.5 mm of a thickness not less than two and not more than five micrometres	0
ex 32.09 A II and ex 39.01 C V	Polyurethane of 2,2'-(<i>tert</i> -butylimino)diethanol and 4,4'-methylenedi(cyclohexylisocyanate), dissolved in <i>N,N</i> -dimethylacetamide, with a copolymer content of not less than 48 % by weight	0
ex 32.09 A II and ex 39.02 C XIV a)	Copolymer of <i>p</i> -cresol and divinylbenzene, dissolved in <i>N,N</i> -dimethylacetamide, with a copolymer content of not less than 48 % by weight	0
ex 35.07	Bromelains (INN)	0
ex 35.07	Mixture of streptokinase (INN) and streptodornase (INN)	0
ex 35.07	Peroxidase	0
ex 37.02 B	Colour negative film of a width not less than 75 mm and not more than 105 mm and of a length of 100 m or more, for use in the manufacture of instant picture film packs (a)	0
ex 38.08 C	Hydroabietyl alcohol	0
ex 38.19 G	Catalysts, consisting essentially of diphosphorus pentaoxide on an inert support	0
ex 38.19 G	Catalysts, in the form of spherical grains, with a diameter of not less than 1.4 mm and not more than 1.8 mm, consisting of boron trifluoride on an aluminium oxide support	0
ex 38.19 G	Catalysts, in the form of rodlets, having a length of not more than 5.0 mm and a diameter of not more than 3.6 mm, consisting of copper oxide and dichromium trioxide	0
ex 38.19 G	Catalysts, consisting of copper chloride, supported on aluminium oxide, for the preparation of dichloroethane, ethylene, hydrochloric acid and oxygen, with a surface area of less than 90 m ² /g (a)	0
ex 38.19 G	Catalysts consisting of chromium or dichromium trioxide fixed on a silicon dioxide support with a pore volume, as determined by the nitrogen absorption method, of not less than 2 cm ³ /g	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ex 38.19 G	Catalysts, in the form of rodlets, having a length of not less than 3 mm and not more than 6 mm, and a diameter of not more than 3.8 mm, consisting of not less than 18 % and not more than 21 % by weight of dichromium trioxide, and not less than 78 % and not more than 81 % by weight of aluminium oxide	0
ex 38.19 G	Catalysts, in the form of granules, consisting of a mixture of oxides on a carrier of aluminium oxide and containing, by weight: — Not less than 12 % and not more than 20 % of nickel, — Not less than 5 % and not more than 10 % of copper, — Not less than 0.5 % and not more than 1.5 % of manganese The pore volume is not less than 0.25 cm ³ /g and not more than 0.95 cm ³ /g and the apparent specific gravity is not less than 0.5 and not more than 1.25	0
ex 38.19 G	Catalysts, in the form of grains, of which not less than 90 % by weight have a particle size of less than 10 micrometres, consisting of a mixture of oxides on a carrier of magnesium silicate and containing, by weight: — Not less than 20 % and not more than 35 % of copper, — Not less than 2 % and not more than 3 % of bismuth The catalyst has an apparent specific gravity of not less than 0.2 and not more than 1.0	0
ex 38.19 G	Catalysts in the form of granules having a diameter of not more than 1.4 mm, consisting of cobalt oxide on a silicon dioxide support	0
ex 38.19 G	Catalysts, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing not less than 20 % and not more than 25 % by weight of titanium and not less than 60 % and not more than 72 % by weight of chlorine	0
ex 38.19 G	Catalysts in the form of rodlets with a diameter of not less than 1.5 mm and not more than 9.5 mm, containing not less than 60 % of pentairon lithium octaoxide by weight, not less than 8 % of dipotassium oxide by weight and not less than 0.5 % of dichromium trioxide by weight, the pentairon lithium octaoxide being in the spinel structure	0
ex 38.19 K	Sintered magnesite mixed with small quantities of mineral oils	0
ex 38.19 X	Calcined bauxite (refractory grade)	0
ex 38.19 X	Diosgenin crude	0
ex 38.19 X	4-(6-Fluoro-2-methylinden-3-ylmethyl)phenyl methyl sulphide dissolved in toluene	0
ex 38.19 X	Mixtures of x-butyl-4,4'-isopropylidenediphenol and x,x'-dibutyl-4,4'-isopropylidenediphenol	0
ex 38.19 X	Mixture of nitromethane and 1,2-epoxybutane	4

CCT heading No	Description	Rate of autonomous duty (%)
ex 38.19 X	Residues of manufacture containing not less than 40 % by weight of 11- <i>beta</i> , 17,20,21-tetrahydroxy-6-methylpregna-1,4-dien-3-one 21-acetate	0
ex 38.19 X	Intermediate products from the manufacture of monensin salts	0
ex 38.19 X	Tetramethylammonium hydroxide dissolved in methanol	0
ex 38.19 X	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Streptomyces tenebrarius</i> , whether or not dried	0
ex 38.19 X	Dibutylmagnesium dissolved in organic solvents to a concentration of less than 28 % by weight	0
ex 38.19 X	Flame retardant reaction products of acetaldehyde, ethylene oxide and phosphorus trichloride containing by weight: — Not less than 14 % and not more than 16 % of phosphorus, — Not less than 27 % and not more than 33 % of chlorine	0
ex 38.19 X	Butylethylmagnesium dissolved in organic solvents to a concentration of not less than 19 % and not more than 22 % by weight	0
ex 38.19 X	Products obtained by the N-ethylation of sisomicin (INN)	0
ex 38.19 X	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Micromonospora purpurea</i> , whether or not dried	0
ex 38.19 X	Cholic acid and 3- <i>alpha</i> , 12- <i>alpha</i> -dihydroxy-5- <i>beta</i> -cholan-24-oic acid (deoxycholic-acid), crude	0
ex 38.19 X	Crude bile acids	0
ex 38.19 X	A mixture of 5-ethyl-2-methyl-2-oxo-1,3,2- <i>lambda</i> ⁵ -dioxaphosphoran-5-ylmethyl methyl methylphosphonate and bis(5-ethyl-2-methyl-2-oxo-1,3,2- <i>lambda</i> ⁵ -dioxaphosphoran-5-ylmethyl) methylphosphanate	0
ex 38.19 X	Colloidal antimony pentaoxide	0
ex 38.19 X	Tetrakis(2-chloroethyl) ethylene ^{bis} phosphate	5

CCT heading No	Description	Rate of autonomous duty (%)
ex 38.19 X	Biosynthetic peptide having the structure of the 'A' chain of human insulin, in the form of a salt of the S-sulphonate derivative	0
ex 38.19 X	Biosynthetic peptide having the structure of the 'B' chain of human insulin, in the form of a salt of the S-sulphonate derivative	0
ex 39.01 A	Colestipol hydrochloride (INN)	0
ex 39.01 C II a)	Polycondensation products of formaldehyde and a mixture of toluene-2-sulphonamide and toluene-4-sulphonamide	0
ex 39.01 C III a)	Reflecting polyester sheeting, embossed in a regular pyramidal pattern, whether or not in rolls	0
ex 39.01 C III a)	Reflecting polyester sheeting in which microspheres are embedded, whether or not in rolls	0
ex 39.01 C III a)	Transparent film, consisting of polyester coated with a layer of indium and silver	0
ex 39.01 C III b) and ex 39.03 B II b) 2, B III b) 4 aa) and B IV b) 4 aa)	Waste and scrap of photographic (including cinematographic) and X-ray film	0
ex 39.01 C III b)	Polyester of a mixture of isophthalic acid and terephthalic acid with 4,4'-isopropylidenediphenol	0
ex 39.01 C III b)	Waste and scrap from polyester foil coated with a tungsten compound or with rare-earth compounds	0
ex 39.01 C III b)	Poly(oxy-1,4-phenylenecarbonyl) in powder form	0
ex 39.01 C V	Polyurethane polymers in one of the forms mentioned in Note 3 (a) to Chapter 39, based on a mixture of 2-methyl and 4-methyl- <i>m</i> -phenylene di-isocyanates and branched chain triols with an average molecular weight of not less than 6 000, and containing terminal epoxy groups	10

CCT heading No	Description	Rate of autonomous duty (%)
ex 39.01 C V	Reflecting polyurethane sheeting, whether or not in rolls	0
ex 39.01 C VII	Polyimide sheet and strip, whether or not in rolls	0
ex 39.01 C VII	Polyethylene oxide having a molecular weight of not less than 4 000 000	8
ex 39.01 C VII	Poly[oxy(2,6-dibromo-1,4-phenylene)] for use in the manufacture of polyamide (a)	0
ex 39.01 C VII	Poly(oxy-1,4-phenylenesulphonyl-1,4-phenyleneoxy-1,4-phenyleneisopropylidene-1,4-phenylene), in one of the forms mentioned in Note 3 (b) to Chapter 39	0
ex 39.01 C VII	Liquid poly(oxypropylene) with 3-(3-[2-[2-(2-mercaptoethoxy)ethoxy]ethylthio]propoxycarbonylamino)- <i>p</i> -tolylcarbamoxyloxy as the end group	0
ex 39.02 A	Membranes, consisting of a woven textile fabric, coated on both sides, with a copolymer of poly(tetrafluoroethylene) and poly[oxy(perfluoropropylene)] with carboxylic acid end groups, whether or not in rolls	0
ex 39.02 A	Membranes, consisting of a woven fabric of which one side is coated, with a copolymer of poly(tetrafluoroethylene) and poly[oxy(perfluoropropylene)] with carboxylic acid end groups, and the other side is coated with the same copolymer but with sulphonic acid end groups, whether or not in rolls	0
ex 39.02 C I a)	Moist sheets made from finely branched fibrils of a mixture of polyethylene and a polyethylene copolymer, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing polyvinyl alcohol dissolved in water as the moistening agent	0
ex 39.02 C II	Microporous polytetrafluoroethylene film, coated on one side with a polymer permeable to water vapour, not less than 30 cm in width and weighing not more than 50 g/m ² , whether or not in rolls	0
ex 39.02 C III	Polysulphohaloethylenes in one of the forms mentioned in Note 3 (a) and (b) to Chapter 39	4
ex 39.02 C VI a)	An A-B-A block copolymer of polystyrene ethylene-butylene copolymer and polystyrene containing not more than 35 % by weight of styrene, in one of the forms mentioned in Note 3 (b) to Chapter 39	0
ex 39.02 C VI a) and b)	Copolymers, solely of allyl alcohol with styrene, which have an acetyl value of not less than 175	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ex 39.02 C VII b)	Polyvinyl chloride sheeting, whether or not in rolls, of a thickness less than 1 mm and coated with an adhesive in which are embedded hollow glass balls having a diameter of not more than 100 micrometres	0
ex 39.02 C VII b)	Reflecting polyvinyl chloride sheeting, wholly embossed on one side in a regular pyramidal pattern, whether or not in rolls	0
ex 39.02 C VIII	Copolymers of vinylidene chloride with vinyl chloride, containing not less than 79.5 % by weight of vinylidene chloride, in one of the forms mentioned in Note 3 (a) and (b) to Chapter 39, for the manufacture of fibres, monofil or strip (a)	0
ex 39.02 C XI	Poly(vinyl formal), in one of the forms mentioned in Note 3 (b) to Chapter 39, having a molecular weight not less than 10 000 and not more than 40 000 and containing, by weight: — Not less than 9.5 % and not more than 13 % of the acetyl groups, expressed as vinyl acetate, — Not less than 5 % and not more than 6.5 % of the hydroxy groups, expressed as vinyl alcohol	0
ex 39.02 C XII	Poly(2-diethylaminoethyl methacrylate) dissolved in <i>N,N</i> -dimethylacetamide, with a polymer content of not less than 55 % by weight	0
ex 39.02 C XII	Copolymer of 2-di-isopropylaminoethyl methacrylate and decyl methacrylate dissolved in <i>N,N</i> -dimethylacetamide, with a copolymer content of not less than 55 % by weight	0
ex 39.02 C XII	Reflecting polyacrylic sheeting, whether or not in rolls	0
ex 39.02 C XII	Copolymerization products of acrylic and methacrylic esters, in the form of film, with a thickness not exceeding 150 micrometres, whether or not in rolls	0
ex 39.02 C XII	Copolymer of acrylic acid and 2-ethylhexyl acrylate, containing not less than 10 % and not more than 11 % by weight of 2-ethylhexyl acrylate	0
ex 39.02 C XII	Poly(<u>N</u> -(3-hydroxyimino-1,1-dimethylbutyl)=acrylamide/	0
ex 39.02 C XIV a)	Copolymers of vinylidene chloride and acrylonitrile, in the form of expandable beads of a diameter not less than four and not more than 20 micrometres	0
ex 39.02 C XIV a)	Copolymers of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight not less than 89 % and not more than 92 % of vinyl chloride, not less than 2 % and not more than 6 % of vinyl acetate and not less than 4 % and not more than 8 % of vinyl alcohol, in one of the forms mentioned in Note 3 (a) and (b) to Chapter 39	0
ex 39.02 C XIV a)	Fluorinated ethylene propylene copolymers, for the manufacture of flat (ribbon), cable containing not less than 60 cores (a)	0
ex 39.02 C XIV a)	Poly(1-ethylethylene) (Polybutene-1) in one of the forms mentioned in Note 3 (b) to Chapter 39	0
ex 39.02 C XIV a)	Alternating copolymer of ethylene and maleic anhydride, for use as a thickener in textile pigment printing pastes (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ex 39.02 C XIV a)	Copolymer of tetrafluorethylene and hexafluorpropylene compounded with materials which are opaque to X-rays and containing not less than 15 % and not more than 30 % by weight of such materials	0
ex 39.02 C XIV a)	Copolymer of acrylonitrile and methylacrylate modified with polybutadiene-acrylonitrile (NBR)	0
ex 39.02 C XIV a)	Ionomer resin consisting of a salt of a copolymer of ethylene and methacrylic acid	0
ex 39.02 C XIV a)	Ionomer resin consisting of a salt of a terpolymer of ethylene, isobutyl acrylate, and methacrylic acid	0
ex 39.02 C XIV a)	Polyvinyl fluoride, in one of the forms mentioned in Note 3 b) to Chapter 39	0
ex 39.02 C XIV a)	Poly-tribromostyrene containing not less than 66% and not more than 71% by weight of bromine, in one of the forms mentioned in Note 3 b) to Chapter 39	0
ex 39.02 C XIV b)	Polyvinyl fluoride sheet, whether or not in rolls	0
ex 39.02 C XIV b)	Reflecting sheeting of an acrylic polymer modified by melamine-formaldehyde, whether or not in rolls	0
ex 39.02 C XIV b)	Polyvinylidene fluoride film, whether or not in rolls	0
39.03 B V a) 1	Ethylcellulose, not plasticized	4
ex 39.03 B V a) 2	Ethylhydroxyethylcellulose, insoluble in water	4
ex 39.03 B V a) 2	Hydroxypropylcellulose	0
ex 39.06 B	O-(2-hydroxyethyl)amylopectin hydrolysate	0
ex 39.07 B V d)	Perforated polyethylene film, of a width of not less than 4.5 cm and not more than 5.5 cm and having a molecular weight of not less than 4 000 000, in rolls for use as conveyor belts in machines, for manufacturing cigars (a)	0
ex 40.05 C	Strip, whether or not in rolls, consisting of polybutadiene-acrylonitrile containing, in the mass, microspheres, laminated on the upper surface, with a polyvinyl chloride sheet also containing microspheres	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
41.02 B	Bovine cattle leather (including buffalo leather) not further prepared than chrome-tanned, in the wet-blue state	0
ex 41.02 C	Leather of East India kip, whole, whether or not the heads and legs have been removed, each weighing more than 4.5 kg net and not more than 8 kg, not further prepared than vegetable tanned, whether or not having undergone further preservative treatment with oil, but obviously unsuitable for immediate use in the manufacture of leather articles	0
41.03 B I	Sheep and lambskin leather, except leather falling within heading No 41.06 or 41.08, other, not further prepared than tanned	0
41.04 B I	Goat and kidskin leather, except leather falling within heading No 41.06 or 41.08, other, not further prepared than tanned	0
41.05 B I	Other kinds of leather, except leather falling within heading No 41.06 or 41.08, other, not further prepared than tanned	0
ex 44.22 B	Used casks and barrels of oak, whether assembled or not; their staves and heads	0
ex 44.28 D II	Shingles for roofs and walls, of coniferous wood	0
45.01	Natural cork, unworked, crushed, granulated or ground; waste cork	0
45.02	Natural cork, in blocks, plates, sheets or strips (including cubes or square slabs, cut to size for corks or stoppers)	4
ex 48.07 D	Kraft paper with latex addition to the stock, coated on one side with polybutadiene-styrene, weighing not less than 104 g and not more than 130 g/m ² , for the manufacture of all-in-one disposable nappies (a)	6
ex 49.11 B	Microcopies on an opaque base for data banks and libraries (a)	0
ex 51.01 A	Yarn of polytetrafluorethylene	0
ex 51.01 A	Yarn of polyvinyl alcohol, soluble in water at a temperature of 50 °C, for use in the manufacture of welfless 'felts' for papermaking machines (a)	0
ex 51.01 A	Yarn, multiple, of polyamide, coated, impregnated or covered with a phenolic resin	0
ex 51.01 A	Yarn of a copolymer of glycollic acid and lactic acid for the manufacture of surgical sutures (a)	0
ex 51.01 A	Yarn wholly of polyglycollic acid	0
ex 51.01 A	Yarn of poly(1,4-dioxanone)	0
ex 51.01 A	Yarn of poly(<i>p</i> -phenyleneterephthalamide), for uses other than the manufacture of tyres or of products used in the manufacture of tyres (a)	2
ex 51.01 A	Non-textured filament yarn of poly(vinyl alcohol) for the manufacture of sleeves for printing rollers (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 51.02 A I	Monofil of polytetrafluoroethylene	0
ex 51.02 A I	Monofil ^{of} poly(1,4-dioxanone)	0
ex 51.02 A II	Polyimide strip, whether or not in rolls	0
ex 51.02 A II	Strip of polytetrafluoroethylene, whether or not in rolls, with an extension at break not exceeding 25 %	0
ex 51.04 A IV	Woven fabrics of polyvinyl alcohol fibres, for machine embroidery	0
ex 56.01 A	Textile fibres of polytetrafluoroethylene	0
ex 56.01 A and ex 59.01 B I	Fibres of poly(<i>p</i> -phenyleneterephthalamide)	2
ex 56.01 A	Textile fibres exclusively of aromatic polyamides obtained by the polycondensation of <i>m</i> -phenylenediamine and isophthalic acid, for uses other than the manufacture of articles falling within Chapters 60, 61, 64 and 65 or of materials used in the manufacture of such articles (a)	0
ex 56.01 A	Polyvinyl alcohol fibres, whether or not acetalised	0
ex 58.07 A and ex 59.04	Braid, wholly of polyglycollic acid yarn	0
ex 58.07 A and ex 59.04	Braid of yarn of a copolymer of glycollic acid and lactic acid, whether or not coated, for the manufacture of surgical sutures (a)	0
ex 59.03	Bonded fibre fabrics and similar bonded yarn fabrics of aromatic polyamide man-made fibres obtained by polycondensation of <i>m</i> -phenylenediamine and isophthalic acid, whether or not impregnated or coated, in the piece or cut into rectangles	0
ex 59.03	Bonded-fibre fabrics, with a thickness of not more than 300 micrometres of spunbonded polyethylene fibres, with a weight not exceeding 115 g/m ² , whether or not impregnated or coated, in the piece or cut into rectangles	0
ex 59.03	Poly(vinyl alcohol) bonded fibre fabrics, with a thickness of not less than 200 micrometres and not more than 280 micrometres and of a weight of not less than 20 g/m ² and not more than 50 g/m ² , whether or not impregnated or coated, in the piece or cut into rectangles	0
ex 59.04	Coir yarn, for the manufacture of carpets, carpeting and rugs, mats and the like (a)	0
ex 59.08	Knitted or woven fabric coated or covered on one side with artificial plastic material in which are embedded microspheres	0
ex 59.12	Textile fabrics coated with adhesive in which are embedded microspheres the diameter of which is not more than 75 micrometers, and weighing not more than 550 g/m ²	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ex 59.17 A	Needle punched synthetic fibre felts on a woven synthetic fibre base coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (a)	0
ex 59.17 D	Yarn of poly(<i>p</i> -phenyleneterephthalamide), impregnated, oiled	0
ex 59.17 D	Yarn and strip of impregnated polytetrafluoroethylene, whether or not oiled or graphited	0
ex 68.16 B	Microspheres containing more than 90% by weight of barium and titanium expressed as barium oxide and titanium dioxide with a diameter of less than 100 micrometers and a refractive index of not less than 2.1 and not more than 2.4	0
ex 69.09 B	Catalyst supports, consisting of porous cordierite ceramic pieces of roughly circular or oval cross-section with parallel sides, having an overall volume of not less than 240 ml and not more than 11 100 ml, and having a minimum dimension of not less than 70 mm and a maximum dimension of not more than 480 mm, having not less than 28 continuous channels per 100 mm ² running parallel to the main axis of symmetry, the total channel cross-section area being not less than 50 % and not more than 80 % of the whole cross-section area	0
ex 70.19 A IV b)	Beads of a diameter of less than 0.1 mm and with a refractive index of 2.26	0
ex 70.20 A	Non-textile glass fibres having a diameter of less than four micrometres	0
ex 70.19 A IV b)	Glass beads of a diameter of less than 0.1 mm and with a refractive index of 2.26	0
ex 70.20 B	Glass-fibre yarns, with a filament diameter of not more than four micrometres, for the manufacture of carpets (a)	0
ex 75.04 A	Tubes of nickel, not alloyed, of a purity not less than 99 % by weight, not deviating from straightness lengthwise by more than 1 mm per 150 cm of length, and with an outside diameter either: — Not less than 213.36 mm and not more than 214 mm, or — Not less than 209.95 mm and not more than 210.59 mm, or — Not less than 168.28 mm and not more than 168.78 mm	0
76.01 B I b)	Waste of aluminium, other (including factory rejects)	0
ex 76.03	Aluminium alloy strip in coils, containing not less than 18 % by weight and not more than 23 % by weight of tin and not less than 0.7 % by weight and not more than 1.5 % by weight of copper as the major alloying elements and having a width of not less than 75 and not more than 230 mm and a thickness of not less than 3 and not more than 6.5 mm	0
ex 81.03 B	Wire of unalloyed tantalum, of a diameter not less than 0.2 mm and not more than 0.5 mm, for the manufacture of capacitors (a)	0
ex 81.04 D I b)	Chromium, in the form of cathode chips, pellets or briquettes, which contains not more than 0.10 % by weight of total oxygen, not more than 0.015 % by weight of total aluminium and not more than 0.001 % by weight of aluminium compounds insoluble in boiling 5N hydrochloric acid and in boiling fuming perchloric acid, and evaluated as aluminium, for the production of alloy for the manufacture of the following parts of gas turbines and jet engines (a): — Blades, fixed or movable, including their rings, — Vanes, — Nozzles	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex 81.04 G I	Electrolytic manganese of a purity of at least 99.7 % by weight, for the chemical industry (a)	0
ex 81.04 G I	Electrolytic manganese of a purity of at least 99.7 % by weight, for the production of non-ferrous alloys (a)	0
ex 84.18 C II b)	Components of separators for the isolation of <i>gases</i> from gas mixtures, consisting of a bundle of permeable hollow fibres passing through a block of plastic material at one end and sealed at the other end - the whole being enclosed within a metal cylindrical container with a series of holes round the circumference at one end, of an overall length of not less than 300 mm and not more than 3 700 mm and a diameter of not more than 350 mm	0
ex 84.63 D	Integrally forged and roughly shaped generator and turbine shafts of a weight exceeding 180 tonnes	0
ex 85.01 B I b)	D.C. electric motor having an output of 4 watts, an operating voltage of 12 volts, a maximum absorbed current under no-load conditions of 160 mA, and a speed of up to 2 400 revolutions per minute, equipped with self-centring bushes and a tachometric dynamo, the whole being contained in a cylindrical metallic casing whose diameter does not exceed 30 mm	0
ex 85.19 B	Potentiometers, for use as volume control, contained in a housing whose diameter does not exceed 4.5 mm, whether or not fitted with an on/off switch, for the manufacture of appliances falling within subheading 90.19 B I (a)	0
ex 90.01 A	Octagonal Fresnel lens of acrylic resin unmounted, for use in overhead projectors (a)	0
ex 90.01 B	Material consisting of a polarizing film, supported on one or both sides by transparent material	0
ex 98.10 B	Flint wheels, whether or not with guard wheels, for use in the manufacture of non-refillable gas-fuelled pocket lighters (a)	0
ex 98.10 B	Piezo-electric ignition mechanism	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

