

Strathprints Institutional Repository

Oterkus, Erkan and Oterkus, Selda (2016) Peridynamics : a novel approach for material and structural modelling. Journal of New Turkey, 22 (90). pp. 378-381. ,

This version is available at http://strathprints.strath.ac.uk/58573/

Strathprints is designed to allow users to access the research output of the University of Strathclyde. Unless otherwise explicitly stated on the manuscript, Copyright © and Moral Rights for the papers on this site are retained by the individual authors and/or other copyright owners. Please check the manuscript for details of any other licences that may have been applied. You may not engage in further distribution of the material for any profitmaking activities or any commercial gain. You may freely distribute both the url (<u>http://strathprints.strath.ac.uk/</u>) and the content of this paper for research or private study, educational, or not-for-profit purposes without prior permission or charge.

Any correspondence concerning this service should be sent to Strathprints administrator: strathprints@strath.ac.uk

Peridynamics: A Novel Approach for Material and Structural Modelling

Erkan Oterkus and Selda Oterkus University of Strathclyde, Glasgow, United Kingdom

Solid mechanics is an interdisciplinary subject mainly deals with deformation of materials and structures under external loading conditions. In many applications, safety is an important concern. For instance, a small crack can cause catastrophic damage to an airplane which can result in loss of many lives (see Fig. 1a). Moreover, such incidents can cause significant damage to the environment which might take years for complete recovery process such as the effect of oil spill due to a damaged tanker (see Fig. 1b), corroded pipeline, etc. In order to prevent from such undesired incidents, several approaches are commonly followed within the solid mechanics framework. One common approach is to perform experiments to test the durability of materials and structures. Although such an approach can provide us realistic data, such experiments are not always possible and they are mostly expensive. Today, engineers and researchers commonly use theoretical or computational approaches as an alternative to analyse the problems that they are working on. Theoretical approaches mostly depend on various assumptions to simplify the calculations. Moreover, they are restricted to specific geometries and loading conditions. Hence, it is essential to use a technique which does not have such limitations and is also economically feasible. Computational techniques are very good candidates for this purpose and they are commonly used both in industry and academia.



Fig. 1. (a) Damaged airplane fuselage and (b) oil spill from a tanker

There are currently various computational approaches available and some of these techniques are implemented as part of commercial softwares. Amongst these, finite element method (FEM) is the most common and popular approach. In FEM, the material or structure to be analysed is divided into "finite" number of small regions called "elements" (see Fig. 2). All elements are connected to each other through "nodes". FEM basically tries to solve a governing equation which is a different representation of well-known Newton's second law and it is a partial differential equation from mathematical point of view. Although FEM is a very successful technique to analyse many problems that engineering community is dealing with, it encounters a difficulty when predicting failure or crack initiation and propagation in materials and structures due to its mathematical structure. For such special cases, a newly introduced approach called "peridynamics" can be utilized and it is the main focus of this paper.




Fig. 2. Finite element analysis of a cooling fan (Comsol) [1]

Peridynamics

Peridynamics was introduced by Dr. Stewart Silling from Sandia National Laboratories in USA. The first scientific paper was published in 2000 [2]. The word "peridynamics" is composed of two Greek words "peri" and "dynamics" which mean "horizon" and "force", respectively. Peridynamics is a new continuum mechanics formulation which uses integrodifferential equations for governing equations as opposed to partial differential equations which are used in classical continuum mechanics and FEM approach as mentioned earlier. The main advantage of peridynamics is that it doesn't use spatial derivatives in its formulation which causes problems when predicting failure. Moreover, it is a non-local formulation due to its length scale parameter called "horizon". Hence, "non-local" effects, which can be seen at very small scales, can be captured [3]. "Horizon" defines the range of interactions between material points. "Material point" is the basic object of a continuum formulation which represents an infinitesimal volume.

There are currently mainly three different peridynamic formulations which can be found in the literature. These are "bond based peridynamics", "ordinary state based peridynamics" and "non-ordinary state based peridynamics" [4-7]. The main difference between these three types is the forces that material points are acting on each other. "Non-ordinary state based peridynamics" is the most general form in which the peridynamic forces between material points can be in any direction and magnitude (see Fig. 3a). "Ordinary state based peridynamics" is based on the assumption that the peridynamic forces between two material points are along the "bond" direction between material points, but can have a different magnitude (see Fig. 3b). "Bond based peridynamics" is the original peridynamic formulation that Silling introduced in 2000 [2] and based on the assumption that peridynamic forces between two material points are equal and opposite to each other (see Fig. 3c). Moreover, peridynamic forces only depend on the deformation behaviour of material points which are associated with them as opposed to the other two "state based" formulations in which them as opposed to the other two "state based" formulations in which their horizons.




Fig. 3. Various peridynamic formulations; (a) non-ordinary state based peridynamics, b) ordinary state based peridynamics and (c) bond based peridynamics [5]

For the last 15 years, there has been significant research efforts on peridynamics. Currently, there are peridynamic formulations not only for elastic material behaviour, but also for plastic [8], viscoelastic [9] and viscoplastic [10] material behaviours. Moreover, it is not only limited for the analysis of isotropic materials that we commonly use such as steel, aluminium, etc. Various peridynamic formulations are proposed in the literature to analyse composite materials [11-17] which are also becoming a popular material in many industries due to their superior properties and low densities with respect to some other traditional materials. It is difficult to solve peridynamic equations analytically. Therefore, generally a "meshless" discretization scheme is utilized for numerical solutions (see Fig. 4).




Fig. 4. A meshless discretization for a peridynamic model of a cylindrical bar under tension loading [18]

In order to analyse some sophisticated problems of today such as cracking behaviour of electronic packages, lightening strike damage, hydraulic fracturing, etc., it may not be sufficient to perform a single field analysis. Hence, it is essential to take into account the effect of multiple physical fields on each other. We name this type of analysis as "multiphysics analysis". Today, peridynamic formulations for many other physical fields are also available such as for heat transfer analysis, moisture diffusion analysis, porous flow analysis, etc. [19-26]. Hence, it is possible to perform "multiphysics analysis" in a single peridynamic framework which eliminates possible difficulties in linking different solution tools.

Conclusions

Peridynamics is a new non-local continuum mechanics formulation which is especially useful for failure prediction in materials and structures. It is not only applicable to be used at large scales, but also can be used at small scale analysis due to its "non-local" characteristic. Moreover, it is also suitable for "multiphysics analysis" since there are existing peridynamic formulations for many physical fields.

References

[1] https://www.comsol.com/multiphysics/fea-software

[2] Silling, S. A., "Reformulation of Elasticity Theory for Discontinuities and Long-range Forces," *Journal of the Mechanics and Physics of Solids*, Vol. 48, 2000, pp. 175-209.

[3] Oterkus, E., Diyaroglu, C., Zhu, N., Oterkus, S., & Madenci, E. (2015). Utilization of Peridynamic Theory for Modeling at the Nano-Scale. In *Nanopackaging: From Nanomaterials to the Atomic Scale* (pp. 1-16). Springer International Publishing.

[4] Silling, S.A., Epton, M., Weckner, O., Xu, J. and Askari, A, "Peridynamics States and Constitutive Modeling," *Journal of Elasticity*, Vol. 88, No. 2, 2007, pp. 151-184.

[5] Madenci, E., & Oterkus, E. (2014). *Peridynamic theory and its applications* (Vol. 17). New York: Springer.

[6] Oterkus, E., Barut, A., & Madenci, E. (2012). Peridynamics based on principle of virtual work. In 53rd AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics and Materials Conference 20th AIAA/ASME/AHS Adaptive Structures Conference 14th AIAA (p. 1540).

[7] Oterkus, E., & Madenci, E. (2012). Ordinary state-based peridynamic material constants. In 53rd AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics and Materials Conference 20th AIAA/ASME/AHS Adaptive Structures Conference 14th AIAA (p. 1946).

[8] Madenci, E. and Oterkus, S., "Ordinary State-based Peridynamics for Plastic Deformation According to von Mises Yield Criteria with Isotropic Hardening," *Journal of the Mechanics and Physics of Solids*, Vol. 86, 2016, pp. 192-219.

[9] Mitchell, J. A., "A Non-local, Ordinary-State-Based Viscoelasticity Model for Peridynamics," *Sandia National Laboratories Report*, 2011, SAND2011-8064.

[10] Amani, J., Oterkus, E., Areias, P., Zi, G., Nguyen-Thoi, T., & Rabczuk, T. (2016). A nonordinary state-based peridynamics formulation for thermoplastic fracture. *International Journal of Impact Engineering*, 87, 83-94.

[11] Oterkus, E., & Madenci, E. (2012). Peridynamic analysis of fiber-reinforced composite materials. *Journal of Mechanics of Materials and Structures*, 7(1), 45-84.

[12] Kilic, B., Agwai, A. and Madenci, E., "Peridynamic Theory for Progressive Damage Prediction in Centre-Cracked Composite Laminates" *Composite Structures*, Vol. 90, 2009, pp. 141-151.

[13] Oterkus, E., Madenci, E., Weckner, O., Silling, S., Bogert, P., & Tessler, A. (2012). Combined finite element and peridynamic analyses for predicting failure in a stiffened composite curved panel with a central slot. *Composite Structures*, *94*(3), 839-850.

[14] Oterkus, E., & Madenci, E. (2012). Peridynamic theory for damage initiation and growth in composite laminate. In *Key Engineering Materials* (Vol. 488, pp. 355-358). Trans Tech Publications.

[15] Diyaroglu, C., Oterkus, E., Madenci, E., Rabczuk, T., & Siddiq, A. (2016). Peridynamic modeling of composite laminates under explosive loading. *Composite Structures*, *144*, 14-23.

[16] Oterkus, E., Barut, A., & Madenci, E. (2010, April). Damage growth prediction from loaded composite fastener holes by using peridynamic theory. In *Proceedings of the 51st AIAA/ASME/ASCE/AHS/ASC structures, structural dynamics, and materials conference.*

[17] Oterkus, E., & Madenci, E. (2012). Peridynamics for failure prediction in composites. In 53rd AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics and Materials Conference 20th AIAA/ASME/AHS Adaptive Structures Conference 14th AIAA (p. 1692).

[18] https://en.wikipedia.org/wiki/Peridynamics

[19] De Meo, D., Diyaroglu, C., Zhu, N., Oterkus, E., & Siddiq, M. A. (2016). Modelling of stress-corrosion cracking by using peridynamics. *International Journal of Hydrogen Energy*, *41*(15), 6593-6609.

[20] Oterkus, S., Fox, J., & Madenci, E. (2013, May). Simulation of electro-migration through peridynamics. In *2013 IEEE 63rd Electronic Components and Technology Conference* (pp. 1488-1493). IEEE.

[21] Oterkus, S., & Madenci, E. (2013). Crack growth prediction in fully-coupled thermal and deformation fields using peridynamic theory. *54th AIAA Structures, Structural Dynamics and MaterialsConference, Boston, Massachusetts.*

[22] Oterkus, S., Madenci, E. and Agwai, A (2014). "Peridynamic Thermal Diffusion" Journal of Computational Physics, Vol. 265, pp. 71-96.

[23] Oterkus, S., Madenci, E., & Agwai, A. (2014). Fully coupled peridynamic thermomechanics. *Journal of the Mechanics and Physics of Solids*, 64, 1-23.

[24] Oterkus, S., & Madenci, E. (2014). Fully coupled thermomechanical analysis of fiber reinforced composites using peridynamics. In *55th AIAA/ASMe/ASCE/AHS/SC Structures, Structural Dynamics, and Materials Conference-SciTech Forum and Exposition 2014.*

[25] Oterkus, S., Madenci, E., Oterkus, E., Hwang, Y., Bae, J. and Han, S., (2014) "Hygrothermo-mechanical Analysis and Failure Prediction in Electronic Packages by Using Peridynamics" 64th Electronic Components and Technology Conference (ECTC).

[26] Oterkus, S. (2015). Peridynamics for the solution of multiphysics problems.