

CONFERENCE PROCEEDINGS BOOK



**INTERNAZIONALE  
MARMI E MACCHINE  
CARRARA SPA**



**CARRARA  
MARMOTEC  
2016**

**1<sup>st</sup>** **INTERNATIONAL  
SUSTAINABLE  
STONE**  
CONFERENCE

CARRARA, 20 MAY 2016



**INTERNAZIONALE  
MARM E MACCHINE  
CARRARA SPA**



THE CONFERENCE IS ORGANIZED BY:



**INTERNAZIONALE  
MARM E MACCHINE  
CARRARA SPA**



**CARRARA  
MARMOTEC  
2016**

# 1<sup>st</sup> INTERNATIONAL **SUSTAINABLE STONE**

CONFERENCE

CARRARA, 20 MAY 2016

WITH THE SUPPORT OF:

REGIONE  
TOSCANA



TOSCANA  
PROMOZIONE



**Table 1.** Carrara marble physical-mechanical characteristics (on average)

Physical characteristics	Value
Bulk density	2688 kg/m <sup>3</sup>
Simple compression strength	1209 kg/cm <sup>2</sup>
Compression strength after freezing	1181 kg/cm <sup>2</sup>
Indirect Tensile Strength (Brazilian test)	174 kg/cm <sup>2</sup>
Impact strength test	73.8 cm
Moisture absorption (by weight)	0.16%

On the basis of the grain size and of chemical characteristics, several applications as SRM are possible: eg. Asphalt, cement, plaster, rubber, sealants, paper, paint, plastic, etc. Other potential applications as by-products are: aggregate for concrete; crushed materials for embankments and armoured stones. Moreover, the big chance for the future – due to solve also hydrogeological and stability problems in Carrara Basin - is treating “poor” material (called “terre”) to new, performing markets.

On the basis of these information a preliminary research about Carrara Marble QW recovery was set. Two areas were sampled (Calocara and Lorano) and the sampled materials were analyzed to get information about: size distribution, density, Atterberg limits, Los Angeles test, freezing and heat test, flat and shape indexes, chemical analysis, mineralogy. At present, analysis activities are still in progress and the first results shows a good attitude for QW to be recovered.

The present research will show the state of the art and the potentiality of QW exploitation in Carrara; highlighting best practices and efficient recovery processes (technologies and techniques).

## STRUCTURE FROM MOTION TECHNIQUE OF PROXIMAL-SENSING AIRBORNE DATA FOR 3D RECONSTRUCTION OF EXTRACTION SITES

*Tufarolo Emanuele<sup>1</sup>, Salvini Riccardo<sup>1</sup>, Seddaiu Marcello<sup>2</sup>, Bernardinetti Stefano<sup>3</sup>, Petrolo Francesco<sup>2</sup>, Lanciano Chiara<sup>2</sup>, Luigi Carmignani<sup>1</sup>, Giovanni Massa<sup>4</sup>, Diego Pieruccioni<sup>2</sup>*

<sup>1</sup>University of Siena, Department of Environment, Earth and Physical Sciences and Centre of Geotechnologies CGT, Via Vetri Vecchi 34, San Giovanni Valdarno (Arezzo, Italy).

<sup>2</sup>University of Siena, Centre of Geotechnologies CGT, Via Vetri Vecchi 34, San Giovanni Valdarno (Arezzo, Italy).

<sup>3</sup>University of Cagliari, Department of Chemical and Geological Sciences and Centre of Geotechnologies CGT, Via Vetri Vecchi 34, San Giovanni Valdarno (Arezzo, Italy).

<sup>4</sup>CGT Group, Strada Provinciale delle Miniere - Polo Industriale di Bomba, Cavriglia (Arezzo, Italy).

Tel. +390554650086, Fax +390559119439, [tufarolo@cgt-spinoff.it](mailto:tufarolo@cgt-spinoff.it)

## **Abstract**

Digital photogrammetry based on Structure from Motion (SfM) algorithms nowadays represents a low-cost, valid and rapid technique for the tridimensional detection and mapping of large areas of particular geologic-geomorphologic, natural and environmental interest.

Products derived from the photogrammetric processing, such as tridimensional point clouds, digital surface and terrain models (DSM and DTM), and high-resolution orthophotos, allow to study and monitor the territory and its productive activities. In this case study we used images captured from a small aircraft, agile and extremely inexpensive, for the 3D reconstruction of extraction sites and zones of geo-structural importance. The aircraft, called RadGyro (property of the CGT Group, University of Siena), is able to deal with complex flight plans and low altitudes in a way to make possible the detailed detection of desired features even in very complex areas. An example of this complex situation is represented by the test area here presented, located in the marble district of the Apuan Alps, the biggest and most exploited European extractive basin. The aircraft is equipped to acquire series of photos in an independent manner, using two digital cameras characterized by a full frame sensor and 35 mm fixed lens. Moreover, five GPS antennas and an inertial navigation system (INS) allow associating to each frame the position and the angular orientation of the camera. Flying at an altitude varying from 100 m to 400 m above ground level, the cameras can detect about 50 km<sup>2</sup> and 200 km<sup>2</sup>, respectively, with a ground resolution of 3.5 cm and 10.0 cm. The exterior orientation of images can be improved, if necessary, acquiring some ground control points through traditional topographic survey. Info about the exterior orientation, associated to each frame, is therefore used to finalize the photogrammetric processing, using appropriate software. Structure from Motion techniques and algorithms allow to detect millions of “tie points” necessary for the accurate alignment of photos. The photogrammetric processing, then, is finalized by the creation of 3D point clouds, DSM, DTM and orthophotos. These products are used in this case study for the detailed analysis of the marble quarries morphology and geology and, through a multitemporal acquisition, for the assessment of the volumetric variations related to the extraction activities. Moreover, we want to point out, finally, how the RadGyro is able to provide data for environmental researches thanks to the following additional equipment: an hyperspectral camera in the range from 400 nm to 1000 nm, a thermal camera (7500 -1300 nm) and a gamma ray spectrometer equipped with detectors.