

Strategies to Improve Physical Properties in Eco-Friendly Materials through Cation Engineering

Saket Asthana

Advanced Functional Materials Laboratory, Department of Physics,
Indian Institute of Technology, Hyderabad
Email: asthanas@iith.ac.in

Abstract

Bulk ferro/piezoelectric ceramics are the backbone for several components utilized in communication systems, industrial automation, medical diagnostics, information-technology, energy storage and harvesting. From the application point of view, ferro/piezoelectric materials should have high piezoelectric coefficients, high remnant polarization (P_r), low coercive field (E_C), wide temperature stability and good mechanical strength [1]. In most of the high performance piezoelectric applications, the material of choice is ultimately based upon lead based materials such as PZT (i.e., $\text{Pb}(\text{Zr}, \text{Ti})\text{O}_3$). Even though PZT has excellent piezoelectric properties suitable for device applications, the prime concern is about lead (Pb) which is highly toxic and hazardous in nature. Hence, it has become a serious threat for environmental protection during the waste disposal and also it indirectly induces health related issues. In this regard, worldwide environmental considerations are demanding the elimination of lead-based materials from all consumer items [2].

In order to replace PZT based systems, new lead free systems have to be developed for specific applications based on their piezoelectric performance. In the recent years perovskite based A-site disordered (i.e., A-site being shared equally by two cations) lead free ferroelectrics such as $\text{Na}_{0.5}\text{Bi}_{0.5}\text{TiO}_3$ (NBT), $\text{Bi}_{0.5}\text{K}_{0.5}\text{TiO}_3$ (BKT), $\text{K}_{0.5}\text{Na}_{0.5}\text{NbO}_3$ (KNN) and their solid solutions have been actively studied for lead free piezoelectric ceramics. Among them NBT and its derivatives has received much attention because of their stable ferro/piezoelectric properties. At room temperature the parent NBT system exhibits a remanent polarization $P_r = 38 \mu\text{C}/\text{cm}^2$ along with a large coercive field of $E_C \cong 63 \text{ kV}/\text{cm}$. The piezoelectric charge coefficients (d_{33}) for NBT vary from 70-100 pC/N.

The physical properties of the materials can be tuned with different approaches. Here, the chemical modification through site specific cation engineering and solid-solution approaches have been used to tune the physical properties. The grain size variation at nano-scale and their refinement have also shown interesting observations in properties [3]. Since structure of the materials also plays crucial role to modify the properties, structural-property correlation has been also addressed [4-6].

References

1. Kenji Uchino, *Ferroelectric Devices*, Marcel Dekker, Inc. New York, 2000
2. Shashank Priya and Shan Nahm, *Lead free piezoelectrics*, Springer Publications (2012)
3. Saket Asthana et al., *J Mater Sci: Mater Electron* **26** (2015) 9746
4. Saket Asthana et al *Mater. Res. Express* **2** (2015) 096301
5. Saket Asthana et al *AIP Advances* **4** (2014) 017111
6. Saket Asthana et al *J. Appl. Phys.* **113** (2013) 194106