TOPOLOGY PRESERVATION AND CONTROL APPROACH FOR INTERFERENCE-AWARE NON-OVERLAPPING CHANNEL ASSIGNMENT IN WIRELESS MESH NETWORKS

ASHRAF ALZUBIR MOHAMMAD ALI

UNIVERSITI TEKNOLOGI MALAYSIA

TOPOLOGY PRESERVATION AND CONTROL APPROACH FOR INTERFERENCE-AWARE NON-OVERLAPPING CHANNEL ASSIGNMENT IN WIRELESS MESH NETWORKS

ASHRAF ALZUBIR MOHAMMAD ALI

A thesis submitted in fulfilment of the requirements for the award of the degree of Doctor of Philosophy (Computer Science)

> Faculty of Computing Universiti Teknologi Malaysia

> > MAY 2015

To my late father **Alzubir Mohammad Ali**. May Allah SWT be pleased with him and grant him Al Jannah (Ameen)

ACKNOWLEDGMENT

First and foremost, I would like to express my deepest gratitude to ALLAH (SWT), who guided, helped and made my life meaningful even outside the confines of this PhD candidature.

I would like to thank my supervisor **Assoc. Prof. Dr. Kamalrulnizam Abu Bakar** for his support and guidance throughout my research study. He has been incredibly wise, helpful, understanding, and generous. I would like to thank him for his patience and personal kindness.

I am grateful to Universiti Teknologi Malaysia for the IDF financial support during my study. I am also thankful to all the staff at Universiti Teknologi Malaysia for their support and help. I would also like to thank International African University Sudan.

I must express my sincerest and heartiest thanks to my mother for her continuous support and believing in whatever I do. Without her Duaa, love and supports, I would never be able to finish this thesis. Also, I would like to thank all the members of my family, friends and relatives for their constant love and help that moves me towards my goals.

I deeply thank my wife. Her support and understanding have helped me to overcome the most difficult period, encouraging me to forget the bad things and giving me a new hope whenever I was down.

ABSTRACT

The Wireless Mesh Networks (WMN) has attracted significant interests due to their fast and inexpensive deployment and the ability to provide flexible and ubiquitous internet access. A key challenge to deploy the WMN is the interference problem between the links. The interference results in three problems of limited throughput, capacity and fairness of the WMN. The topology preservation strategy is used in this research to improve the throughput and address the problems of link failure and partitioning of the WMN. However, the existing channel assignment algorithms, based on the topology preservation strategy, result in high interference. Thus, there is a need to improve the network throughput by using the topology preservation strategy while the network connectivity is maintained. The problems of fairness and network capacity in the dense networks are due to limited available resources in WMN. Hence, efficient exploitation of the available resources increases the concurrent transmission between the links and improves the network performance. Firstly, the thesis proposes a Topology Preservation for Low Interference Channel Assignment (TLCA) algorithm to mitigate the impact of interference based on the topology preservation strategy. Secondly, it proposes the Max-flow based on Topology Control Channel Assignment (MTCA) algorithm to improve the network capacity by removing useless links from the original topology. Thirdly, the proposed Fairness Distribution of the Non-Overlapping Channels (F-NOC) algorithm improves the fairness of the WMN through an equitable distribution of the non-overlapping channels between the wireless links. The F-NOC is based on the Differential Evolution optimization algorithm. The numerical and simulation results indicate that the proposed algorithms perform better compared to Connected Low Interference Channel Assignment algorithm (CLICA) in terms of network capacity (19%), fractional network interference (80%) and network throughput (28.6%). In conclusion, the proposed algorithms achieved higher throughput, better network capacity and lower interference compared to previous algorithms.

ABSTRAK

Rangkaian Mesh Tanpa Wayar (WMN) telah menarik minat yang ketara disebabkan oleh penggunaannya yang cepat dan murah serta keupayaannya untuk menyediakan akses ke internet yang fleksibel dan sentiasa ada. Cabaran utama untuk menggunakan WMN adalah masalah gangguan antara pautan. Hasilnya gangguan terbahagi kepada tiga masalah iaitu daya pemprosesan terhad, kapasiti dan keadilan bagi WMN. Strategi pemeliharaan topologi digunakan dalam kajian ini bagi meningkatkan daya pemprosesan dan menangani masalah kegagalan pautan dan pembahagian WMN. Walau bagaimanapun, algoritma penyerahan saluran sedia ada yang berasaskan strategi pemeliharaan topologi telah menyebabkan gangguan yang tinggi. Oleh itu, terdapat keperluan bagi meningkatkan daya pemprosesan rangkaian dengan menggunakan strategi pemeliharaan topologi sambil mengekalkan sambungan rangkaian. Masalah keadilan dan kapasiti rangkaian dalam rangkaian padat adalah disebabkan oleh sumber sedia ada yang terhad dalam WMN. Oleh itu, eksploitasi sumber sedia ada yang cekap dapat meningkatkan penghantaran serentak antara pautan dan meningkatkan prestasi rangkaian. Pertamanya, tesis ini mencadangkan algoritma Pemeliharaan Topologi Penyerahan Saluran Gangguan Rendah (TLCA) untuk mengurangkan kesan gangguan berasaskan strategi pemeliharaan topologi. Kedua, ia mencadangkan algoritma Aliranmaksima berasaskan Penyerahan Saluran Kawalan Topologi (MTCA) untuk meningkatkan kapasiti rangkaian dengan membuang pautan tidak berguna daripada topologi asal. Ketiga, algoritma Kesaksamaan Pengagihan Saluran Tidak Bertindih (F-NOC) yang dicadangkan dapat meningkatkan keadilan pada WMN melalui pembahagian sama rata bagi saluran tidak bertindih antara pautan tanpa wayar. F-NOC adalah berasaskan algoritma pengoptimuman Evolusi Berbeza. Keputusan berangka dan simulasi menunjukkan bahawa algoritma yang dicadangkan mempunyai prestasi yang lebih baik berbanding dengan algoritma Penyerahan Saluran Gangguan Rendah Bersambung (CLICA) dari segi kapasiti rangkaian (19%), gangguan pecahan rangkaian (80%) dan daya pemprosesan rangkaian (28.6%). Kesimpulannya, algoritma yang dicadangkan mencapai daya pemprosesan yang lebih tinggi, kapasiti rangkaian yang lebih baik dan gangguan yang lebih rendah berbanding dengan algoritma sebelumnya.

TABLE OF CONTENTS

CHAPTER	TITLE				
	DEC	ii			
	DEI	DICATI	ION	iii	
	ACH	KNOW]	LEDGMENT	iv	
	ABS	STRAC	Т	v	
	ABS	STRAK		vi	
	TAE	BLE OF	F CONTENTS	vii	
	LIS	T OF T	ABLES	xiv	
	LIS	T OF F	IGURES	xvii	
	LIS	T OF A	BBREVIATIONS	xvii	
1	INT	RODU	CTION	1	
	1.1	Overv	iew	1	
	1.2	Proble	m Background	3	
		1.2.1	Topology Preservation for Low		
			Interference Channel Assignment	5	
		1.2.2	Topology Control based on Non-		
			overlapping Channels Assignment	7	
		1.2.2	Fairness Distribution of the Non-		
			Overlapping Channels	10	
	1.3	Proble	m Statement	12	
	1.4	Resear	ch Questions	13	
	1.5	The A	im	14	
	1.6	Resear	ch Objectives	15	
	1.7	Signifi	icance of the Study	15	
	1.8	Resear	rch Scope	16	
	1.9	Thesis	Organization	16	

2	LIT	ERAT	URE RE	VIEW	18		
	2.1	Overv	view		18		
	2.2	Archi	tecture of	Wireless Mesh Network	19		
		2.2.1	Compo	nents of WMN	20		
		2.2.2	Signal H	Propagation and Interference in WMNs	21		
		2.2.3	IEEE 8	02.11s MAC Protocol	23		
	2.3	Interf	erence Mo	odels	24		
		2.3.1	Protoco	l Model of Interference	24		
		2.3.2	Extende	ed Protocol Model of Interference	26		
		2.3.3	Geomet	ric Model of Interference	27		
		2.3.4	Naveed	's Model of Interfering Links	29		
	2.4	Capac	ity Challe	enges in Multi-Radio Multi-Channel	31		
	2.5	The Interference Metrics					
		2.5.1	Interfer	ence Factor	34		
		2.5.2	Interfer	ence Matrix	36		
		2.5.3	Conflic	t Graph Model	37		
	2.6	Chanı	nel Assigr	nment Strategies	38		
		2.6.1	Knowle	dge-based Channel Assignment	38		
			2.6.1.1	Centralized Channel Assignment			
				Strategies	39		
			2.6.1.2	Distributed Channel Assignment			
				Strategies	39		
		2.6.2	Switchi	ng-Frequency in Channel			
			Assignr	nent	40		
			2.6.2.1	Static Channel Assignment			
				Strategies	41		
			2.6.2.2	Dynamic Channel Assignment			
				Strategies	41		
			2.6.2.3	Hybrid Channel Assignment			
				Strategies	42		
	2.7	Interf	ference A	ware Channel Assignment			
		Algo	rithms		43		
		2.7.1	Channel	Assignment based on the			
			Topolog	y Preservation Strategy	44		

		2.7.1.1	Cluster Based Channel	
			Assignment Algorithm	44
		2.7.1.2	Development Particle Swarm	
			Optimization Algorithm	45
		2.7.1.3	Low Interference Channel	
			Assignment Algorithm	46
	2.7.2	Channel	Assignment based on the Topology	
		Control	Strategy	46
		2.7.2.1	Topology-controlled	
			Interference-aware Channel-	
			assignment Algorithm	47
		2.7.2.2	Utility Based Channel	
			Assignment Algorithm	49
		2.7.2.3	The Channel Assignment based	
			on NSGA-II Algorithm	50
	2.7.3	Channel	Assignment based on the	
		Fairness	s Distribution Strategy	52
		2.7.3.1	Interference-free Communication	
			Based on Minimum Number of	
			Channels	52
		2.7.3.2	Discrete Particle Swarm based on	
			Channel Assignment Algorithm	53
2.8	Diffe	rential Ev	olution	55
2.9	Sum	mary		57
RES	SEARC	CH MET	HODOLOGY	58
3.1	Introc	luction		58
3.2	Resea	rch Fram	ework	58
	3.2.1	Phase 1	: Topology Preservation for Low	
		Interfer	ence Channel Assignment	59
	3.2.2	Phase 2	2: Max Flow based on Topology	
		Contro	l Channel Assignment	61
	3.2.3	Phase (3: Fairness Distribution of the Non-	
		Overla	pping Channels	64

3

	2.2	Dagaa	rah Imple	mantation of the Droposed Work	66
	5.5 2.4	Dorfor	ren impie	valuation	60
	3.4				07
		5.4.1 2.4.2	Simulat	ion setup of MTCA	08
		5.4.2 2.4.2	Simula	ion setup of MICA	/1
	25	5.4.5	Simulat	ion setup of F-NOC	12
	5.5 2.6	Anary	sis and v		75
	3.0 2.7	Assun	npuons a	nd Limitations	75
	3.7	Summ	lary		/4
4	TO	POLO	GY PRES	SERVATION FOR LOW	
	INT	ERFE	RENCE	CHANNEL ASSIGNMENT	75
	4.1	Introd	uction		75
	4.2	Overv	iew of P	roposed TLCA	76
		4.2.1	Channe	l Assignment Constraints	76
	4.3	Propo	sed TLC	A Design	79
		4.3.1	The Pri	ority of the Nodes and Links	83
		4.3.2	The Fu	nction of Least Interference	
			Channe	l (FLIC)	85
	4.4	Evalu	ation		90
		4.4.1	Numeri	cal Results	90
			4.4.1.1	Impact of Varying Numbers of	
				Nodes	91
		4.4.2	Simulat	ion Results	92
			4.4.2.1	The Effect of End-to-End	
				Throughput of Single Hop Flows	93
			4.4.2.2	The Effect of End-to-End	
				Throughput of Multi-Hop Flows	95
			4.4.2.3	The Effect of Different Number	
				of Peer-to-Peer Traffic Profiles	98
	4.5	Summ	nary		100
5	MA	X FLO	W BASE	D ON TOPOLOGY CONTROL	
	CH	ANNEI	ASSIG	NMENT	102
	5.1	Introd	uction		
					102

	5.2	Overv	view of Pr	oposed TLCA	103
		5.2.1	Impact	of Removing the Useless Links on	
			the Net	work Capacity	104
		5.2.2	Networ	k Model	106
	5.3	Propo	sed MTC	A Design	107
		5.3.1	The Pri	ority of the Wireless Links	112
		5.3.2	Functio	n Selection Channel (FSC)	113
	5.4	Evalu	ation		118
		5.4.1	Numeri	cal Results	118
			5.4.1.1	Impact of Varying Numbers of	
				Nodes	119
		5.4.2	Simulat	ion Results	121
			5.4.2.1	The Effect of End-to-End	
				Throughput of Single Hop Flows	121
			5.4.2.2	The Effect of Different Number	
				of Peer-to-Peer Traffic Profiles	122
			5.4.2.2	Impact of Removing the Useless	
				Links	125
	5.5	Summ	nary		126
6	FAI	RNESS	S DISTR	IBUTION OF THE NON-	
	OV	ERLAF	PPING C	HANNELS	127
	6.1	Introd	uction		127
	6.2	Overv	view Prop	osed F-NOC	127
		6.2.1	Impact	of Interference on Fairness	128
	6.3	Propo	sed F-NC	OC Design	130
		6.3.1	Initializ	ation Operation	131
		6.3.2	Mutatio	on Operation	132
		6.3.3	Crossov	ver Operation	134
		6.3.4	Selectio	on Operation	135
	6.4	The F	-NOC Fit	ness Function	137
	6.5	The R	oulette W	Vheel Channel Selection Method	140
	6.6	Evalu	ation		142
		6.6.1	Numeri	cal Results	142

xi

			6.6.1.1	Impact of Varying Numbers of	
				Nodes	142
		6.6.2	Simulat	ion Results	145
			6.6.2.1	The Effect of End-to-End	
				Throughput of Single Hop Flows	145
			6.6.2.2	The Effect of Different Number	
				of Peer-to-Peer Traffic Profiles	147
			6.6.2.3	The Effect of End-to-End	
				Throughput of Multi-Hop Flows	149
	6.7	Sumn	nary		150
7	CO	NCLUS	SIONS		152
	7.1	Overv	view		152
	7.2	Resea	rch Achi	evement	153
		7.2.1	Topolog	gy-preservation for Low	
			Interfer	ence Channel Assignment	153
		7.2.2	Max-flo	ow based on Topology-control	
			Channe	l Assignment	154
		7.2.3	Fairnes	s-distribution of the Non-	
			Overlap	pping Channels	155
	7.3	Limita	ations of (the Proposed Algorithms	155
	7.4	Future	e Work D	irections	156
		7.4.1	Topolog	gy-preservation for Low	
			Interfer	ence Channel Assignment	156
		7.4.2	Max-flo	ow based on Topology-control	
			Channe	l Assignment	157
		7.4.3	Fairnes	s-distribution of the Non-	
			Overlap	ping Channels	157

REFERENCES

158

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	The I-Factor model for the spectrums of IEEE 802.11b	
	standard	35
2.2	The interference range	36
2.3	The interference matrix	37
2.4	The advantage and limitation of the channel assignment of	
	KCA	40
2.5	The advantage and limitation of the channel assignment of	
	SFCA	43
3.1	Parameter values used in numerical model for the TLCA	
	algorithm	69
3.2	Parameter values used in simulation model for the TLCA	
	algorithm	71
4.1	The list of channels in PICh	86
4.2	The list of channels in ACS	88
5.1	The list of channels in PICh	116
5.2	The list of channels in ACS	116
6.1	The channel assignment in a given network topology	139
6.2	The fitness values for each channel in a given topology	140

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	Components of wireless mesh network	2
1.2	Protocol stack of MR-MC and SR-SC	4
2.1	Structure of the literature review	19
2.2	The architecture and components of WMN	20
2.3	Propagation behavior of a wireless signal	22
2.4	Protocol model of interference	25
2.5	Extended protocol model of interference	26
2.6	Scenario of sender connected	27
2.7	Scenario of asymmetric incomplete state	28
2.8	Scenario of symmetric incomplete state	29
2.9	Coordinated interference links	30
2.10	Non-coordinated interference links	31
2.11	The free spectrum in IEEE 802.11b standard	32
3.1	The research framework	59
3.2	The framework of TLCA algorithm	61
3.3	The framework of MTCA algorithm	63
3.4	The framework of F-NOC algorithm	65
4.1	Network topology graph of WMN	78
4.2	Flowchart of the TLCA algorithm; dark gray blocks are the	
	contributions of the proposed algorithm	82
4.3	TLCA channel assignment	83
4.4	The network capacity	91
4.5	The fractional network interference	92
4.6	The throughput of the single hop flows (3 channels and 2	
	interfaces)	94

4.7	The throughput of the single hop flows (12 channels and 3	
	interfaces)	95
4.8	The throughput of the multi-hop flows (3 channel 2	
	interfaces)	96
4.9	The throughput of the multi-hop flows (12 channel 3	
	interfaces)	97
4.10	The throughput of the network topology (Gateway Profile)	99
4.11	The throughput of the network topology (Random Profile)	100
5.1	Channel assignment strategy	105
5.2	The architecture of wireless mesh network	107
5.3	Flowchart of the proposed MTCA; dark gray blocks are the	
	contributions of the proposed algorithm	109
5.4	The network topology of WMN	110
5.5	The network capacity	119
5.6	The fractional network interference	120
5.7	The throughput of the single hop flows	122
5.8	The throughput of the multi-hop flows (Gateway Profile)	123
5.9	The throughput of the multi-hop flows (Random Profile)	124
5.10	The throughput of the network topology	125
6.1	The network topology of WMN	130
6.2	The population representation	132
6.3	The steps of the proposed F-NOC algorithm	134
6.4	Flowchart of the F-NOC; dark gray blocks are the	
	contributions of the proposed algorithm	138
6.5	Network topology graph of WMN	139
6.6	The network capacity	143
6.7	The fractional network interference	144
6.8	The throughput of the network topology	146
6.9	The throughput of the network topology (Gateway Profile)	148
6.10	The throughput of the network topology (Random Profile)	149
6.11	The throughput of the multi-hop flows	150

XV

LIST OF ABBREVIATIONS

ACK	-	Acknowledgment
ACS	-	Available Channel Set
BFS-CA	-	Breadth First Search Channel Assignment
CAEPO	-	Channel Assignment Exploiting Partially Overlapping
		Channels
CAEPO-G	-	Load-Aware Channel Assignment Exploiting Partially
		Overlapping Channels
CAS	-	Channel Assignment Server
CBCA	-	Cluster Based Channel Assignment
CCA	-	Common Channel Assignment
CCL	-	Candidate Channels List
CG	-	Conflict Graph
CIL	-	Coordinated Interference Links
CLICA	-	Connected Low Interference Channel Assignment
CSMA/CA	-	Carrier Sense Multiple Access with Collision Avoidance
CTS	-	Clear-To-Send
DCAS	-	Dynamic Channel Assignment Strategies
DCF	-	Distributed Coordination Function
DE	-	Differential Evolution
DPSO	-	Discrete Particle Swarm Optimization
DPSO-CA	-	Discrete Particle Swarm Optimization for Channel Assignment
DSSS	-	Direct Sequence Spread Spectrum
ESS	-	Extended Service Set
ETT	-	Expected Transmission Time
FLIC	-	Function of the Least Interference Channel
FNI	-	Fractional Network Interference
F-NOC	-	Fairness distribution of the Non-Overlapping Channels
FSC	-	Function Selection Channel

HCAS	-	Hybrid Channel Assignment Strategies
IBSS	-	Independent Basic Service Set
IEEE	-	Institute of Electrical and Electronics Engineers
I-Factor	-	Interference Factor
I-Matrix	-	Interference Matrix
KCA	-	Knowledge-based Channel Assignment
LANs	-	Local Area Networks
LIC	-	Least Interference Channel
MAC	-	Medium Access Control
MCG	-	Multi Conflict Graph
MCS	-	Mesh Clients Set
MGS	-	Mesh Gateways Set
MR-MC	-	Multi-Radios Multi-Channels assignments
MRS	-	Mesh Routers Set
MTCA	-	Max-flow based on Topology-control Channel Assignment
NC	-	Network Capacity
NCIL	-	Non-Coordinated Interference Links
NNs	-	Neighboring Nodes
NR	-	Noise Ratio
NS	-	Network Simulator
OFDM	-	Orthogonal Frequency Division Multiplexing
PCF	-	Point Coordination Function
PCU-CA	-	Probabilistic Channel Usage based Channel Assignment
PICh	-	Potentially Interfere Channel
PSO	-	Particle Swarm Optimization
RTS	-	Request-To-Send
RW	-	Roulette Wheel
SAIS	-	Scenario of Asymmetric Incomplete State
SCAS	-	Static Channel Assignment Strategies
SIR	-	Signal-to-Interference Ratio
SR-SC	-	Single-Radio Single-Channel
SS	-	Signal Strength
SSC	-	Scenario of Sender Connected
SSIS	-	Scenario of Symmetric Incomplete State

TCA	-	Topology Control Algorithm
ТСР	-	Transmission Control Protocol
TICA	-	Topology-controlled Interference-aware Channel-assignment
		Algorithm
TLCA	-	Topology preservation for Low interference Channel
		Assignment
UBCA	-	Utility Based Channel Assignment
UDP	-	User Datagram Protocol
U-NII	-	Unlicensed National Information Infrastructure
VCA	-	Varying Channel Assignment
WMN	-	Wireless Mesh Network

CHAPTER 1

INTRODUCTION

1.1 Overview

Recently, wireless network technologies are emerging everywhere and become more popular. Wireless Mesh Network (WMN) is one of the innovative wireless technologies that provide effective multi hop solutions to provide internet connectivity to a large number of wireless nodes at low cost of construction (Vural et al., 2013; Tsao et al., 2014). As shown in Figure 1.1, the components of a WMN consist of Mesh Clients Set (MCS), Mesh Routers Set (MRS) and Mesh Gateways Set (MGS) (Kumar and Chilamkurti, 2012). MRS connects the mesh clients with the mesh gateways through multi-hop wireless mesh environment. MRS has the ability to support the simultaneous transmission between the wireless links to improve the network capacity. This is because the architecture of the MRS is equipped by multiinterface to connect with varying channels. The architecture of Multi-Radio Multi-Channel (MR-MC) of the mesh router is defined by the IEEE 802.11s standard (Wang and Lim, 2008). The protocol stack architecture of MR-MC mesh router is designed to support multiple radio interfaces to assign multiple channels which can be used for the transmission between the routers in WMN. In the architecture of MR-MC, the network capacity is improved based on the architecture design of the Medium Access Control (MAC) and Physical layer that are installed for each radio within the mesh routers (Benyamina et al., 2012).



Figure 1.1: Components of wireless mesh network (Ali et al., 2014)

In WMNs, the interference is a major factor that affects the throughput of the wireless links (Kumar *et al.*, 2011). Therefore, the throughput limitation between the wireless links is one of the basic challenges faced by the WMNs, compared to the links in wired networks. This is because the communication medium in the wireless networks is shared and affected by the signal strength of the frequency rather than the wired networks which take place through a dedicated medium (Ali *et al.*, 2014). The location of the overlapping wireless links and the distribution of non-overlapping channels between these links have a big impact on mitigating the interference problem (Skalli *et al.*, 2007a). However, the limitation on the non-overlapping channels in IEEE 802.11 standard and number of the interfaces within each node makes the interference problem extraordinarily complicated for WMNs. Moreover, the overall throughput of the wireless network can be affected by the signal strength of the channels assigned to the co-located interfering links (Ding and Xiao, 2011).

The Interference problem affects both the transmission source and destination sides. On source side, the rate of the data transfer is adversely affected by the interaction of Carrier Sense Multiple Access with Collision Avoidance (CSMA/CA) based MAC layer. On destination side, the interference problem causes data collisions that result in packet loss sent by source which may lead to reduction of overall throughput of the link (Saurav et al., 2011). Moreover, the source nodes start sending packets simultaneously when the random access of the protocol CSMA/CA MAC is employed. Thus, the transmission opportunity of the active links stops by the CSMA/CA to avoid the collision of the packet between the interfering links. The impact of interference between the links and the behavior of the MAC protocols has been studied extensively in the literature. However, most of the proposed interference models have limitations when captured and analyzed the impact of the interference based on the behavior of the CSMA/CA MAC protocol (Ali et al., 2014). Consequently, one of the challenges faced in the design of interference aware channel assignment algorithms is selection of the appropriate interference model which is compatible with the behavior of the CSMA/CA MAC protocol to improve the network performance. The motivation of this research is to address the impact of interference between the wireless links by developing the channel assignment algorithms using the appropriate interference model to improve the performance of the network.

1.2 Problem Background

WMNs are considered as promising solution for internet access in wide areas. In WMN, the problem of network capacity in the architecture of Single-Radio Single-Channel (SR-SC) is improved significantly by the architecture of the MR-MC. Figure 1.2(a) and Figure 1.2(b) illustrates the protocol stack of the MR-MC and SR-SC respectively. In MR-MC, the capacity of the network can be improved by a factor equal to the number of radio interfaces which are installed on the nodes (Riggio *et al.*, 2011). This is because, the concept of MR-MC supports the concurrent transmission between the wireless links and then the capacity of the overall network is increased (Chaudhry et al., 2010a; Gálvez and Ruiz, 2013). The use of multiple channels can decrease the effect of interference present between the links. However, the channel assignment on the basis of interference present between the co-located channels becomes critical due to some constraints such as: the number of all the available non-overlapping wireless channels in IEEE 802.11 standard is limited (Duarte et al., 2012; Ning et al., 2014; Wu et al., 2014). In the MR-MC architecture, the wireless nodes has limited number of radio interfaces to assign varying channels. Based on the test bed results defined by Bahl et al. (2004), the maximum number of interfaces that are equipped on each node must not exceed four radio interfaces per node. Additionally, the network is considered more connected when a common channel is used between all the links. However, using a common channel in a given network leads to increase the impact of interference between the links (Ahmed *et al.*, 2014; Athota and Negi, 2014). Therefore, to maintain the network connectivity is a challenging task faced by most of the algorithms that aims to mitigate the impact of interference between the links. Thus, the balance between mitigation of the impact of interference and to maintain the network connectivity, to increase the overall performance of the network, is a complex task.

Multi-R	adio Multi-C		Single-Radio Single-Channe	
				Radio 1
Radio 1	Radio 2	Radio 3		MAC 802.11
MAC 802.11	MAC 802.11	MAC 802.11		
PHY 802.11	PHY 802.11	PHY 802.11		PHY 802.11
C1	C2	C3		C1
	(a)		(b)	

Figure 1.2: Protocol stack of MR-MC and SR-SC

The following sub-sections discuss in detail the issues related to the design of the channel assignment algorithms.

1.2.1. Topology Preservation for Low Interference Channel Assignment

Topology preservation is a strategy used to address the problems of link failure and partitioning of the wireless network (Doraghinejad *et al.*, 2014). In this strategy all the links in the original topology exist in the final topology after the channel assignment process in order to maintain the network connectivity. The main challenge faced by this strategy is the high impact of interference between the links in MR-MC of the WMNs. This is because the number of the available channels and the number of radio interfaces per node is limited. The channel assignment process in the topology preservation strategy is considered as a NP-hard due to the restrictions mentioned in the Section 1.2 (Marina *et al.*, 2010; Kumar *et al.*, 2011; Athota and Negi, 2014; Doraghinejad *et al.*, 2014).

In WMNs, the direction for most of the data traffic in the wireless mesh network is to/from the mesh gateway. Thus, the links close to the gateway are crowded and considered as high-performance links. Consequently, most of the work in the topology preservation field such as Marina *et al.* (2010), Kumar *et al.* (2011), Yong *et al.* (2013) and Athota and Negi (2014) gives the channel assignment priority to links close to the gateway to avoid the congestion problem. Hence, unfair distribution of the channels between the links close to the gateway may cause the problems of bottleneck links and data collisions in a given network topology (Yong *et al.*, 2013). To this end, most of the existing algorithms in the literature aims to assigning varying non-overlapping channels efficiently to mitigate the impact of interference between the links. Thus, some of the existing channel assignment to distribute the channels effectively and mitigate the impact of interference between the links.

The CBCA proposal by Athota and Negi (2014) presents a clustering algorithm named Cluster Based Channel Assignment. The CBCA consists of three stages such as nodes clustering, interfaces binding and channel assignment process. The main target of this algorithm is to mitigate the impact of co-channel interference and ripple effect between the links based on the availability of the channels and interfaces in WMN. In this algorithm, all the radio interfaces of the nodes are used by channels to guarantee the network connectivity between the nodes in different clusters. Moreover, all the nodes are divided into clusters based on the number of hops to utilize the available channels effectively and mitigate the impact of interference between the nodes in the same cluster. However, the CBCA lacks of a mechanism to guarantee the channels are distributed equitably between the links in a given topology. Accordingly, the overall capacity of the network is affected.

Doraghinejad *et al.* (2014) proposed an interference aware channel assignment algorithm based on Gravitational Search Algorithm (GSA). The proposed algorithm named as Improved version of GSA (IGSA). The IGSA aims to utilization of available channels effectively while maintaining on the network connectivity. The proposed algorithm has the abilities of exploration and exploitation the available resources concurrently to find out the best solution. The IGSA algorithm guarantees the network connectivity. However, major challenge faced by the IGSA is associated with the lack of a mechanism to guarantee the effective distribution of the channels between the links close to the gateway.

Cheng *et al.* (2013) proposed an interference aware channel assignment algorithm based on Particle Swarm Optimization (PSO) technique. The proposed algorithm named as Discrete PSO (DPSO) algorithm. The DPSO aims to mitigate the impact of interference between the wireless links while maintaining on the network connectivity. DPSO uses the values of the best solution (pBest) and global best value (gBest) to select the least interference channel for each link. In the DPSO, the channels are assigned randomly to all the links in the network topology. Thus, the DPSO algorithm guarantees the communication between all the nodes in the network topology. However, major challenge faced by the DPSO is associated with the lack of a mechanism used to distinguish between the links in the given network topology, especially the wireless links close to the gateway in order to avoid the bottleneck problem.

Marina *et al.* (2010) proposed an interference aware channel assignment algorithm named Connected Low Interference Channel Assignment (CLICA) algorithm. The proposed algorithm is static channel assignment based on graph coloring problems. The main target of the CLICA is to construct a network topology with low interference while preserving the network connectivity. The CLICA assigns a rank, to all the nodes in the network topology, based on shortest path construction and the number of free radio interfaces. In this algorithm, the channel assignment priority is given to a node that has only a single unassigned radio interface. The drawback of this algorithm is to dynamically adjust the nodes priority which lead to high overhead in the network (Si *et al.*, 2010). Moreover, the connectivity constraint between the nodes in CLICA is achieved by using the topology preservation strategy. However, the main limitation faced by the CLICA is leaves some nodes with unassigned radio interfaces, which reduces the throughput of the network.

Finally, most of the existing interference aware channel assignment algorithms based on topology preservation strategy focused on mitigating the impact of interference between the links. However, most of these algorithms lack a mechanism to ensure distribution of the channels equitably between the links. Additionally, most of these algorithms also aim to distribution of the channels between the links regardless of the behavior of CSMA/CA protocol that developed to improve the overall throughput of the network.

1.2.2. Topology Control based on Non-overlapping Channels Assignment

The strategies of the topology control in the WMN are used to mitigate the impact of interference problem between the links, or improving the energy consumption while maintaining on the network connectivity (Chaudhry *et al.*, 2012; Liu and Bai, 2012). In the literature, most of the works apply the topology control interlinked with channel assignment in MR-MC to enhance the network performance (Naveed *et al.*, 2007). Moreover, the properties of the multi paths in the MR-MC are used in the network topology to maximize the network capacity by increasing the

simultaneous transmissions between the wireless links (Nezhad and Cerda-Alabern, 2010).

One of the challenges faced by the topology control strategies, in the dense network topology, is the number of co-located interfering links between the mesh nodes is higher. Consequently, it is difficult to eliminate the impact of interference between the links completely in dense wireless networks while maintaining on the network connectivity, due to the restrictions that have been discussed in the Section 1.2 (Ali *et al.*, 2014). However, some of these algorithms focus to utilize all the available non-overlapping channels effectively to reduce the impact of interference between the links while maintaining on the network connectivity. In practice, routing protocols favor links which offer higher performance. Therefore most of the links with lower quality are likely useless. In the literature , some of the work applied the process of channel assignment based on removing the useless links from the original topology to improve the network capacity.

Chaudhry *et al.* (2012) proposed an interference aware channel assignment algorithm based on topology control strategy. The proposed algorithm names as Topology-controlled Interference-aware Channel-assignment Algorithm (TICA). The main target of this algorithm is mitigating the impact of interference problem while maintaining on the network connectivity. TICA proposed a new technique names as *select x for less than x* to intelligently assign the non-overlapping channels between the wireless links. The technique of the *select x for less than x* is used to build connected network topology based on the shortest path length (selecting the nearest neighbors for each node). In the TICA, the radio interfaces available on each node are static. One interface on each node is used for control message through a common channel, while the other interfaces are used for data traffic. The main challenge faced by the technique of the *select x for less than x* in the proposed TICA algorithm is used to build connected network topology based on shortest path length regardless to find alternative paths between the nodes.

Nezhad et al. (2010) proposed an algorithm named as Utility Based Channel Assignment (UBCA) in order to assign the non-overlapping channels between the links. The UBCA aims to select a set of links to be used out of all available links in the network topology. The main objective of this algorithm is to mitigate the impact of interference over high performance wireless links. The UBCA gives each link in the network topology a weight equal to the number of links that potentially interfere with target link. Thus, the process of channel assignment in UBCA starts from links with the higher weight. The UBCA removes some of the useless links from the original topology, when the alternative path between the nodes exists and the two nodes which established the link do not have any free radio interfaces to assign the channel. In the case if there is no free radio interface between the two nodes that constituted the link then, the channel merging process is applied to find a common channel between the two nodes. Therefore, the UBCA algorithm guarantees the multi-paths between two nodes in the network topology. Moreover, the UBCA assigns a channel for each link in the network topology in order to maintain the network connectivity. However, the main limitation faced by the UBCA algorithm is that there is no mechanism used to guarantee that the channels are distributed equitably between the links in a given topology. Moreover, the problem of channel merging in the UBCA algorithm may lead to hinder the channels distribution, between the links, optimally.

Chen *et al.* (2009) proposed a channel assignment algorithm based on the genetic NSGA-II algorithm to improve the throughput of the WMNs. The main target of proposed algorithm is to find the optimal topology with minimum interference and maximum number of links between the nodes. The proposed algorithm aims to choose a subset of links among all the links in the network topology to assign the channels without affecting much on the efficiency of the network topology. The main challenge faced by the GAs is a random channel distribution between the nodes based on the fitness function values. Accordingly, in the GAs algorithm no mechanism is used to ensure the fair distribution of the channels between the links to maximize the network capacity. Additionally, there is no mechanism used to distinguish the links between the nodes in the given network topology, especially the links close to the gateway to avoid the bottleneck problem.

Finally, the existing channel assignment algorithms based on the strategies of topology control focus on mitigating the impact of interference between the links by selecting a set of high performance links. However, some of the algorithms have limitations on the equitable channel distribution between the links. There are some algorithms which select a set of high performance links in order to assign the channels regardless to find out the alternative paths between the nodes.

1.2.3. Fairness Distribution of the Non-Overlapping Channels

Generally, the fairness in WMNs be classified into two strategies, fairness perflow and fairness per-node. The fairness per-flow aims to equal share of the amount of packets flowing between the multiple paths. The challenge faced by this strategy is associated with unfair flows between the links close to the gateway when the multiple traffic flows share the same link which lead to the congestion problem (Chaudhry et al., 2012). The fairness per-node aims to equal access, to the wireless medium, for each node in the network topology. The challenge faced by this strategy is that the impact of interference between the links leads to obstruct the nodes that operate on a conflicting channel to access the wireless medium. Consequently, the interference problem in WMNs severely affects the overall network throughput in the schemes of multi-hop flows (Jianjun et al., 2014). Usually, the end-to-end throughput is affected by the link which has minimum throughput due to the impact of interference. One of the critical issues in the fair distribution of the non-overlapping channels is to provide high bandwidth between the nodes to ensure effective communication between them. Hence, a fair distribution of channel capacity between the links in the network topology is significantly important. This is because of the fact that the average of overall network throughput in multi-hop flows is limited by the wireless link which has the least throughput.

To improve the overall throughput of the network, most of the existing work focuses on to distribute the non-overlapping channels between the links effectively and mitigate the impact of interference between the links. Thus, the capability of the whole network topology depends on the total bandwidths of the channels that assigned between the links. In the literature many research works use the fairness distribution channels between the wireless links to improve the overall throughput of WMNs.

Chaudhry et al. (2015) proposed simple computational strategies to find the interference-free communication based on minimum number of channels. The proposed strategies are formulated based on the Signal-to-Interference Ratio (SIR) model. In this work, one radio interface in each node is used as control radio to exchange the control messages between the nodes in a given network topology. This work uses the conflict graph based on the SIR model to capture and analyze the impact of interference between the wireless links. The coloring of conflict graph strategy is used to mitigate the impact of interference between the wireless links. The technique of the select x for less than x in the TCA algorithm defined by Chaudhry et al. (2012) is used to find the minimum number of channels with interference free. The main objective of this work is to improve the throughput while maintaining the fairness among the traffic flows. However, the main challenge faced by this work is to use one radio interface from each node to exchange the control messages between the nodes while the number of interfaces is less as compared to the number of the channels. As a result, the available resources are not utilized optimally to improve the throughput of the WMNs.

In another research, Jianjun *et al.* (2014) proposed a dynamic channel assignment algorithm based on the bipartite-graph model. The proposed algorithm aims to achieve relative fairness between the nodes to maximize the end-to-end throughput flows in multi-hop flows. This work uses the bipartite-graph to model the channels and nodes in a given network topology. In this algorithm, each node uses only the channels that are located within the transmission range. The channel is available to only one node at a time. This work uses minimal of the total bandwidths of the channels assigned between the nodes to represent fairness. The proposed algorithm aims to distribute the channels between the links effectively to improve the fairness between the links. The main challenge of this algorithm is the overhead of channel switching.

Cheng et al. (2012) proposed a non-overlapping channel assignment algorithm named as a Discrete Particle Swarm Optimization for Channel Assignment (DPSO-CA). The proposed algorithm is based on topology preservation as explained by Subramanian et al. (2008). The authors designed channel assignment algorithm using the technique of the DPSO to find the optimal network topology. DPSO-CA is based on the multi-objective function which achieves two conflicting goals (mitigate the interference problem while maintaining on the network connectivity). Moreover, the proposed algorithm DPSO-CA aims to balance between the maintained network connectivity and mitigation of the co-channel interference based on organizing the mesh nodes with available channels. The DPSO-CA selects one radio interface within each node to assign a common channel in the initialization process of the network topology. The major challenge faced by the DPSO-CA is that there is no mechanism to ensure that the channels are distributed equitably between the links. The equitable distribution of the channels between the links helps to improve the network capacity by increasing the simultaneous transmissions between the links. Additionally, the usage of a common channel between the nodes makes the network topology more connected, but this leads to increase the impact of interference between the links.

Recently, many researchers have used the optimization techniques in the interference aware channel assignment algorithms to improve the overall throughput of the WMN (Alabady and Salleh, 2013; Cheng *et al.*, 2013; Doraghinejad *et al.*, 2014). Hence, the selection and adaptation of an appropriate optimization technique, for channel assignment with a mechanism to ensure equitable channel distribution between the links, have a significant impact in improving the throughput of the WMNs.

1.3 Problem Statement

This research addresses the problem of interference in the WMN which limits the throughput, capacity and fairness of the network. In the WMNs, the topology preservation strategy is used to improve the throughput and addresses the problem of the network connectivity. However, the impact of interference between the links is high in the topology preservation strategy due to all the links in the original topology which exist in the final topology after the channel assignment process.

In the dense network topology, the network capacity is adversely affected, due to the higher number of co-located interfering links and the limited available number of the non-overlapping channels which are operating between these links. Consequently, the number of the concurrent transmission between the wireless links deteriorates.

The fairness in the WMN is adversely affected by the impact of interference between the wireless links which obstructs the nodes, to access the wireless medium, that operate on a conflicting channel. Consequently, the interference problem severely affects the overall network throughput in the multi-hop flows schemes. The overall network throughput average in multi-hop flows is limited by the wireless link which has the least throughput.

1.4 Research Questions

This research raises several challenges and these challenges are addressed by providing the answers to the following questions:

- i. How to select the least interference channel effectively to improve the throughput and mitigate the impact of interference between the wireless links while the network connectivity is maintained?
 - a. What parameters should be considered to distinguish the wireless links to improve the overall network performance?
 - b. What metrics should be considered to select the least interference channel among all the non-overlapping channels?

- ii. How to remove the useless links from the original topology to increase the concurrent transmission between the wireless links and improve the network capacity?
 - a. What criteria should be considered to maintain the network connectivity?
 - b. How to derive multi-criteria functions to distinguish and rank the wireless links of the network topology and assign them the non-overlapping channels?
- iii. How to distribute the non-overlapping channels equitably between the wireless links to improve the fairness of the WMN?
 - a. How to develop and adapt the differential evolution algorithm with a roulette wheel method to find and reassign the optimal channel to each link to improve the fairness of the network?
 - b. What criteria should be considered to select the least interference channel among all the non-overlapping channels?

1.5 The Aim

The aim of this research is to mitigate the impact of interference between the wireless links in order to improve the throughput, capacity and fairness of the WMN. However, the network connectivity is maintained by the efficient utilization of the non-overlapping channels between the links.

1.6 Research Objectives

The main objectives of this research are:

- i. To develop an algorithm to select the least interference channel from the available non-overlapping channels using the topology preservation strategy to improve the throughput while the network connectivity is maintained.
- ii. To develop an algorithm to improve the network capacity by increasing the concurrent transmission between the links while satisfying the connectivity constraints by applying the topology control strategy.
- iii. To develop an improved algorithm for fairness by distributing the nonoverlapping channels equitably between the links to enhance the overall throughput of the WMN.

1.7 Significance of the Study

The increased density of the WMNs deployments can provide the users an improved network performance. In the WMN, an equitable distribution of the non-overlapping channels between the links may result in the delivery of better quality of service such as video and voice streaming. However, an increased interference may lead to the challenges of significant degradation of throughput, capacity and fairness. The location of the overlapping links and the distribution of the non-overlapping channels between these links help to mitigate the impact of the interference.

In this research, the proposed algorithms guarantee that the non-overlapping channels are distributed equitably between the links to improve the throughput and to mitigate the impact of interference. The links close to the gateway are classified as high performance links and are assigned varying channels to avoid the bottleneck link problem. The channel assignment algorithms are formulated based on the CSMA/CA protocol to avoid the data collision between the nodes. The removal of the useless links from the original topology, while the connectivity constraints are satisfied, may result in an improved network capacity performance by increasing the concurrent transmissions between the links. Moreover, the use of optimization techniques significantly improves the WMNs fairness through an equitable distribution of the channels capacity between the links.

1.8 Research Scope

The scope of this research covers the following points:

- i. All the mesh routers in the network are equipped with multiple radio interfaces in order to assign multiple channels.
- ii. The external interference which generated by the wireless links of the adjacent networks is not under consideration.
- iii. The partial channels in the IEEE 802.11a/b standards are out of the scope of this research.
- iv. The number of distinct channels that can be assigned to a mesh router is bounded by the number of radio interfaces.
- v. The proposed channel assignment algorithms are static in nature and are executed when the WMNs is initialized.

1.9 Thesis Organization

This research comprises seven chapters. The remaining chapters are organized as follows:

Chapter 2 provides an extensive review of the literature of the area of research, problem background and highlight the shortcomings of most of existing algorithms that have been employed in the interference aware channel assignment algorithms. The chapter has highlighted the shortcomings and advantages of the most of the interference models which are used to capture and evaluate the impact of interference in the WMNs.

Chapter 3 describes the research methodology and experiments used to obtain the objectives of this research. It highlights the design, implementation and verification of the proposed interference-aware non-overlapping channel assignment algorithms that are applied in this research.

Chapter 4 presents the proposed Topology-preservation for Low-interference Channel Assignment (TLCA) algorithm that develops to improve the throughput while maintaining on the network connectivity using topology preservation strategy.

Chapter 5 presents a detailed description for the design and development of the proposed Max-flow based on Topology-control Channel Assignment (MTCA) algorithm. The MTCA is developed to increase the network capacity by removing the useless links from the original topology to increase the number of concurrent transmissions between the links.

Chapter 6 presents the details of the design and implementation of the proposed Fairness distribution of the Non-Overlapping Channels (F-NOC) algorithm. The algorithm is developed to improve the fairness of the WMNs through the equitable distribution of the non-overlapping channels between the links while satisfying the constraints of the network connectivity.

Chapter 7 concludes the research and presents the research achievements. Moreover, the possible future directions are also described in detail.

REFERENCES

- Ahmed, E., Gani, A., Abolfazli, S., Yao, L. J., & Khan, S. U. (2014). Channel Assignment Algorithms in Cognitive Radio Networks: Taxonomy, Open Issues, and Challenges. IEEE Communications Surveys & Tutorials, 99, 1-1.
- Alabady, S. A., & Salleh, M. (2013). Overview of Wireless Mesh Networks. Journal of Communications, 8(9), 134-144.
- Alawieh, B., Yongning, Z., Assi, C., & Mouftah, H. (2009). Improving Spatial Reuse in Multihop Wireless Networks - A Survey. IEEE Communications Surveys & Tutorials, 11(3), 71-91.
- Ali, S., Naveed, A., Ngadi, M., & Chaudhry, J. (2014). Interference Nomenclature in Wireless Mesh Networks. Wireless Personal Communications, 75(4), 1983-2003.
- Athota, K., & Negi, A. (2014). A topology preserving cluster-based channel assignment for wireless mesh networks. International Journal of Communication Systems 2014; DOI: 10.1002/dac.2807, to appear.
- Athota, K., Negi, A., & Rao, C. R. (2010). Interference-Traffic aware Channel Assignment for MRMC WMNs. In Proceedings of the 2010 IEEE 2nd International Advance Computing Conference (IACC), 19-20 Feb. IEEE, 273-278.
- Bahl, P., Adya, A., Padhye, J., & Walman, A. (2004). Reconsidering wireless systems with multiple radios. ACM SIGCOMM Computer Communication Review, 34(5), 39-46.

- Balakrishnan, H., Barrett, C. L., Kumar, V. A., Marathe, M. V., & Thite, S. (2004). The distance-2 matching problem and its relationship to the MAC-layer capacity of ad hoc wireless networks. IEEE Journal on Selected Areas in Communications, 22(6), 1069-1079.
- Beigy, H., & Meybodi, M. R. (2009). Cellular Learning Automata Based Dynamic Channel Assignment Algorithms. International Journal of Computational Intelligence and Applications, 08(03), 287-314.
- Benyamina, D., Hafid, A., & Gendreau, M. (2012). Wireless Mesh Networks Design-A Survey. IEEE Communications Surveys & Tutorials, 14(2), 299-310.
- Bokhari, F., & Záruba, G. (2012). Partially Overlapping Channel Assignments in Wireless Mesh Networks. InTech Open Access Publisher 2012.
- Brandimarte, P. (2013). Numerical methods in finance and economics: a MATLABbased introduction: John Wiley & Sons.
- Burkhart, M., Rickenbach, P. v., Wattenhofer, R., & Zollinger, A. (2004). Does topology control reduce interference?. In Proceedings of the 5th ACM international symposium on Mobile ad hoc networking and computing, Roppongi Hills, Tokyo, Japan, 9-19.
- Cardieri, P. (2010). Modeling Interference in Wireless Ad Hoc Networks. IEEE Communications Surveys & Tutorials, 12(4), 551-572.
- Carrano, R. C., Magalha, x, es, L. C. S., Saade, D. C. M., & Albuquerque, C. V. N. (2011). IEEE 802.11s Multihop MAC: A Tutorial. IEEE Communications Surveys & Tutorials, 13(1), 52-67.
- Chakchouk, N., & Hamdaoui, B. (2011). Traffic and Interference Aware Scheduling for Multiradio Multichannel Wireless Mesh Networks. IEEE Transactions on Vehicular Technology, 60(2), 555-565.
- Chang, C. Y., Lee, S. C., & Chen, Y. C. (2011). Channel-switching and power control mechanisms for improving network connectivity in wireless mesh networks. Wireless Communications & Mobile Computing, 11(6), 750-766.

- Chaudhry, A., Ahmad, N., & Hafez, R. (2012). Improving throughput and fairness by improved channel assignment using topology control based on power control for multi-radio multi-channel wireless mesh networks. EURASIP Journal on Wireless Communications and Networking, 2012(1), 1-25.
- Chaudhry, A. U., Hafez, R. H. M., Aboul-Magd, O., & Mahmoud, S. A. (2010).
 Throughput Improvement in Multi-Radio Multi-Channel 802.11a-Based
 Wireless Mesh Networks. In Proceedings of the 2010 IEEE International
 Conference on Global Telecommunications (GLOBECOM), 6-10 Dec. IEEE, 15.
- Chaudhry, A. U., Hafez, R. H. M., & Chinneck, J. W. (2015). On the impact of interference models on channel assignment in multi-radio multi-channel wireless mesh networks. Ad Hoc Networks, 27(0), 68-80.
- Chen, J. A., Jia, J., Wen, Y. Y., Zhao, D. Z., & Liu, J. R. (2009). A Genetic Approach to Channel Assignment for Multi-radio Multi-channel Wireless Mesh Networks. World Summit on Genetic and Evolutionary Computation. 09, 39-46.
- Cheng, H., Xiong, N., Vasilakos, A. V., Tianruo Yang, L., Chen, G., & Zhuang, X. (2012). Nodes organization for channel assignment with topology preservation in multi-radio wireless mesh networks. Ad Hoc Networks, 10(5), 760-773.
- Cheng, H., Xiong, N., Yang, L., Chen, G., Zhuang, X., & Lee, C. (2013). Links organization for channel assignment in multi-radio wireless mesh networks. Multimedia Tools and Applications, 65(2), 239-258.
- Chieochan, S., & Hossain, E. (2013). Channel Assignment for Throughput Optimization in Multichannel Multiradio Wireless Mesh Networks Using Network Coding. IEEE Transactions on Mobile Computing, 12(1), 118-135.
- Coelho, L. d. S., Bora, T. C., & Mariani, V. C. (2014). Differential evolution based on truncated Lévy-type flights and population diversity measure to solve economic load dispatch problems. International Journal of Electrical Power & Energy Systems, 57(0), 178-188.
- Conti, M., Das, S. K., Lenzini, L., & Skalli, H. (2008). Channel Assignment Strategies for Wireless Mesh Networks. In Wireless Mesh Networks. Springer US, 113-142.

- Crichigno, J., Wu, M. Y., & Shu, W. (2008). Protocols and architectures for channel assignment in wireless mesh networks. Ad Hoc Networks, 6(7), 1051-1077.
- Das, S., & Suganthan, P. N. (2011). Differential Evolution: A Survey of the State-ofthe-Art. IEEE Transactions on Evolutionary Computation, 15(1), 4-31.
- Ding, Y., & Xiao, L. (2011). Channel allocation in multi-channel wireless mesh networks. Computer Communications, 34(7), 803-815.
- Dongsheng, W., Pin, L., Yingwen, C., & Ming, X. (2011). POCAM: Partially overlapped channel assignment in multi-radio multi-channel wireless mesh network. In Proceedings of the 2011 IEEE International Conference on Communications and Information Technologies (ISCIT), 12-14 Oct. IEEE, 188-193.
- Doraghinejad, M., Nezamabadi-pour, H., & Mahani, A. (2014). Channel assignment in multi-radio wireless mesh networks using an improved gravitational search algorithm. Journal of Network and Computer Applications, 38, 163-171.
- Draves, R., Padhye, J., & Zill, B. (2004). Routing in multi-radio, multi-hop wireless mesh networks. In Proceedings of the 10th annual international conference on Mobile computing and networking. Philadelphia, USA, 114-128.
- Drieberg, M. (2010). Channel assignment strategies for throughput enhancement in high density wireless local area networks. Ph.D. Thesis. Centre for Telecommunications and Micro-Electronics, Faculty of Health, Engineering and Science, Victoria University, Melbourne, Australia
- Duarte, P. B. F., Fadlullah, Z. M., Hashimoto, K., & Kato, N. (2010). Partially Overlapped Channel Assignment on Wireless Mesh Network Backbone. In Proceedings of the 2010 IEEE International Conference on Global Telecommunications (GLOBECOM 2010), 6-10 Dec. IEEE, 1-5.
- Duarte, P. B. F., Fadlullah, Z. M., Vasilakos, A. V., & Kato, N. (2012). On the Partially Overlapped Channel Assignment on Wireless Mesh Network Backbone: A Game Theoretic Approach. IEEE Journal on Selected Areas in Communications, 30(1), 119-127.
- Feng, W. S., Zhang, L., & Wang, H. P. (2009). Approximation algorithm for maximum edge coloring. Theoretical Computer Science, 410(11), 1022-1029.

- Gálvez, J. J., & Ruiz, P. M. (2013). Efficient rate allocation, routing and channel assignment in wireless mesh networks supporting dynamic traffic flows. Ad Hoc Networks, 11(6), 1765-1781.
- Garetto, M., Salonidis, T., & Knightly, E. W. (2008). Modeling per-flow throughput and capturing starvation in CSMA multi-hop wireless networks. IEEE/ACM Transactions on Networking (TON), 16(4), 864-877.
- Garetto, M., Shi, J., & Knightly, E. W. (2005). Modeling media access in embedded two-flow topologies of multi-hop wireless networks. In Proceedings of the 11th annual international conference on Mobile computing and networking (MobiCom '05). ACM, New York, NY, USA, 200-214.
- Gupta, P., & Kumar, P. R. (2000). The capacity of wireless networks. IEEE Transactions on Information Theory, 46(2), 388-404.
- He, Y., Xu, L., & Wu, W. (2014). A local joint fast handoff scheme in cognitive wireless mesh networks. Security and Communication Networks, 7(2), 455-465.
- Hong, X. Y., Gu, B., Hoque, M., & Tang, L. (2010). Exploring Multiple Radios and Multiple Channels in Wireless Mesh Networks. IEEE Wireless Communications, 17(3), 76-85.
- Hoque, M. A., & Hong, X. (2011). Channel Assignment Algorithms for Mrmc Wireless Mesh Networks. International Journal of Wireless & Mobile Networks, 3(5), 76-94.
- Hoque, M. A., Hong, X. Y., & Afroz, F. (2009). Multiple Radio Channel Assignement Utilizing Partially Overlapped Channels. In Proceedings of the 2009 IEEE International Conference on Global Telecommunications, Nov. 30 -Dec. 4. IEEE, 1-7.
- Iyer, A., Rosenberg, C., & Karnik, A. (2009). What is the right model for wireless channel interference?. IEEE Transactions on Wireless Communications, 8(5), 2662-2671.
- Jain, K., Padhye, J., Padmanabhan, V., & Qiu, L. (2005). Impact of Interference on Multi-Hop Wireless Network Performance. Wireless Networks, 11(4), 471-487.
- Jang, S. Y., & Lee, C. Y. (2011). Multipath selection and channel assignment in wireless mesh networks. Wireless Networks, 17(4), 1001-1014.

- Ji-Pyng, C., Chung-Fu, C., & Chao-Ching, W. (2014). Hybrid Differential Evolution for Static Economic Dispatch. In Proceedings of the 2014 IEEE International Symposium on Computer, Consumer and Control (IS3C), 10-12 June. IEEE, 950-953.
- Jianjun, Y., Yin, W., Kun, H., & Wei, W. (2014). Fairness based dynamic channel allocation in wireless mesh networks. In Proceedings of the 2014 IEEE International Conference on Computing, Networking and Communications (ICNC), 3-6 Feb. IEEE, 556-560.
- Johansson, T., & Carr-Moty, L. (2005). Reducing interference in ad hoc networks through topology control. In Proceedings of the 2005 joint workshop on Foundations of mobile computing, Cologne, Germany, 17-23.
- Khan, S. (2009). Design of rate-adaptive MAC and medium aware routing protocols for multi-rate, multi-hop wireless networks. Doctoral dissertation, School of Engineering and Design, Brunel University, United Kingdom.
- Khushaba, R., Al-Ani, A., & Al-Jumaily, A. (2009). Feature Subset Selection Using Differential Evolution. In M. Köppen, N. Kasabov & G. Coghill (Eds.), Advances in Neuro-Information Processing. 5506, 103-110. Springer Berlin Heidelberg.
- Khushaba, R. N., Al-Ani, A., & Al-Jumaily, A. (2011). Feature subset selection using differential evolution and a statistical repair mechanism. Expert Systems with Applications, 38(9), 11515-11526.
- Kim, S. H., Kim, D. W., & Suh, Y. J. (2011). A Cooperative Channel Assignment protocol for multi-channel multi-rate wireless mesh networks. Ad Hoc Networks, 9(5), 893-910.
- Kim, S. H., & Suh, Y. J. (2010). A distributed channel assignment protocol for rate separation in wireless mesh networks. Computer Communications, 33(11), 1281-1295.
- Kumar, N., & Chilamkurti, N. (2012). Agent assisted mobility and load aware fast handoff scheme in wireless mesh networks. International Journal of Internet Protocol Technology, 7(1), 26-38.

- Kumar, N., Kumar, M., & Patel, R. B. (2011). Capacity and interference aware link scheduling with channel assignment in wireless mesh networks. Journal of Network and Computer Applications, 34(1), 30-38.
- Kyasanur, P., & Vaidya, N. H. (2005). Routing and interface assignment in multichannel multi-interface wireless networks. In Proceedings of the 2005 IEEE International Conference on Wireless Communications and Networking, 13-17 March. IEEE, 2051- 2056.
- Lei, H.-j., Gao, C., Guo, Y.-c., & Zhang, Z.-z. (2011). Survey of multi-channel MAC protocols for IEEE 802.11-based wireless Mesh networks. The Journal of China Universities of Posts and Telecommunications, 18(2), 33-44.
- Li, M., Guang-xi, Z., & Bo-Yun, Y. (2008). Optimization Models of Multi-Channel Assignment in Multi-Radio Wireless Mesh Networks. In Proceedings of the 2008 IEEE International Conference on Wireless Communications, Networking and Mobile Computing, 12-14 Oct. IEEE, 1-5.
- Lin, J.-W., & Lin, S.-M. (2014). A weight-aware channel assignment algorithm for mobile multicast in wireless mesh networks. Journal of Systems and Software, 94(0), 98-107.
- Lindholm, T., Yellin, F., Bracha, G., & Buckley, A. (2014). The Java virtual machine specification: Pearson Education.
- Liu, C., Wang, G., Xie, Q., & Zhang, Y. (2014). Vibration Sensor-Based Bearing Fault Diagnosis Using Ellipsoid-ARTMAP and Differential Evolution Algorithms. Sensors, 14(6), 10598-10618.
- Liu, F., & Bai, Y. (2012). An overview of topology control mechanisms in multiradio multi-channel wireless mesh networks. EURASIP Journal on Wireless Communications and Networking, 2012(1), 1-12.
- Liu, Y. T., Venkatesan, R., & Li, C. (2009). Channel assignment exploiting partially overlapping channels for wireless mesh networks. In Proceedings of the 2009 IEEE International Conference on Global Telecommunications. 30 Nov–4 Dec. IEEE, 1-5.

- Liu, Y. T., Venkatesan, R., & Li, C. (2010). Load-Aware Channel Assignment Exploiting Partially Overlapping Channels for Wireless Mesh Networks. In Proceedings of the 2010 IEEE International Conference on Global Telecommunications, 6-10 Dec. IEEE, 1-5.
- Mak, T. K., Laberteaux, K. P., Sengupta, R., & Ergen, M. (2009). Multichannel Medium Access Control for Dedicated Short-Range Communications. IEEE Transactions on Vehicular Technology, 58(1), 349-366.
- Maqbool, W., Yusof, S. K. S., Latiff, N. M. A., Hafizah, S., Nejatian, S., Farzamnia, A., & Zubair, S. (2013). Interference aware channel assignment (IACA) for cognitive wireless mesh networks. In Proceedings of the 2013 IEEE Malaysia International Conference on Communications (MICC), 26-28 Nov. IEEE, 330-334.
- Marina, M. K., Das, S. R., & Subramanian, A. P. (2010). A topology control approach for utilizing multiple channels in multi-radio wireless mesh networks. Computer Networks, 54(2), 241-256.
- Mishra, A., Rozner, E., Banerjee, S. and Arbaugh, W. (2005a). Exploiting partially overlapping channels in wireless networks: Turning a peril into an advantage. In Proceedings of the 5th ACM SIGCOMM conference on Internet Measurement. ICM 2005. Berkeley, CA, USA, 29–29.
- Mogaibel, H. A., Othman, M., Subramaniam, S., & Asilah Wati Abdul Hamid, N. (2012). On-demand channel reservation scheme for common traffic in wireless mesh networks. Journal of Network and Computer Applications, 35(4), 1329-1351.
- Naveed, A., & Kanhere, S. S. (2009). Cluster-based Channel Assignment in Multiradio Multi-channel Wireless Mesh Networks. In Proceedings of the 2009 IEEE 34th Conference on Local Computer Networks. LCN 2009. 20-23 Oct .Zurich, Switzerland, 53–60.
- Naveed, A., Kanhere, S. S., & Jha, S. K. (2007). Topology control and channel assignment in multi-radio multi-channel wireless mesh networks. In Proceedings of the 2007 IEEE International Conference on Mobile Ad-hoc and Sensor Systems. 8-11 Oct. Pisa, Italy, 1–9.

- Newton, M. A. H., Pham, D., Tan, W., Portmann, M., & Sattar, A. (2013). Stochastic Local Search Based Channel Assignment in Wireless Mesh Networks. In Principles and Practice of Constraint Programming. 8124, 832-847: Springer Berlin Heidelberg.
- Nezhad, M. A., & Cerda-Alabern, L. (2010). Utility Based Channel Assignment Mechanism for Multi Radio Mesh Networks. In Proceedings of the 8th ACM international workshop on Mobility management and wireless access (MobiWac '10). New York, USA, 68-74.
- Ngadi, M. A., Ali, S., Abdullah, A. H., & Khokhar, R. H. (2012). A taxonomy of cross layer routing metrics for wireless mesh networks. EURASIP J. Wireless Comm. and Networking, 2012, 177.
- Ning, L., Plets, D., Joseph, W., & Martens, L. (2014). An algorithm for optimal network planning and frequency channel assignment in indoor WLANs. In Proceedings of the 2014 IEEE International Symposium on the Antennas and Propagation Society (APSURSI), 6-11 July. IEEE, 1177-1178.
- Pak, W., & Bahk, S. (2011). Traffic Flow Estimation based Channel Assignment for Wireless Mesh Networks. Ksii Transactions on Internet and Information Systems, 5(1), 68-82.
- Palit, A. K., & Popovic, D. (2006). Computational intelligence in time series forecasting: theory and engineering applications. 1st. ed. Springer Science & Business Media. 2006.
- Pathak, P. H., & Dutta, R. (2011). A Survey of Network Design Problems and Joint Design Approaches in Wireless Mesh Networks. IEEE Communications Surveys and Tutorials, 13(3), 396-428.
- Perahia, E. (2008). IEEE 802.11n Development: History, Process, and Technology. IEEE Communications Magazine. 46(7), 48–55.
- Plummer, A., & Biswas, S. (2011). Distributed spectrum assignment for cognitive networks with heterogeneous spectrum opportunities. Wireless Communications & Mobile Computing, 11(9), 1239-1253.

- Price, K., Storn, R. M., & Lampinen, J. A. (2006). Differential evolution: a practical approach to global optimization: 1st. ed. Springer Science & Business Media. 2006.
- Qin, A. K., Huang, V. L., & Suganthan, P. N. (2009). Differential Evolution Algorithm With Strategy Adaptation for Global Numerical Optimization. IEEE Transactions on Evolutionary Computation 13(2), 398-417.
- Rahman, M., Agarwal, A., & Alsarahn, A. (2008). Capacity Based Channel Assignment in Multi-Interface Wireless Mesh Networks. In Proceedings of the 2008 IEEE International Conference on Computer and Information Technology (ICCIT), 24-27 Dec. IEEE, 57-64.
- Ramachandran, K. N., Belding, E. M., Almeroth, K. C., & Buddhikot, M. M. (2006).
 Interference-aware channel assignment in multi-radio wireless mesh networks.
 In 25th IEEE International Conference on Computer Communications.
 INFOCOM 2006. Barcelona, Catalunya, Spain, 1–12.
- Raniwala, A. and Cker Chiueh, T. (2005). Architecture and algorithms for an IEEE 802.11-based multi-channel wireless mesh network. In Proceedings of 24th Annual Joint Conference of the IEEE Computer and Communications Societies, INFOCOM 2005, 13-17 March. Miami, FL, USA, 2223–2234.
- Raniwala, A., Gopalan, K., & Chiueh, T.C. (2004). Centralized channel assignment and routing algorithms for multi-channel wireless mesh networks. ACM SIGMOBILE Mobile Computing and Communications Review, 8(2), 50-65.
- Riggio, R., Rasheed, T., Testi, S., Granelli, F., & Chlamtac, I. (2011). Interference and traffic aware channel assignment in WiFi-based wireless mesh networks. Ad Hoc Networks, 9(5), 864-875.
- Saurav, G., Niva, D., & Tanmoy, S. (2011). A Cluster Based Multi-Radio Multi-Channel Assignment Approach in Wireless Mesh Networks. Computer Networks and Information Technologies. 142, 487-491. Springer Berlin Heidelberg.

- Shah, I., Jan, S., & Kok-Keong, L. (2010). Selfish Flow Games in Non-cooperative Multi-radio Multi-channel Wireless Mesh Networks with Imperfect Information.
 In Proceedings of the 2010 IEEE International Conference on Wireless and Mobile Communications (ICWMC), 20-25 Sept. IEEE, 219- 225.
- Shah, I. A. (2012). Channel assignment and routing in cooperative and competitive wireless mesh networks. Doctoral dissertation, Brunel University School of Engineering and Design.
- Si, W., Selvakennedy, S., & Zomaya, A. Y. (2010). An overview of Channel Assignment methods for multi-radio multi-channel wireless mesh networks. Journal of Parallel and Distributed Computing, 70(5), 505-524.
- Sikdar, B. (2007). An Analytic Model for the Delay in IEEE 802.11 PCF MAC-Based Wireless Networks. IEEE Transactions on Wireless Communications, 6(4), 1542-1550.
- Siris, V. A., & Delakis, M. (2011). Interference-aware channel assignment in a metropolitan multi-radio wireless mesh network with directional antennas. Computer Communications, 34(12), 1518-1528.
- Skalli, H., Ghosh, S., Das, S. K., Lenzini, L., & Conti, M. (2007). Channel assignment strategies for multiradio wireless mesh networks: Issues and solutions. IEEE Communications Magazine, 45(11), 86-93.
- Storn, R., & Price, K. (1997). Differential Evolution A Simple and Efficient Heuristic for global Optimization over Continuous Spaces. Journal of Global Optimization, 11(4), 341-359.
- Subramanian, A. P., Gupta, H., & Das, S. R. (2007). Minimum interference channel assignment in multi-radio wireless mesh networks. In Proceedings of the 4th Annual IEEE Communications Society Conference on Sensor, Mesh and Ad-Hoc Communications and Networks. IEEE, 481-490.
- Subramanian, A. P., Gupta, H., Das, S. R., & Cao, J. (2008). Minimum Interference Channel Assignment in Multiradio Wireless Mesh Networks. IEEE Transactions on Mobile Computing, 7(12), 1459-1473.

- Tang, J., Xue, G. and Zhang,W. (2005). Interference-aware topology control and QoS routing in multi-channel wireless mesh networks. In Proceedings of the 6th ACM international symposium on Mobile ad hoc networking and computing. MobiHoc 2005. Urbana-Champaign, IL, USA, 68–77.
- Tsao, S.-L., Su, J.-J., Huang, K.-L., Shih, Y.-C., & Tseng, C.-C. (2014). An end-toend channel allocation scheme for a wireless mesh network. International Journal of Communication Systems, 27(12), 4407-4429.
- Vesterstrom, J., & Thomsen, R. (2004). A comparative study of differential evolution, particle swarm optimization, and evolutionary algorithms on numerical benchmark problems. In Proceedings of the 2004 IEEE Conference on Evolutionary Computation (CEC2004). 19-23 June. IEEE, 1980- 1987.
- Vetrichelvi, G., & Kumar, G. M. (2013). Implementation Of Ars-Str In Str For Effective Energy Transmission. Journal of Applied Sciences Research, 9(5).
- Vural, S., Dali, W., & Moessner, K. (2013). Survey of Experimental Evaluation Studies for Wireless Mesh Network Deployments in Urban Areas Towards Ubiquitous Internet. Communications Surveys & Tutorials, IEEE, 15(1), 223-239.
- Wang, X., & Lim, A. O. (2008). IEEE 802.11s wireless mesh networks: Framework and challenges. Ad Hoc Networks, 6(6), 970-984.
- Wu, D., Yang, S.-H., Bao, L., & Liu, C. (2014). Joint multi-radio multi-channel assignment, scheduling, and routing in wireless mesh networks. Wireless Networks, 20(1), 11-24.
- Yildiz, A. R. (2013). Hybrid Taguchi-differential evolution algorithm for optimization of multi-pass turning operations. Applied Soft Computing, 13(3), 1433-1439.
- Ying-Yu, C., Chien, C., & Rong-Hong, J. (2013). Impact of interface constraint on channel assignment in wireless mesh networks. In Proceedings of the 2013 IEEE International Conference on Wireless Communications and Networking (WCNC), 7-10 April. IEEE, 1309 - 1314.

- Yong, D., Pongaliur, K., & Li, X. (2013). Channel Allocation and Routing in Hybrid Multichannel Multiradio Wireless Mesh Networks. IEEE Transactions on Mobile Computing, 12(2), 206-218.
- Yong, D., Yi, H., Guokai, Z., & Li, X. (2012). Using Partially Overlapping Channels to Improve Throughput in Wireless Mesh Networks. IEEE Transactions on Mobile Computing, 11(11), 1720-1733.
- Zhou, X., Zhang, Z., Wang, G., Yu, X., Zhao, B. Y., & Zheng, H. (2013). Practical conflict graphs for dynamic spectrum distribution. In ACM SIGMETRICS Performance Evaluation Review, 41(1), 5-16.