Technical University of Denmark



# Support effect on the activity and thermal stability of platinum nanoparticles for diesel oxidation

Silva, Hugo José Lopes; Mazantti, Nicola ; Spiga, Cristiano; Damsgaard, Christian Danvad; Chorkendorff, Ib; Chakraborty , Debasish

Publication date: 2016

Document Version Peer reviewed version

Link back to DTU Orbit

Citation (APA):

Silva, H. J. L., Mazantti, N., Spiga, C., Damsgaard, C. D., Chorkendorff, I., & Chakraborty, D. (2016). Support effect on the activity and thermal stability of platinum nanoparticles for diesel oxidation. Abstract from European Advanced Material Congress, Stockholm, Sweden.

### DTU Library Technical Information Center of Denmark

### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim. 1. Please mention the conference Session/Topics you are interested to: .....

2. If this abstract is to be submitted for a Symposium, please mention the Symposium title: .....

3. Please submit the MS word version of the abstract and avoid submitting a PDF version

## Support effect on the activity and thermal stability of platinum nanoparticles for diesel oxidation

Hugo Silva<sup>1</sup>, Nicola Mazantti<sup>1</sup>, Cristiano Spiga<sup>2</sup>, Christian D. Damsgaard<sup>2</sup>, Ib Chorkendorff<sup>1</sup>,

Debasish Chakraborty\*1

1: DTU Physics; 2: DTU Cen

\*Corresponding author e-mail: debc@fysik.dtu.dk

### Abstract:

Diesel engines generate harmful gases with environmental and public health implications. Tighter emission regulations is driving the automotive industry to develop highly efficiency catalytic converter devices, where the diesel oxidation catalyst (DOC) has the crucial role of decreasing the pollution levels through the oxidation reaction of nitrogen oxides (NO<sub>x</sub>), carbon monoxide (CO), unburned hydrocarbons (HC, e.g. propene) and sulfur oxides (SO<sub>x</sub>) [1].


The state of the art catalysts for diesel exhaust oxidation are scarce and precious nanoparticles, eg. platinum (Pt) and palladium (Pd), supported in high surface area metal oxides (e.g.  $\gamma$ -Al<sub>2</sub>O<sub>3</sub>, SiO<sub>2</sub>). During the driving cycle, the active nanoparticles are prone to sintering by particle migration or Ostwald ripening mechanism [2], leading to a loss of metallic surface area and subsequent efficiency. Hydrothermal durability required up to 700-800 °C coupled with low-temperature activity (< 200 °C), is one of the main challenges of the current technology.

In this work, the activity for HC oxidation and thermal stability of platinum catalysts prepared by incipient wetness impregnation method was studied regarding the support effect (MgAl<sub>2</sub>O<sub>4</sub>, SiO<sub>2</sub>). The Pt/MgAl<sub>2</sub>O<sub>4</sub> catalyst presented a remarkable stability at extreme conditions (750 °C, 10% O<sub>2</sub>) as showed in Figure 1A during in situ x-ray powder diffraction (XRD) measurements. Accordingly, the crystallite size of the platinum nanoparticles increased from 15 nm to 28 nm after 12 h at 750 °C in a oxygenrich environment, whereas in the SiO<sub>2</sub> support the nanoparticles size reached the 58 nm. High resolution transmission electron microscopy images (HR-TEM) corroborated the in situ XRD results. As another interesting result, the Pt/MgAl<sub>2</sub>O<sub>4</sub> presented a enhance activity after a

reduction pre-treatement at 800 °C/2h with 5 % hydrogen. As visible in Figure 1B the conversion for propene oxidation increased from ca. 5 % to 45 % after the former mentioned pre-treatment. Contrary to this, the conversion for the Pt/SiO<sub>2</sub> catalyst didn't suffer any improvement. Moreover, it was possible to regenerate the activity of an aged Pt/MgAl<sub>2</sub>O<sub>4</sub> catalyst with the reduction pre-treatement (result not shown).

The MgAl<sub>2</sub>O<sub>4</sub> support is found to be a promising alternative for increasing the activity and stability of platinum nanoparticles for diesel oxidation. The obtained results are obtained within the framework of CatProDiesel project, in collaboration with Dinex (industrial partner), Danish Technological Institute (DTI) and Center for Materials Crystallography.

**Keywords**: Diesel oxidation, platinum nanoparticles, support effect, MgAl<sub>2</sub>O<sub>4</sub>, thermal stability, propene oxidation, reduction pre-treatment.



**Figure 1** – A: Crystallite size of Pt on different supports (SiO<sub>2</sub>, MgAl<sub>2</sub>O<sub>4</sub>) determined through *in situ* XRD measurements and acquired at 750 °C with 10 % O<sub>2</sub> balanced in N<sub>2</sub> during a 15 h period. B: Stability at 200 °C of the Pt/SiO<sub>2</sub> and Pt/MgAl<sub>2</sub>O<sub>4</sub> catalyst for propene oxidation reaction, before and after a reduction pretreatment at 800 °C in 5 % H<sub>2</sub> balanced in N<sub>2</sub> for 2 h.

### **References:**

1. Russell A, Epling WS (2011) Diesel Oxidation Catalysts. Catal Rev 53:337–423.

2. Simonsen SB, Chorkendorff I, Dahl S, et al. (2012) Effect of Particle Morphology on the Ripening of Supported Pt Nanoparticles. J Phys Chem C 116:5646–5653.