

Technical University of Denmark



Design Optimization of Piles for Offshore Wind Turbine Jacket Foundations

Sandal, Kasper; Zania, Varvara

Publication date:
2016

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Sandal, K., & Zania, V. (2016). Design Optimization of Piles for Offshore Wind Turbine Jacket Foundations. Poster session presented at 12th EAWE PhD seminar on Wind Energy in Europe, Lyngby, Denmark.

DTU Library Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



Design Optimization of Piles for Offshore Wind Turbine Jacket Foundations

Kasper Sandal, PhD student, DTU Wind Energy, kasp@dtu.dk

Varvara Zania, Associate Professor, DTU Civil Engineering




Figure 1: Jacket foundation.

Numerical methods can optimize the pile design

The aim of this study is to automatically design optimal piles for offshore wind turbine jacket foundations (Figure 1). Pile mass is minimized with constraints on axial and lateral capacity. Results indicate that accurate knowledge about soil characteristics can translate into significant cost reductions.

Pile design can be formulated as an optimization problem

Let F and M be the loads on the pile head, and $Q(x)$ the capacity of the pile (Figures 2 & 3). The aim is to minimize the total pile mass while keeping the capacities larger than the loads.




Figure 2: Offshore wind turbine and loads.




Figure 3: Loads and capacity on pile.

$$\begin{aligned} & \text{minimize}_{x=(d,t,l) \in \mathbb{R}^3} c(x) = \rho \pi (d^2 - d_i^2) l \\ & \text{subject to} \quad F - Q_F(x) \leq 0 \\ & \quad \quad \quad M - Q_M(x) \leq 0 \\ & \quad \quad \quad d - l/10 \leq 0 \\ & \quad \quad \quad 0.0063 + d/100 - t \leq 0 \end{aligned}$$

Acknowledgment

This work is part of the Danish strategic research project ABYSS (www.abyss.dk), funded by Innovation Fund Denmark.

Design optimization generates specific pile design

An offshore wind turbine on a jacket is subjected to an extreme thrust force. For a specific choice of soil properties, the optimization problem is solved (Figure 4). Only one soil layer is considered.




Figure 4: Overview of optimization setup. JADOP is a package for jacket optimization developed by the first author and Alexander Verbart.

The optimized piles have a total mass of 153 tons. Thickness does not contribute to capacity, and is therefore minimized. The result is considered realistic, but has not been validated.

Complete soil data and automatic pile design can reduce cost

Automatic preliminary pile design is demonstrated, and it is observed that pile design is very sensitive to selected soil properties. If a wind farm is constructed without full knowledge of soil data, one either runs the risk of non-conservative designs, or the cost of over-conservative designs. Designing piles specifically for each turbine can reduce this expense, and automatic pile design can be a useful tool.

Soil parameters influence the optimal pile design

Pile capacity $Q(x)$ changes with soil conditions. The optimization problem is solved repeatedly for small changes in the soil properties (Figures 5 & 6).




Figure 5: Result of parameter study for piles in clay. The shear strength has a large influence on the pile design.




Figure 6: Result of parameter study for piles in sand. Both soil weight and angle of friction have a large influence on the pile design.