

Technical University of Denmark



Design of Passive Acoustic Wave Shaping Devices and Their Experimental Validation

Christiansen, Rasmus Ellebæk; Sigmund, Ole; Fernandez Grande, Eflen

Publication date:
2017

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Christiansen, R. E., Sigmund, O., & Fernandez Grande, E. (2017). Design of Passive Acoustic Wave Shaping Devices and Their Experimental Validation. Abstract from 12th World Congress of Structural and Multidisciplinary Optimization, Braunschweig, Germany.

DTU Library
Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Design of Passive Acoustic Wave Shaping Devices and Their Experimental Validation

Authors:

Rasmus Ellebæk Christiansen¹, Ole Sigmund.

Department of Mechanical Engineering, Technical University of Denmark.

Efren Fernandez-Grande

Department of Electrical Engineering, Technical University of Denmark.

Abstract

We discuss a topology optimization based approach for designing passive acoustic wave shaping devices and demonstrate its application to; directional sound emission [1], sound focusing and wave splitting. Optimized devices, numerical and experimental results are presented and benchmarked against other designs proposed in the literature. We focus on design problems where the size of the device is on the order of the wavelength, a problematic region for traditional design methods, such as ray tracing.

The acoustic optimization problem is formulated in the frequency domain and modeled by the Helmholtz equation. An exterior 2D model domain is used and an array of point sources is considered as sound emitters. The optimization goal is to identify a distribution of solid material in a design sub-domain which produces a desired spatial sound field pattern across a frequency band of interest in a target sub-domain. The objective is the integral of the deviation in pressure magnitude, between a prescribed sound field and the solution to the model problem for a given design realization over the target sub-domain. Filtering is used for regularization and to allow for meaningful optimization for geometric robustness [2]. The Globally Convergent Method of Moving Asymptotes is used to perform the optimization [3].

References

- [1] Christiansen, R. E. and Efren Fernandez-Grande, *Design of passive directional acoustic devices using Topology Optimization - from method to experimental validation*. J. Acoust. Soc. Am. 140, p. 3862-3873, 2016.
- [2] Rasmus E. Christiansen and Boyan S. Lazarov and Jakob S. Jensen and Ole Sigmund, *Creating geometrically robust designs for highly sensitive problems using topology optimization - Acoustic Cavity Design*. Struct Multidisc Optim 52, p. 737-754, 2015.
- [3] Svanberg Krister, *A class of globally convergent optimization methods based on conservative convex separable approximations*. SIAM Journal of Optimization 12, p. 555-573, 2002.

¹E-mail: raelch@mek.dtu.dk

Address: Nils Koppels Allé 404, DK-2800 Kgs. Lyngby, Denmark