Technical University of Denmark



TEM characterization of Ni-Ga intermetallic catalysts for hydrogenation of CO2

Spiga, Cristiano; Silva, Hugo José Lopes; Wagner, Jakob Birkedal; Chorkendorff, Ib; Damsgaard, Christian Danvad

Publication date: 2017

Document Version Peer reviewed version

Link back to DTU Orbit

Citation (APA):

Spiga, C., Silva, H. J. L., Wagner, J. B., Chorkendorff, I., & Damsgaard, C. D. (2017). TEM characterization of Ni-Ga intermetallic catalysts for hydrogenation of CO2. Abstract from North American Catalysis Society Meeting 2017, Denver, United States.

DTU Library Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

TEM characterization of Ni-Ga intermetallic catalysts for hydrogenation of CO₂

Cristiano Spiga^{1,2}*, Hugo J.L. Silva², Jakob B. Wagner¹, Ib Chorkendorff², and Christian D. Damsgaard^{1,2} ¹Center for Electron Nanoscopy, Technical University of Denmark, DK-2800 Kgs. Lyngby, Denmark ²SurfCat, Department of Physics, Technical University of Denmark, DK-2800 Kgs. Lyngby, Denmark *: presenting author, email:crispi@cen.dtu.dk

Introduction

Nanostructured intermetallics dispersed on high surface area supports are assuming increasingly importance within the heterogeneous catalysis field. The atomic structure of the active NPs is highly linked to the performances of those catalysts that seems to behave differently compared to their relative single-metal NPs. This study presents local and structural investigation of Ni-Ga NPs dispersed on ~120 nm SiO₂ nanospheres. The catalyst shows similar size distribution and activity pr. surface area as the high-surface area supported catalyst confirming that the system is reliable in terms of catalytic behavior. An Environmental Transmission Electron Microscope (ETEM) equipped with a differential pumping system to confine a controlled gas flow around the specimen, offers a unique tool to investigate individual NPs at the atomic level during in-operando conditions of the catalyst ^[1]. Nevertheless, the morphology of the high surface area support tends to complicate the interpretation of TEM micrographs on the atomic level and blurs the spectroscopic information due to limited depth of field and multiple scattering events. One way to circumvent this, is to reduce the complexity of the mesoporous high-surface area support by developing low-surface area (non-porous) supports that consist of nanosized SiO₂ spheres. 2D model catalysts has also been developed by synthesizing the NPs on 20 nm thick membranes^[2].

Materials and Methods

The catalyst formation process and reaction at the atomic level are investigated in the ETEM by following the morphology change (surface structure, facets, NP size, crystal structure, material composition) during NPs formation and CO₂ hydrogenation to methanol. Different chemical synthesis have been performed to prepare δ -Ni₅Ga₃ catalysts on a high and low surface area SiO₂ support. The investigation is supported by complementary techniques such as *in-situ* X-Ray Diffraction (XRD) and activity tests coupled with Gas Chromatograph (GC) and a Mass Spectrometer (MS).

Results and Discussion

SiO₂ spheres supported model catalyst features numerous NPs that can be illuminated directly with the electron beam (Figure 1) enabling atomic resolved structural and investigation on local chemical compositions. XRD shows the active δ -phase of the NiGa catalyst upon reduction in pure hydrogen at T=700°C. Normalizing by the surface area of the catalyst we find comparable activities between high-surface and low-surface area supported catalyst (Figure 2).




Figure 1. ETEM micrographs of NiGa NPs supported on: a) high-surface mesoporous SiO_2 powder; b) 150 nm SiO_2 spheres, $P_{(H2)}=115$ Pa, T=700°C.




Figure 2. a) XRD pattern of NiGa/SiO₂ powder after reduction at 700° C in pure H₂ ($P_{(H2)}$ =10⁵ Pa); b) activity test during methanol reaction over NiGa/SiO₂ catalyst for high-surface area (black) and low-surface area (blue) SiO₂ supports. Reaction conditions: 75 mL/min of H₂ + 25 mL/min of CO₂, P = 10⁵ Pa, T=180-250°C.

Significance

The optimized Ni-Ga catalyst is promising for CO_2 hydrogenation to methanol with comparable activities to the preferred commercial $Cu/Zn/Al_2O_3$ catalyst system ^[3-4].

References

- 1. Hansen, T.W., et al., Materials Science and Technology 11(2010), p. 1338.
- 2. C.D. Damsgaard et al., Microscopy 63(2014), p. 397.
- 3. Studt, F., et al., Nature Chemistry 6(2014), p. 320.
- 4. Sharafutdinov, I., et al., Journal of Catalysis, 320(2014), p. 77.