Technical University of Denmark



Membrane-aerated Nitrifying Biofilms: Continuous versus Intermittent Aeration

Ma, Yunjie; Piscedda, A.; Smets, Barth F.

Publication date: 2017

Document Version Publisher's PDF, also known as Version of record

Link back to DTU Orbit

Citation (APA): Ma, Y., Piscedda, A., & Smets, B. F. (2017). Membrane-aerated Nitrifying Biofilms: Continuous versus Intermittent Aeration. Abstract from 10th International Conference on Biofilm Reactors, Dublin, Ireland.

DTU Library Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



Membrane-aerated Nitrifying Biofilms: Continuous versus Intermittent Aeration

Y. Ma, A. Piscedda and B. F. Smets

Department of Environmental Engineering, Technical University of Denmark, Kongens Lyngby 2800 Denmark (E-mail: *yuma@env.dtu.dk*; *bfsm@env.dtu.dk*)

ABSTRACT

This study evaluated the process performance of a lab-scale membrane-aerated nitrifying biofilm under continuous versus intermittent aeration regimes. Effects of intermittent aeration on the competition between individual microbial communities and the emission of nitrous oxide (N₂O) were specifically studied. The principle observation under continuous aeration was more efficient ammonium removal (4.3 gNH₄⁺_N/m²/day) but also higher N₂O emission (2.9% of the N loading) and minor anaerobic ammonium oxidizer (AMX) activity compared to intermittent aeration (3.1 gNH₄⁺_N/m²/day, 0.3% of the N loading). AMX activity increased at the expense of decreasing nitrite oxidizer (NOB) activity with intermittent aeration. Dissolved oxygen and pH microprofiles under each aeration regimes revealed that the dynamic variation of pH relevant effects could be the potential causes to these different performances. A high intermittency in aeration favors the suppression of NOB with positive effects on N₂O emission reduction.

MATERIIALS & METHODS

Reactor operation and N mass balance analysis

The lab-scale membrane-aerated biofilm reactor (MABR) used PDMS membranes (3100506, Labmarket, Germany) and was inoculated with nitrifier-enriched biomass. Synthetic wastewater was fed with an influent NH_4^+ concentration of 75 mg NH_4^+ _N/L providing a surface loading of 9 gN/m²/day. The reactor was operated with continuous aeration (100% air) until effluent N concentrations remained stable for several HRTs (hydraulic retention time). Then MABR was switched to intermittent aeration consisting of a 6-hour aeration (100% air) followed by a 6-hour non-aeration (100% N₂). Bulk N species were recorded; N₂O was measured in the bulk liquid phase, in the lumen gas phase and within the biofilm. Bulk DO and pH were monitored with electrodes, and profiles of pH, DO, and N₂O within the biofilm under each aeration regime were measured with micro-electrodes.

Consumption/production of individual N species was calculated using mass balance equations. Anammox process was assumed to follow reported stoichiometry (Strous, 1998). Heterotrophic denitrification was assumed to be supported solely by organic carbon derived from endogenous biomass decay (no external COD in the influent) and solely with NO₃-N as electron acceptor.

$$NH_{4}^{+}AOB + NH_{4}^{+}AMX = NH_{4}^{+}in - NH_{4}^{+}out$$
 (1)

 $NH_{4}^{+}AOB - NO_{2}^{-}NOB - 1.32 NH_{4}^{+}AMX = NO_{2}^{-}out$ (2)

 $NO_{2} NOB + 0.26 NH_{4}^{+}AMX - NO_{3} HB = NO_{3} out$ (3)

 $NH_4^+AOB * Y_AOB + NO_2^-NOB * Y_NOB + NH_4^+AMX * Y_AMX = 2.86 NO_3^-HB/(1-Y_HB)$ (4)

where NH_4^+ _AOB, NH_4^+ _AMX, NO_2^- _NOB, NO_3^- _HB (mgN/L) are NH_4^+ _N consumption by AOB, NH_4^+ _N consumption by AMX, NO_2^- _N consumption by NOB, NO_3^- _N consumption by HB, respectively.

Microprofiling measurements and quantitative PCR

Under each aeration regimes commercially available DO, pH and N₂O microsensors (Unisense, Denmark) were used for replicate (n > 3) *in situ* profiling within the biofilm at steady state. Biomass samples were collected at the end. Fractions of different phylogenetic groups (approximating functional guilds) in the inoculum and biofilm were measured using quantitative PCR assays.

RESULTS & DISCUSSION

Process performance and N consumption under different aeration regimes

A nitrifying biofilm readily developed when the MABR was initially operated under continuous aeration: NO_3 was the dominant NO_x N species in the effluent and NO_2 was at or below 1 mg/L after 2 months operation. N consumptions by individual microbial groups were calculated to estimate relative microbial activities (Figure 1). The ratio of NH_4^+ AOB to NO_2^- NOB reflects the oxygen competition between AOB and NOB: it was 1.31 at day 50-67 suggesting active NOB activity with continuous aeration. The ratio of NO_2^- AMX to NO_2^- NOB reflects the NO_2^- competition between NOB and AMX: it was 0.26 showing minor AMX activity. Total N_2O emission in the gas plus liquid phase under continuous aeration was ca. 2.91% of the total N loading (Table 1).



Figure 1. Calculated N consumption by individual microbial groups under different aeration regimes.

At day 67, MABR was switched to intermittent aeration (6-hour aeration and 6-hour non-aeration).

NOB activity was suppressed significantly after 2 weeks with increasing ratios of NH_4^+ _AOB/NO₂⁻_NOB and NO_2^- _AMX/NO₂⁻_NOB. While the oxygen loading was reduced 50% under intermittent aeration, NH_4^+ _AOB reduced only by 46~23%, which is probably due to the gradually activated AMX thus prompting AOB activity and enhancing oxygen transfer rate. Moreover, N₂O emission decreased to 0.35% of the total N loading (Table 1, Figure 2C).

Potential causes of NOB suppression and N₂O mitigation in intermittent aeration

Competition between AOB and NOB can be caused by DO and pH conditions, involving such phenomena as DO limitation, pH effects on enzyme activities and pH effects on substrate speciation (free ammonia, FA and free nitrous acid, FNA) (Park, 2015). Therefore, DO and pH microprofiles in the biofilm were compared between continuous and intermittent aeration to further evaluate variations of each influencing factors under. The main observations are: 1. DO profiles in the biofilms were insignificantly different between continuous aeration and during aeration phases in intermittent aeration, in terms of interface oxygen concentrations and oxygen penetration depths (Figure 2A). After aeration transitions in intermittent aeration, DO profiles in the biofilm became time-invariant within 3 minutes (data not shown); 2. pH profiles during the aeration phases in intermittent aeration were similar to profiles in continuous aeration (Figure 2B). However, during non-aeration pH upshifts at the deeper biofilm depths were significant and pH profiles became steady after 30 minutes in the following aeration phase (data not shown). We conclude that the pH shifts, and especially its effect on FA/FNA speciation, was the key factor leading to NOB suppression in intermittent aeration. Once NOB were suppressed at the biofilm base, NO_2 became available for AMX growth in the outer anoxic biofilm layers. Bulk NO₂ concentrations were below detection limit once intermittent aeration started, which suggested that the N₂O mitigation was related to NO₂ absence. Effects of various patterns of intermittent aeration on NOB suppression, N₂O emission, and community composition are being tested.



Figure 2. Comparison of microprofiles under continuous (day 51-67) and intermittent (day 81-94) aeration regimes.

REFERENCES

- Park, S., Chung, J., Rittmann, B. E., and Bae, W. (2015) Nitrite accumulation from simultaneous freeammonia and free-nitrous-acid inhibition and oxygen limitation in a continuous-flow biofilm reactor. Biotechnology and Bioengineering, **112**(1), 43–52.
- Strous, M., Heijnen, J. J., Kuenen, J. G., and Jetten, M. S. M. (1998) The sequencing batch reactor as a powerful tool for the study of slowly growing anaerobic ammonium-oxidizing microorganisms. Applied Microbiology and Biotechnology, **50**, 589–596.