June 1964

brought to you by T CORE

## Brief 63-10344

## NASA TECH BRIEF



This NASA Tech Brief is issued by the Technology Utilization Division to acquaint industry with the technical content of an innovation derived from the NASA space program.

## **Cooling Method Prolongs Life of Hot-Wire Transducer**



**The problem:** One method of measuring the power density of a particle beam, such as from the exhaust of an ion rocket engine, involves the use of a probe (a hot-wire transducer) consisting of very-small-diameter resistance wire, which changes resistance as a function of temperature. The heat developed in the wire probe by the intercepted portion of the energy beam may raise the temperature of the wire above its fusing point and thereby destroy it. **The solution:** An arrangement for cooling the wire probe.

**How it's done**: The two ends of the wire are supported on thermally and electrically conductive rods which are surrounded by a fluid cooling medium. In this way the supporting rods are kept at a substantially constant temperature and prevent the probe from overheating. The illustration schematically shows the

(continued on next page)

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither the United States Government, nor NASA, nor any person acting on behalf of NASA: A. Makes any warranty or the presentation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this document, or that the use of any information, apparatus, method, or process disclosed in this document may not infringe privately-owned rights; or B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this document. apparatus with a coolant fluid circulating around the conductive rods.

## Notes:

- 1. Instead of using a cooling fluid to control the temperature of the wire, the ends of the conductive supporting rods for the probe may be placed in intimate contact with metal blocks which serve as a heat sink.
- 2. The change in resistance of the wire probe due to its heating by an energy beam may be measured by a conventional constant-current circuit.

3. For further information about this innovation inquiries may be directed to:

Technology Utilization Officer Lewis Research Center 21000 Brookpark Road Cleveland, Ohio 44135 Reference: B63-10344

**Patent status:** NASA encourages the immediate commercial use of this invention. It is owned by NASA, and a patent application has been filed. When patented, royalty-free nonexclusive licenses for its commercial use will be available. Inquiries concerning license rights should be made to NASA Headquarters, Washington, D.C. 20546.

Source: L. V. Baldwin and V. A. Sandborn (Lewis-41)