September 1965

Brief 65-10272

NASA TECH BRIEF



NASA Tech Briefs are issued by the Technology Utilization Division to summarize specific technical innovations derived from the space program. Copies are available to the public from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia, 22151.

Infrared Shield Facilitates Optical Pyrometer Measurements



The problem: Accurately measuring the temperature of small sheet metal specimens which are subjected to tensile stresses in fatigue tests at $2,000^{\circ}$ to $3,000^{\circ}$ F. An optical pyrometer is a preferred instrument for measuring such high temperatures. To ensure accurate measurements, this instrument must view only the infrared radiation from the heating source or other surfaces. None of the heating or temperaturesensing components must come in contact with the test specimen.

The solution: A water-cooled shield to exclude direct or reflected radiation from one face of the metal

specimen and to permit viewing of this face of the specimen by an optical pyrometer.

How it's done: A water-cooled reflector and quartz lamp are used to heat the specimen on one side and the shield is used to permit pyrometer measurements on the other side. The shield assembly is water-cooled and has a viewing port for the optical pyrometer. The test specimen is placed between the infrared source (lamps and reflector) and the shield. A 1/32-inch gap is maintained between the specimen and shield. Serrated radiation traps are provided on the edges of the shield-assembly reservoir to prevent radiation leakage through the gap.

(continued overleaf)

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States Government assumes any liability resulting from the use of the information contained in this document, or warrants that such use will be free from privately owned rights.

Note:

A related invention is described in NASA Tech Brief B63-10345, June 1964. Inquiries may also be directed to:

Technology Utilization Officer Langley Research Center Langley Station Hampton, Virginia, 23365 Reference: B65-10272 **Patent status:** NASA encourages the immediate commercial use of this invention. Inquiries about obtaining rights for its commercial use may be made to NASA, Code AGP, Washington, D.C., 20546.

Source: Walter Illg and Fred F. Eichenbrenner (Langley-133)