

March 1966


Brief 66-10120

# NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U. S. space program and to encourage their commercial application. Copies are available to the public from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

## Oxygen-Hydrogen Torch is a Small-Scale Steam Generator



### The problem:

Corrosion-rate analysis of various metals frequently requires the use of steam at high temperatures and pressures. Water-boiling steam generators are cumbersome, expensive, pose safety problems, and permit little or no flexibility in oxygen or hydrogen content control.

### The solution:

A standard oxygen-hydrogen torch that generates steam through local combustion inside a test chamber under constant temperature and pressure control.

### How it's done:

The torch nozzle is sealed into one end of the test chamber. Oxygen and hydrogen are metered to the torch in the desired ratio and ignited by a conventional spark source. Discharge from the test chamber is regulated by a bleed valve to maintain desired chamber pressure. Test chamber walls are hollow for heating or cooling through a wide temperature range. The sample under test is held in a simple mount at the bottom of the chamber directly in the path of the nozzle discharge.

(continued overleaf)

**Notes:**

1. Chamber pressure can be as high as 2,000 psig with torch gas flow rates of 0.1 to 1.0 standard cfm.
2. This system has been used successfully in corrosion-rate measurements of stainless steel at 500°F with various oxygen-to-hydrogen ratios.
3. Although the system was used for corrosion-attack studies, it is apparent that single or coupled torches can be employed to generate limited quantities of steam in a variety of applications.
4. Particular care must be exercised to prevent explosions in thin-wall chamber configurations, or where personnel or other hazards may exist. Designs should assure (a) pre-ignition purging, (b) optical viewing of the nozzle area, (c) the existence of a continuous ignition spark at the nozzle prior to the start of gas flow.

5. Inquiries concerning this innovation may be directed to:

Technology Utilization Officer  
AEC-NASA Space Nuclear Propulsion  
Office

U.S. Atomic Energy Commission  
Washington, D.C., 20545

Reference: B66-10120

**Patent status:**

No patent action is contemplated by NASA.

Source: C. E. Maskell  
of Aerojet-General Corporation  
under contract to  
Space Nuclear Propulsion Office  
(NU-0042)