

NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U. S. space program and to encourage their commercial application. Copies are available to the public from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

Panels Illuminated by Edge-Lighted Lens Technique

The problem:

To provide instrument panel lighting that produces no glare and thus reduces eye strain in the viewer. A means other than incandescent lamps is necessary to meet this requirement.

The solution:

The use of electroluminescent lamps to edge-light a specially ground lens provides the nonglare, reduced eye strain panel illumination.

How it's done:

The combination of a planoconcave lens to which four electroluminescent lamps are bonded, illuminates the panel. The lens is made from a 3-1/2-inch square piece of 0.281-inch thick borosilicate crown #1 glass plate. One surface is ground to a radius of 18 inches, leaving a 3/8-inch band along the diagonal on 4 corners. Electroluminescent lamps are bonded to each of four edges by a special adhesive and wired together to a common point. The concave surface of the lens is turned inward, facing toward the panel to eliminate Newton's rings.

Notes:

1. An alternate technique uses a deposition of electroluminescent elements to produce the light.
2. There is no noticeable falloff in brightness along the lens edge. Light intensity diminishes toward the lens center. A slight halo, observed along the lens edge, has no detrimental effect.
3. Inquiries concerning this innovation may be directed to:

Technology Utilization Officer
Manned Spacecraft Center
Houston, Texas 77058
Reference: B66-10507

Patent status:

No patent action is contemplated by NASA.

Source: G. E. Haag and R. B. Horsfall
of North American Aviation, Inc.
under contract to
Manned Spacecraft Center
(MSC-871)

Category 02