July 1967



# **AEC-NASA TECH BRIEF**



Brief 67-10224

AEC-NASA Tech Briefs describe innovations resulting from the research and development program of the U.S. AEC or from AEC-NASA interagency efforts. They are issued to encourage commercial application. Tech Briefs are published by NASA and may be purchased, at 15 cents each, from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

## Computer Program Calculates Steady-State Temperature Distribution Within Plane or Axisymmetric Solids

#### The problem:

To provide a numerical procedure and a computer program for the steady-state temperature determination within plane or axisymmetric solids composed of many different materials of practically any geometry. The output of such a program could be used to plot isotherms or provide data to enable the performance of stress analyses or heat transfer calculations upon the bodies.

#### The solution:

A digital computer program using the finite element analysis technique to determine the steady-state temperature distribution within plane or axisymmetric solids.

#### How it's done:

The continuous body is replaced by a system of triangular or quadrilateral elements. Each element is numbered. Each nodal point of each element is identified by its X and Y coordinate. Input into the program consists of nodal point identification, temperature or heat flow at boundary nodal points, material identification of each element, conductivity of each material, and convective heat transfer coefficient and temperature at each boundary nodal point. Each quadrilateral element is divided into four triangular elements. The conductivity matrix for each triangle is formed and then combined to form a  $5 \times 5$  conductive matrix with respect to the five points. The  $5 \times 5$  matrix is then reduced to the  $4 \times 4$  quadrilateral conductivity matrix by standard tech-

niques. The quadrilateral conductivity matrix is then added to the conductivity matrix for the complete body. The nodal point temperatures are then found from the solution of the resulting matrix equations. Within the program this is accomplished by a large capacity, band matrix solver. All temperatures are then printed.

### Notes:

- 1. This program is written in Fortran IV for an IBM 7094 computer.
- 2. A feature of this program is that it provides output which is compatible for input to available finite element stress analysis programs.
- 3. This program can be applied to heat transfer problems related to many heat exchanger applications.
- 4. Inquiries concerning this program may be directed to:

COSMIC Computer Center University of Georgia Athens, Georgia 30601 Reference: B67-10224

#### Patent status:

No patent action is contemplated by AEC or NASA.

Source: Edward L. Wilson of Aerojet General under contract to AEC-NASA Space Nuclear Propulsion Office (NUC-10049) Category 06

This document was prepared under the sponsorship of the Atomic Energy Commission and/or the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States Government assumes any liability resulting from the use of the information contained in this document, or warrants that the use of any information, apparatus, method, or process disclosed in this document may not infringe privately owned rights.