

July 1969

Brief 69-10251


NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U.S. space program, to encourage their commercial application. Copies are available to the public at 15 cents each from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

Low-Loss "C" Band Parasitic Probe

XKS 09348



The problem:

To design a device that can, at one and the same time, receive an rf signal from a transmitter at low power levels and receive it clearly by a technique of inhibiting stray radiation or "noise".

The solution:

A low insertion-loss "C" band parasitic probe, for coupling rf energy from a transmitting medium to a receiving medium with a minimum of interference in order to minimize power requirements.

How it's done:

A housing of suitable configuration is made of an rf-absorbent material and within it are mounted a polystyrene rod and helix antenna that form the operating low-loss "C" band parasitic probe. The polystyrene rod acts as a dielectric low-loss path for rf energy. An insertion loss of 10 db is realized by cementing this rod to the face of a receiving medium helix antenna installed in a housing lined with rf-absorbent material.

(continued overleaf)

Notes:

1. This probe requires 20 db less signal than conventional devices, thus increasing overall system efficiency by a like amount.
2. No additional documentation is available.
3. Technical questions may be directed to:
Technology Utilization Officer
Kennedy Space Center
Kennedy Space Center, Florida 32899
Reference: B69-10251

Patent status:

This invention is owned by NASA, and a patent application has been filed. Royalty-free, non-exclusive licenses for its commercial use will be granted by NASA. Inquiries concerning license rights should be made to NASA, Code GP, Washington, D.C. 20546.

Source: Herbert Edmond Cribb
Kennedy Space Center
(XKS-09348)