## NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U.S. space program, to encourage their commercial application. Copies are available to the public at 15 cents each from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

## Energy-Storage of a Prescribed Impedance

The best-known reflector antenna is the parabolic type; proper focus requires a point-source feed for illumination of the reflector, so that control of the amplitude of the illumination function is severely limited.

This new reflector-type antenna offers almost complete control of its aperture-illumination function, which is its principal advantage. This control enables the engineer to design for either maximum gain or low side lobes, whichever is required. The feed is either a close approximation to a line source, or some structure that is electrically equivalent to one; thus any desired distribution can be designed into the feed. This distribution is then reflected to the aperture of the cone by the conical surface, altered only predictably by the distance traveled by the wave before it strikes the reflecting surface.

Another advantage is that this antenna's beam width can be changed easily by excitation of various amounts of the line-source feed: wide beams are generated when only a little of the feed, near the apex of the cone, is excited; the beams are progressively narrower as additional sections of the feed, progressively further from the apex, are excited; and the beam is narrowest when the whole feed is excited. The conical reflector collimates a beam when the feed complies with certain geometric constraints. The line-source feed may be either directly broadside or scanned off at an angle; in either case a large crosspolarized component exists if the feed is not specifically designed for its suppression. Tests of a prototype antenna have verified the basic concepts of collimation by the conical reflector, and of cancellation of the cross-polarization by specific design of the feed.

Although designed primarily for use in spacecraft, for which it has many advantages, this antenna may interest manufacturers of antennas for aircraft and other communications systems.

## Note:

Documentation is available from:

Clearinghouse for Federal Scientific and Technical Information Springfield, Virginia 22151 Price \$3.00 Reference: TSP69-10380

## Patent status:

This invention is owned by NASA, and a patent application has been filed. Royalty-free nonexclusive licenses for its commercial use will be granted by NASA. Inquiries concerning license rights should be made to NASA, Code GP, Washington, D.C. 20546.

> Source: A. F. Seaton of Hughes Aircraft Company under contract to NASA Pasadena Office (NPO-10303)

> > Category 01

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States Government assumes any liability resulting from the use of the information contained in this document, or warrants that such use will be free from privately owned rights.