

February 1970


Brief 70-10109

# NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U.S. space program, to encourage their commercial application. Copies are available to the public at 15 cents each from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

## Improved Quick-Disconnect Electrical Connector



This connector has several new and unusual features. The connector receptacle is fitted with an "O" ring that provides a moisture-proof seal when the connector is in the lock position. The connector is shielded in both the mated and unmated positions. For locking, the connector is equipped with one keying and three locking spheres, reducing manufacturing costs as compared to the costs of the conventional keyway lock connector.

To assemble the connector in the mated position, the male plug is fitted to the receptacle with the keying sphere aligned with the receptacle slot. When the connection is made, the locking spheres seat in the receptacle indentations, allowing the collar to slide

forward, depressing the locking spheres in the locked position. The connector is unlocked by sliding the locking collar back (away from the joint), allowing the spring-loaded locking spheres to free the receptacle half of the connector.

### Note:

No further documentation is available. Specific questions, however, may be directed to:

Technology Utilization Officer  
Marshall Space Flight Center  
Huntsville, Alabama 35812  
Reference: B70-10109

(continued overleaf)

**Patent status:**

No patent action is contemplated by NASA.

Source: Robert F. Horton  
Marshall Space Flight Center  
(MFS-20610)