

December 1970


Brief 70-10640

NASA TECH BRIEF



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Division, NASA, Code UT, Washington, D.C. 20546.

Low-Noise Flow Valve for Air Ducts



Longitudinal Section of Manual Valve

A valve assembly for controlling air flow from a feeder into a main duct, with a minimum of turbulence, friction, pressure differential, and noise has been developed. As shown in the illustration, the valve contains three pieces: a damper, a deflector, and a spring. The streamlining of the damper and deflector acts to merge the flows smoothly, minimizing turbulence, while the spring reduces noise by keeping the damper and deflector in contact, thus eliminating valve chatter and damping vibrations.

The figure shows a manually controlled valve which was actually built and tested. Another design, for a pressure-controlled, automatically regulated valve,

is currently in the conceptual stage. This design concept, which uses a unique, zero-gradient calibrating spring, would control gas flow reasonably accurately within a wide range of supplied pressures, and, because of the simplicity of the design, would be reliable and relatively inexpensive.

Note:

Requests for further information may be directed to:

Technology Utilization Officer
Manned Spacecraft Center, Code BM7
Houston, Texas 77058
Reference: TSP70-10640

(continued overleaf)

Patent status:

No patent action is contemplated by NASA.

Source: E. A. Gallo of
Service Technology Corp.
under contract to
Manned Spacecraft Center
(MSC-13441)