

May 1971

Brief 71-10124

NASA TECH BRIEF

Marshall Space Flight Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

EKG Isolator

The problem:

Design a system for recording an electrocardiogram without exposing the patient to possible severe electrical shock.

The solution:

Use a light beam to transmit the heartbeat signal from the electrodes on the patient to the electrocardiograph.

How it's done:

Use conventional type electrical contacts for connecting the electrocardiograph to the patient. Amplify the heartbeat signals and feed them to the EKG isolator, which converts the signal from an electrical impulse to a light beam, using a light emission diode. Relay the signal by a light beam from the diode to a photo transistor in the output portion of the isolator and subsequently to the electrocardiograph.

This system provides complete isolation between the patient and the EKG instrumentation.

Note:

Requests for further information should be directed to:

Technology Utilization Officer
Code A&TS-TU
George C. Marshall Space Flight Center
Huntsville, Alabama 35812
Reference: B71-10124

Patent status:

This invention is owned by NASA, and a patent application has been filed. Royalty-free nonexclusive licenses for its commercial use will be granted by NASA. Inquiries concerning license rights should be made to:

Patent Counsel
Mail Code A&TS-PAT
George C. Marshall Space Flight Center
Marshall Space Flight Center, Alabama 35812

Source: Euple Palmer, John R. Rasquin, and
Hubert E. Smith
Marshall Space Flight Center
(MFS-21236)

Category 01,05