


NASA TECH BRIEF

Marshall Space Flight Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Precision Die-Punch for Trimming the Conductors of Flat Conductor Cable



A precision die-punch will trim the conductors of FCC to a width of 0.040 in., adapting the cable for termination with a standard FCC plug which employs a window piece with 0.048 in. openings and a conductor spacer with 0.044 in. wide slots.

Before insertion into the die-punch, the cable is cut square and stripped with a stripping tool. An adjustable guide, flush with an edge of the cable, is moved right or left until the center of the insulation (between the most central conductors) corresponds with the registration mark on the die. The registration assures that the conductor material is trimmed symmetrically from each side of the conductor when the punch is lowered and raised. This operation trims each conductor to a width of 0.004 in. and consistently leaves 0.035 in. spaces between adjacent conductors.

Note:

Requests for further information may be directed to:

Technology Utilization Officer
Code A&TS-TU
Marshall Space Flight Center
Huntsville, Alabama 35812
Reference: B71-10419

Patent status:

No patent action is contemplated by NASA.

Source: G.E. Weeks, Jr.
Marshall Space Flight Center
(MFS-20142)

Category 08