NASA TECH BRIEF

Marshall Space Flight Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Fixture for Multiple-FCC Chemical Stripping and Plating

A special fixture facilitates handling several long pieces of FCC during the chemical stripping (to remove polyester insulations) and plating of the exposed conductor ends. The illustration shows eight FCC's on a spool supported by the fixture and

Electrical
Contact Point
Support Arms

Metal
Vise
Locking Pin
Spool

Plate
(for Conductor Protection)

locked in position to prevent uncoiling. Enough slack is allowed to clamp one end of the cable in the vise and to wedge the conductors at the other end (to be chemically stripped or electroplated) in the eight slots at the bottom of the fixture.

For chemical stripping, lead tape is applied near the ends to be stripped to protect the insulation above a desired margin. The taped ends are submerged in the stripping solution to cover about half of each tape segment. For electropolating, both ends of each FCC must be stripped: the ends at the top for electrical contact, and the others for submersion in the electroplating solution.

Note:

Requests for further information may be directed to:

Technology Utilization Officer Code A&TS-TU Marshall Space Flight Center Huntsville, Alabama 35812 Reference: B71-10420

Patent status:

No patent action is contemplated by NASA.

Source: W. Angele and W.E. Norton Marshall Space Flight Center (MFS-20237)

Category 08