

November 1971

Brief 71-10446

NASA TECH BRIEF


NASA Pasadena Office



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Axisymmetric and Cylindrical Isostable Structures: A Concept

A mathematical formulation, suitable for the analytical design of structural networks with uniform local stability, has yielded idealized solutions for specific two-family networks. However, much work remains to be done before idealized structures such



Axisymmetric, Gravity-Loaded Isostabiloid: Side and Top View

as that shown in the figure can be reduced to practice. For example, the effects of multiple loading and of unavoidable imperfections found in real construction materials remain to be considered. Nevertheless, such configurations may eventually be used in the design of practical structures.

A structure that uses the minimum amount of material is frequently described theoretically by specifying that each structural component fail simultaneously under a unique ultimate tensile load. Examples of such structures, called "isotensoids," are uniformly stressed Maxwell-Michell networks, isotropically stressed structural "soap-film" membranes, and uniformly stressed filamentary structures.

Uniformly compressed structures analogous to the isotensoids can also be found. However, these "isocompressoids" may fail because of buckling, at a point well below their maximum compressive strength.

The referenced report is a first attempt to treat isocompressoid structures. It avoids the complex effects of general instability, matrix support, and articulate loading by constraining each element of the structure to buckle as an Euler column upon reaching its ultimate compressive load. The term "isostabiloid" is used to describe structures which satisfy this condition. The report gives particular attention to the existence of closed-dome isostabiloids, because such structures appear to have the greatest practical value.

The differential equations for the geometry of compression-loaded, two-family filamentary structures are established. The analytical formulation requires that failure due to local instability occurs simultaneously in the whole structure. Solutions such as the one illustrated are obtained for the particular case where the structure's own weight, under earth gravity, is the only load. For this case, the shape of the meridian and the cross section are determined, as well as the pattern of the filaments.

(continued overleaf)

Note:

Requests for further information may be directed to:

Technology Utilization Officer
NASA Pasadena Office
4800 Oak Grove Drive
Pasadena, California 91103
Reference: TSP71-10446

Patent status:

No patent action is contemplated by NASA.

Source: P. Preiswerk, J.M. Hedgepeth,
and H.U. Scheurch of
Astro Research Corp.
under contract to
NASA Pasadena Office
(NPO-12049)