

NASA TECH BRIEF

Ames Research Center




NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Electrical Grounding Bracket

The problem:

To provide a device which serves as a common grounding point for the shielded wires of a multipin electrical connector and permits addition or removal of ground leads without disturbing the other grounded wires.



The solution:

A specially shaped bracket which fits around the connector and supports a grounding bar to which shield ground wires can be fastened.

How it's done:

The grounding bracket shown in the shaded portion of the diagram conforms to the exterior configuration of a typical multiple-pin connector. In essence, it is simply a rigidly supported, rounded strip of metal onto which may be soldered the shield-ground leads of the shielded wires leading to the connector pins.

The electrical grounding bracket simplifies solder operations and the dressing of shield terminations. Because each shield-ground lead can be soldered independently to the bracket, it is a simple matter to alter the wiring configuration of the connector or to remove or add shielded wires. The bracket also permits addition or deletion of a ground circuit without disturbing the remaining ground wires, and the grounding bracket may itself be unfastened from the connector for electrical tests. Although the bracket provides a minimum of two parallel DC ground paths through the connector shell, by appropriate insulation of one mounting screw, only one path can be obtained; multiple paths or selective grounding points can be obtained by wires attached to the bracket.

Note:

No additional documentation is available. Specific questions, however, may be directed to:

Technology Utilization Officer
Ames Research Center
Moffett Field, California 94035
Reference: B72-10045

Patent status:

Title to this invention, covered by U.S. Patent 3,513,433, has been waived under the provisions of the National Aeronautics and Space Act [42 U.S.C. 2457(f)] to the TRW Systems Group, TRW, Inc., One Space Park, Redondo Beach, California.

Source: C. E. Carroll of
TRW Systems Group, TRW, Inc.
under contract to
Ames Research Center

(ARC-10041)

Category 01