View metadata, citation and similar papers at core.ac.uk

JUIY 1972

B72-10439

NASA TECH BRIEF Lewis Research Center

Electron Beam Chemistry Produces High Purity Metals

NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Electron Beam Titanium Foil (0.005 cm Thick) Inert Gas Inier Inert Gas Outlet Glass Frit Reaction Zone Metal Salt Solution Glass Frit Read Product

Production of Metals and Compounds by Radiation Chemistry

The use of radiation chemistry as a practical tool for inorganic preparations is being developed. Most of the effort has involved the deposition of metals by irradiation of their aqueous metal salt solutions with high energy (2' MeV) electrons. The active species in irradiated water are solvated electrons (e^{-} solvated), atomic hydrogen (H·), and hydroxyl radicals (OH·). Addition of certain organic compounds such as primary alcohols generate, by scavenging oxidizing OH·, a reducing medium composed of e^{-} solvated and H·. These reducing species then reduce the metal ion in solution to deposit the free metal.

The irradiation of the solution is accomplished in the reaction vessel shown in the figure, although other geometries will, of course, occur to practitioners. The titanium foil serves as the inlet window for the vertical electron beam from a linear accelerator. An inactive gas, He, Ar or N_2 , passing through a glass frit at the base of the vessel, agitates the liquid through a reaction zone about one centimeter deep (range of penetration of

(continued overleaf)

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States 2 MeV electrons) and about 4 centimeters in diameter (width of beam). The gas then exhausts through the outlet tube.

The features of the radiochemical technique that lend themselves to the preparation of high purity materials are as follows:

- 1. Low temperatures may be employed thereby minimizing contamination such as that due to diffusion of container material into the product.
- 2. A wide variety of liquid systems may be used for a particular preparation.
- 3. The product is deposited as a precipitate thereby affording effective separation of product from reactants.

In a typical experiment, an aqueous solution containing 0.2 molar copper (II) sulfate, 0.05 molar sulfuric acid and 1.0 molar methanol (OH \cdot scavenger) was irradiated with 2 MeV electrons and 20 microamperes beam current. This procedure produced finely divided spectrographic grade copper (crystal size down to 0.1 micron) at a rate of about 50 grams per kW-h beam energy. Ten other metals have been prepared by this method. They are silver, zinc, cadmium, thallium, tin, lead, antimony, cobalt, nickel, and palladium.

The reducing species $e_{solvated}$ and H can also be generated by irradiating certain organic liquids; thus metals can be deposited from nonaqueous media. Antimony and zinc have been precipitated by irradiation of their halide solutions in dry polar organic liquids (e.g., primary alcohols).

Metals may also be deposited by the radiolytic decomposition of alkyl and aryl metal compounds. For example, finely divided lead forms on irradiating a solution of lead tetramethyl in heptane. Likewise, bismuth is radiochemically deposited from a solution of triphenylbismuth in dibutyl ether. These systems would allow the radiolytic preparation of the more electropositive metals such as aluminum and lithium.

Preparations by radiochemical techniques are not confined to the deposition of metals, but can also be

used to synthesize pure compounds. Pure anhydrous copper (I) bromide and iron (II) chloride have been prepared in good yield by irradiation of copper (II) bromide and iron (III) chloride, respectively, in organic media.

Theoretical considerations and preliminary experimentation indicate that radiation of considerably less than 2 MeV energy may be used in the radiochemical preparative method; thus a relatively unsophisticated electron source would suffice.

Notes:

 The following documentation may be obtained from: National Technical Information Service Springfield, Virginia 22151 Single document price \$3.00 (or microfiche \$0.95)

> Reference: NASA TM-X-67982 (N72-14142), Use of Radiation in Preparative Chemistry

 Technical questions may be directed to: Technology Utilization Officer Lewis Research Center
21000 Brookpark Road Cleveland, Ohio 44135 Reference: B72-10439

Patent status:

Inquiries about obtaining rights for the commercial use of this invention may be made to:

Patent Counsel Mail Stop 500-311 Lewis Research Center 21000 Brookpark Road Cleveland, Ohio 44135

> Source: Warren H. Philipp, Charles E. May, Stanley J. Marsik, and Robert A. Lad Lewis Research Center (LEW-11639)

Category 04