NASA TECH BRIEF Langley Research Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Theoretical Prediction of Interference Loading on Aircraft Stores: Part II – Supersonic Speeds

The problem:

Accurate prediction of interference loads on pylonmounted aircraft stores.

The solution:

A program was developed for theoretically predicting the loading on pylon-mounted stores in supersonic flow.

How it's done:

Linear theory is used, without two dimensional or slender body assumptions, to predict the flow field produced by the aircraft wing, nose, inlet, and pylons. Aircraft shock wave locations are predicted, and their effect on the flow field is included through a transformation of the aircraft geometry. The interference loading is integrated over the store length by considering the local crossflow, its axial and radial derivatives, and buoyancy. Store moment calculations under an F-4 aircraft at Mach 1.2 are compared to wind tunnel data. The method is computerized, and program user information is included. A companion Tech Brief (see notes) discusses a similar program for subsonic speeds.

Notes:

- 1. This program was written in FORTRAN IV for the CDC-6400 computer.
- 2. Reference: Theoretical Prediction of Interface Loading of Aircraft Stores, Part I – Subsonic Speeds, NASA Tech Brief B73-10184.
- 3. Inquiries concerning this program should be directed to:

COSMIC 112 Barrow Hall University of Georgia Athens, Georgia 30601 Reference: LAR-11250

> Source: Charles H. Fox Langley Research Center and F. Fernandes of General Dynamics under contract to Langley Research Center (LAR-11250)

> > Category 06, 09