

NASA TECH BRIEF

Langley Research Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia, 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Method for Predicting Rotor Free-Wake Positions and the Resulting Rotor Blade Airloads

The problem:

Accurate predictions of rotor free-wake positions and the resulting rotor blade airloads require time-consuming and tedious calculations.

The solution:

A computer program has been designed and written to eliminate this problem.

How it's done:

Rotor-wake geometries are predicted by a process similar to that used for startup of a rotor in a free stream. An array of discrete trailing-and-shed vortices is generated, with vortex strengths corresponding to step-wise radial and azimuthal blade circulations, and is limited to an arbitrary number of azimuthal steps behind each blade. The remainder of the wake model of each blade is an arbitrary number of trailing vortices. Vortex element end points are allowed to be transported by the resultant velocity of the free-stream and vortex-induced velocities. Wake geometry, wake flow, and wake-induced velocity-influence coefficients are generated by this program for use in the blade-loads portion of the calculations.

Blade-loads computations include the effects of non-uniform inflow due to free wake, nonlinear airfoil characteristics, and response of flexible blades to applied loads. Computed wake flows and blade loads are

compared with experimentally measured data. Predicted blade loads, response, and shears and moments are obtained for a model rotor system having two independent rotors. The effects of advance ratio, vertical separation of rotors, different blade-radius ratios, and different azimuthal spacing of the blades of one rotor with respect to the other, are investigated.

Notes:

1. This program is written in FORTRAN IV for use on an IBM-360 computer.
2. Requests for further information may be directed to:
COSMIC
112 Barrow Hall
University of Georgia
Athens, Georgia 30601
Reference: LAR-10674

Source: Dariene Deen and
Wayne R. Mantay
Langley Research Center and
S. Gene Sadler of
Rochester Applied Research Associates, Inc.
under contract to
Langley Research Center
(LAR-10674)

Category 09, 06