

# NASA TECH BRIEF

## Lyndon B. Johnson Space Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.


### Flange Design for Large-Scale Modular Assembly Jigs

#### The problem:

In previous large-scale modular assembly jigs, the mounting and interconnecting flanges have been attached by welding. Such all-welded structures have the usual disadvantages associated with welding, e.g., the lack of accurate dimensioning, coplanarity, and parallelism. Thus during the assembly of such modules special alinement of the flanged joints is necessary.

#### The solution:

A new technique incorporates a weld-free method for securing flanges to the projecting ends of an unmachined box-beam framework in such a way that the flanged structure may be reused without modification. One such framework may be readily assembled to another by simply matching the flanges together and passing connecting members between preformed holes in the structures.



Weld-Free Installation of Load-Bearing Flanges

(continued overleaf)

**How it' done:**

The technique consists of alining and doweling sets of precision-machined locating pads and collars to the unmachined square box-beam ends of the modular assembly jig to provide distortion-free load-bearing flanges (see figure). The floating pad-and-collar design permits the lateral alinement of the pad centers relative to master grid-plate centers. At the pad centers are tooling holes 3/4 in. (1.9 cm) in diameter. These holes are alined on 70.00-in. (177.80-cm) grid centers, which are accurately located with respect to each other within  $\pm 0.005$  in. ( $\pm 0.013$  cm).

The collar is connected to the pad by a set of machine screws, passing through slightly oversize holes in the collar and into tapped holes in the pad, and by a pair of dowel pins driven through registering holes in both members. The attachment collars then permit movement for exact length and perpendicularity alinement, prior to being attached by dowels to the box-beam ends. By this means, the combined planar deviation relative to the master tooling grid-plate can be held to  $\pm 0.015$  in. ( $\pm 0.038$  cm). Because the tooling is held to close tolerance while being fabricated, special alinement during the buildup of several modules is not necessary.

**Note:**

Requests for further information may be directed to:

Technology Utilization Officer  
Johnson Space Center  
Code AT3  
Houston, Texas 77058  
Reference: TSP74-10273

**Patent status:**

This invention is owned by NASA, and a patent application has been filed. Inquiries concerning non-exclusive or exclusive license for its commercial development should be addressed to:

Patent Counsel  
Johnson Space Center  
Code AM  
Houston, Texas 77058

Source: M. M. Gilman of  
Rockwell International Corp.  
under contract to  
Johnson Space Center  
(MSC-19372)