

NASA TECH BRIEF

Lyndon B. Johnson Space Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

High-Strength Rivet Does Not Require Aging

The problem:

Conventional rivets used in the manufacture of aircraft require high-temperature and high-shear properties. They are kept in cold storage (aged) at approximately -18°C (0°F) temperature and must be installed within 2 hours after removal from the cold storage. This makes their handling inconvenient.

The solution:

A new aluminum rivet is simpler to handle. It does not need aging and provides better high-temperature and shear properties than conventional rivets.

How it's done:

The new rivet can be used at temperatures up to 180°C (350°F); conventional rivets are limited to temperatures below 120°C (250°F). The new rivet is constructed from 2219-aluminum alloy and is heat treated to condition T62. It has been designed with flush, flush shear, and universal heads. Double-shear tests show the rivet has a shear strength of 2.21×10^8 N/m^2 (32 ksi). The new rivets are capable of being driven with a minimum head diameter of 1.4 rivet

diameters and a minimum head height of 0.3 rivet diameters. Tests at the upset height of up to 1.7 diameters have shown the rivets to have exceptionally good crack resistance.

Note:

Requests for further information may be directed to:

Technology Utilization Officer
Johnson Space Center
Code AT3
Houston, Texas 77058
Reference: TSP75-10044

Patent status:

NASA has decided not to apply for a patent.

Source: J. F. Charles of
Rockwell International Corp.
under contract to
Johnson Space Center
(MSC-19301)

Categories: 06 (Mechanics)
07 (Machinery)