

# NASA TECH BRIEF

*Lyndon B. Johnson Space Center*



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

## Powered Fire Nozzle for Fast Penetration of Structures: A Concept

A special fire-extinguishing nozzle has been proposed with a tip that will punch through a wall very quickly. It would allow an extinguishing agent to be delivered inside a closed structure in a minimum amount of time. Powersaws, fire axes, and sledgehammer-driven nozzles have been used to penetrate walls. Unlike these, the powered nozzle will penetrate a wall almost instantly, an important consideration in firefighting.

Two versions of the nozzle have been conceived: one operated from a hydraulic pressure source and the other activated by an explosive charge.

The hydraulic ram shown in Figure 1 has a solid head connected to a hollow tube with nozzles on one end and a piston on the other. The piston end is mounted in a hydraulic cylinder. The cylinder has

inlet and outlet hydraulic ports that can be opened or closed to extend or retract the ram. The ports can be operated by a hand valve or by remote control. The extinguishing agent is fed through a flex line into the ram cavity and is expelled through four nozzles behind the penetration head. The device would also include a method (not shown) to adjust the length of the ram stroke to prevent the penetration of objects inside a wall. One version of the device would be mounted on a boom and a platform so operators would be at a safe distance from a fire.

A scaled-down portable version (Figure 2) of the nozzle could be operated by two men. This device would use an explosive charge as a power source. Otherwise it is similar to the hydraulic nozzle.




Figure 1. Hydraulic-Ram Nozzle

(continued overleaf)




Figure 2. Explosive-Powered Nozzle

**Note:**

Requests for further information may be directed to:

Technology Utilization Officer  
 Johnson Space Center  
 Code AT3  
 Houston, Texas 77058  
 Reference: TSP75-10111

**Patent status:**

NASA has decided not to apply for a patent.

Source: J. F. Parker and R. L. Robbins of  
 Rockwell International Corp.  
 under contract to  
 Johnson Space Center  
 (MSC-19528)