

CRYOGENIC FLUID TRANSFER - ORBITAL TRANSFER VEHICLE

431

0100 11107 2

LEON J. HASTINGS
MARSHALL SPACE FLIGHT CENTER
HUNTSVILLE, ALABAMA

EP6598

ORGANIZATION:
STRUCTURES & PROPULSION
LABORATORY EP43
CHART NO.:

MARSHALL SPACE FLIGHT CENTER
CRYOGENIC FLUID TRANSFER
ORBITAL TRANSFER VEHICLE

NAME:
LEON J. HASTINGS

DATE:
JUNE 1982

PRESENTATION OUTLINE

✓ REQUIREMENT OVERVIEW

- OTV CONFIGURATIONS
- SIZE RANGE
- INTERNAL HARDWARE
- GENERAL REFUELING CONCEPT

DESIGN/TECHNOLOGY CONSIDERATIONS


- TANK CHILLDOWN
- INITIAL TANK CONDITIONS
- CHILLDOWN THERMODYNAMICS
- TANK FILL
- FILL THERMODYNAMICS
- SUPPLY TANK EFFECTS
- SPECIAL ISSUES
- RESIDUALS
- START BASKET OR TANK PRESENCE

CONCLUSIONS

ORIGINAL PAGE IS
OF POOR QUALITY

OTV CONFIGURATION OVERVIEW


ORIGINAL PAGE IS
OF POOR QUALITY



VEHICLE	PROPELLANT	TANK VOLUME M ³ (FT ³)	PROPELLANT LOAD KG (LB)	OPERATING PRESS kN/M ² (PSI)	MISSION
POTV	LO ₂	41 (1450)	44,550 (99,000)	172 (25)	4 MEN FROM LEO TO GEO AND RETURN OR 100K TO GEO AND 60K RETURN WITH GEO REFUELING
COTV	LH ₂	116 (4100)	7,875 (17,500)	172 (25)	500K FROM LEO TO GEO

OTV CRYOGEN MANAGEMENT CONSIDERATIONS

EP4401



ORIGINAL PAGE IS
OF POOR QUALITY


ORBITAL CRYOGEN TRANSFER CONSIDERATIONS

SUPPLY TANK

- STORAGE/VENTING
- ACQUISITION/EXPULSION
 - LIQUID ORIENTATION
 - BOILING/SCREEN DRYING
 - PRESSURIZATION
 - OUTFLOW RATE
 - RESIDUALS

RECEIVER (OTV)

- PRECHILL
 - INLET FLOWRATE/DISTRIBUTION
 - WALL CHILLDOWN
 - NO VENT FILL
 - NON-EQUILIBRIUM THERMODYNAMICS
 - HELIUM PRESENCE
- START BASKET REFILL
- MASS GAUGING



TRANSFER LINE

- CHILLDOWN - PRESSURE SURGES
- FLUID LOADS
 - TRANSIENT
 - STEADY-STATE

ORIGINAL PAGE IS
OF POOR QUALITY

EP6599

ORGANIZATION:
STRUCTURES & PROPULSION
LABORATORY EP43

CHART NO.:

MARSHALL SPACE FLIGHT CENTER

CRYOGENIC FLUID TRANSFER
ORBITAL TRANSFER VEHICLE

NAME:

LEON J. HASTINGS

DATE:

JUNE 1982

PRESENTATION OUTLINE

REQUIREMENT OVERVIEW

- OTV CONFIGURATIONS
- SIZE RANGE
- INTERNAL HARDWARE
- GENERAL REFUELING CONCEPT


✓ DESIGN/TECHNOLOGY CONSIDERATIONS

- TANK CHILLDOWN
- INITIAL TANK CONDITIONS
- CHILLDOWN THERMODYNAMICS
- TANK FILL
- FILL THERMODYNAMICS
- SUPPLY TANK EFFECTS
- SPECIAL ISSUES
- RESIDUALS
- START BASKET OR TANK PRESENCE

CONCLUSIONS

ORIGINAL PAGE IS
OF POOR QUALITY

INITIAL WALL TEMPERATURE EFFECTS ON POTV
LH₂ TANK PRESSURES AFTER FILL




ORIGINAL PAGE IS
OF POOR QUALITY


POTV LH₂ TANK THERMODYNAMICS DURING CHILLDOWN

EP6560

ORIGINAL PAGE IS
OF POOR QUALITY




POTV LH₂ TANK PRESSURES DURING ORBITAL FILL



ORIGINAL PAGE IS
OF POOR QUALITY

EP6564

ENTERING LH₂ VAPOR PRESSURE EFFECTS ON POTV
TANK PRESSURE AT FILL COMPLETION




ORIGINAL PAGE IS
OF POOR QUALITY


EP6561

LH₂ SUPPLY TANK THERMODYNAMIC CONDITIONS

ORIGINAL FILED
OF POOR QUALITY



NOTE:





SUPPLY TANK
VOLUME = 85M³ (3000 FT³)

ORIGINAL PAGE IS
OF POOR QUALITY

RESIDUAL HELIUM PARTIAL PRESSURES
AT 97% FILL LEVEL


EP6566




PROPELLANT BUBBLE COLLAPSE
BY INCREASING ULLAGE PRESSURE

ORIGINAL PAGE IS
OF POOR QUALITY

LIQUID HYDROGEN



LIQUID OXYGEN



NOTE: ΔP = ULLAGE PRESSURE - SATURATION PRESSURE

CONCLUSION: COLLAPSE OF BUBBLES IN START BASKETS
COULD REQUIRE ACTIVE CIRCULATION

EP6600

ORGANIZATION:

STRUCTURES & PROPULSION
LABORATORY EP43

CHART NO.:

MARSHALL SPACE FLIGHT CENTER

CRYOGENIC FLUID TRANSFER
ORBITAL TRANSFER VEHICLE

NAME:

LEON J. HASTINGS

DATE:

JUNE 1982

PRESENTATION OUTLINE

REQUIREMENT OVERVIEW

- OTV CONFIGURATIONS
- SIZE RANGE
- INTERNAL HARDWARE
- GENERAL REFUELING CONCEPT


DESIGN/TECHNOLOGY CONSIDERATIONS

- TANK CHILLDOWN
- INITIAL TANK CONDITIONS
- CHILLDOWN THERMODYNAMICS
- TANK FILL
- FILL THERMODYNAMICS
- SUPPLY TANK EFFECTS
- SPECIAL ISSUES
- RESIDUALS
- START BASKET OR TANK PRESENCE

✓ CONCLUSIONS

ORIGINAL PAGE IS
OF POOR QUALITY

POTV PROPELLANT TRANSFER TIMELINE



ORIGINAL PAGE IS
OF POOR QUALITY

NOTES:

- TWO OR MORE ADDITIONAL VENT CYCLES REQUIRED IF HELIUM PRESENT
- TIMELINE IS FOR REFUELING TO 50% LEVEL

EP6595

ORGANIZATION:

STRUCTURES & PROPULSION
LABORATORY EP43

CHART NO.:

MARSHALL SPACE FLIGHT CENTER

CRYOGENIC FLUID TRANSFER
ORBITAL TRANSFER VEHICLE

NAME:

LEON J. HASTINGS

DATE:

JUNE 1982

CONCLUSIONS

PRE-CHILL PREPARATIONS

- DILUTION OF HELIUM RESIDUALS PRIOR TO REFUELING REQUIRED TO PREVENT:
 - EXCESSIVE PRESSURES AT END OF FILL
 - INACCURATE KNOWLEDGE OF PROPELLANT VAPOR PRESSURES
 - START BASKET HELIUM ENTRAPMENT
 - INACCURATE THERMODYNAMIC MASS GAUGING
- APPROXIMATE DILUTION LEVELS REQUIRED (POTV)
 - LH₂ < .9 KG (2 LBS)
 - LO₂ < .09 KG (.2 LBS)
- PROCEDURAL/TECHNOLOGY CONCERNS
 - DURATION OF VENT/HOLD CYCLES
 - KNOWLEDGE OF HELIUM RESIDUAL MAGNITUDE

} FURTHER DILUTION REQUIRED IF
THERMODYNAMIC MASS GAUGING
UTILIZED

ORIGINAL PAGE IS
OF POOR QUALITY

EP6596

ORGANIZATION:
STRUCTURES & PROPULSION
LABORATORY EP43

CHART NO.:

MARSHALL SPACE FLIGHT CENTER

CRYOGENIC FLUID TRANSFER
ORBITAL TRANSFER VEHICLE

NAME:

LEON J. HASTINGS

DATE:

JUNE 1982

CONCLUSIONS

TRANSFER LINE/TANK CHILLDOWN:

- REQUIREMENT: REDUCE TRANSFER LINE/TANK WALL TEMPERATURES SUFFICIENTLY TO PREVENT EXCESSIVE LINE PRESSURE/FLOW SURGES AND TO ENABLE A NON-VENTED TANK FILL
- PROCEDURAL/TECHNOLOGY CONCERNS:
 - TANK CHARGE/HOLD/VENT CYCLE DEFINITION
 - SEMI-EMPIRICAL MODELING LACKS EXPERIMENTAL DATA
 - LACK OF HARDWARE EXPERIENCE
 - WALL CHILLDOWN CRITERION: CURRENT RANGE = 95°K TO 200°K (170°R TO 360°R)
 - CHARGE MASS/FLOWRATE SELECTION: CURRENT LH₂ RANGE = 20 TO 70 KG (40 TO 155 LB) @ .5 TO 1.5 KG/SEC (1 TO 3 LB/SEC)
- LACK OF TRANSFER LINE CHILLDOWN EXPERIENCE – PREVENTION OF EXCESSIVE SURGES AND LINE LOADS
- INSTRUMENTATION TO MONITOR CHILLDOWN PROCESS

ORIGINAL PAGE 18
OF POOR QUALITY

LP0097

ORGANIZATION:

STRUCTURES & PROPULSION
LABORATORY EP43

CHART NO.:

MARSHALL SPACE FLIGHT CENTER

CRYOGENIC FLUID TRANSFER
ORBITAL TRANSFER VEHICLE

NAME:

LEON J. HASTINGS

DATE:

JUNE 1982

CONCLUSIONS

TANK FILL

- REQUIREMENT: LH₂ & LO₂ TANK FILL WITHOUT VENTING
- PROCEDURAL/TECHNOLOGY CONCERNS:
 - ASSURANCE OF ADEQUATE CIRCULATION TO MAINTAIN NEAR-THERMAL EQUILIBRIUM, i.e., LOW PRESSURES
 - GOOD MIXING/HEAT EXCHANGE BETWEEN ULLAGE/LIQUID REQUIRED
 - EXISTING SEMI-EMPIRICAL MODELS LACK EXPERIMENTAL DATA
 - LACK OF IN-FLIGHT HARDWARE EXPERIENCE
 - MECHANICAL MIXER PROBABLY REQUIRED
 - LACK OF ZERO-G MASS GAUGING DEVICE
 - SPECIAL FILL PROVISIONS FOR START BASKET
 - BLEED LINE FOR DIRECT FILL OF BASKET
 - ACTIVE CIRCULATION TO ASSURE ENTRAPPED VAPOR COLLAPSE
- SUPPLY TANK VAPOR PRESSURE ≤ 2.2 kN/M² (15 PSIA), NO HELIUM PASSAGE ALLOWABLE
- PREVENTION OF EXCESSIVE TRANSFER LINE LOADS AT $\dot{m} = 1-1.5$ KG/SEC (2-3 LB/SEC)

ORIGINAL PAGE IS
OF POOR QUALITY