N92-15083

INDUSTRIAL CODE DEVELOPMENT

W. Shapiro Mechanical Technology Inc.

The industrial codes will consist of modules of 2-D and simplified 3-D or 1-D codes, intended for expeditious parametric studies, analysis and design of a wide variety of seals. Integration into a unified system is accomplished by the industrial KBS, which will also provide User Friendly interaction, contact sensitive and hypertext help, design guidance and an expandable database.

Major seal types include Cylindrical Seals and Face Seals, and within each type are a wide variety of configurations. For example, cylindrical seals include uniform, step, taper, hydrostatic, segmented, damping, labyrinth, and spiral-groove configurations. More advanced types include brush seals, electro-fluids seals and smart seals.

The types of analyses to be included with the industrial codes are interfacial performance (leakage, load, stiffness, friction losses, etc.), thermoelastic distortions, and dynamic response to rotor excursions.

The first three codes to be completed and which are presently being incorporated into the KBS are the compressible spiral-groove codes, SPIRALG, the incompressible cylindrical code, ICYL, and the compressible cylindrical code, GCYL.

The spiral-groove codes analyzes both shaft seals and face seals with finite eccentricity and misalignment. Four degrees of freedom are included for cylindrical seals, and three for face seals. The code predicts load, flow, power loss, and cross-coupled dynamic spring and damping coefficients, shaft displacements and minimum film thickness.

The ICYL (Incompressible Cylindrical Code) is a 2-D isoviscous code that includes roughness, multiple geometries (steps, pockets, tapers, preloaded axes, and hydrostatic), turbulence, cavitation, and inertia at inlets to the film. Included are eccentricity and misalignment and variable grid specifications. Specified pressure and periodic boundary conditions can be applied. It produces pressures, flows, load, righting moments, film thickness, power loss and cross-coupled dynamic spring and damping coefficients.

GCYL is a gas cylindrical code that can treat varying geometries (steps, tapers, hydrostatic, lobed, segmented). Shaft eccentricity, misalignment, specified boundary pressures or periodic boundary conditions can be applied. The program produces the clearance distribution, pressure distribution, leakage, load, moments, power loss and cross-coupled dynamic spring and damping coefficients.

15

Objectives:

- Compile and generate sets of verified 2D and simplified 3D or 1D codes
- Codes are intended for expeditious parametric studies, analysis and design of a wide variety of seals
- Integration is accomplished by the Industrial KBS.
 Additional functions of the KBS are:
 - User Friendly Interaction
 - Contact Sensitive and Hypertext Help
 - Design Guidance
 - Expandable Database

SEAL TYPES - COMPRESSIBLE OR INCOMPRESSIBLE

Bushing and Ring Seals

- Uniform
- Axial Step
- Axial Taper
- Hydrodynamic Step
- Hydrodynamic Taper
- Self-Energized Hydrostatic
- Segmented
- Damping Seals
- Spiral Groove

16




Circumferential Muilliobe


(with or without grouves)

Circumferential

Rayleigh Step




Tapered In Flow Direction




Rayleigh Step in Direction of Flow

Sell-Energized — Hydrostatic


(Inherent Compensation Orifice Compensation Spot Orifices Receases)






SEGMENTED RING SEAL

ORIGINAL PAGE IS OF POOR QUALITY



DAMPING SEAL-LEAKAGE FLOW DAMPENS ROTOR MOTION;

ROUGH STATOR HINDERS ROTOR WHIRL




SPIRAL-GROOVE


SEAL TYPES - COMPRESSIBLE OR INCOMPRESSIBLE

Face Seals

- Contact Face Seals
- Radial Step
- Radial Taper
- Hydrodynamic Step
- Hydrodynamic Taper
- Hydrostatic
- Spiral Groove
- Multi-pad




Circumferential Tapered Land



Radial Rayleigh Step


÷ 1



Radial Tapered Land


GFACE Configurations

ORIGINAL PAGE IS OF POOR QUALITY




Groove Angle = α Groove Depth = GD Land Width/Groove Width = γ

SPIRAL GROOVE PARAMETERS



831853-1

CONTACT FACE SEAL WITH ROTATING SEAL RING



CONTACT FACE SEAL WITH NON-ROTATING SEAL RING

(Dimensions in mm Unless Otherwise Noted)

Brush Seals

.

Labyrinth Seals



Electro-Fluids Seals

Smart Seals








DIAGRAM SHOWING TYPICAL BRUSH SEAL ARRANGEMENT









OPTIMIZED STRAIGHT INLET SEAL


MAGNETIC FLUID SEAL



FUNDAMENTAL SEAL CONFIGURATION



ANALYTICAL TRIAD



Code Deliverables

Code Module	Approximate Delivery Date
GCYL (Gas Cylindrical)	02/01/91
ICYL (Incompressible Cylindrical)	03/01/91 🗲
SPIRALG (Gas Spiral Groove)	04/01/91 🗨 🛶
CFD Cylindrical Code	02/01/92
IFACE (Incompressible Face)	02/01/92
GFACE (Gas Face)	03/01/92
<pre>\$PIRALI (Incompressible-Spiral Groove)</pre>	04/01/92
FACEDY (Face-Dynamics)	02/01/93
RINGDY (Ring-Dynamics)	03/01/93
LABYRINTH (Gas)	04/01/93
Augmented CFD Cylindrical Module	02/01/94
FACECON (Face Contact)	02/01/94
DISTORTION (Thermo Elastic Distortion)	04/01/94
Additional Codes	04/01/95
• Brush	
 Damping Seal 	
CFD Code, Face, Wave, Groove Module	09/01/95
Industrial KBS	04/01/96
Scientific KBS	04/01/96
CFD, Tip, Contact, Non-Continuous Module	09/01/96

PLANNED ACTIVITY

- Code unification and completion
 - Unified Grid Generator
 - On-line Help
- Code documentation
 - Consistent with KBS usage
- Additional problems and checkout
- Annual report