

11-13
4-5-13ISSFD XIVANGULAR-RATE ESTIMATION USING QUATERNION MEASUREMENTS p6Ruth Azor* ,Itzhack Y. Bar-Itzhack+ Julie K. Deutschmann#,
and Richard R. Harman#**Abstract**

In most spacecraft (SC) there is a need to know the SC angular rate. Precise angular rate is required for attitude determination, and a coarse rate is needed for attitude control damping. Classically, angular rate information is obtained from gyro measurements. These days, there is a tendency to build smaller, lighter and cheaper SC, therefore the inclination now is to do away with gyros and use other means and methods to determine the angular rate. The latter is also needed even in gyro equipped satellites when performing high rate maneuvers whose angular-rate is out of range of the on board gyros or in case of gyro failure.

There are several ways to obtain the angular rate in a gyro-less SC. When the attitude is known, one can differentiate the attitude in whatever parameters it is given and use the kinematics equation that connects the derivative of the attitude with the satellite angular-rate and compute the latter¹. Since SC usually utilize vector measurements for attitude determination, the differentiation of the attitude introduces a considerable noise component in the computed angular-rate vector. To overcome this noise, the computed rate components can be filtered by a low pass filter of

* Senior Control Engineer, Systems and Space Technology, Electronics Division, MBT, Systems Engineering Department. Israel Aircraft Industries, Inc. Yehud Industrial Zone 56000, Israel.

+ Sophie and William Shamban Professor of Aerospace Engineering, Faculty of Aerospace Engineering, Technion-Israel Institute of Technology. Member Technion Asher Space Research Institute. Haifa 32000, Israel. Tel: +972-4-829-3196. Fax: +972-4-823-1848. E-mail address: ibaritz@tx.technion.ac.il

Aerospace Engineer, Flight Dynamics Analysis Branch, Code 572, NASA Goddard Space Flight Center, Greenbelt, MD 20771.

the form $G(s) = (1/\tau)/(s+1/\tau)$. This, however, introduces a delay in the computed rate¹. When using an active filter like a Kalman filter, the delay can be eliminated^{2,3}.

Another approach may also be adopted to the problem of angular-rate computation where the vector measurements themselves are differentiated. This approach was used by Natanson⁴ for estimating attitude from magnetometer measurements and by Challa, Natanson, Deutschmann and Galal⁵ to obtain attitude as well as rate. Similarly, Challa, Kotaru and Natanson⁶ used derivatives of the earth magnetic field vector to obtain attitude and rate.

All these methods use differentiation of either the attitude parameters or of the measured directions which normally determine the attitude parameters. Another approach is that of using the attitude parameters, or the measured directions, as measurements in some kind of a Kalman filter. In this case the kinematics equation that connects the attitude parameters or the directions with their derivatives are included in the dynamics equation used by the filter thereby, as will be shown in the ensuing, *the need for differentiation is eliminated*^{7,8}. New sensor packages have been introduced lately that yield the SC attitude in terms of the attitude quaternion⁹. Therefore it is possible to use the quaternion supplied by such sensors as measurements and, as mentioned before, eliminate the need for differentiation.

In this paper we present an algorithm for estimating the angular-rate vector of a gyro-less satellite using quaternion measurements. In order to examine the new algorithm, two approaches are compared. In the first approach, raw quaternion measurements are fed into two different filters; namely, a Pseudo-Linear Kalman Filter (PSELIKA) and a State Dependent Algebraic Riccati Equation (SDARE) filter. For the sake of comparison, another approach is tested, in which the measurements *are* differentiated to yield a coarse rate measurement that is then fed into the same two filters. Both filters rely on the ability to decompose the non-linear angular-rate dependent part

of the dynamics equation of a rigid body into a product of an angular-rate dependent matrix and the angular-rate vector itself. This decomposition, which is not unique, enables the treatment of the nonlinear spacecraft dynamics model as a linear one and, consequently, the application of the PSELIKA filter as well as the SDARE filter which is a special, more effective, Kalman filter that is based on solving the State Dependent Algebraic Riccati Equation in order to compute the Kalman gain matrix. This eliminates the need to propagate and update the filter covariance matrix.

Actual Rossi X-Ray Timing Explorer (RXTE) satellite flight data is used to test these algorithms, and results of these tests are presented in the full paper which demonstrate the efficiency of the suggested estimators.

REFERENCES

1. Harman, R.R., and Bar-Itzhack, I.Y., "Angular Rate Computation Using Attitude Differentiation," Technical Report No. TAE-881, Faculty of Aerospace Engineering, Technion-Israel Institute of Technology, Haifa 32000, Israel, Dec. 97.
2. Harman, R.R., and Bar-Itzhack, I.Y., "The Use of Pseudo-Linear and SDARE Filtering for Satellite Angular-Rate Estimation," AIAA Guidance, Navigation, and Control conference, Boston, MA, August 10-12, 1997.
3. Azor, R., Bar-Itzhack, I. Y., and Harman, R. R., "Satellite Angular rate Estimation from Vector Measurements," *Journal of Guidance, Control, and Dynamics*, Vol. 21, No. 3, May-June, 1998, pp. 450-457.
4. Natanson, G., "A Deterministic Method for Estimating Attitude from Magnetometer Data Only," Proceedings of the 43rd IFA Congress, Paper No. IFA-92-0036, Washington, DC, Aug. 28 - Sept. 5, 1992.
5. Challa, M., Natanson, G., Deutschmann, J., and Galal, K., "A PC-Based Magnetometer-Only Attitude and Rate Determination System for Gyroless Spacecraft," Proceedings of the Flight Mechanics/Estimation Theory Symposium, NASA-Goddard Space Flight Center, April 1995.
6. Challa, M., Kotaru, S., and Natanson, G., "Magnetometer-Only Attitude and Rate Estimates During the Earth Radiation Budget Satellite 1987 Control Anomaly," AIAA Guidance, Navigation, and Control conference, New-Orleans, LA, August 11-13, 1997.

7. Dellus, F., "Estimation of Satellite Angular Velocity Using Sequential Measurements of a Single Inertial Vector," M.Sc. Thesis, Faculty of Aerospace Engineering, Technion-Israel Institute of Technology, June 1998. (In Hebrew).
8. Oshman, Y., and Markley, F. L., "Sequential Attitude and Attitude-Rate Estimation Using Integrated-Rate Parameters," to be published in the *Journal of Guidance, Control, and Dynamics*.
9. Van Bezooijen, R. W. H., "AST Capabilities," Lockheed Martin Advanced Technology Center, Palo Alto, CA 95304-1191. (Slide presentation).

PUBLIC DOMAIN DECLARATION

CAUTION: Export of technical data (information) with respect to the design, development, production, manufacture, assembly, operation, repair, testing, maintenance or modification of defense articles, i.e. all space flight hardware, ground tracking systems, launch vehicles to include sounding rockets and meteorological rockets, radiation hardened hardware and associated hardware and engineering units for listed items are controlled by the State Department, International Traffic in Arms Regulations (ITAR). Export of technical data (information) with respect to ground based sensors, detectors, National Security and Missile Technology items are controlled by the U.S. Commerce Department. Please contact the GSFC Export Control office if your export applies to the above or for further clarification of the U.S. State Department (ITAR) and the U.S. Department of Commerce Regulations.

(Failure to comply with the ITAR regulations and/or the Commerce Department regulations may subject one to fines of up to \$1 million dollars and/or up to 10 years imprisonment per violation)

If your technical data does not apply with the above criteria, please select the numbered category below which best supports your declaration:

◆ Public Domain - information which is published and which is generally accessible or available to the public


1. through sales at news stands and bookstores;
2. through subscriptions which are available without restriction to any individual who desires to obtain or purchase the published information;
3. through second class mailing privileges granted by the U.S. government
4. at libraries open to the public or from which the public can obtain documents;
5. through patents available at any patent office
6. through unlimited distribution at a conference, meeting, seminar, trade show or exhibition, generally accessible to the public, in the United States,
7. through fundamental research in science and engineering at accredited institutions of higher learning in the U.S. where the resulting information is ordinarily published and shared broadly in the scientific community.

Fundamental research is defined to mean basic and applied research in science and engineering where the resulting information is ordinarily published and shared broadly within the scientific community, as distinguished from research the results of which are restricted for proprietary reasons or specific U.S. Government access and dissemination controls. University research will not be considered fundamental research if:

(i) The University or its researchers accept other restrictions on publication of scientific and technical information resulting from the project or activity, or

(ii) The research is funded by the U.S. Government and specific access and dissemination controls protecting information resulting from the research are applicable.

8. through public release (i.e., unlimited distribution in any form (e.g. not necessarily in published form) after approval by the cognizant U.S. government department and agency
9. **Publicly Available Technology and Software-** that technology and software that are already published or will be published; arise during, or result from fundamental research; are educational; or are included in certain patent applications (see 15 CFR 734)


Signature

9/15/98
Date

7
Category No.