


NASA/TM-2005-213777



The Derivation of the Gradient of the Acoustic Pressure on a Moving Surface for Application to the Fast Scattering Code (FSC)

F. Farassat
Langley Research Center, Hampton, Virginia

Kenneth S. Brentner
Pennsylvania State University, University Park, Pennsylvania

July 2005

The NASA STI Program Office . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers, but having less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.


- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or co-sponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results ... even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA STI Help Desk at (301) 621-0134
- Phone the NASA STI Help Desk at (301) 621-0390
- Write to:
NASA STI Help Desk
NASA Center for AeroSpace Information
7121 Standard Drive
Hanover, MD 21076-1320

NASA/TM-2005-213777



The Derivation of the Gradient of the Acoustic Pressure on a Moving Surface for Application to the Fast Scattering Code (FSC)

F. Farassat
Langley Research Center, Hampton, Virginia

Kenneth S. Brentner
Pennsylvania State University, University Park, Pennsylvania

National Aeronautics and
Space Administration

Langley Research Center
Hampton, Virginia 23681-2199

July 2005

Available from:

NASA Center for AeroSpace Information (CASI)
7121 Standard Drive
Hanover, MD 21076-1320
(301) 621-0390

National Technical Information Service (NTIS)
5285 Port Royal Road
Springfield, VA 22161-2171
(703) 605-6000

The Derivation of the Gradient of the Acoustic Pressure on a Moving Surface for Application to the Fast Scattering Code (FSC)

F. Farassat

NASA Langley Research Center, Hampton, Virginia

Kenneth S. Brentner

Pennsylvania State University, University Park, Pennsylvania

Abstract- In this paper we develop an analytic expression for calculation of the gradient of the acoustic pressure from a rotating blade on a moving surface for application to the Fast Scattering Code (FSC). The analytic result is intended to be used in the helicopter noise prediction code PSU-WOPWOP. One of the goals of the derivation is obtaining a result that will not use any more information than are needed for the prediction of the thickness and loading noise. The result derived here achieves this goal and its incorporation in PSU-WOPWOP is straight forward and attainable.

1. Introduction

The Fast Scattering Code (FSC) developed by Mark H. Dunn [1] requires the satisfaction of impenetrability condition on the scattering code. This condition requires the knowledge of the acoustic velocity produced by the incidence acoustic wave on the scattering surface. To find this velocity, one needs to find the gradient of the acoustic pressure on this surface. The particular incidence field that we are interested is generated by a helicopter rotor and is calculated from the rotor noise prediction code PSU-WOPWOP [2- 4]. Any other code for noise prediction of rotating blades based on the acoustic analogy can also be used to generate the incident wave.

Ideally, one would like to derive an analytic result for the gradient of the acoustic pressure which would require no more input data than those needed to calculate the thickness and loading noise. If we could get such a result, then the gradient of the acoustic pressure could be computed concurrently with the acoustic pressure using the geometric and kinematic data prepared for the acoustic calculations. This scheme will result in an efficient algorithm for calculating the gradient of the acoustic pressure on a computer. We will show in this paper that it is possible to obtain an analytic expression for the gradient of the acoustic pressure which requires the same data as the thickness and loading noise for its evaluation. In the next section, we will present our derivation of this result.

2. Derivation of The Gradient of the Acoustic pressure

2.1. The Governing Wave Equations

The governing wave equations that we will work with are those generating the thickness and loading noise in the Ffowcs Williams-Hawkings (FW-H) equation [5]. These are

$$\square^2 p'_T = \frac{\partial}{\partial t} [\rho_o v_n \delta(f)] \quad (1)$$

$$\square^2 p'_L = -\frac{\partial}{\partial x_i} [p n_i \delta(f)] \quad (2)$$

$$p' = p'_T + p'_L \quad (3)$$

The blade surface is described by the equation $f(\mathbf{x}, t) = 0$, where $f(\mathbf{x}, t)$ is defined in such a way that $\nabla f = \mathbf{n}$, \mathbf{n} being the unit outward normal to the blade with components n_i . Here p' is the acoustic pressure, and p'_T and p'_L are the thickness and loading noise, respectively. The density of the undisturbed medium is ρ_o and the local normal velocity of the blade surface is v_n . The blade surface pressure is denoted p and $\delta(f)$ is the Dirac delta function with the support on the blade surface $f = 0$. The solution of the above wave equations was given by Farassat and Succi [6] and Brentner [7]. The resulting solution, known as *Formulation 1A of Farassat*, is used in PSU-WOPWOP. The readers need some familiarity with the derivation of this Formulation to follow our mathematical work below. We recommend reference [7] for this purpose.

2.2. The Gradient of the Acoustic Pressure

We have

$$\nabla p' = \nabla p'_T + \nabla p'_L \quad (4)$$

We will now work with the formal solutions of eqs. (1) and (2) and manipulate them without integrating the delta functions in the integrands for several steps. We first work on finding the gradient of the thickness noise.

Let (\mathbf{x}, t) and (\mathbf{y}, τ) be the observer and the source space-time variables, respectively. The Green's function of the wave equation in the unbounded domain is:

$$G(\mathbf{y}, \tau; \mathbf{x}, t) = \begin{cases} \frac{\delta(g)}{4\pi r} & \tau \leq t \\ 0 & \tau > t \end{cases} \quad (5)$$

$$g = \tau - t + \frac{r}{c} \quad (6)$$

where $r = |\mathbf{x} - \mathbf{y}|$ and c is the speed of sound in the undisturbed medium.

2.2.1. The Gradient of the Thickness Noise

We introduce a new symbol for the thickness source strength as follows: $Q = \rho_o v_n$. The formal solution of eq. (1) is:

$$4\pi p'_T(\mathbf{x}, t) = \frac{\partial}{\partial t} \int \frac{Q}{r} \delta(f) \delta(g) d\mathbf{y} d\tau \quad (7)$$

where the volume integration is over the entire 3-dimensional space and the source time integration is over $(-\infty, t]$.

From eq. (7) we find that

$$4\pi \nabla p'_T(\mathbf{x}, t) = \nabla \frac{\partial}{\partial t} \int \frac{Q}{r} \delta(f) \delta(g) d\mathbf{y} d\tau = \frac{\partial}{\partial t} \int Q \delta(f) \nabla_x \left(\frac{\delta(g)}{r} \right) d\mathbf{y} d\tau \quad (8)$$

where the symbol ∇_x stands for gradient operator with respect to the observer variable \mathbf{x} . We now use the following result in the integrand of the last integral on the right of eq. (8):

$$\nabla_x \left(\frac{\delta(g)}{r} \right) = -\frac{1}{c} \frac{\partial}{\partial t} \left(\frac{\hat{\mathbf{r}} \delta(g)}{r} \right) - \frac{\hat{\mathbf{r}} \delta(g)}{r^2} \quad (9)$$

where $\hat{\mathbf{r}} = (\mathbf{x} - \mathbf{y})/r$ is the unit radiation vector from the source to the observer. Using this relation in eq. (8) and bringing the observer time derivative out of the integral, we obtain

$$4\pi \nabla p'_T(\mathbf{x}, t) = -\frac{\partial}{\partial t} \left(\frac{1}{c} \frac{\partial}{\partial t} \int \frac{\hat{\mathbf{r}} Q}{r} \delta(f) \delta(g) d\mathbf{y} d\tau + \int \frac{\hat{\mathbf{r}} Q}{r^2} \delta(f) \delta(g) d\mathbf{y} d\tau \right) \quad (10)$$

The interpretation of the integrals in this equation using generalized function theory is fairly straight forward [5- 8]. We will just write down the final result here:

$$4\pi \nabla p'_T(\mathbf{x}, t) = -\frac{\partial}{\partial t} \left(\frac{1}{c} \frac{\partial}{\partial t} \int_{f=0} \left[\frac{\hat{\mathbf{r}} Q}{r(1-M_r)} \right]_{\text{ret}} dS + \int_{f=0} \left[\frac{\hat{\mathbf{r}} Q}{r^2(1-M_r)} \right]_{\text{ret}} dS \right) \equiv -\frac{\partial \mathbf{E}_1}{\partial t} \quad (11)$$

where M_r is the local Mach number in radiation direction and

$$\mathbf{E}_1 = \frac{1}{c} \frac{\partial}{\partial t} \int_{f=0} \left[\frac{\hat{\mathbf{r}} Q}{r(1-M_r)} \right]_{\text{ret}} dS + \int_{f=0} \left[\frac{\hat{\mathbf{r}} Q}{r^2(1-M_r)} \right]_{\text{ret}} dS = \frac{1}{c} \int_{f=0} \frac{\partial}{\partial t} \left[\frac{\hat{\mathbf{r}} Q}{r(1-M_r)} \right]_{\text{ret}} dS + \int_{f=0} \left[\frac{\hat{\mathbf{r}} Q}{r^2(1-M_r)} \right]_{\text{ret}} dS \quad (12)$$

We now use the following result in the first integral on the right side of eq. (12):

$$\frac{\partial}{\partial t} [\dots]_{\text{ret}} = \left[\frac{1}{1-M_r} \frac{\partial}{\partial \tau} \dots \right]_{\text{ret}} \quad (13)$$

We obtain

$$\begin{aligned} \mathbf{E}_1 &= \frac{1}{c} \int_{f=0} \frac{\partial}{\partial t} \left[\frac{\hat{\mathbf{r}} Q}{r(1-M_r)} \right]_{\text{ret}} dS + \int_{f=0} \left[\frac{\hat{\mathbf{r}} Q}{r^2(1-M_r)} \right]_{\text{ret}} dS = \\ &= \frac{1}{c} \int_{f=0} \left[\frac{1}{1-M_r} \frac{\partial}{\partial \tau} \left(\frac{\hat{\mathbf{r}} Q}{r(1-M_r)} \right) \right]_{\text{ret}} dS + \int_{f=0} \left[\frac{\hat{\mathbf{r}} Q}{r^2(1-M_r)} \right]_{\text{ret}} dS = \\ &= \frac{1}{c} \int_{f=0} \left[\frac{\hat{\mathbf{r}}}{1-M_r} \frac{\partial}{\partial \tau} \left(\frac{Q}{r(1-M_r)} \right) \right]_{\text{ret}} dS + \frac{1}{c} \int_{f=0} \left[\frac{Q}{r(1-M_r)^2} \frac{\partial \hat{\mathbf{r}}}{\partial \tau} \right]_{\text{ret}} dS + \int_{f=0} \left[\frac{\hat{\mathbf{r}} Q}{r^2(1-M_r)} \right]_{\text{ret}} dS \end{aligned} \quad (14)$$

Examining the integrand of the first integral on the right of the second equality sign, we note that

$$E_T \equiv \left[\frac{1}{1-M_r} \frac{\partial}{\partial \tau} \left(\frac{Q}{r(1-M_r)} \right) \right]_{\text{ret}} \quad (15)$$

is the integrand of the thickness noise [6, 7]. This we will write down shortly in detail. Furthermore, we can show that [7]

$$\frac{\partial \hat{\mathbf{r}}}{\partial \tau} = \frac{c(M_r \hat{\mathbf{r}} - \mathbf{M})}{r} = -\frac{c(1-M_r) \hat{\mathbf{r}}}{r} + \frac{c(\hat{\mathbf{r}} - \mathbf{M})}{r} \quad (16)$$

where \mathbf{M} is the local Mach number of the blade surface based on the sound speed c . We remind the readers that the blade surface velocity used in \mathbf{M} is described in the frame fixed to the undisturbed medium.

Using eqs. (15) and (16) in eq. (14), we get

$$\mathbf{E}_1 = \frac{1}{c} \int_{f=0} [\hat{\mathbf{r}}]_{\text{ret}} E_T dS + \int_{f=0} \left[\frac{(\hat{\mathbf{r}} - \mathbf{M}) Q}{r^2(1-M_r)^2} \right]_{\text{ret}} dS \quad (17)$$

From references [6, 7], we have

$$E_T = \left[\frac{\dot{Q}}{r(1-M_r)^2} \right]_{\text{ret}} + \left[\frac{\dot{\mathbf{M}} \cdot \hat{\mathbf{r}} Q}{r(1-M_r)^3} \right]_{\text{ret}} + \left[\frac{c(M_r - M^2) Q}{r^2(1-M_r)^3} \right]_{\text{ret}} \quad (18)$$

where the dot on a symbol denotes the rate of change in the source time variable. We note that, by eq. (11), we have

$$4\pi \nabla p'_T(\mathbf{x}, t) = -\frac{\partial}{\partial t} \left\{ \frac{1}{c} \int_{f=0} [\hat{\mathbf{r}}]_{\text{ret}} E_T dS + \int_{f=0} \left[\frac{(\hat{\mathbf{r}} - \mathbf{M}) Q}{r^2(1 - M_r)^2} \right]_{\text{ret}} dS \right\} \quad (19)$$

where E_1 is given by eq. (17). We propose that the observer time derivative in eq. (19) be taken numerically in PSU-WOP-WOP. Then we see that for calculating the gradient of the thickness noise, we do not need any more data than is needed to calculate the thickness noise. This is the result we were looking for.

2.2.2. The Gradient of the Loading Noise

We will now find the gradient of the loading noise. We write eq. (2) in vector form as follows:

$$\square^2 p'_L = -\nabla \cdot [p \mathbf{n} \delta(f)] \quad (20)$$

The Green's function solution of this equation is

$$4\pi p'_L(\mathbf{x}, t) = -\nabla \cdot \int \frac{p \mathbf{n}}{r} \delta(f) \delta(g) d\mathbf{y} d\tau = -\int p \delta(f) \mathbf{n} \cdot \nabla_x \left(\frac{\delta(g)}{r} \right) d\mathbf{y} d\tau \quad (21)$$

We now use eq. (9) in the integrand of the last integral and then take the observer time derivative outside the integral. The result is

$$4\pi p'_L(\mathbf{x}, t) = \frac{1}{c} \frac{\partial}{\partial t} \int \frac{p \mathbf{n} \cdot \hat{\mathbf{r}}}{r} \delta(f) \delta(g) d\mathbf{y} d\tau + \int \frac{p \mathbf{n} \cdot \hat{\mathbf{r}}}{r^2} \delta(f) \delta(g) d\mathbf{y} d\tau \quad (22)$$

From this result, we get

$$4\pi \nabla p'_L(\mathbf{x}, t) = \frac{1}{c} \frac{\partial}{\partial t} \int p \delta(f) \mathbf{n} \cdot \nabla_x \left(\frac{\hat{\mathbf{r}} \delta(g)}{r} \right) d\mathbf{y} d\tau + \int p \delta(f) \mathbf{n} \cdot \nabla_x \left(\frac{\hat{\mathbf{r}} \delta(g)}{r^2} \right) d\mathbf{y} d\tau \quad (23)$$

We remind the readers that at this stage of algebraic manipulations, the observer and the source space-time variables are independent because none of Dirac delta functions have been integrated. This approach makes it easy to interpret the differentiation operators. Had we been working with the integrated results, we would be dealing with heavy algebraic manipulations and the differentiation operators would require careful interpretation.

To carry the analysis in eq. (23) further, we use the following two relations which can be derived easily

$$\mathbf{n} \cdot \nabla_x \left(\frac{\hat{\mathbf{r}} \delta(g)}{r} \right) = \mathbf{n} \cdot \nabla_x \left(\frac{\hat{\mathbf{r}}}{r} \right) \delta(g) + \frac{\mathbf{n} \cdot \hat{\mathbf{r}} \hat{\mathbf{r}}}{c r} \delta'(g) = \frac{\mathbf{n} - 2 \cos \theta \hat{\mathbf{r}}}{r^2} \delta(g) - \frac{\cos \theta \hat{\mathbf{r}}}{c r} \frac{\partial}{\partial t} \delta(g) \quad (24)$$

$$\mathbf{n} \cdot \nabla_x \left(\frac{\hat{\mathbf{r}} \delta(g)}{r^2} \right) = \mathbf{n} \cdot \nabla_x \left(\frac{\hat{\mathbf{r}}}{r^2} \right) \delta(g) + \frac{\mathbf{n} \cdot \hat{\mathbf{r}} \hat{\mathbf{r}}}{c r^2} \delta'(g) = \frac{\mathbf{n} - 3 \cos \theta \hat{\mathbf{r}}}{r^3} \delta(g) - \frac{\cos \theta \hat{\mathbf{r}}}{c r^2} \frac{\partial}{\partial t} \delta(g) \quad (25)$$

where $\cos \theta = \mathbf{n} \cdot \hat{\mathbf{r}}$, i.e., θ is the angle between local outward normal to the blade surface and the radiation direction. Substituting eqs. (24) and (25) in eq. (23) and gathering terms, we obtain

$$\begin{aligned} 4\pi \nabla p'_L(\mathbf{x}, t) = & \frac{1}{c} \frac{\partial}{\partial t} \left\{ -\frac{1}{c} \frac{\partial}{\partial t} \int \frac{p \cos \theta \hat{\mathbf{r}}}{r} \delta(f) \delta(g) d\mathbf{y} d\tau + \int \frac{p(\mathbf{n} - 3 \cos \theta \hat{\mathbf{r}})}{r^2} \delta(f) \delta(g) d\mathbf{y} d\tau \right\} + \\ & \int \frac{p(\mathbf{n} - 3 \cos \theta \hat{\mathbf{r}})}{r^3} \delta(f) \delta(g) d\mathbf{y} d\tau = \\ & \frac{1}{c} \frac{\partial}{\partial t} \left\{ -\frac{1}{c} \int_{f=0} \left[\frac{1}{1 - M_r} \frac{\partial}{\partial \tau} \left(\frac{p \cos \theta \hat{\mathbf{r}}}{r(1 - M_r)} \right) \right]_{\text{ret}} dS + \int_{f=0} \left[\frac{p(\mathbf{n} - 3 \cos \theta \hat{\mathbf{r}})}{r^2(1 - M_r)} \right]_{\text{ret}} dS \right\} + \\ & \int_{f=0} \left[\frac{p(\mathbf{n} - 3 \cos \theta \hat{\mathbf{r}})}{r^3(1 - M_r)} \right]_{\text{ret}} dS \end{aligned} \quad (26)$$

We now manipulate the first integral in the curly bracket on the right side of this equation to pull out the integrand of the loading noise. To help the readers to follow the algebraic steps below, we mention that the integrand of the loading noise is [6, 7]:

$$E_L = \frac{1}{c} \left[\frac{1}{1-M_r} \frac{\partial}{\partial \tau} \left(\frac{p \cos \theta}{r(1-M_r)} \right) \right]_{\text{ret}} + \left[\frac{p \cos \theta}{r^2(1-M_r)} \right]_{\text{ret}} =$$

$$\frac{1}{c} \left[\frac{\dot{p} \cos \theta}{r(1-M_r)^2} \right]_{\text{ret}} + \left[\frac{p(\cos \theta - M_n)}{r^2(1-M_r)^2} \right]_{\text{ret}} + \frac{1}{c} \left[\frac{\dot{\mathbf{M}} \cdot \hat{\mathbf{r}} p \cos \theta}{r(1-M_r)^3} \right]_{\text{ret}} + \left[\frac{p \cos \theta (M_r - M^2)}{r^2(1-M_r)^3} \right]_{\text{ret}} \quad (27)$$

With this knowledge, we manipulate the following integral as follows

$$\frac{1}{c} \int_{f=0} \left[\frac{1}{1-M_r} \frac{\partial}{\partial \tau} \left(\frac{p \cos \theta \hat{\mathbf{r}}}{r(1-M_r)} \right) \right]_{\text{ret}} dS = \frac{1}{c} \int_{f=0} \left[\frac{p \cos \theta}{r(1-M_r)^2} \frac{\partial \hat{\mathbf{r}}}{\partial \tau} \right]_{\text{ret}} dS +$$

$$\int_{f=0} \left\{ \frac{\hat{\mathbf{r}}}{c} \left[\frac{1}{1-M_r} \frac{\partial}{\partial \tau} \left(\frac{p \cos \theta}{r(1-M_r)} \right) \right]_{\text{ret}} + \left[\frac{p \cos \theta \hat{\mathbf{r}}}{r^2(1-M_r)} \right]_{\text{ret}} - \left[\frac{p \cos \theta \hat{\mathbf{r}}}{r^2(1-M_r)} \right]_{\text{ret}} \right\} dS =$$

$$\frac{1}{c} \int_{f=0} \left[\frac{p \cos \theta}{r(1-M_r)^2} \left(-\frac{c(1-M_r)\hat{\mathbf{r}}}{r} + \frac{c(\hat{\mathbf{r}}-\mathbf{M})}{r} \right) \right]_{\text{ret}} dS =$$

$$\int_{f=0} [\hat{\mathbf{r}}]_{\text{ret}} E_L dS - 2 \int_{f=0} \left[\frac{p \cos \theta \hat{\mathbf{r}}}{r^2(1-M_r)} \right]_{\text{ret}} dS + \int_{f=0} \left[\frac{p \cos \theta (\hat{\mathbf{r}}-\mathbf{M})}{r^2(1-M_r)^2} \right]_{\text{ret}} dS \quad (28)$$

Here, we have used eq. (16) on the right of the first equality sign. We now use this result in eq. (26) which looks without simplification as:

$$4\pi \nabla p_L(\mathbf{x}, t) = \frac{1}{c} \frac{\partial}{\partial t} \left\{ - \left\{ \int_{f=0} [\hat{\mathbf{r}}]_{\text{ret}} E_L dS - 2 \int_{f=0} \left[\frac{p \cos \theta \hat{\mathbf{r}}}{r^2(1-M_r)} \right]_{\text{ret}} dS + \int_{f=0} \left[\frac{p \cos \theta (\hat{\mathbf{r}}-\mathbf{M})}{r^2(1-M_r)^2} \right]_{\text{ret}} dS \right\} + \right.$$

$$\left. \int_{f=0} \left[\frac{p(\mathbf{n}-3\cos\theta\hat{\mathbf{r}})}{r^2(1-M_r)} \right]_{\text{ret}} dS \right\} + \int_{f=0} \left[\frac{p(\mathbf{n}-3\cos\theta\hat{\mathbf{r}})}{r^3(1-M_r)} \right]_{\text{ret}} dS \quad (29)$$

We next simplify this result to get the result we are seeking:

$$4\pi \nabla p_L(\mathbf{x}, t) = \frac{1}{c} \frac{\partial}{\partial t} \left\{ - \int_{f=0} [\hat{\mathbf{r}}]_{\text{ret}} E_L dS + \int_{f=0} \left[\frac{p(\mathbf{n}-\cos\theta\hat{\mathbf{r}})}{r^2(1-M_r)} \right]_{\text{ret}} dS - \int_{f=0} \left[\frac{p \cos \theta (\hat{\mathbf{r}}-\mathbf{M})}{r^2(1-M_r)^2} \right]_{\text{ret}} dS \right\} +$$

$$\int_{f=0} \left[\frac{p(\mathbf{n}-3\cos\theta\hat{\mathbf{r}})}{r^3(1-M_r)} \right]_{\text{ret}} dS \quad (30)$$

We propose again that the observer time derivative in eq. (30) be taken numerically in PSU-WOPWOP. We see that we do not need any more data than those needed to calculate the loading noise to find the gradient of the loading noise.

3. Concluding Remarks

This analysis was performed to find the gradient of the acoustic pressure in PSU-WOPWOP which will be used in the Fast Scattering Code of Dunn [1]. Our main results, eqs. (19) and (30), use only the geometric and kinematic data available for thickness and loading noise calculation. This means that the gradient of the acoustic pressure can be calculated concurrently with the thickness and loading calculation in PSU-WOPWOP. The inclusion of our results in PSU-WOPWOP is quite easy and minimal programming will be involved. One does not expect noticeable increase in the execution time on a computer as compared to that of acoustic calculation only.

We mention here that the choice of our main results was dictated by the use of Formulation 1A in PSU-WOPWOP. Another option available to us is to take the time derivatives in eqs. (19) and (30) analytically using the same method we have fol-

lowed above. Such a method will give a new analytic expression for the gradient of the acoustic pressure without the need for numerical differentiation with respect to the observer time. We have, however, rejected this procedure for the following reasons:

1. The new analytic expression will have many more terms than those in eqs. (19) and (30). Checking the accuracy of the algebraic manipulations used in the derivation will be much harder. Programming and debugging of the new expression will be time consuming.
2. There will be some new quantities needed in the evaluation of the new analytic expression, e.g., the second time derivative of the blade surface pressure, that will have to be prepared in the preprocessor. These quantities are not needed in Formulation 1A and the preparation of these quantities for the input file will need new programming effort and debugging.
3. Although numerical differentiation is avoided and this will reduce the execution time on a computer, more time will be spent on the evaluation of quantities that are not needed in Formulation 1A which will increase the execution time. Therefore, there may not be any net reduction of execution time by getting rid of the numerical differentiation.

The extreme simplicity of implementing eqs. (19) and (30) in PSU-WOPWOP makes them ideal for the calculation of the gradient of the acoustic pressure needed in the Fast Scattering Code (FSC).

4. References

1. Mark H. Dunn, Ana F. Tinetti, Aeroacoustic Scattering Via The Equivalent Source Method, 2004, AIAA 2004-2937.
2. G. A. Brès, *Modeling the noise of arbitrary maneuvering rotorcraft: Analysis and implementation of the PSU-WOPWOP noise prediction code*, June 2002, M.S. Thesis, Department of Aerospace Engineering, The Pennsylvania State University.
3. G. Perez, *Investigation of the influence of maneuver on rotorcraft noise*, June 2002, M.S. thesis, Department of Aerospace Engineering, The Pennsylvania State University.
4. Kenneth S. Brentner, G. Perez, G. A. Brès, H. E. Jones, Maneuvering Rotorcraft Noise Prediction, 2003, *Journal of Sound and Vibration*, 39 (3-5), 719- 738.
5. J. E. Ffowcs Williams, D. L. Hawkings, Sound generation by turbulence and surfaces in arbitrary motion, *Philosophical Transactions of the Royal Society of London A* 264 (1969) 321–514.
6. F. Farassat, G. P. Succi, A review of propeller discrete frequency noise prediction technology with emphasis on two current methods for time domain calculations, 1980, *Journal of Sound and Vibration*, 71(3), 399-419
7. Kenneth K. Brentner, Prediction of Helicopter Discrete Frequency Rotor Noise: A Computer Program Incorporating Realistic Blade Motions and Advanced Formulation, October 1986, NASA TM 87721.
8. F. Farassat, Introduction to Generalized Functions With Applications in Aerodynamics and Aeroacoustics, May 1994 (Corrected April 1996), NASA Technical Paper 3428

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
1. REPORT DATE (DD-MM-YYYY)		2. REPORT TYPE		3. DATES COVERED (From - To)	
01-07-2005		Technical Memorandum			
4. TITLE AND SUBTITLE The Derivation of the Gradient of the Acoustic Pressure on a Moving Surface for Application to the Fast Scattering Code (FSC)				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Farassat, F.; and Brentner, Kenneth S.				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER 23-781-10-33	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) NASA Langley Research Center Hampton, VA 23681-2199				8. PERFORMING ORGANIZATION REPORT NUMBER L-19138	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, DC 20546-0001				10. SPONSOR/MONITOR'S ACRONYM(S) NASA	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) NASA/TM-2005-213777	
12. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified - Unlimited Subject Category 71 Availability: NASA CASI (301) 621-0390					
13. SUPPLEMENTARY NOTES Farassat: Langley Research Center; Brentner: Pennsylvania State University. An electronic version can be found at http://ntrs.nasa.gov					
14. ABSTRACT In this paper we develop an analytic expression for calculation of the gradient of the acoustic pressure from a rotating blade on a moving surface for application to the Fast Scattering Code (FSC). The analytic result is intended to be used in the helicopter noise prediction code PSU-WOPWOP. One of the goals of the derivation is obtaining a result that will not use any more information than are needed for the prediction of the thickness and loading noise. The result derived here achieves this goal and its incorporation in PSU-WOPWOP is straight forward and attainable.					
15. SUBJECT TERMS Aeroacoustics; Fast scattering code (FSC); Helicopter noise; Noise Prediction; PSU WopWop; Fuselage scattering					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			STI Help Desk (email: help@sti.nasa.gov)
U	U	U	UU	11	19b. TELEPHONE NUMBER (Include area code) (301) 621-0390