


## **Development of Non Destructive Evaluation Techniques for the In-Situ Inspection of the Orbiter's Thermal Protection System**

José M. Hernández  
NASA – Johnson Space Center  
Houston, Texas

One of the Columbia Accident Investigation Board's (CAIB) recommendation is to develop and implement an inspection plan to determine the structural integrity of all Reinforced Carbon-Carbon (RCC) system components that make part of the Space Shuttle's thermal protection system. This presentation focuses on the efforts to leverage non-destructive evaluation (NDE) expertise from academia, private industry, and government agencies resulting in the design of a comprehensive health monitoring program for RCC components. The different NDE techniques that were considered are presented along with the chosen techniques and preliminary inspection results of RCC materials.




**IEEE Symposium  
Guadalajara, Mexico**

**Jose M. Hernandez  
NASA - Johnson Space Center  
April 2, 2004**



# Introduction




## Objective


Enhance NASA's approach to the development of a comprehensive NDE program for the in-situ health monitoring of Space Shuttle Orbiter RCC components.



# Reinforced Carbon-Carbon (RCC)





- RCC is composed of Carbon substrate, Silicon Carbide conversion "coating", and a Type A sealant
  - Carbon Substrate – "Carry the Load"
  - Silicon Carbide Coating – "Protect the Carbon"
    - In-situ coating – outer 0.020-0.040 inch "converted" to SiC.
  - TEOS and Type A – "Help Protect the Carbon"
    - TEOS provides internal protection against porosity within the laminate.





# Space Shuttle Reinforced Carbon-Carbon (RCC) Components



Nose Cap, Chin Panel, and Seals

Forward External Tank Attachment "Arrowhead" Plate

Wing Leading Edge Panels and Tee Seals



## **Detection Requirements**





**The Shuttle program has stipulated inspection techniques be able to detect the following flaws:**

- **Tubular voids**
- **Coating damage**
- **Delaminations**
- **Backside damage**
- **Cracks**





# Columbia Accident Investigation



- T+81 sec after launch of STS-107 a piece of debris was noted to come off the external tank (ET) and impact the LH wing of the Shuttle
- Analysis during the flight identified a zone where the debris had the potential to impact
  - MLG Door, Wing, RCC and Carrier Panel
- Tasks were initiated to better understand foam projectile impacts on potential impact zones and develop improved in-situ NDE inspection techniques




# Ascent Debris Position based on Photographic Analysis







# Development NDE RCC Inspection Systems



## Took a two-phase approach:

- **Phase 1:** Quantitatively determine viability of most promising non-destructive evaluation (NDE) techniques:
  - Held a Technical Integration Meeting with NDE community at KSC (May 2003)
  - Both long and near term technologies were identified
  - Near term defined as ability to field technique  $\leq$  12 months (i.e. focused on mature technologies)
  - Everything else categorized as advanced NDE techniques
  - Held 2<sup>nd</sup> Technical Integration Meeting (November 2003)
  - Reached consensus on which techniques to pursue
- **Phase 2:** Develop selected techniques into “turn-key” systems. (12 months)
  - Presently implementing phase 2



# Results of Feasibility Studies




Selected the four most promising in-situ techniques with <12 months total development time


Short Term <12 months	Thermography Contact Ultrasonics Eddy Current  * Not Selected	Radiography Non-contact Ultrasonics* Shearography *
Long Term >12 months	Micro-Power Impulse Radar* Thermal Conductivity Msmts.* Digital Radiography Limited Angle CT X-ray transmission msmts. * Health Monitoring Sensors* Phased Array Ultrasonics	MRI* Tera-Hertz Imaging* Back Scatter X-ray Guided Wave Ultrasonics 3-D microwave* Remote Acoustic Impact Doppler* Ultrasonic Spectroscopy*




# RCC Validation Test Specimen Set




- Boeing disks w/ arc jet exposure
- 0.25" th. central section (coating)
- 0.44" th. edge section (no coating)
- 8L post impact – 4 panel round robin
- 0.25" th. section with natural flaws (coating)
- 8L "blind specimen" (Bill's Box)
- Uncoated "blind specimen" (Sam's Box)
- Complete RCC panel (manuf. reject)
- Various other pieces




**RCC Blind Test Box (Bill's Box)**



**RCC Blind Test Box (Sam's Box)**







**X-ray Test Specimen      0.44" RCC Panel**

















# RCC Puck Samples







# NDE Results of Various RCC Samples






# UT - 0.24" & 0.44" Panel with Coating



Back\* Side  
Mid  
Front\* Side

## 0.24" Thickness Sample

# P-E UT Optimum Coupling





Back Side 0.4"  
Mid 0.22"  
Front Side 0.04"

## 0.44" Thickness Sample



# NASA Took Advantage of Foam Impact Tests conducted at SwRI






# RCC testing in support of the Investigation




Two full scale RCC panel tests were conducted during the Investigation


- Panel 6
  - Material: BX 250 foam
  - Dimensions: 5.63" x 11.56" x 21.38"
  - Mass: 763.8 g (1.68 lb)
  - Actual launch velocity: 768 ft/sec
  - CG angle of impact: 20.6°
  - 5½" long through thickness crack
  - Located on the lock side approximately 6" below the stagnation
  - Transverses the entire rib width, extends through the lock side channel and onto panel lower face.
  - Approximate 3/4" crack on the lower face
  - T-seal crack 2.5" long on rib








# Thermography Inspections




## OV-103 6L Pre Impact



Thermal Image of the location of the crack

**Outboard  
(W/out T-seal)**

## OV-103 6L Post Impact




Thermal Image of the crack through the part


**Outboard  
(W/ T-seal)**



# Thermography Inspections




## OV-103 6L Post Impact PCA Analysis of thermal data





# Capabilities of Chosen Techniques



Technique	Physical Contact Req'd	Deep Delams	Cracks	Large Voids	Sig. Porosity	Local Mass Loss	Impact Damage	Coat Msmt	Inspect Stem Fastener Area
Thermal		X	X	X	X	X	X		
UT	X	X	X	X	X	X	X		
Eddy Current	X		X		X			X	
X-ray	X		X		X		X		X