



The **Middle-Loop Sensing Gradiometer** concept shows a schematic illustration of cryostat wall geometry (cut-off view). The imaging volume is in between two middle loops, outside the cryostat at room temperature.

comes the imaging volume with the enclosing cryostat built accordingly.

Because of the sensing middle loops at both ends of the imaging volume, the sensitivity at the center of the im-

aging volume is twice that of conventional geometry with the same SQUID noise. Only about half of the induced energy is lost in the non-sensing loops in the new scheme. The symmetric

placement of the sensing loops gives more uniform sensitivity. There is no inductance matching penalty associated with the new configuration, because the geometry and the inductance remain to be that of a single second-order gradiometer.

This work was done by Konstantin Penanen, Inseob Hahn, and Byeong Ho Eom of Caltech for NASA's Jet Propulsion Laboratory. Further information is contained in a TSP (see page 1).

In accordance with Public Law 96-517, the contractor has elected to retain title to this invention. Inquiries concerning rights for its commercial use should be addressed to:

Innovative Technology Assets Management

JPL

Mail Stop 202-233

4800 Oak Grove Drive

Pasadena, CA 91109-8099

E-mail: iaoffice@jpl.nasa.gov

Refer to NPO-45720, volume and number of this NASA Tech Briefs issue, and the page number.

Volcano Monitor: Autonomous Triggering of *In-Situ* Sensors

NASA's Jet Propulsion Laboratory, Pasadena, California

In-situ sensors near volcanoes would be alerted by the Earth Observing-1 (EO-1) craft to take more frequent data readings. This project involves developing a sulfur-dioxide-sensing volcano monitor that will be able to transmit its readings through an Iridium modem. The monitor, when integrated into the Sensor Web network, will demonstrate the autonomous capabilities of the Sensor Web, as well as the speed and accuracy of the network. A potential scenario might involve an Earth-based sensor near the volcano, such as a tilt meter or a seismometer, encountering a critical

reading. This particular sensor could alert EO-1, which could then look for other sensors in the area. It would then send an alert message down to the Volcano Monitoring Box, which would increase the frequency of its readings from once an hour to once a minute. All these data would then be collected on a Web site that is accessible by volcanologists and other scientists. A typical data reading will include a date, time, temperature reading, humidity reading, and sulfur dioxide reading.

By using the speed and ease with which EO-1 transmits data, information

about volcanic activity can be collected quickly and autonomously. In better understanding the volcanoes of Earth, this technology will enable better study and understanding of volcanoes on other moons and planets as NASA sends unmanned vehicles to farther regions of space.

This work was done by Kate Boudreau of University of Idaho, Johanna Cecava of New Mexico State University, and Alberto Behar, Ashley Davies, and Daniel Q. Tran of Caltech for NASA's Jet Propulsion Laboratory. For more information, contact iaoffice@jpl.nasa.gov. NPO-45445

Wireless Fluid-Level Sensors for Harsh Environments

Sensors can be encased for protection, and are interrogated without wire connections.

Langley Research Center, Hampton, Virginia

Magnetic-field-response sensors have been developed for use in measuring levels of fluids under extreme conditions. The sensors work without wire

connections or direct physical contact with power sources, microprocessors, data-acquisition equipment, or electrical circuitry. For fuel-level sensors, the ab-

sence of wire connections offers an important safety advantage in elimination of potential ignition sources.

The sensors can be designed for