

BASIS FUNCTION APPROXIMATION OF TRANSONIC AERODYNAMIC INFLUENCE COEFFICIENT MATRIX

Wesley W. Li and Chan-gi Pak
NASA Dryden Flight Research Center, Edwards, CA 93523-0273

Keywords: *aerodynamic influence coefficient matrix, basis function approximation, flutter analysis, least squares method, multidisciplinary design optimization*

Abstract

A technique for approximating the modal aerodynamic influence coefficients [AIC] matrices by using basis functions has been developed and validated. An application of the resulting approximated modal AIC matrix for a flutter analysis in transonic speed regime has been demonstrated. This methodology can be applied to the unsteady subsonic, transonic and supersonic aerodynamics. The method requires the unsteady aerodynamics in frequency-domain. The flutter solution can be found by the classic methods, such as rational function approximation, k , p - k , p , root-locus et cetera. The unsteady aeroelastic analysis for design optimization using unsteady transonic aerodynamic approximation is being demonstrated using the ZAERO™ flutter solver (ZONA Technology Incorporated, Scottsdale, Arizona). The technique presented has been shown to offer consistent flutter speed prediction on an aerostructures test wing [ATW] 2 configuration with negligible loss in precision in transonic speed regime. These results may have practical significance in the analysis of aircraft aeroelastic calculation and could lead to a more efficient design optimization cycle.

1 Introduction

Supporting the Aeronautics Research Mission Directorate guidelines, the National Aeronautics and Space Administration [NASA] Dryden Flight Research Center [DFRC] is developing an object-oriented multidisciplinary design, analysis, and optimization [MDAO]

tool [1]. This tool will leverage existing tools and practices, and allow the easy integration and adoption of new state-of-the-art software. At the heart of the object-oriented MDAO tool is the central executive module [CEM] as shown in figure 1. In this module, the user will choose an optimization methodology; provide starting and side constraints for continuous as well as discrete design variables and external file names for performance indices, which communicate between the CEM and each analysis module; submit script commands to prepare input data for each analysis code; execute analyses codes; compute performance indices using post-processor codes; and compute an objective function and constraint values from performance indices. The structural analyses modules such as computations of the structural weight, stress, deflection, buckling, and flutter and divergence speeds have been developed and incorporated into the object-oriented MDAO framework.

With the increased complexity of the configuration and the need to increase the fidelity of the nonlinear aerodynamic equations to be solved in transonic regime, the computational cost of the unsteady aeroelastic analysis required to generate aerodynamic influence coefficients [AIC] matrices for full aeroelastic response and design optimizations is very high [1]. Also, these analyses are usually performed repeatedly to optimize the final design. Even though the computational cost may be reduced by the use of advanced algorithms and improved computer hardware processing speeds, these full aeroelasticity analyses cannot be incorporated effectively

within a preliminary design and optimization environment.

The integration of traditional unsteady computational fluid dynamics [CFD] into MDAO involving disciplines such as aeroelasticity and aeroservoelasticity is, at present, a costly and impractical venture [1]. At industry, aircraft designs using nonlinear CFD codes are mainly based on the manual trial and error approach, and this will considerably slow down the whole design procedure. As a result, there is considerable motivation to be able to perform unsteady aeroelastic calculations more quickly and inexpensively. The development of a MDAO tool to automate this process is needed to reduce time required for the early conceptual and/or preliminary design stages.

The results of the rapid computation of a modal AIC matrix and aeroelastic response calculations using an approximated modal AIC matrix based on basis function approximation [BFA] has been previously validated and demonstrated successfully in subsonic speed regime to reduce the computation time. This approach reduces the modal AIC computation time using existing AIC matrices during optimization procedure by 80 percent [2]. This paper extends the study and validation of the application of the BFA from the subsonic speed regime to the transonic speed regime.

The transonic speed range introduces some particular flutter problems that are not commonly treated by classic linear flutter theory. Classic coupled torsion and bending wing flutter occurs when, with increase in dynamic pressure, the bending frequency increases and the torsional frequency decreases until the separation between these two frequencies becomes sufficiently small to allow exchange of energy between the two corresponding modes of the structure. In contrast, for wings with attached flow at transonic speeds, the flutter mechanism is somewhat different. It is very important to determine the location of the shocks, which is known to have fundamental importance on the correct estimation of the unsteady aerodynamic loads, for the transonic flutter prediction. The capture of the shock is impossible using any

linear code at transonic speed. The general aeroelastic problem involving the interaction between the aircraft structure and the unsteady transonic flow with the presence of shock waves can only be solved using CFD codes, based on transonic small disturbance [TSD] theory, Euler codes, or the complete Navier-Stokes equations. The order of complexity and computational costs increases from the level of the TSD theory to the Navier-Stokes theory that can accurately predict interactions between boundary layers and local shocks on typical aerodynamic surfaces. In this paper, CAP-TSDv [3] code is used to capture the shock at steady state and flutter prediction.

This paper presents the flutter results of the aerostructures test wing [ATW] 2 model without tip boom, in transonic speeds using BFA and traditional methods also called the direct method throughout the rest of the paper. The MSC NASTRAN (MSC Software Corporation, Santa Ana, California) [4], CAP-TSDv, ZAERO ZONA6 linear code, and ZTAIC nonlinear code [5] (ZONA Technology Incorporated, Scottsdale, Arizona) are used in this study for computing the flutter boundary.

2 Basis Function Approximation

In linear algebra, a basis is a set of vectors that, in a linear combination, can represent every vector in a given vector space or free module, and such that no element of the set can be represented as a linear combination of the others [6]. In other words, a basis is a linearly independent spanning set. Since mode shapes are orthogonal to each other and each mode has a natural frequency associated with the eigenvalue, structural mode shapes obtained from different mass or various stiffness configurations of the airplane can be used as the basis functions. These basis functions are comparison functions [7] since all the geometric and natural boundary conditions of the airplane are satisfied. The mode shapes of the airplane with any of the configurations in the design spaces can be used to generate the basis functions. Furthermore, each mode shape of the target configuration of the airplane can be approximated as a linear combination of a

set of basis functions. This basis function approximation has been described in reference 2.

In general, a time-domain approach is more convenient for analysis tasks and nonlinear problems; on the other hand, a frequency-domain approach is better for design tasks and linear problems. Most modern CFD codes were developed using the time-domain approach, and therefore, the results of these CFD runs are usually the time-histories of pressure distributions, structural displacements et cetera. To use the modern CFD computation for our design optimization studies, we are interested in developing an approximate unsteady computational aeroelastic analysis in the frequency-domain to dramatically reduce the required computation time for optimization runs in the transonic speed regime. To accomplish these objectives, the BFA method in reference 2 can be extended and evaluated for approximation in transonic speeds. The BFA method requires the unsteady aerodynamics to be represented in the frequency domain. The flutter solution can be found by classic methods, such as rational function approximation, k, p-k, p, g method, and root-locus et cetera.

The computation of a modal AIC matrix and aeroelastic response calculations in transonic speeds will be discussed in this paper and the approximation process is outlined in the flowchart given in figure 2.

In step 1, a set of representative basis functions, Ψ , is chosen with the intent to capture salient features of the modal responses the airplane is expected to encounter in the various design spaces.

In step 2, the steady state pressure distributions for the transonic speed analysis can be obtained by using a CFD code or wind tunnel test.

In step 3, a set of representative basis modal AIC matrices, \tilde{Q} , are computed corresponding to the representative basis functions defined in step 1 and steady pressure distributions obtained in step 2 at any Mach number and reduced frequencies. These basis modal AIC matrices are used as input for

approximate modal AIC matrix calculation in step 5. These basis modal AIC matrices are computed only once and stored before starting optimization.

In step 4, during optimization, for a set of given structural mode shapes, ϕ , each mode shape is decomposed in a linear combination of the basis functions, Ψ . The i-th mode shape, ϕ_i , ($i=1, 2, \dots, m$, where m is the number of mode shapes) is approximated through the use of a least squares fitting together with the following basis functions as shown in equation (1),

$$\phi_i \approx \sum_{k=1}^n \beta_k^i \psi_k \quad (1)$$

where ψ_k is the k-th basis function and a coefficient, β_k^i , is the modal participation factor of the k-th basis function on the i-th mode shape and n is the number of basis functions.

In step 5, an approximate modal AIC matrix, \bar{Q} , is computed based on a basis modal AIC matrix, \tilde{Q} , and modal participation factors in equation (2),

$$Q_{ij} \approx \bar{Q}_{ij} = \sum_{r=1}^n \sum_{s=1}^n \beta_s^i \beta_r^j \tilde{Q}_{sr} \quad (2)$$

where Q_{ij} is the i-th row and j-th column element of the modal AIC matrix Q .

In step 6, the flutter analysis is performed using the approximate modal AIC matrix in equation (2). The flutter speed and frequency could be used for optimization.

3 Applications

In an effort to validate the BFA in transonic speed, a modified ATW2 model was chosen and the flutter results using approximate method were compared with the direct flutter results for both subsonic and transonic speed. To simplify the problem, especially for CFD mesh generation in CAP-TSDv, the wing tip boom is removed from this application. The

original ATW2 [8] with wing tip boom is the test article actually designed, built, and tested at NASA DFRC as shown in figure 3. The ATW2 was clamped onto a circular plate, which was bolted to a mounting panel. The mounting panel was attached to the flight test fixture [FTF] [9]. The FTF was installed on the centerline F-15B (McDonnell Douglas, now The Boeing Company, Chicago, Illinois) pylon in flight configuration.

For the direct method, the flutter analysis of the target design configuration is performed using the ZAERO linear subsonic method (ZONA6) and nonlinear transonic method (ZTAIC) with the first 10 structural modes and 16 reduced frequencies at 4 Mach numbers (Mach 0.80, 0.90, 0.95, and 0.98). The steady state pressure input data as the initial condition for the ZTAIC method used in the present analysis are obtained by using the CAP-TSDv code at all four Mach numbers. In order to prove the setup and the process of the ZTAIC method correctly, the flutter results from both the ZONA6 and ZTAIC methods are compared and used to verify the process at subsonic Mach numbers. At a subsonic Mach number like Mach 0.80, before any shock is formed, both the linear and nonlinear solver should predict similar flutter results. Once the process was verified, the ZTAIC method was used for the flutter prediction in the transonic speed regime.

The CAP-TSDv calculations were performed on a $150 \times 80 \times 80$ points computational grid with 41 points along each of the 57 spanwise chords on the wing as shown in figure 4. The steady pressure distributions obtained from the CAP-TSDv computations at Mach 0.80, 0.90, 0.95, and 0.98 all at 0.0 deg and 1.0 deg of angle of attack [AOA] are shown in figure 5 and 6; and the steady pressure differences between the upper and the lower surfaces under 1.0 deg AOA at the same Mach numbers are shown in figure 7. With 3 percent structural damping, the primary flutter speed and flutter frequency comparison of the ZONA6 and ZTAIC methods are summarized in figure 8. At the subsonic Mach number of 0.80, the ZTAIC

results are in close agreement with those of the ZONA6, as expected, since a transonic shock has not formed yet.

The primary flutter mode is the first bending mode at Mach 0.80. However, the second bending mode becomes the primary flutter mode when the Mach number is 0.98. On the other hand, the flutter mode interchange does not happen with the ZONA6 computation. At Mach 0.98, the primary flutter mode with the ZTAIC computation is the second mode, 81 Hz, as shown in figure 8, while the primary flutter mode with the ZONA6 computation is the first mode, 55 Hz. This mode interchange may be caused by the local high pressure zone near the center of the wing as shown in figures 5 and 6.

Based on the pressure differences in figure 7, the aerodynamic load distributions at Mach 0.80 and 0.90 are fairly similar in shape, which are basically the subsonic distributions, (i.e. high near the leading-edge area and low near the trailing-edge area). When the Mach number became 0.95, the area of the high aerodynamic loads was extended to the aft section of the wing-root chord, and an even higher load area was formed near the leading-edge of the wing mid chord. At Mach 0.98, aerodynamic load distributions are changed drastically, and compared to the Mach 0.95 case, highly concentrated aerodynamic load distributions are observed from the leading edge of the wing tip chord to the trailing edge of the wing root chord. From these observations, we may conclude that the transonic effects start to happen between Mach numbers of 0.90 and 0.95, and strong shocks are formed at Mach 0.98 as shown in figures 5 and 7. Probably the second bending mode in figure 9 can be easily excited by the concentrated aerodynamic load distributions at Mach 0.98.

In this ATW2 example, five different design configuration points in the parameter design space are selected for generating basis functions for the approximate flutter solution. The design variations used in this study are variations in wing thickness and stiffness that are effected by variations in the number and

orientation of the composite laminate plies. These design variations are intended to capture salient features of the modal responses resulting from mass and stiffness variations in the design space. The structural mode shapes obtained from those five design configurations are used as the basis functions. The finite element model and the first three mode shapes of the target configuration are shown in figure 10. The total weight and center of gravity of the various fictitious and target design configurations are listed in table 1. The target configuration in this paper is simply an arbitrary design point within the design space and is used as a check case.

First, 10 structural mode shapes for each design configuration (a total of 50 basis functions) are generated using MSC/NASTRAN. The natural frequencies of the various fictitious and target design configurations are listed in table 2. Next, the size of 50 by 50 basis modal AIC matrix corresponding to those 50 basis functions is computed for each of the 16 reduced frequencies at Mach 0.80, 0.90, 0.95, and 0.98 using ZONA6 and ZTAIC. To solve the modal participation factors, the mode shapes of the target design configuration are fitted using the basis functions with a least squares method. Then the approximate modal AIC matrices are computed based on the modal participation factors. Finally, the approximate flutter boundaries can be solved by using any linear frequency domain flutter solution code and the approximated modal AIC matrices. It is important to point out that in order to provide meaningful comparisons of the direct method with the BFA method, the ZTAIC method is used to predict the flutter boundaries in this paper. Given that the BFA approach can be used with any kind of CFD code, ZTAIC is selected for CFD simulation in this paper due to limited resources. The focus in this paper is to demonstrate that the BFA method can be used to predict adequate flutter speed and flutter frequency at transonic speed regime regardless the level of CFD code.

As shown in table 3, using ZTAIC, both methods predicted similar flutter speed and flutter frequency at Mach 0.80, 0.90, 0.95, and

0.98. The speed versus damping, $V-g$, and speed versus frequency, $V-\omega$, curves from the direct and BFA methods at Mach 0.90, 0.95, and 0.98 are given in figures 11, 12, and 13. These figures indicate that an interchange between the first bending and the second bending flutter modes results when Mach number increased from 0.90 to 0.98. At Mach 0.90, the first bending mode, 56 Hz, is predicted as the primary flutter mode. This flutter mode became the hump mode at Mach 0.95 and stable mode at Mach 0.98. Meanwhile, the stable second mode at Mach 0.90 became unstable at Mach 0.95 and later became primary flutter mode at Mach 0.98. With 3 percent structural damping, the primary flutter speed and flutter frequency are summarized in table 3 and figure 14. The largest percentage error of flutter speed and frequency is 1.60 percent at Mach 0.98 and 1.27 percent at Mach 0.80 respectively. Although a different CFD code may generate different unsteady AIC and predict different flutter results, the important point is that the results of the BFA method is following the one predicted by the direct method. Overall, the resulting flutter boundaries prediction using the BFA method is well compared with the direct method in transonic speed. The flutter boundaries prediction based on the BFA method are essentially identical to those using direct solution on the target design configuration.

Table 4 lists the computational cost of computing the modal AIC matrices with given structural mode shapes at one Mach number and 16 reduced frequencies using the direct method and the BFA method. The size of the ATW2 model is about 260 degrees of freedom. The computational cost of generating the modal AIC using the direct method and the BFA method is about 43 s and 8 s using ZONA6 and 49 s and 8 s using ZTAIC respectively in this ATW2 example. As a result, the BFA approach reduces the modal AIC computation time using existing AIC matrices by 80 percent. The comparison was done on an Intel® Core™2 2.80GHz CPU computer (Intel Corporation, Santa Clara, California). The computational cost of

generating the basis functions before the parametric study is not included in the comparison.

4 Concluding Remarks

Many of the most interesting engineering applications are very complex systems, such as aeroelastic analyses and optimization in which the analysis is achieved through the use of expensive and time consuming numerical simulations. The processing times on even the most powerful workstations may be too expensive. A technique for approximating the modal AIC matrix by using basis function approximation has been applied in transonic speed regime, and a process for using the resulting AIC matrix in aeroelastic analyses has been developed and demonstrated. The technique presented has been shown to offer consistent flutter speed prediction on an ATW2 configuration with insignificant small loss in accuracy, less than 1.6 percent error in the ATW2 test case, and the results are essentially identical to those using direct solution. The BFA approach has been demonstrated successfully in the transonic speed regime to reduce the computation time of generating modal AIC using basis functions. The BFA approach has shown an 80 percent reduction in the modal AIC computation time using existing AIC matrices. These results may have practical significance in the aeroelastic analysis of an aircraft and could lead to a more efficient design optimization cycle in a transonic speed regime. For the design optimization and parameter study, hundreds or even thousands of analyses have to be performed. Creation of an

approximated modal AIC matrix using basis functions allows for analysis, and a parameter optimization cycle of the system in minutes, rather than hours of computer time on common personal computers.

References

- [1] Pak C and Li W. Multidisciplinary design, analysis and optimization tool development using a genetic algorithm. *Proceedings of the 26th Congress of International Council of the Aeronautical Science*, Anchorage, Alaska, 2008.
- [2] Pak C and Li W. Application of approximate unsteady aerodynamics for flutter analysis. *Proceedings of the 51st AIAA Structures, Structural Dynamics, and Materials Conference*, Orlando, Florida, AIAA-2010-3085, pp 1-18, April 12-15, 2010.
- [3] Batina J, Seidel D, Bennett R and Bland S. *Preliminary user's manual for CAP-TSD (version 1.0)*, 1988.
- [4] *MSC/NASTRAN quick reference guide version 69*. The MacNeal Schwendler Corporation, 1996.
- [5] *ZAERO theoretical manual version 8.3*, ZONA Technology, Inc., 2007.
- [6] Kahaner D, Moler C and Nash, S. *Numerical methods and software*. Prentice-Hall, 1989.
- [7] Meirovitch L. *Analytical methods in vibrations*, Prentice-Hall, 1967.
- [8] Lung S and Pak C. Updating the finite element model of the aerostructures test wing using ground vibration test data. *Proceedings of the 50th AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics, and Materials Conference*, Palm Springs, California, AIAA-2009-2528, pp 1-17, May 4-7, 2009.
- [9] Richwine D. F-15B/flight test fixture II: a test bed for flight research. NASA-TM-4782, 1996.

Tables

Table 1. Summary of total weight and center of gravity location for the ATW2 without the tip boom model with different fictitious design configurations.

| Fictitious configuration | Config. 1 | Config. 2 | Target | Config. 3 | Config. 4 | Config. 5 |
|--------------------------|-----------|-----------|--------|-----------|-----------|-----------|
| Total weight, lb | 2.38 | 2.53 | 2.81 | 2.88 | 3.66 | 4.09 |
| X _{CG} , in | 12.56 | 12.70 | 12.93 | 12.98 | 13.41 | 13.58 |
| Y _{CG} , in | -7.17 | -7.24 | -7.35 | -7.38 | -7.59 | -7.67 |
| Z _{CG} , in | -3.12 | -2.95 | -2.66 | -2.59 | -2.05 | -1.85 |

Table 2. Summary of natural frequencies (Hz) of the ATW2 without the tip boom model with different design configurations.

| Mode | Config. 1 | Config. 2 | Target | Config. 3 | Config. 4 | Config. 5 |
|------|-----------|-----------|--------|-----------|-----------|-----------|
| 1 | 23.08 | 22.77 | 22.06 | 21.88 | 20.01 | 19.13 |
| 2 | 85.61 | 85.76 | 84.85 | 84.49 | 79.34 | 76.50 |
| 3 | 120.67 | 126.71 | 131.30 | 131.62 | 126.99 | 122.32 |
| 4 | 147.99 | 168.97 | 194.28 | 194.17 | 183.32 | 177.44 |
| 5 | 193.02 | 195.30 | 194.80 | 198.63 | 223.60 | 228.76 |
| 6 | 261.81 | 277.74 | 291.27 | 292.60 | 286.04 | 277.39 |
| 7 | 315.54 | 322.42 | 323.05 | 322.07 | 304.26 | 295.76 |
| 8 | 399.82 | 423.26 | 442.11 | 443.74 | 434.38 | 426.50 |
| 9 | 459.62 | 472.40 | 472.64 | 470.78 | 442.33 | 431.65 |
| 10 | 560.99 | 582.69 | 595.67 | 595.64 | 572.74 | 561.21 |

Table 3. Summary of the ATW2 without the tip boom model flutter results comparison for BFA and the direct method using ZTAIC.

| Mach | Flutter speed, KEAS | | | Flutter frequency, Hz | | |
|------|---------------------|--------|--------|-----------------------|--------|--------|
| | BFA | Direct | Error | BFA | Direct | Error |
| 0.80 | 621.77 | 622.94 | -0.19% | 59.85 | 60.62 | -1.27% |
| 0.90 | 612.39 | 612.38 | 0.00% | 56.56 | 56.56 | 0.00% |
| 0.95 | 641.94 | 640.68 | 0.20% | 53.63 | 54.01 | -0.70% |
| 0.98 | 557.56 | 566.60 | -1.60% | 81.23 | 81.10 | 0.16% |

Table 4. Computational cost comparison of BFA and the direct method.

| | ZONA6 | ZTAIC |
|----------------------------|-------|-------|
| Direct method elapsed time | 43 s | 49 s |
| BFA method elapsed time | 8 s | 8 s |

Figures




Fig. 1. Object-oriented multidisciplinary design, analysis, and optimization tool.




Fig. 4. CAP-TSD wing surface mesh.




Fig. 2. Flowchart of the flutter analysis module in the object-oriented MDAO tool.




Fig. 5. Steady pressure distributions on the upper surface using CAP-TSDv code (0 deg angle of attack).




Fig. 3. Aerostructures test wing 2.




Fig. 6. Steady pressure distributions on the upper surface using CAP-TSDv code (1 deg angle of attack).




Fig. 7. Steady pressure difference under 1 deg angle of attack using CAP-TSDv code.




Fig. 9. V-g and V- ω plots for the ATW2 at Mach 0.98 using ZONA6 and ZTAIC methods.




Fig. 8a. Flutter speed.




Fig. 8b. Flutter frequency.

Fig. 8. Flutter results for the ATW2 without tip boom (ZONA6 compared with ZTAIC).




Fig. 10. The aerostructures test wing 2 without tip boom mode shapes.




Fig. 11. V-g and V- ω plots for the ATW2 at Mach 0.90 using direct ZTAIC and BFA ZTAIC methods.




Fig. 12. V-g and V- ω plots for the ATW2 at Mach 0.95 using direct ZTAIC and BFA ZTAIC methods.




Fig. 13. V-g and V- ω plots for the ATW2 at Mach 0.98 using direct ZTAIC and BFA ZTAIC methods.




Fig. 14a. Flutter speed.




Fig. 14b. Flutter frequency.

Fig. 14. Flutter results for the ATW2 without tip boom.

Copyright Statement

The authors confirm that they, and/or their company or organization, hold copyright on all of the original material included in this paper. The authors also confirm that they have obtained permission, from the copyright holder of any third party material included in this paper, to publish it as part of their paper. The authors confirm that they give permission, or have obtained permission from the copyright holder of this paper, for the publication and distribution of this paper as part of the ICAS2010 proceedings or as individual off-prints from the proceedings.



Basis Function Approximation of Transonic Aerodynamic Influence Coefficients Matrix

Wesley Li and Chan-gi Pak, Ph.D.

Structural Dynamics Group, Aerostructures Branch
NASA Dryden Flight Research Center

27th Congress of the International Council of the Aeronautical Sciences
Nice, France, 19-24 September 2010 15, 2010



Agenda



- Introduction / Background
- Objective
- Methodology - Basis Function Approximation (BFA)
- Validation
- Computational Cost Comparison
- Concluding Remarks



Introductions

□ In support of the Aeronautics Research Mission Directorate (ARMD) guidelines, the NASA Dryden has developed an Object-Oriented Optimization (O³) tool. This tool leverages existing tools and practices, and allow the easy integration and adoption of new state-of-the-art software.

- ❖ Choose an optimization method.
- ❖ Define objective and constraint functions from performance indices.
- ❖ Provide starting and side constraints for continuous as well as discrete design variables and executable and I/O file names for each module.
- ❖ Submit script commands for executing each module.
- ❖ Structural analyses modules such as computations of the structural weight, stress, deflection, buckling, and flutter and divergence speeds as well as a structural model update module have been developed and incorporated.





Introductions (continued)

- Unsteady aeroelastic analysis and optimization is a challenging task
 - ❖ With the increased complexity of the model configuration and the need to increase the fidelity of the nonlinear aerodynamic equations, huge DOF problems, to be solved, the computational cost of the unsteady aeroelastic analysis required to generate aerodynamic influence coefficients (AIC) matrices for full aeroelastic response is very high, especially in transonic regime.
 - ❖ Also, these analyses are usually performed repeatedly to optimize the final design. Even though the computational cost may be reduced by the use of advanced algorithms and improved computer hardware processing speeds, these full aeroelasticity analyses **cannot be incorporated effectively** within a preliminary design and optimization environment.
 - ❖ The integration of traditional unsteady computational fluid dynamics (CFD) into MDAO involving disciplines such as aeroelasticity and aeroservoelasticity is, at present, a costly and impractical venture. At industry, aircraft designs using nonlinear CFD codes are mainly **based on the manual trial and error approach**, and this will considerably slow down the whole design procedure.




Objectives

- ❑ To be able to perform aeroelastic calculations more quickly and inexpensively by reducing the computation time for generating modal AIC matrices using Basis Function Approximation (BFA) method during the optimization procedure.



Basis Function

- ❑ In linear algebra, a basis is a set of vectors that, in a linear combination, can represent every vector in a given vector space or free module, and such that no element of the set can be represented as a linear combination of the others.
- ❑ Mode shapes are orthogonal to each other and each mode has a natural frequency associated with the eigenvalue, therefore, structural mode shapes can be used as the basis functions.
- ❑ Mode shapes are comparison functions for the original eigenvalue problem since all the geometric and natural boundary conditions of the airplane are satisfied.
- ❑ Mode shapes obtained from different mass or various stiffness configurations of the airplane can be used to capture significant features of the modal responses of the airplane to encounter in the various design space.






Basis Function Approximation (BFA)

□ The results of the rapid computation of a modal AIC matrix and aeroelastic response calculations using an approximated modal AIC matrix based on basis function approximation (BFA) has been previously validated and demonstrated successfully in subsonic speed regime to reduce the computation time. (*AIAA-2010-3085, pp 1-18, April 12-15, 2010*)

- ❖ Compute unsteady aerodynamics **in the frequency domain** using Basis Function Approximation method.
- ❖ Approximate Modal AIC has been validated by comparing the aeroelastic solution instead of just comparing each of the elements in the matrices. The flutter solution can be found by the classic methods, such as rational function approximation, k, p-k, p, g-method etc.
- ❖ The BFA approach reduces the modal AIC computation time using existing AIC matrices during optimization procedure **by 80 percent.**




□ **This paper extends the study and validation of the application of the BFA from the subsonic speed regime to the transonic speed regime.**



Flutter Analysis Module Flowchart

- ❑ In step 1, generate a set of “representative” structural basis function using structural mode shapes.
- ❑ In step 2, compute the steady state pressure for CFD run
- ❑ In step 3, compute the basis modal AIC matrices corresponding to the structural basis functions defined in step 1 at each Mach number and reduced frequencies. These basis modal AIC matrices are used as input for approximate modal AIC matrix calculation in step 5.



Flutter Analysis Module Flowchart




Flutter Analysis Module Flowchart (continued)

- ❑ In step 4, decompose each given structural mode shape in a linear combination of the basis functions Ψ using least squares fitting. The i -th mode shape, Φ_i , is defined as

$$\phi_i \approx \sum_{k=1}^n \beta_k^i \psi_k$$

- ❑ In step 5, compute the approximate modal AIC matrix based on a basis modal AIC matrices and modal participation factors. This approximate modal AIC matrix will be used for flutter analysis.

$$\bar{Q}_{ij} = \sum_{r=1}^n \sum_{s=1}^n \beta_s^i \beta_r^j \tilde{Q}_{sr}$$



Flutter Analysis Module Flowchart

where n is the number of basis functions,

where Q_{ij} is the i -th row and j -th column element of the modal AIC matrix Q .


where ψ_k is the k -th basis function and a coefficient, β_k^i , is the modal participation factor of the k th basis function on the i -th mode shape and n is the number of basis functions.



Validations

- ❑ In order to validate the BFA method in transonic flight regimes, the results of the flutter solution using this approximate method are compared with the direct flutter solution for both subsonic and transonic speed (analytical only).
- ❑ Test case: ATW2 without tip boom model.

- ❑ *The original ATW2 with wing tip boom is the test article actually designed, built, and tested at NASA DFRC.*
- ❑ *The ATW2 was clamped onto a circular plate, which was bolted to a mounting panel. The mounting panel was attached to the flight test fixture (FTF). The FTF was installed on the centerline F-15B pylon in flight configuration.*





Validations (continue)

- ❑ To demonstrate that the BFA method can be used to predict adequate flutter speed and flutter frequency at transonic speed regime regardless the level of CFD code.

- ❑ To provide meaningful comparisons of the direct method with the BFA method, the identical flutter solver is used to predict the flutter boundaries.

- ❑ The BFA approach can be used with any kind of CFD code, ZAERO nonlinear transonic method, ZTAIC is selected for CFD simulation in this study due to limited resources.

- ❑ To prove the setup and the process of using ZTAIC method correctly, the flutter results from both the linear subsonic method, ZONA6 and ZTAIC methods are compared at subsonic Mach numbers.





- ❑ The flutter analysis of the target design configuration is performed with the first 10 structural modes and 16 reduced frequencies at 4 Mach numbers (Mach 0.80, 0.90, 0.95, and 0.98).

- ❑ The steady state pressure input data as the initial condition for the ZTAIC method used in the flutter analysis are obtained by using the CAP-TSDv code.



CAP-TSDv Steady Pressure Results

- The CAP-TSDv calculations were performed on a $150 \times 80 \times 80$ points computational grid with 41 points along each of the 57 spanwise chords on the wing.







Steady pressure difference under 1 deg angle of attack using CAP-TSDv code.

Steady pressure distributions on the upper surface using CAP-TSDv code (1 deg angle of attack).



Flutter Results - ZONA6 vs. ZTAIC

- At the subsonic Mach number of 0.80, the ZTAIC results are in close agreement with those of the ZONA6, as expected, since a transonic shock has not formed yet.
- At the transonic Mach number of 0.95 and 0.98, the flutter mode interchange does not happen with the ZONA6 computation. This mode interchange may be caused by the local high pressure zone near the center of the wing





A modified ATW2 Fictitious Configuration

- ❑ To generating basis functions for the approximation modal AIC and the approximate flutter solution, five different design configuration points in the parameter design space are selected.
- ❑ The design variations used in this study are variations in wing thickness and stiffness that are effected by variations in the number and orientation of the composite laminate plies.
- ❑ The design variations are intended to capture salient features of the modal responses resulting from mass and stiffness variations in the design space.

| Fictitious configuration | Config. 1 | Config. 2 | Target | Config. 3 | Config. 4 | Config. 5 |
|--------------------------|-----------|-----------|--------|-----------|-----------|-----------|
| Total weight, lb | 2.38 | 2.53 | 2.81 | 2.88 | 3.66 | 4.09 |
| X_{CG} , in | 12.56 | 12.70 | 12.93 | 12.98 | 13.41 | 13.58 |
| Y_{CG} , in | -7.17 | -7.24 | -7.35 | -7.38 | -7.59 | -7.67 |
| Z_{CG} , in | -3.12 | -2.95 | -2.66 | -2.59 | -2.05 | -1.85 |

Summary of total weight and center of gravity location for the ATW2 without the tip boom model with different fictitious design configurations (MSC NASTRAN).




Natural Frequencies & Mode Shapes

- Summary of natural frequencies of the ATW2 with different fictitious mass and stiffness configurations using MSC NASTRAN.

Summary of natural frequencies (Hz) of the ATW2 without the tip boom model with different design configurations.

| Mode | Config. 1 | Config. 2 | Target | Config. 3 | Config. 4 | Config. 5 |
|------|-----------|-----------|--------|-----------|-----------|-----------|
| 1 | 23.08 | 22.77 | 22.06 | 21.88 | 20.01 | 19.13 |
| 2 | 85.61 | 85.76 | 84.85 | 84.49 | 79.34 | 76.50 |
| 3 | 120.67 | 126.71 | 131.30 | 131.62 | 126.99 | 122.32 |
| 4 | 147.99 | 168.97 | 194.28 | 194.17 | 183.32 | 177.44 |
| 5 | 193.02 | 195.30 | 194.80 | 198.63 | 223.60 | 228.76 |
| 6 | 261.81 | 277.74 | 291.27 | 292.60 | 286.04 | 277.39 |
| 7 | 315.54 | 322.42 | 323.05 | 322.07 | 304.26 | 295.76 |
| 8 | 399.82 | 423.26 | 442.11 | 443.74 | 434.38 | 426.50 |
| 9 | 459.62 | 472.40 | 472.64 | 470.78 | 442.33 | 431.65 |
| 10 | 560.99 | 582.69 | 595.67 | 595.64 | 572.74 | 561.21 |



- Structural finite element model mode shapes of the ATW2 with target mass and stiffness configuration.



Number of DOFs ~260



Flutter Results - Direct vs. BFA


- Summary of the ATW2 without the tip boom model flutter results comparison for BFA and the direct method using ZTAIC.

| Mach | Flutter speed, KEAS | | | Flutter frequency, Hz | | |
|------|---------------------|--------|--------|-----------------------|--------|--------|
| | BFA | Direct | Error | BFA | Direct | Error |
| 0.80 | 621.77 | 622.94 | -0.19% | 59.85 | 60.62 | -1.27% |
| 0.90 | 612.39 | 612.38 | 0.00% | 56.56 | 56.56 | 0.00% |
| 0.95 | 641.94 | 640.68 | 0.20% | 53.63 | 54.01 | -0.70% |
| 0.98 | 557.56 | 566.60 | -1.60% | 81.23 | 81.10 | 0.16% |









Modified ATW2 Flutter Results – Vg Plots, Mach 0.90



V-g and V- ω plots for the ATW2 at Mach 0.90 using direct ZTAIC and BFA ZTAIC methods.







Modified ATW2 Flutter Results – Vg Plots, Mach 0.95



V-g and V- ω plots for the ATW2 at Mach 0.95 using direct ZTAIC and BFA ZTAIC methods.



Modified ATW2 Flutter Results – Vg Plots, Mach 0.98



V-g and V- ω plots for the ATW2 at Mach 0.98 using direct ZTAIC and BFA ZTAIC methods.



Computational Cost Comparison

- Computational cost comparison of BFA and Direct method.
 - ❖ The computational cost of computing the modal AIC with a given structural mode shape at one Mach number using the direct method and the BFA method. The comparison was done on an Intel® Core™2 2.80 GHz CPU computer.
 - ❖ The computational cost of generating the basis functions before the parametric study is not included in the comparison.

| | ZONA6 | ZTAIC |
|----------------------------|---------------|---------------|
| Direct method elapsed time | 43 sec | 49 sec |
| BFA method elapsed time | 8 sec | 8 sec |

BFA is 5 times faster than Direct.

- For the design optimization and parameter study, hundreds or even thousands of analyses have to be performed. Creation of an approximated modal AIC matrix using basis functions allows for analysis, and a parameter optimization cycle of the system in minutes, rather than hours of computer time on common personal computers.



Concluding Remarks

- ❑ Many of the most interesting engineering applications are very complex systems, such as aeroelastic analyses and optimization in which the analysis is achieved through the use of expensive and time consuming numerical simulations. The processing times on even the most powerful workstations may be too expensive.
- ❑ The basis function approximation (BFA) has been validated and demonstrated successfully in the subsonic and transonic speed regime to reduce the computation time of generating modal AIC using basis functions. A process for using the resulting AIC matrix in aeroelastic analyses has been developed and demonstrated as well.
- ❑ The BFA technique presented has been shown to offer consistent flutter speed prediction on an ATW2 configuration **with insignificant small loss in accuracy**, less than 1.6 percent error in the ATW2 test case, and the results are essentially identical to those using direct solution. The BFA approach has shown an 80 percent reduction in the modal AIC computation time using existing AIC matrices, **5 times faster than direct method.**
- ❑ For the design optimization and parameter study, hundreds or even thousands of analyses have to be performed. Creation of an approximated modal AIC matrix using basis functions may have practical significance in the aeroelastic analyses of an aircraft and could lead to a more efficient design optimization cycle.



Questions?