

# Environmental Science and Pollution Research

## Effect of multilayer substrate configuration in horizontal subsurface flow constructed wetlands: Assessment of treatment performance, biofilm development and solid accumulation

--Manuscript Draft--

<b>Manuscript Number:</b>	ESPR-D-17-00923R1	
<b>Full Title:</b>	Effect of multilayer substrate configuration in horizontal subsurface flow constructed wetlands: Assessment of treatment performance, biofilm development and solid accumulation	
<b>Article Type:</b>	Research Article	
<b>Corresponding Author:</b>	Tao Lv, Ph.D Nottingham Trent University UNITED KINGDOM	
<b>Corresponding Author Secondary Information:</b>		
<b>Corresponding Author's Institution:</b>	Nottingham Trent University	
<b>Corresponding Author's Secondary Institution:</b>		
<b>First Author:</b>	Yanli Ding	
<b>First Author Secondary Information:</b>		
<b>Order of Authors:</b>	Yanli Ding	
	Tao Lv, Ph.D	
	Shaoyuan Bai	
	Zhenling Li	
	Haijing Ding	
	Shaohong You	
	Qinglin Xie	
<b>Order of Authors Secondary Information:</b>		
<b>Funding Information:</b>	National Natural Science Foundation of China (51408147)	Mr. Yanli Ding
	National Natural Science Foundation of China (41404116)	Mr. Yanli Ding
	National Natural Science Foundation of China (51638006)	Mr. Yanli Ding
	Science research and technology development project of Guangxi (Guikehe1599005-2-2)	Mr. Yanli Ding
	Guangxi Scientific Experiment Center of Mining, Metallurgy and Environment (KH2012ZD004)	Mr. Yanli Ding
	high level innovation team and standing scholar in Guangxi colleges and universities (002401013001)	Mr. Yanli Ding
<b>Abstract:</b>	This study investigates the influence of multilayer substrate configuration in horizontal subsurface flow constructed wetlands (HSCWs) on their treatment performance, biofilm development, and solid accumulation. Three pilot-scale HSCWs were built to treat campus sewage and have been operational for three years. The HSCWs included	

	<p>mono-layer (CW1), three-layer (CW3), and six-layer (CW6) substrate configurations with hydraulic conductivity of the substrate increasing from the surface to bottom in the multilayer CWs. It was demonstrated the pollutants removal performance after 3-year operation improved in the multilayer HSCWs (49-80%) compared to the monolayer HSCW (29-41%). Simultaneously, the multilayer HSCWs exhibited significant features that prevented clogging compared to the mono-layer configuration. The amount of accumulated solids was notably higher in the mono-layer CW compared to multilayer CWs. Further, multilayer HSCWs could delay clogging by providing higher biofilm development for organics removal and consequently, lesser solid accumulations. Principal component analysis strongly supported the visualization of the performance patterns in the present study and showed that multilayer substrate configuration, season, and sampling locations significantly influenced biofilm growth and solid accumulation. Finally, the present study provided important information to support the improved multilayer configured HSCW implication in the future.</p>
<b>Response to Reviewers:</b>	Please see the attached file, named as "response to comments".
<b>Additional Information:</b>	
<b>Question</b>	<b>Response</b>
§Are you submitting to a Special Issue?	No

## Response to Comments

**Manuscript Number: ESPR-D-17-00923**

### **Answers to Editors and Reviewers**

The revised manuscript entitled “Effect of multilayer substrate configuration in horizontal subsurface flow constructed wetlands: Assessment of treatment performance, biofilm development and solid accumulation” was earlier submitted for publication in *Environmental Science and Pollution Research*.

We are obliged to the reviewers of this manuscript, which contributed to improve its quality. The response explaining how the authors have dealt with the specific referees’ comments are integrated in the reviewer’s text. Relevant changes (highlighted with yellow colour) were introduced throughout the manuscript text and marked with page and line number in the attached word file.

### **Reviewer #1**

[1] This is a good manuscript, I do have only few questions and comments.

**Answer: Thank you very much for the comments.**

#### General comment:

[2] Three years of operation is not a long term performance. It is difficult to say exactly, however, in my opinion, it should be at least 10 years of operation.

**Answer: Thank you very much for your comments. It is truly that the common life span of a well-designed/maintained CWs will be 10-15 years or even longer. However, the established CWs for basic research in the publications are always shorter than 3 years. By considering the reviewer’s comment, in order to make the language more accurate in this scientific paper, the terms of “long term performance” were either deleted or changed to “performance after 3-year operation” or “after relatively long term (3-year) operation” in the whole paper. (Page 1, line 31 and 46; Page 3, line 26; Page 4, line 16; Page 15, line 46)**

[3] Page 4, line 44: The reference is not correctly written.

**Answer: The typo was modified. It should be the location of the experiment site (latitude and longitude) rather a reference. Thus, the wrong term “(N25cember 2012 at.” was changed to “N25° 28’, E110° 31’”. (Page 4, line 47)**

[4] Why TVC was calculated using this weird approximation and not counted?

**Answer:** In the present paper, total viable cells were quantified by extraction of phospholipids and analysis of phosphate (cleaved from phospholipids). Compare with plate count method, phospholipids have the advantages that their concentration remains fairly constant in relation to cell biomass and once a cell dies the phospholipids have a short half-life. Thus, the more accurate and precise method was selected to be used in the present study.

[5] Page 9, line 4: what kind of improvement do authors speak?

**Answer:** The sentence was re-written to improve the clarity. Thus the old sentence “Both maximum and minimum temperatures showed clearly improvement along with the season changes from April to September.” was changed to “Along with the season changes from April to September, the maximum and minimum air temperatures showed clearly improvement from approximately 25 °C to 30 °C and 17 °C to 25 °C, respectively.”. (Page 9 , line 4-10)

[6] Did authors measure hydraulics in various layers?

**Answer:** Thanks for raising this point. We did not measure the hydraulics in various layers in the present study. However, it is an interesting point which is worth to be investigated in the followed study.

[Click here to view linked References](#)

# Effect of multilayer substrate configuration in horizontal subsurface flow constructed wetlands: Assessment of treatment performance, biofilm development and solid accumulation

Yanli Ding<sup>1,2</sup>, Tao Lv<sup>3\*</sup>, Shaoyuan Bai<sup>4\*</sup>, Zhenling Li<sup>2</sup>, Haijing Ding<sup>2</sup>, Shaohong You<sup>4</sup>, Qinglin Xie<sup>2</sup>

<sup>1</sup> College of Earth Sciences, Guilin University of Technology, Guilin 541004, China ;

<sup>2</sup> Collaborative Innovation Center for Water Pollution Control and Water Safety in Karst Area, Guilin University of Technology, Guilin 541004, China

<sup>3</sup> School of Animal, Rural and Environmental Sciences, Nottingham Trent University, Brackenhurst Campus, Southwell NG25 0QF, United Kingdom

<sup>4</sup> Guangxi Key Laboratory of Environmental Pollution Control Theory and Technology, Guilin University of Technology, Guilin 541004, China;

\*Correspondence author, E-mail: tao.lyu@ntu.ac.uk (L.T.); Shaoyuanbai@126.com (S.B.)

## Abstract

This study investigates the influence of multilayer substrate configuration in horizontal subsurface flow constructed wetlands (HSCWs) on their treatment performance, biofilm development, and solid accumulation. Three pilot-scale HSCWs were built to treat campus sewage and have been operational for three years. The HSCWs included mono-layer (CW1), three-layer (CW3), and six-layer (CW6) substrate configurations with hydraulic conductivity of the substrate increasing from the surface to bottom in the multilayer CWs. It was demonstrated the pollutants removal performance after 3-year operation improved in the multilayer HSCWs (49-80%) compared to the monolayer HSCW (29-41%). Simultaneously, the multilayer HSCWs exhibited significant features that prevented clogging compared to the mono-layer configuration. The amount of accumulated solids was notably higher in the mono-layer CW compared to

1  
2 multilayer CWs. Further, multilayer HSCWs could delay clogging by providing higher  
3  
4 biofilm development for organics removal and consequently, lesser solid accumulations.  
5  
6  
7 Principal component analysis strongly supported the visualization of the performance  
8  
9 patterns in the present study and showed that multilayer substrate configuration,  
10  
11 season, and sampling locations significantly influenced biofilm growth and solid  
12  
13 accumulation. Finally, the present study provided important information to support the  
14  
15 improved multilayer configured HSCW implication in the future.  
16  
17  
18  
19  
20

21 **Keywords:** Biofilm growth; clogging; organics removal; spatial difference; total valid  
22  
23 cell count  
24  
25  
26

## 27 **1. Introduction**

28  
29 Horizontal subsurface flow constructed wetlands (HSCWs) have been widely used  
30  
31 for wastewater treatment as an environmental friendly technology (Kadlec & Wallace,  
32  
33 2008; Vymazal, 2009). However, clogging is the most common problem encountered in  
34  
35 HSCWs, which can result in a large proportion of the influent water passing over the  
36  
37 bed as surface-runoff. Clogging reduces the possibility of contact between pollutants  
38  
39 and biofilm required for biodegradation in the HSCWs, which significantly weakens  
40  
41 treatment performance and shortens their life span (Osorio et al., 2007). Thus,  
42  
43 solutions that prevent clogging and optimize CW utilization have gained considerable  
44  
45 attention in the recent decades.  
46  
47  
48  
49  
50  
51  
52  
53

54  
55 Substrate configuration is an important factor that influences clogging as most  
56  
57 clogging solids wrap around the substrate pores (Brovelli et al., 2011). Theoretically,  
58  
59  
60  
61  
62  
63  
64  
65

1 substrate configuration can be improved by placing finer media with low hydraulic  
2 conductivity on the top and coarser media with high hydraulic conductivity at the  
3  
4  
5  
6  
7 bottom, which should prevent short-circuit of water flow on the surface and decrease  
8  
9  
10 dead zones at the bottom. It is believed that this substrate configuration enables a  
11  
12  
13 natural and even water flow, which prevents insalubrious clogging of the CWs (Knowles  
14  
15  
16 et al., 2011; Morales et al., 2013). Furthermore, the uniform water flow pattern would  
17  
18  
19 improve pollutants biodegradation due to high biofilm/pollutant contact possibility.  
20  
21 The system following this concept was built and recorded higher pollutants removal  
22  
23  
24 efficiencies the year following construction (Bai et al., 2016). However, the  
25  
26 performance after relatively long term (3-year) operation has not been evaluated after  
27  
28  
29 over three years of operation.  
30

31  
32 Clogging is a complex process, however, the exact mechanisms and  
33  
34  
35 consequences of clogging are not completely clear. Blazejewski and Murat-Blazejewska  
36  
37  
38 (1997) reported that biofilm growth and solid accumulation are important factors that  
39  
40  
41 cause clogging. An investigation of the development process of biofilm during changing  
42  
43  
44 seasons showed that temperature was an important factor in clogging (Platzer and  
45  
46  
47 Mauch, 1997). Higher temperatures result in higher biological activity, which decreases  
48  
49  
50 organic matter accumulation. However, it may also cause higher biofilm growth that  
51  
52  
53 promotes clogging. In horizontal flow CWs, solids accumulation has been recognized as  
54  
55  
56 a major factor that decreases CW longevity (Cooper et al., 2005). Accumulated solids in  
57  
58  
59 CWs include both organic and inorganic solids (Knowles et al., 2011). However,  
60  
61  
62  
63  
64  
65

1 comprehensive investigation of biofilm growth and solid accumulation related to  
2 spatial and seasonal differences in HSCWs with multilayer substrate configuration has  
3  
4  
5  
6  
7 not been conducted.  
8  
9

10 The aim of this study was to determine the influence of multilayer substrate  
11 configuration on treatment performance, biofilm development, and solid accumulation  
12 after 3-year operation in HSCWs. Pollutant removal efficiencies were measured in a  
13 pilot HSCW treating campus sewage that had been operational for three years. Biofilm  
14 development and solid accumulation were analyzed in different seasons (April, July,  
15 and September) of 2016 to compare the spatial difference between monolayer and  
16 multilayer HSCWs. Total viable cell counts (TVC), extracellular polysaccharide (EPS), and  
17 extracellular protein (EP) were measured to represent biofilm development. Different  
18 solid components, including organic and inorganic matters, were investigated to  
19 evaluate solid accumulation.  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36

## 37 **2. Materials and methods**

### 38 **2.1 Experimental setup**

39 Three parallel pilot-scale HSCWs were constructed in December 2012 at Guilin  
40 University of Technology, in south-west China (N25° 28', E110° 31'). A detailed  
41 description of the experimental setup can be found in Bai et al. (2016). Briefly, each  
42 system had distinct dimensions of 2 m length, 1.2 m width, 0.7 m height, and water  
43 depth of 0.6 m (Fig. 1a). Each HSCW was divided into influent distribution zone (0.2 m  
44 long), main reaction bed (1.6 m long), and effluent collection zone (0.2 m long). The  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65



1  
2 main reaction beds of the three HSCWs had different configurations (Fig. 1b). CW1 was  
3  
4 mono-layer substrate configured, filled with quartz sand (0-6 mm) with hydraulic  
5  
6 conductivity (K) of 65 m/d. CW3 consisted of three equal layers with 0.2 m thickness.  
7  
8 The K values of the layers were 26, 36, and 64 m/d from the surface to the bottom, and  
9  
10 the corresponding sand diameters were 0-0.4, 0.4-0.6, and 1-3 mm, respectively. CW6  
11  
12 comprised of six equal layers with 0.1 m thickness. From the top to bottom, sand sizes  
13  
14 were 0-0.4, 0.4-0.6, 0.6-0.9, 1-2, 2-4, and 4-6 mm, with K values of 26, 36, 43, 55, 75,  
15  
16 and 176 m/d, respectively.  
17  
18  
19  
20  
21  
22  
23

24 The laboratory facility was subject to natural temperature variations and light  
25  
26 exposure but protected from rain by a glass roof. The influent of this experiment was  
27  
28 original campus sewage pre-treated by a septic tank. The three HSCWs shared a 200 L  
29  
30 influent tank with separate pump stations functioning at identical hydraulic loading  
31  
32 rate (HLR) of 0.3 m<sup>3</sup>/m<sup>2</sup>/d, to ensure consistent operation mode. The systems had  
33  
34 been continually operational for the past three years. The present study was  
35  
36 conducted from April 1, 2016 to September 1, 2016. All HSCWs were planted with  
37  
38 *Canna indica* at the density of 20 individuals per square meter. The average influent  
39  
40 COD, NH<sub>4</sub><sup>+</sup>-N, TN, and TP were approximately 145, 23, 32, and 5 mg/L during  
41  
42 experimentation period (Table 1).  
43  
44  
45  
46  
47  
48  
49  
50  
51

## 52 **2.2 Water sampling and measurement**

53  
54

55 Triplicate water samples were collected from the influent tank and effluent pipes  
56  
57 of the HSCWs once a week to monitor water quality and pollutants removal. The pH  
58  
59  
60  
61  
62  
63  
64  
65

1 and ORP were measured in situ using a Hanna Hi9828 multi-parameter portable meter.

2  
3  
4 Air and influent water temperatures were recorded everyday using an automatic  
5  
6  
7 temperature logger connected to the sensor. Individual water samples were stored in  
8  
9  
10 100 mL sterile plastic bottles, cooled to 5 °C, and transported to the laboratory. The  
11  
12 concentrations of chemical oxygen demand (COD), ammonium ( $\text{NH}_4^+\text{-N}$ ), nitrate  
13  
14 ( $\text{NO}_3^-\text{-N}$ ), nitrite ( $\text{NO}_2^-\text{-N}$ ), total nitrogen (TN), and total phosphorous (TP) were  
15  
16 analyzed within 24 h using standard methods (APHA, 2005).  
17  
18  
19  
20

### 21 **2.3 Substrate sampling**

22  
23  
24 Substrate samples of the attached biofilm and solid accumulation analyses were  
25  
26 collected on April 1, July 1, and September 1, 2016 using a push core sampler ( $\varnothing$  5 cm,  
27  
28 length 100 cm). Substrate samples were taken from the front and back parts of each  
29  
30 HSCW at a distance of 0.3 m and 1.7 m from the inlet, respectively. Three 50 g samples  
31  
32 were taken from each sampled core at depths of -10 cm (A1), -30 cm (A2), and -50 cm  
33  
34 (A3) from the surface (Fig. 1a). Visible roots and debris were removed and samples  
35  
36 were stored in sterile plastic bags, placed on ice, and transferred immediately to the  
37  
38 lab for the following analyses.  
39  
40  
41  
42  
43  
44  
45

### 46 **2.4 Biofilm analysis**

47  
48  
49 Total viable cell counts (TVC), extracellular polysaccharide (EPS), and extracellular  
50  
51 protein (EP) were tested to evaluate biofilm development (Ragusa et al., 2004). TVC  
52  
53 was measured using the method described by Findlay et al. (1989). Briefly,  
54  
55 phospholipids were extracted from substrate samples and concentrations of phosphate  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

1 released by phospholipids were determined using the method described by Shatton et  
2 al. (1983). TVC was calculated from the phosphate concentration using the conversion  
3  
4  
5  
6  
7 factor, 1 nmol phosphate is proportional to  $3.4 \times 10^7$  cells as determined by Findlay et al.  
8  
9  
10 (1989). Additionally, bovine serum albumin was used for construction of standard  
11  
12  
13 curves. The quantification of biofilm EPS was assayed in phenol sulfuric acid, as  
14  
15  
16 detailed by Frolund et al. (1996). The substrate samples were placed in glass reaction  
17  
18  
19 tubes. Subsequently, 1ml each of distilled water and 5% phenol were added to  
20  
21  
22 individual tubes. The tubes were mixed in a vortex mixer for 30 s. The volume of 5 mL  
23  
24  
25 concentrated sulfuric acid was added to each tube during the mixing process.  
26  
27  
28 Absorbance was measured at 485 nm after cooling. Glucose was used to construct  
29  
30  
31 standard curves for polysaccharide concentration. EP was extracted from the substrate  
32  
33  
34 samples by adding 1N NaOH and incubating at 55 °C for 2 h. Equal volumes of 1N HCl  
35  
36  
37 were added to each sample to neutralize the NaOH after cooling to room temperature  
38  
39  
40 (Ragusa et al., 2004). The solubilised protein was quantified using PIERCE (Rockford IL,  
41  
42  
43 USA) BCA Protein Assay Reagent Kit (Cat. No. 23227) according to the method specified  
44  
45  
46 by Lowry et al. (1951).

## 46 **2.5 Solid analysis**

47  
48  
49 Accumulated solids were detached from 5 g substrate samples using ultrasound  
50  
51  
52 equipment for 15 min with 100 mL phosphorus buffer ( $K_2HPO_4$ , 9.3 g/L;  $KH_2PO_4$ , 1.8 g/L)  
53  
54  
55 to form an accumulated solids solution (AS solution). Initially, the AS solution was  
56  
57  
58 manually divided into two 50 mL portions. The first 50 mL AS solution was dried at  
59  
60  
61

1  
2 105 °C for 24 h. Subsequently, the dry residue was burned at 550 °C for 15 min. The  
3  
4 weight difference between the final burned crucible and original clear crucible was  
5  
6  
7 estimated as the total inorganic matter (TIM) content. The weight difference of the  
8  
9 crucible before and after burning was estimated as the total organic matter content.  
10  
11  
12 The second 50 ml AS solution was filtrated using 0.45 µm filter membrane, and the  
13  
14 filtrate solution was analyzed using the same method described above to indicate  
15  
16 dissolved organic matter (DOM). The weight difference between total organic matter  
17  
18 (the first 50 ml AS solution) and DOM (the second 50 ml AS solution) was calculated as  
19  
20 insoluble organic matter (IOM). DOM and IOM were added to calculate the  
21  
22 accumulated total organic matter. The accumulation of total solids was the sum of TIM,  
23  
24 DOM, and IOM. Additionally, the total organic matter and total inorganic matter (TIM)  
25  
26 were added to represent the accumulated total matter.  
27  
28  
29  
30  
31  
32  
33  
34

## 35 **2.6 Statistical analyses**

36  
37  
38 One-way analysis of variance (ANOVA) at 95% confidence level ( $p < 0.05$ ) was used  
39  
40 to evaluate significant differences in pollutant removal efficiencies between the three  
41  
42 HSCWs. The performance patterns of biofilm growth and solid accumulation for the  
43  
44 HSCWs were analyzed using principal components analysis (PCA). XLStat Pro® (XLStat,  
45  
46 Paris, France) was used for plotting and data analyses in the present study.  
47  
48  
49  
50  
51

## 52 **3. Results and discussion**

### 53 **3.1 Water quality and pollutants removal**

54  
55  
56  
57  
58 The experiment site was located in a typical subtropical environment with  
59  
60  
61  
62  
63  
64  
65

1 maximum and minimum air temperature ranged of 22-36°C and 13-28°C, respectively,  
2  
3 during the whole experiment (Fig. 2). Along with the season changes from April to  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

maximum and minimum air temperature ranged of 22-36°C and 13-28°C, respectively, during the whole experiment (Fig. 2). Along with the season changes from April to September, the maximum and minimum air temperatures showed clearly improvement from approximately 25 °C to 30 °C and 17 °C to 25 °C, respectively. The influent water temperature also showed a similar tendency which increased from around 20°C to 26°C from April to June and then kept relative stable until September (Fig. 2). Additionally, the ORP values of effluent for the three HSCWs (CW1, CW3 and CW6) were not significantly different with an average of -100 mV. The 3 HSCWs also showed similar pH values in a range of 6.9-7.5 along the experiment (data are not shown).

Significantly higher pollutants removal abilities were continually observed in the multi-layer substrate configured CW6, followed by CW3, and the monolayer CW1 throughout the experiment (Fig. 3). The average removal efficiencies of COD, NH<sub>4</sub><sup>+</sup>-N, TN, and TP were about 70%, 78%, 62%, and 80% for CW6; 58%, 60%, 49%, and 63% for CW3; and 29%, 40%, 30%, and 41% for CW1, respectively. Generally, pollutants removal performance before June fluctuated notably and recorded slightly lower than average values for all the HSCWs than the corresponding values between June and September.

Our previous study had reported that multilayer substrate configuration enhanced pollutants removal in the HSCW in the year following system construction (Bai et al., 2016). The higher removal efficiencies were attributed to the multilayer configuration with larger size substrate set at the bottom that improved hydraulic

1 performance by reducing short circuit in the HSCWs. After three operational years, the  
2 same enhanced performance was observed in the present study, which indicated that  
3  
4 the optimized multilayer configuration can promote stable and positive effect on  
5  
6 pollutants removal. The corresponding values were slightly lower than values observed  
7  
8 three years ago, especially for CW1, which may be due to solid accumulation and clogging  
9  
10 (Blazejewski & Murat-Blazejewska, 1997; Morales et al., 2013). Additionally, higher  
11  
12 pollutants removal abilities after June may be due to higher temperature (Fig. 2). The  
13  
14 microorganisms responsible for COD and nitrogen removal function optimally in  
15  
16 relatively higher temperature conditions (Akratos & Tsihrintzis, 2007; Lv et al., 2016).  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26

### 27 **3.2 Biofilm development**

28  
29 Multilayer substrate configured HSCWs generally recorded higher concentrations  
30  
31 of TVC, EPS, and EP than the monolayer HSCW in samples acquired both from the front  
32  
33 and back parts (Fig. 4). The results indicated that multilayer configuration promoted  
34  
35 biofilm growth under better hydraulic performance in the HSCWs. Regarding  
36  
37 pollutants removal, organic matters and nitrogen were mostly degraded by substrate  
38  
39 attached biofilms (Lee et al., 2009; Lv et al., 2017). TVC represents the absolute  
40  
41 number of bacterial cells that contribute to pollutants degradation. Polymers are  
42  
43 mainly composed of polysaccharide (EPS) and protein (EP) and extracellular polymers  
44  
45 can trap, bind, and concentrate organic materials increasing their susceptibility to  
46  
47 bacterial biodegradation (Zhao et al., 2009). Thus, the superior biofilm amount in CW3  
48  
49 and CW6 supported improved pollutants removal performance, as shown in Fig. 3.  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

1  
2 Seasonal differences in the biofilm development were also clearly observed. The  
3  
4 concentrations of TVC, EPS, and EP showed distinct increase from April to July and  
5  
6  
7 September (Fig. 4a-c). The total TVC values in CW1, CW3, and CW6 showed similar  
8  
9 values in July and September with a range of  $3.6\text{-}3.9 \times 10^5$  CFU/g DM. However, in April,  
10  
11 CW1 exhibited a significantly lower total TVC value ( $1.5 \times 10^5$  CFU/g DM) compared to  
12  
13 CW3 ( $2.4 \times 10^5$  CFU/g DM) and CW6 ( $2.7 \times 10^5$  CFU/g DM). Similar tendencies were  
14  
15  
16 also observed for EPS and EP concentrations, which was probably due to warmer  
17  
18 temperature as well as active plant growth during July and September. Relatively  
19  
20  
21 higher temperatures are suitable for bacterial survival and biofilm growth, and  
22  
23  
24 presence of active plants provide more rhizosphere area for bacterial attachment  
25  
26  
27 (Stein & Hook, 2005; Wynn & Liehr, 2001).  
28  
29  
30

31  
32 Notably, the seasonal change in biofilm growth also presented a spatial  
33  
34 difference, especially for the samples collected at different depths. In April, the values  
35  
36 of TVC located in the top layer (A1 at depth of -10 cm) were clearly lower than the  
37  
38 deeper layers. However, A1 TVC increased significantly in July and September, which  
39  
40 may attributed to oxygen release from active plants and bacteria growth. The bacteria  
41  
42 located in the top layer of the HSCW was mainly aerobic, such as heterotrophic and  
43  
44 nitrifying bacteria (Samsó & García, 2013). These results are in agreement with  
45  
46  
47 Chazarenc et al. (2009) who measured higher bacterial cell count in aerated CWs with  
48  
49  
50 higher oxygen content. The TVC in the deeper positions of A2 and A3 were generally  
51  
52  
53 stable over the experimentation period, which may be mainly due to bacterial survival  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

1  
2 under anaerobic conditions were not dramatically change.  
3  
4

### 5 **3.3 Solids accumulation** 6

7  
8 All the HSCWs exhibited significant increase in total solid contents from April to  
9  
10 September for both front and back parts of the systems (Fig. 5). It is evident that the  
11  
12 increase rate and accumulated amount was higher in CW1, followed by CW3 and CW6.  
13  
14 This elevated accumulation could be a consequence of decrease in large void space  
15  
16 availability with time. Additionally, the amount of solid accumulated probably  
17  
18 increased due to biofilm development and solid trapping ability, which showed an  
19  
20 increasing tendency (Fig. 4). A comparison of the total solid accumulation between the  
21  
22 different HSCWs revealed that the multi-layer HSCWs had notably lower values than  
23  
24 the mono-layer CW. Optimized hydraulics with even water flow path may distribute  
25  
26 solid trapping possibility to a larger area in each HSCW. Moreover, the total solid  
27  
28 accumulation was generally always higher in the front part (In) compared to the back  
29  
30 part (Out) of the CWs. Chazarenc et al. (2009) also indicated that more solids would be  
31  
32 trapped in the front part of CWs when the influent begins flowing into the CWs and  
33  
34 majority of the solid would be trapped by the substrate.  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45

46  
47 Fig. 6 shows the accumulation of DOM, IOM, and TIM in each CW with time. TIM  
48  
49 was the main component of the total solids in all three CWs (72-85%), and the amount  
50  
51 increased slightly from April to September. Nevertheless, it was assumed that the TIM  
52  
53 did not play a crucial role in clogging. As confirmed by previous studies, clogging matter  
54  
55 typically consists of highly hydrated gels and sludge with inorganic and organic solids,  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65



1 and the porosity loss due to inorganic solid accumulation is very small (Llorens et al.,  
2  
3  
4 2009). This may be due to substrate micro-pore clogging by dead bacteria or growth of  
5  
6  
7 organic matter such as active biofilm inside.  
8  
9

10 Organic matter (OM) accumulations were predominantly composed of humic,  
11  
12 humin, and fulvic acids, derived from lignocellulosic humic compounds and plant  
13  
14 detritus. Nearly, 63-96 % of these organic matter fractions were relatively refractory  
15  
16 (Nguyen, 2000). Humic compounds are highly colloidal and amorphous with high  
17  
18 hydrophilic potential and physical binding properties. They can form complexes with  
19  
20 small quantities of biological fraction to form low-density gelatinous sludge with very  
21  
22 high water retention capacity. All these properties increase the organic matter's  
23  
24 potential to block big pores, which consequently act as a sieve and restricts flow  
25  
26 through of larger particulate solids (Hua et al., 2013). OM contents, including DOM and  
27  
28 IOM, also exert crucial effect on clogging, even though their contribution is less than 20%  
29  
30 of the total solid accumulation. As shown in Fig. 6, an increase in accumulated OM was  
31  
32 found from April to September for all CWs, while multi-layer configuration CW  
33  
34 exhibited lower OM content compared to the mono-layer CW. Lower OM contents in  
35  
36 CW6 exhibited better characteristics to offset clogging.  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48

49 For the contents of DOM and IOM, a higher proportion of the DOM was found in  
50  
51 multi-layer configuration CWs compared to the mono-layer CW, while mono-layer CW  
52  
53 had higher IOM proportion. IOM was composed of refractory matter, while DOM was  
54  
55 mainly composed of adsorbed or entrapped residual pollutants or soluble microbial  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

1  
2 products. Thus, DOM accumulation was assumed to be better than IOM accumulation  
3  
4 for clog prevention, because DOM could be flushed out at certain flow rates, while IOM  
5  
6 stayed for longer periods. Therefore, multi-layer CWs with higher DOM and lower IOM  
7  
8 contents seemed to be more beneficial than mono-layer CW to prevent clogging.  
9  
10

11  
12  
13       Regarding solid accumulation at different depths, most solids accumulated in the  
14  
15 bottom layers (A3 and B3) in CW1. In the multi-layer CWs, solid accumulation was  
16  
17 distributed more homogeneously among the three layers during all three months. In  
18  
19 the mono-layer CW, preferential paths often existed in the surface layer, which led to  
20  
21 higher solids accumulation in the middle and bottom layers, resulting in preferential  
22  
23 water flow through the surface layer (Osorio et al., 2007). Thus, the results proved that  
24  
25 a rational arrangement of substrates with increasing K values from the surface to  
26  
27 bottom was more successful in achieving even distribution and mitigate clogging.  
28  
29  
30  
31  
32  
33

### 34 35 **3.4 Patterns of solid accumulation and biofilm growth**

36  
37  
38       Solid accumulation (TIM, DOM, and IOM) and biofilm growth (TVC, EPS, and EP)  
39  
40 in different layers (A1, A2, and A3) of the three CWs (CW1, CW3, and CW6) under  
41  
42 different sampling seasons (April, July, and September) were analyzed using PCA to  
43  
44 assess performance patterns (Fig. 7). The first two principal components accounted for  
45  
46 64.94% of the variation. The PCA results were further marked to compare the systems  
47  
48 (Fig. 7a), season (Fig. 7b), and spatial differences (Fig. 7c). The performance patterns  
49  
50 for different CWs were generally separated, especially between the multilayer and  
51  
52 monolayer CWs (Fig. 7a). CW1, located closer to the positive direction of PC2 (up  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

1 direction), indicated high contribution of solid accumulation (IOM and TIM). Fig. 7b  
2 shows clearly separated groups in different sampling seasons. The samples from July  
3 and September were located closer to the positive direction of PC1 compared with  
4 April, which was highly contributed by the biofilm development (higher EP, TBC, and  
5 EPS concentrations). The performance patterns of the samples from different layers  
6 (A1, A2, and A3) generally overlapped and did not show clear group differences (Fig.  
7 7c). However, the difference were not found may due to the mixing up of different  
8 HSCWs, and cause the neglect influence of the performance patterns difference. This is  
9 supported by Fig. S1, which shows that spatially different patterns were generally  
10 found for all the HSCWs when each CW was separately analyzed. Thus, the PCA plots  
11 helped visualize the changes in performance patterns under different influencing  
12 factors in the present study. It can be concluded that the multilayer substrate  
13 configuration, season and sampling locations could significantly influence the solid  
14 accumulation and biofilm growth performance.

#### 41 **4. Conclusions**

- 42 ➤ Multilayer substrate configuration HSCWs can promote pollutants removal  
43 efficiencies after relatively long-term (3-year) operation compared to monolayer  
44 HSCW due to optimized hydraulics of the water flow path.
- 45 ➤ Lower solid accumulation was found in multi-layer HSCWs, was attributed to better  
46 use of its available bed space and even flow pattern, which prevented clogging in  
47 CWs.

- 1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36
- Multilayer configured HSCWs can delay clogging by providing higher biofilm development for organics removal and consequently lesser solid accumulations.
  - Principal component analysis strongly supported the visualization of performance patterns and showed that the multi-layer substrate configuration, season, and sampling locations significantly influence solid accumulation and biofilm growth.

### Acknowledgements

19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36

This work was funded by the National Natural Science Foundation of China (No. 51408147, 41404116, 51638006) and the Science research and technology development project of Guangxi (Guikehe1599005-2-2). It was further supported by the Guangxi Scientific Experiment Center of Mining, Metallurgy and Environment (KH2012ZD004) and the project of high level innovation team and standing scholar in Guangxi colleges and universities (002401013001).


### References

- 37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65
- Akratos, C.S., Tsihrintzis, V.A. 2007. Effect of temperature, HRT, vegetation and porous media on removal efficiency of pilot-scale horizontal subsurface flow constructed wetlands. *Ecological engineering*, **29**(2), 173-191.
- APHA. 2005. Standard methods for the examination of water and wastewater. *American Public Health Association (APHA): Washington, DC, USA*.
- Bai, S., Lv, T., Ding, Y., Li, X., You, S., Xie, Q., Brix, H. 2016. Multilayer Substrate Configuration Enhances Removal Efficiency of Pollutants in Constructed Wetlands. *Water*, **8**(12), 556.

- 1  
2 Blazejewski, R., Murat-Blazejewska, S. 1997. Soil clogging phenomena in constructed wetlands with  
3  
4 subsurface flow. *Water Science and Technology*, **35**(5), 183-188.  
5  
6
- 7 Brovelli, A., Carranza-Diaz, O., L. Rossi, D.A.B. 2011. Design methodology accounting for the effects of  
8  
9 porous medium heterogeneity on hydraulic residence time and biodegradation in horizontal  
10  
11 subsurface flow constructed wetlands. *ecological engineering*, **37**, 758–770.  
12  
13  
14  
15
- 16 Chazarenc, F., Gagnona, V., Comeau, Y., Brissona, J. 2009. Effect of plant and artificial aeration on solids  
17  
18 accumulation and biological activities in constructed wetlands. *ecological engineering*, **35**,  
19  
20 1005–1010.  
21  
22  
23
- 24 Cooper, D., Griffin, P., Cooper, P. 2005. Factors affecting the longevity of sub-surface horizontal flow  
25  
26 systems operating as tertiary treatment for sewage effluent. *Water Science and Technology*,  
27  
28 **51**(9), 127-135.  
29  
30  
31  
32
- 33 Findlay, R.H., King, G.M., Watling, L. 1989. Efficacy of phospholipid analysis in determining microbial  
34  
35 biomass in sediments. *Applied and Environmental Microbiology*, **55**(11), 2888-2893.  
36  
37  
38
- 39 Frolund, B., Palmgren, R., Keiding, K., Nielsen, P.H. 1996. Extraction of extracellular polymers from  
40  
41 activated sludge using a cation exchange resin. *Water Research*, **30**(6), 1749–1758.  
42  
43  
44
- 45 Hua, G.F., Li, L., Zhao, Y.Q., Zhue, W., Shen, J.Q. 2013. An integrated model of substrate clogging in  
46  
47 vertical flow constructed wetlands. *Journal of Environmental Management*, **119**, 67-75.  
48  
49  
50
- 51 Kadlec, R.H., Wallace, S. 2008. *Treatment wetlands*. CRC press.  
52  
53
- 54 Knowles, P., Dotro, G., Nivala, J., García, J. 2011. Clogging in subsurface-flow treatment wetlands:  
55  
56 Occurrence and contributing factors. *Ecological Engineering*, **37**(2), 99-112.  
57  
58  
59  
60  
61  
62  
63  
64  
65

- 1  
2 Lee, C.g., Fletcher, T.D., Sun, G. 2009. Nitrogen removal in constructed wetland systems. *Engineering in*  
3  
4 *Life Sciences*, **9**(1), 11-22.  
5  
6  
7 Llorens, E., Puigagut, J., García, J. 2009. Distribution and biodegradability of sludge accumulated in a  
8  
9 full-scale horizontal subsurface-flow constructed wetland. *Desalination and water treatment*,  
10  
11 **4**(1-3), 54-58.  
12  
13  
14  
15  
16 Lowry, O.H., Rosebrough, N.J., Farr, A.L., Randall, R.J. 1951. Protein measurement with the Folin phenol  
17  
18 reagent. *The Journal of Biological Chemistry*, **193**, 165–175.  
19  
20  
21  
22 Lv, T., Carvalho, P.N., Zhang, L., Zhang, Y., Button, M., Arias, C.A., Weber, K.P., Brix, H. 2017. Functionality  
23  
24 of microbial communities in constructed wetlands used for pesticide remediation: Influence of  
25  
26 system design and sampling strategy. *Water Research*, **110**, 241-251.  
27  
28  
29  
30  
31 Lv, T., Zhang, Y., Zhang, L., Carvalho, P.N., Arias, C.A., Brix, H. 2016. Removal of the pesticides imazalil and  
32  
33 tebuconazole in saturated constructed wetland mesocosms. *Water research*, **91**, 126-136.  
34  
35  
36  
37 Morales, L.P., Franco, M., Garvi, D., Lebrato, J. 2013. Influence of the stone organization to avoid clogging  
38  
39 in horizontal subsurface-flow treatment wetlands. *Ecological Engineering*, **54**, 136-144.  
40  
41  
42  
43 Nguyen, L.M. 2000. Organic matter composition, microbial biomass and microbial activity in gravel-bed  
44  
45 constructed wetlands treating farm dairy wastewaters. *Ecological Engineering*, **16**(2), 199-221.  
46  
47  
48  
49 Osorio, A.C., Puigagut, J., Segu, E., Vaello, N.r., Grane's, F., García, D., García, J. 2007. Solids  
50  
51 accumulation in six full-scale subsurface flow constructed wetlands. *Water research*, **41**,  
52  
53 1388-1398.  
54  
55  
56  
57 Ragusa, S., McNevin, D., Qasem, S., Mitchell, C. 2004. Indicators of biofilm development and activity in  
58  
59 constructed wetlands microcosms. *Water research*, **38**(12), 2865-2873.  
60  
61  
62  
63  
64  
65


- 1  
2 Samsó, R., García, J. 2013. Bacteria distribution and dynamics in constructed wetlands based on  
3  
4 modelling results. *Science of the Total Environment*, **461**, 430-440.  
5  
6  
7 Shatton, J.B., Ward, C., Williams, A., Weinhouse, S. 1983. A microcolorimetric assay of inorganic  
8  
9 pyrophosphatase. *Analytical biochemistry*, **130**(1), 114-119.  
10  
11  
12  
13 Stein, O.R., Hook, P.B. 2005. Temperature, plants, and oxygen: how does season affect constructed  
14  
15 wetland performance? *Journal of Environmental Science and Health*, **40**(6-7), 1331-1342.  
16  
17  
18  
19 Vymazal, J. 2009. Horizontal sub-surface flow constructed wetlands Ondřejov and Spálené Poříčí in the  
20  
21 Czech Republic–15 years of operation. *Desalination*, **246**(1-3), 226-237.  
22  
23  
24  
25 Wynn, T.M., Liehr, S.K. 2001. Development of a constructed subsurface-flow wetland simulation model.  
26  
27  
28 *Ecological Engineering*, **16**(4), 519-536.  
29  
30  
31 Zhao, L., Wei, Z., Wei, T. 2009. Clogging processes caused by biofilm growth and organic particle  
32  
33 accumulation in lab-scale vertical flow constructed wetlands. *Journal of Environmental Sciences*,  
34  
35  
36 **21**, 750-757.  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65



**Fig. 1** (a) Schematic diagram of the HSCWs and (b) substrate configuration of the three parallel HSCWs.




Figure 2




**Fig. 2** The daily maximum, minimum air temperature and influent water temperature during the whole experiment.


Figure 3




**Fig. 3** Removal efficiencies of (a) COD, (b) NH<sub>4</sub><sup>+</sup>-N, (c) TN, and (d) TP for monolayer (CW1) and multilayer (CW3, CW6) HSCWs during the experiment.



**Fig. 4** Development of total viable cell counts (TVC), extracellular polysaccharide (EPS), and extracellular protein (EP) at each sampling point in the mono-layer (CW1) and multi-layer CWs (CW3, CW6) in April, July, and September, 2016. A1/B1, A2/B2, and A3/B3 represent the sampling height of -10 cm, -30 cm, and -50 cm, respectively. 'In' and 'Out' represent sampling positions at the front and back parts of each HFCW, respectively.




**Fig. 5** Accumulation of total solid at each sampling point (summary for all layers) in monolayer (CW1) and multilayer CWs (CW3, CW6) in April, July, and September 2016. The dotted lines highlight the increasing tendency of total solid accumulation with time for each CW. 'In' and 'Out' represent the samples from front and back part of each CW, respectively.



**Fig. 6** Accumulated TIM, IOM, and DOM levels at each sampling point in (a) CW1, (b) CW3, and (c) CW6 during April, July, and September. A1, A2, and A3 represent the sampling height of -10 cm, -30 cm, and -50 cm in the front part, respectively. B1, B2, and B3 represent the sampling height of -10 cm, -30 cm, and -50 cm in the back part, respectively.

Figure 7



**Fig. 7** Principal component analysis of the performance patterns of biofilm development (TBC, EPS, and EP) and solid accumulation (DOM, IOM, and TIM) in CW1, CW3, and CW6. The same analysis results with different symbols are shown to compare (a) systems difference, (b) seasonal difference, and (c) spatial difference. The arrows in each plot represent the loading factors in the principal component analysis.

**Table 1**

Physicochemical parameters of the influent for the three HSCWs in the experiment.

Parameters	Values	Unit
pH	$7.3 \pm 0.3$	-
DO	$0.3 \pm 0.2$	mg/L
ORP	$-158 \pm 22$	mV
COD	$145 \pm 36$	mg/L
NH <sub>4</sub> <sup>+</sup> -N	$23 \pm 8$	mg/L
TN	$32 \pm 7$	mg/L
NO <sub>3</sub> <sup>-</sup> -N	$0.9 \pm 0.5$	mg/L
TP	$5 \pm 3$	mg/L

