



Aircraft Engineering and Aerospace Technology

A comprehensive review of vertical tail design

Fabrizio Nicolosi, Danilo Ciliberti, Pierluigi Della Vecchia, Salvatore Corcione, Vincenzo Cusati,

Article information:

To cite this document:

Fabrizio Nicolosi, Danilo Ciliberti, Pierluigi Della Vecchia, Salvatore Corcione, Vincenzo Cusati, (2017) "A comprehensive review of vertical tail design", Aircraft Engineering and Aerospace Technology, Vol. 89 Issue: 4, <https://doi.org/10.1108/AEAT-11-2016-0213>

Permanent link to this document:

<https://doi.org/10.1108/AEAT-11-2016-0213>

Downloaded on: 19 June 2017, At: 03:45 (PT)

References: this document contains references to 0 other documents.

To copy this document: permissions@emeraldinsight.com

The fulltext of this document has been downloaded 19 times since 2017*

Users who downloaded this article also downloaded:

(2017), "12th READ Conference & 6th SCAD Symposium", Aircraft Engineering and Aerospace Technology, Vol. 89 Iss 4 pp. - <https://doi.org/10.1108/AEAT-03-2017-0095>

(2017), "Practical problems of numerical optimization in aerospace sciences", Aircraft Engineering and Aerospace Technology, Vol. 89 Iss 4 pp. - <https://doi.org/10.1108/AEAT-11-2016-0201>

Access to this document was granted through an Emerald subscription provided by emerald-srm:480849 []

For Authors

If you would like to write for this, or any other Emerald publication, then please use our Emerald for Authors service information about how to choose which publication to write for and submission guidelines are available for all. Please visit www.emeraldinsight.com/authors for more information.

About Emerald www.emeraldinsight.com

Emerald is a global publisher linking research and practice to the benefit of society. The company manages a portfolio of more than 290 journals and over 2,350 books and book series volumes, as well as providing an extensive range of online products and additional customer resources and services.

Emerald is both COUNTER 4 and TRANSFER compliant. The organization is a partner of the Committee on Publication Ethics (COPE) and also works with Portico and the LOCKSS initiative for digital archive preservation.

*Related content and download information correct at time of download.

A comprehensive review of vertical tail design

Abstract

Purpose – This work deals with a comprehensive review of design methods for aircraft directional stability and vertical tail sizing. The focus on aircraft directional stability is due to the significant discrepancies that classical semi-empirical methods, as USAF DATCOM and ESDU, provide for some configurations, since they are based on NACA wind tunnel tests about models not representative of an actual transport airplane.

Design/methodology/approach – The authors performed viscous numerical simulations to calculate the aerodynamic interference among aircraft parts on hundreds configurations of a generic regional turboprop aircraft, providing useful results that have been collected in a new vertical tail preliminary design method, named VeDSC.

Findings – The reviewed methods have been applied on a regional turboprop aircraft. The VeDSC method shows the closest agreement with numerical results. A wind tunnel test campaign involving more than 180 configurations has validated the numerical approach.

Practical implications – The investigation has covered both the linear and the non-linear range of the aerodynamic coefficients, including the mutual aerodynamic interference between the fuselage and the vertical stabilizer. Also, a preliminary investigation about rudder effectiveness, related to aircraft directional control, is presented.

Originality/value – In the final part of the paper, critical issues in vertical tail design are reviewed, highlighting the significance of a good estimation of aircraft directional stability and control derivatives.

Introduction

The aircraft vertical tail is the aerodynamic surface that must provide sufficient directional equilibrium, stability, and control. Preliminary sizing is determined by critical conditions as minimum control speed with one engine inoperative (for multi-engine airplanes) and landing in strong crosswinds.

The **airborne minimum control** speed V_{MC} is the calibrated airspeed at which, when the critical engine is suddenly made inoperative, it is possible to maintain control of the airplane with that engine still inoperative and maintain straight flight with an angle of bank of not more than 5° (EASA, 2015). The airborne minimum control speed may not exceed 1.13 the reference stall speed. Thus, this parameter affects the take-off field length, which must be kept as low as possible otherwise the payload could be reduced when the aircraft is operating on short runways. The V_{MC} involves large rudder angles δ_r to keep a small angle of sideslip β . See Figure 1 left. This requires a certain vertical tail area for a given rudder effectiveness τ , which must be the highest possible to keep control authority at 25° or more of rudder deflection.