

Durham Research Online

Deposited in DRO:

16 March 2011

Version of attached file:

Other

Peer-review status of attached file:

Peer-reviewed

Citation for published item:

Gonzalez, G.J. and Mathias, S.A. (2011) 'Pressure buildup due to CO2 injection in brine aquifers.', Novel multi-scale methods for porous media flow II. International Centre for Mathematical Sciences (ICMS), Edinburgh, 14-16 February 2011.

Further information on publisher's website:

<http://www.icms.org.uk/workshops/mediaflow11>

Publisher's copyright statement:

Additional information:

Use policy

The full-text may be used and/or reproduced, and given to third parties in any format or medium, without prior permission or charge, for personal research or study, educational, or not-for-profit purposes provided that:

- a full bibliographic reference is made to the original source
- a [link](#) is made to the metadata record in DRO
- the full-text is not changed in any way

The full-text must not be sold in any format or medium without the formal permission of the copyright holders.

Please consult the [full DRO policy](#) for further details.

Pressure buildup due to CO₂ injection in brine aquifers

Gerardo Gonzalez^{1,2} and Simon A. Mathias¹

1. Department of Earth Sciences, Durham University (Email: s.a.mathias@durham.ac.uk)
2. ERC Equipoise Ltd, London, UK

Introduction

Maximum allowable injection rates of CO₂ are often identified as important bottlenecks in applied CCS chains. Injection rates are limited to ensure pressures do not exceed fracture pressures of reservoir formations. In this context, maximum injection rates of potential CO₂ storage sites are estimated using numerical reservoir simulators. Recently, Mathias et al. (2009; 2011) produced a semi-analytical solution for pressure-buildup estimation. However, derivation involved a number of simplifying assumptions including:

- 1) Negligible vertical pressure gradient.
- 2) Negligible capillary pressure.
- 3) Immiscible displacement.
- 4) Constant fluid properties.
- 5) Linear relative permeability.

This poster seeks to explore the implications of these assumptions by comparison of results from TOUGH2 ECO2N.

Approximate solution

$$p_D \approx \begin{cases} F_D(2/\gamma) - \frac{1}{2} \ln\left(\frac{x}{2\gamma}\right) - 1 + \frac{1}{\gamma}, & x \leq 2\gamma \\ F_D(2/\gamma) - \left(\frac{x}{2\gamma}\right)^{1/2} + \frac{1}{\gamma}, & 2\gamma < x < 2/\gamma \\ F_D(x), & x \geq 2/\gamma \end{cases}$$

$$F_D(x) \approx \begin{cases} \frac{1}{2\gamma} E_1\left(\frac{\alpha x}{4\gamma}\right), & t_D < t_{cD} \\ \frac{2t_D}{\alpha r_{cD}^2} - \frac{1}{\gamma} \left[\frac{3}{4} - \frac{1}{2} \ln\left(\frac{r_{cD}^2}{x t_D}\right) - \frac{(\alpha - 2)t_D}{2\gamma r_{cD}^2} \right], & t_D > t_{cD} \end{cases}$$

$$t_D = \frac{M_0 t}{2\pi(1-S_r)\phi H r_w^2 \rho_o} \quad \gamma = \frac{\mu_o}{k_r \mu_w} \quad r_{cD} = \frac{r_c}{r_w}$$

$$p_D = \frac{2\pi H \rho_o k_r k(p - p_o)}{M_0 \mu_o} \quad r_D = \frac{r}{r_w} \quad t_{cD} = \frac{\alpha r_{cD}^2}{2.246\gamma}$$

$$\alpha = \frac{M_0 \mu_o (c_r + c_w)}{2\pi(1-S_r)H \rho_o k_r k} \quad x = \frac{r_D^2}{t_D}$$

M_0 = mass injection rate [MT⁻¹]

t = time [T]

S_r = residual brine saturation [-]

ϕ = porosity [-]

μ_o = viscosity of CO₂ [ML⁻¹T⁻¹]

μ_w = viscosity of brine [ML⁻¹T⁻¹]

H = formation thickness [L]

r_w = well radius [L]

ρ_o = density of CO₂ [ML⁻³]

k_r = end-point CO₂ relative permeability [-]

k = permeability [L²]

p = pressure [ML⁻¹T⁻²]

p_o = initial pressure [ML⁻¹T⁻²]

c_r = compressibility of formation [M⁻¹L²T⁻²]

c_w = compressibility of brine [M⁻¹L²T⁻²]

r_c = formation radius [L]




Figure 1: Schematic diagram of model.




Figure 2: Schematic view of residual brine saturation.




Figure 3: Relative permeability functions.





Figure 4: Comparison of the approximate solution with output from TOUGH2 ECO2N. Approximate solution 1 uses fluid properties based on the initial pressure. Approximate solution 2 uses fluid properties based on the pressure given by Approximate solution 1 at $t_D = t_{cD}$.




Figure 5: Same as Figure 3a but with non-linear relative permeability. Spike disappears with increasing grid resolution.

Conclusions

Vertical pressure gradients and capillary pressure were found not to significantly affect pressure buildup for the scenarios studied. Similarly, providing fluid properties for the end conditions are used, dynamic variability in fluid properties were also found to have negligible effect. Miscibility was found to reduce pressure due to brine evaporation. Non-linearity in relative permeability leads to increases pressure. A spike in pressure during early times was found to be due to numerical errors. But consideration of Figure 6 raises an interesting problem.




Figure 6: Observed pressure from a CO₂ project injecting at ~ 6 kg/s. (from S. Hovorka, BEG).

Further reading

Mathias, SA, Hardisty, PE, Trudell, MR & Zimmerman, RW 2009. Approximate Solutions for Pressure Buildup During CO₂ Injection in Brine Aquifers. Transport in Porous Media 79(2): 265-284.