



POLITECNICO DI TORINO
Repository ISTITUZIONALE

Fast IRLS for sparse reconstruction based on gaussian mixtures

Original

Fast IRLS for sparse reconstruction based on gaussian mixtures / Ravazzi, Chiara; Magli, Enrico. - ELETTRONICO. - (2015), pp. 24-24. ((Intervento presentato al convegno International BASP Frontiers workshop 2015 tenutosi a Villars-sur-Ollon, Switzerland nel January 25 - 30, 2015.

Availability:

This version is available at: 11583/2623862 since: 2015-11-24T13:42:52Z

Publisher:

Published

DOI:

Terms of use:

openAccess

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

Fast IRLS for sparse reconstruction based on gaussian mixtures

Chiara Ravazzi and Enrico Magli

Dipartimento di elettronica e delle telecomunicazioni, Politecnico di Torino, Italia.

Abstract—The theory of compressed sensing has demonstrated that sparse signals can be reconstructed from few linear measurements. In this work, we propose a new class of iteratively reweighted least squares (IRLS) for sparse recovery. The proposed methods use a two state Gaussian scale mixture as a proxy for the signal model and can be interpreted as an Expectation Maximization algorithm that attempts to perform the constrained maximization of the log-likelihood function. Under some conditions, standard in the compressed sensing theory, the sequences generated by these algorithms converge to the fixed points of the maps that rule their dynamics. A condition for exact sparse recovery, that is verifiable a posteriori, is derived and the convergence is proved to be quadratically fast in a neighborhood of the desired solution. Numerical experiments show that these new reconstructions schemes outperform classical IRLS for ℓ_τ -minimization with $\tau \in (0, 1]$ in terms of rate of convergence and accuracy.

I. SPARSE RECOVERY VIA IRLS FOR ℓ_τ -MINIMIZATION

The basic principle of the compressed sensing theory is that a k -sparse signal $x^* \in \mathbb{R}^n$ (i.e., it has at most k nonzero entries) can be recovered from a smaller number $m \ll n$ of linear measurements $y = Ax^* \in \mathbb{R}^m$ than traditional sampling theory believed necessary [2]. The estimation of the sparsest signal, consistent with the observations, is an NP-hard problem. However, the constrained ℓ_τ -minimization with $\tau \in (0, 1]$, which is the convex or nonconvex surrogate problem, has been proposed in [3] as an appealing alternative for sparse recovery. It consists in selecting the element which is compatible with the observations which has minimal ℓ_τ -norm with $\tau \in (0, 1]$:

$$\min_{x \in \mathbb{R}^n} \|x\|_{\ell_\tau} \quad \text{s.t. } y = Ax. \quad (1)$$

Under certain assumptions on the sensing matrix A , it is known that (1) has a unique solution and it provides the desired solution x^* .

The minimization in (1) can be carried out by an iteratively reweighted least squares method (IRLS, [4]). More precisely, given an initial guess $x^{(0)}$, at each iteration the algorithm requires to solve a constrained weighted least-squares problem:

$$x^{(t+1)} = \arg \min_{y=Ax} \sum_{i=1}^n w_i^{(t)} x_i^2$$

with $w_i^{(t+1)} = ((\epsilon^{(t)})^2 + (x_i^{(t)})^2)^{\tau/2-1}$ and a suitable non-increasing sequence $\epsilon^{(t)}$. In particular, under certain assumptions, these methods have been proved to converge to x^* globally linearly fast when $\tau = 1$ and locally superlinearly fast with rate $2 - \tau$ for $\tau \in (0, 1)$.

Although classical IRLS algorithms appear very attractive for their simplicity, theoretical results guarantee the superlinear convergence only in a neighborhood of the desired solution. In fact, numerical results point out that exact recovery is achieved when τ is not too small (i.e. $\tau > 1/2$) and tends to be trapped in local minima when $\tau < 1/2$ [5]. Heuristic techniques to avoid local minima are currently object of study.

II. GSM BASED IRLS

We derive a new class of IRLS procedures for sparse recovery which outperform the classical procedures. More precisely, we model

the elements of the signal as a two state gaussian mixture (GSM, [1])

$$x_i^* = z_i \sqrt{\alpha} u_i + (1 - z_i) \sqrt{\beta} u_i$$

where u_i are identically and independently distributed (i.i.d.) zero mean Gaussians and z_i are i.i.d. Bernoulli variables with probability mass function $\mathbb{P}(z_i = 1) = 1 - p$, $p = k/n$, $\alpha \approx 0$, and $\beta \gg 0$. The combination of the considered model, used as a proxy for the sparsity assumption, with the maximum log-likelihood estimation provides a new alternative to select the sparsest vector consistent to the data. More precisely, we want to minimize

$$L(x, z, \alpha, \beta, \epsilon) = \sum_{i=1}^n \left[\frac{z_i x_i^2 + \epsilon^2/n}{2\alpha} + \frac{z_i}{2} \log \frac{\alpha}{1-p} + \frac{(1-z_i)x_i^2 + \epsilon^2/n}{2\alpha} + \frac{(1-z_i)}{2} \log \frac{\beta}{p} \right]. \quad (2)$$

subject to the constraint $y = Ax$. We design three iterative techniques: ML-based IRLS, EM-based IRLS, and K -EM based IRLS. These strategies can be interpreted as instances of the Expectation Maximization algorithm. After choosing some initial values for the mixture parameters, two updates are alternated: in the E-step, we use the current values for the parameters to estimate the signal x^* and to evaluate the posterior distribution $\mathbb{P}(z_i = 1)$ of the signal coefficients; in M-step we use these probabilities to re-estimate the mixture parameters α and β .

Besides the design of the algorithms, we prove that, under suitable conditions, the sequence of provided estimations converges to a fixed point of the map that rules their dynamics. Moreover, we derive conditions for exact recovery that are verifiable a posteriori. Finally, the algorithm turn out to be quadratically fast in a neighborhood of x^* . Numerical simulations validate our claims and show that these new procedures avoid local minima, outperforming classical IRLS for sparse recovery in terms of rate of convergence and sparsity-undersampling tradeoff.

REFERENCES

- [1] D. Baron, S. Sarvotham, and R. Baraniuk, "Bayesian compressive sensing via belief propagation," *Signal Processing, IEEE Transactions on*, vol. 58, no. 1, pp. 269–280, Jan 2010.
- [2] E. J. Candès, J. K. Romberg, and T. Tao, "Stable signal recovery from incomplete and inaccurate measurements," *Communications on Pure and Applied Mathematics*, vol. 59, no. 8, pp. 1207 – 1223, 2006. [Online]. Available: <http://dx.doi.org/10.1002/cpa.20124>
- [3] R. Chartrand, "Exact reconstruction of sparse signals via nonconvex minimization," *Signal Processing Letters, IEEE*, vol. 14, no. 10, pp. 707–710, Oct 2007.
- [4] I. Daubechies, R. DeVore, M. Fornasier, and C. S. Güntürk, "Iteratively reweighted least squares minimization for sparse recovery," *Comm. Pure Appl. Math.*, vol. 63, no. 1, pp. 1–38, Jan. 2010.
- [5] M. Fornasier, *Theoretical Foundations and Numerical Methods for Sparse Recovery*. Radon Series on Computational and Applied Mathematics, 2010.