



## Flood warning and monitoring system utilizing internet of things technology

Mohamad Syafiq Mohd Sabre<sup>1</sup>, Shahrum Shah Abdullah<sup>\*2</sup>, Amrul Faruq<sup>\*3</sup>

Malaysia-Japan International Institute of Technology (MJIIT), Universiti Teknologi Malaysia, Malaysia<sup>1,2,3</sup>  
Faculty of Engineering, Universitas Muhammadiyah Malang, Indonesia<sup>3</sup>

### Article Info

#### Keywords:

Flood Monitoring, Early Warning System, Internet of Things, Disaster Risk Reduction

#### Article history:

Received 30 July 2019  
Revised 19 September 2019  
Accepted 5 October 2019  
Published 30 October 2019

#### Cite:

Mohd Sabre, M.S, Abdullah, S.S, & Faruq, A. (2019). Flood Warning and Monitoring System Utilizing Internet of Things Technology. *Kinetik: Game Technology, Information System, Computer Network, Computing, Electronics, and Control*, 4(4). doi:<http://dx.doi.org/10.22219/kinetik.v4i4.898>

\*Corresponding author.

Shahrum Shah Abdullah, Amrul Faruq  
E-mail address:  
shahrum@utm.my, faruq@umm.ac.id

### Abstract

Flooding is one of the major disasters occurring in various parts of the world including Malaysia. To reduce the effect of the disaster, a flood warning and monitoring are needed to give an early warning to the victims at a particular place with high prone to flood. By implementing the Internet of Thing technology into the system, it could help the victim to get an accurate status of flood in real-time condition. This paper develops a real-time flood monitoring and early warning system using wireless sensor node at a high prone area of flood. This system is based on NodeMCU based technology integrated using Blynk application. The wireless sensor node can help the victims by detecting the water levels and rain intensity while giving an early warning when a flood or heavy rain occurs. The sensor node consists of ultrasonic sensors and rain sensor controlled by NodeMCU as the microcontroller of the system which placed at the identified flood area. Buzzer and LED started to trigger and alert the victim when the flood had reached a certain level of hazard. Data detected from the sensors are sent to the Blynk application via wireless connection. The victim will get to know the current status of flood and rain by viewing the interface and receiving a push notification that available in Blynk application via IOS or Android smartphones. The flood level's data sent to the email could help various organizations for further improvement of the system and flood forecasting purposes. As a test result had been conducted, it founds that this prototype can monitor, detect and give a warning with notification to the victim earlier before the occurrence of floods.

### 1. Introduction

Floods are among the most common and damaging disaster types in the world and affect the lives of millions of people worldwide annually. Floods and excessive rainfall are inevitable phenomena that can lead to massive loss of lives and infrastructure destruction. In Malaysia, flash flooding is a regular natural disaster that occurs during the monsoon season almost every year [1]. The Department of Irrigation and Drainage (DID), Malaysia has categorized floods into two categories that are flash floods and monsoon floods [2]. The difference between flash floods and monsoon floods were based on the time taken by the flow of the river to return to its normal position [3]. Flash floods suddenly occur without a warning that surprises people in their everyday lives [4]. Monsoon floods caused by the winds of the Northeast Monsoon occur between the months from November to March and the winds of the Southwest Monsoon from May to September [1].

The floods in December 2006 and January 2007 are also classified as the most damaging flood in Malaysia's history. The water level recorded during the floods reached 2,75 meters, the highest level since 1950. The mortality rate was 18, with more than 100,000 people evacuated during the disaster [3]. Many factors that might be taken from the above cases, such as problems with drainage systems, dam breaks, urbanization and environmental management, weather and pollution, but the one that will be highlighted in this paper is the problem of the early flood monitoring system.

The cost of flood damage is closely related to the warning time given before the occurrence of flood and this makes flood monitoring critical in reducing the cost of damages. Based on Sukeri Khalid et al, most of the people are agreed that the early warning system at Sultan Abu Bakar dam are not working in a good condition which caused a flash flood and about four people die and other property damages [5]. Hence, this shows that early flood monitoring is very important in Malaysia to avoid more victims and flood damages to occur. Based on Mary Anne M. Sahagun et al, [6] the importance of further studies in determining the water level in high-risk areas is consistent to warn the public about the potential rise in flood water level. In Malaysia, most flood cases rise more quickly and people have less time to evacuate and save their life and belongings. This is because some early flood alert systems are usually intended for the respective organizations and authorities [7].

When a flooding scenario occurs at a certain location, it will take time for them to reach as water rises rapidly. At the peak of the flood, there will be flooding in residential areas, public buildings and bridges that cause immediate damage. Lots of flood risk technologies have been developed over the last few decades to minimize the risk of flooding in inhabited areas. The Philippine government has now funded the Science and Technology Department's (DOST) NOAH project [8]. Automated Rain Gauges (ARG) and Water Level Monitoring Stations (WLMS) were installed along the main river basins (RBs) of the country. However, the NOAH project is still under development where some important information is not yet available on its website. This is a huge project that costly and needs a big spent of money for the maintenance and other work related to it.

One of the factors that contribute to the damages and loss of life when the flood occurs is poor flood monitoring system at a high prone area to flood. Poor flood monitoring can cause a disastrous effect to human and environment. Besides, victim cannot get accurate information on the current status and conditions before flood occurs in a short period of time. Accurate data need to be received by the victim quickly as the water level of flood rises rapidly. Lastly, a poor warning system of flood will lead to damages of livelihood and infrastructures.

The technology used to detect floods is now more accurate than the devices of the last decades. Unfortunately, an early warning system still showing some lacks of significant and difficult to alert all the people in the area [5]. Therefore, multiple of factors that need to be considered to develop a wireless sensor node system in order to avoid any failure occurred. The system should be low-cost, multifunctional, low-power and wireless sensor nodes of small size that work together to sense the environment, process the data and communicate wirelessly over a short distance [9]. Sensor is a device that measures and converts a physical quantity into a signal that an observer or an instrument can read [10]. Usually the sensors are used to monitor physical or environmental conditions, such as sound, pressure, pollutants, water level or motion at areas of interest. Accurate data from the sensors are important for many kinds of purposes including forecasting on flood event and for the future improvement of the system.

Study about Internet of Things (IoT) technology has gain popularity and becoming important for solving more problem in various disciplines, for example water monitoring system [11], flood monitoring [12] and weather station application [13]. Elias S. Manolakos et al had proposed a study on wireless sensor network application to detect hazard. The purpose of the study is to monitor and report the environmental status by physical parameters such as the temperature at a rate that can be adapted to current conditions so as not to waste energy and bandwidth [14]. Thinagaran Perumal et al [15] had proposed a study on the Internet of Things for water monitoring system. In their project, they detect on desired parameters by using water level sensor. They proved that when the water level reached at a certain point, the signal will be feed in real time to social network like Twitter. Besides, a cloud server is used to display the result in the dashboard. Priya J et al [16] had proposed a study on IoT based water level monitoring system to inform the user on water level of liquid prevent it from overflowing. The ultrasonic sensors is used to detect and compare the water level with the container depth. While Muthamil Selvan.S et al [17] had proposed a research on Automatic Water Level Indicator using Ultrasonic sensors and GSM Module. IoT describes a system consist of sensors that connect items in the physical world are via wireless or wired Internet connections. Here, things are interconnected without human intervention to automatically identify intended activities [18]. Today, the Internet has become an integral part of the lives of people, influencing almost every human being's for everyday activities. Due to the continuous effects of a wide community, the Internet of Things (IoT) is developing enormously every day.

Hence, in the field of flood disaster risk reduction in particular for early warning and monitoring system, an IoT application is needed to link the victim with the sensor node applied at a high prone area of flood via internet connection so that they will always keep updating on current situation more precisely. Due to the continuous effects of a wide community, the Internet of Things (IoT) is developing enormously every day. The IoT tends to have unlimited applications because in every sphere of life there seem to be unlimited needs. Therefore, with a low-cost and effective flood monitoring system, this paper present a prototype to help communities affected by flood in high prone areas by providing interactive and real-time information on the current water level and rain intensity with alert notifications by using Blynk Application. By applying an Internet of Thing could help victims to monitor the flood water level and rain intensity via the apps in smartphone together with the alerting system for incoming flood via the apps. A wireless sensor node connected with NodeMCU is used which consist of ultrasonic sensors and rain sensor to collect data and sent them via cloud to be viewed in Blynk application.

## 2. Research Method

In this study, flood monitoring system using wireless sensor node is developed to observe the status of flood which could alert people who were in the area frequently affected by floods in Selangor state, Malaysia. The system consists of a sensor node which detects the water level and rain intensity using an Ultrasonic Distance Sensor (HC-SR04) and rain sensor respectively. When the water level and rain intensity reaches a certain level of hazards, the device will generate an alarm system with three different colours of LEDs indicating three levels of detection for flood level in order to notify people on incoming flood in that area that could endanger their life.

Numerous types of ultrasonic sensors with significant differences in frequency and power consumption are available. The high-frequency ultrasonic sensors will have a sharper beam width and may detect obstacles in a longer range. Some of the new sensors also have the same detection range as previous models but less power consumption. The ultrasonic sensors must be able to detect obstacles or objects between 2cm and 50cm in this project. Since the entire system supply is taken out of the supply, less current consumption is crucial and must be capable of operating at low voltage. HC-SR04 meets this project's criteria for detecting the level of flood water after long research between the HC-SR04 and other ultrasonic sensors.

NodeMCU based technology that acts as the microcontroller of this system that attached with ultrasonic and rain sensors to form a wireless sensor node and placed at a high prone area of flood. When the sensors were triggered, all the data will be sent to Blynk application to be viewed on user's smartphone via the wireless connection. The integrated IoT architecture with Blynk application as it illustrated in Figure 1 [18][19]. At the same time, the data is stored in a CSV database. This data can be converted into excel form through email which could alert the local authority for further action once the level reached warning and critical level.

Two sensors are used as inputs to the NodeMCU and power supply of 5V is used to power up the system to function well. The ultrasonic distance sensor is used to detect the flood level at a high prone area of flood (maximum is 3m away from it). In this project, 40cm of distance from the ultrasonic sensors and the water level will trigger the buzzer and LED. The rain module sensor detects the rain intensity and develops a notification alert when raining heavily started. The scope of this project is focusing at a high prone area of flood in Selangor. The Blynk application provides an interactive and easy to access platform for user or victim to get accurate information on the incoming floods by displaying current condition of flood water level and rain intensity in real-time condition.




Figure 1. Blynk IoT-cloud Based Architecture [18] [19]

When there are changes in flood level, the graphs captured the data and change the measurements accordingly. So, when there is immediate change in the measurement, the buzzer and LEDs will turn on which act as alerting purposes. Blynk's alert notification also sent to the victims when the flood water level or rain intensity reached a certain point of hazard. From Figure 2, the flow chart explained the overall system and how it works. First, NodeMCU connected with the internet via Wifi connection. After the Blynk connection is established, ultrasonic sensors and rain sensor act as two different input of the system. When the water level rises, the system will continue to the next steps. Three processes when water level rises which are greater than 20%, greater than 40% and greater than 60% which trigger green, yellow and red LEDs respectively. Buzzer triggered with different frequency for every different process before sending the data to Blynk application. Besides, when the rain intensity rises, two processes occur which are greater than 60% and between 30% to 60%. All of these data are sent to Blynk application on user's smartphone. Finally, notifications via Blynk and email are sent to the user for alerting purposes.




Figure 2. Schematic Diagram of the Proposed Flood Warning and Monitoring System

Blynk was designed to remotely controlled hardware where data can be displayed, data stored and data monitored. The Blynk platform consists of three main stages which are Blynk cloud, Blynk apps and Blynk database as shown in Figure 3.



Figure 3. The Flow Database Via Blynk Apps

In this work, Blynk was used to create a flood monitoring system application for monitoring data from NodeMCU which connected with ultrasonic and rain sensors over the internet by using a smartphone. There will be LCD to display the level indicator (safety, warning and critical level) inside the Blynk’s interface. Next, the value display widget will display the flood’s level sense by ultrasonic sensors. Besides that, different LEDs light up according to the current level to indicate the current status of flood. Lastly, the history graph widget could track the flood’s level and save it into the database. Figure 4 shows the layout design of Blynk used in this work.




Figure 4. Schematic Diagram of Steps to Build Blynk Interface

In Figure 4, the step by step procedure for building the Blynk apps using a smartphone is illustrated. Users could install or download Blynk apps for android or iOS at Google plays store or app store. User needs to install Blynk library in the Arduino IDE library folder to interface with Arduino. The work for Arduino based application as it reported by the Authors [20]. Furthermore, open the apps on the smartphone after the installation is complete and create a new account to log in to a new project. The selected hardware is NodeMCU for this project and the type of communication is WiFi ESP8266. The authentication token must be obtained first to build a project. Once the authentication token is obtained by the user, the Blynk apps can be designed.




Figure 5. Completed System Blynk's Interface

Figure 5 shows the complete setup of Flood Monitoring System via Blynk application. An LCD display indicates flood detection on water level status which appear whether Safety level, Warning level or Critical level. Next, three LEDs that act as an indicator are displayed which triggered based on flood level status. Rain intensity level widget is added to display the rain intensity which acted as the first system's monitoring on rain before huge flood occurs. A flood level is displayed in cm unit and the system sends the alert notification and email to the victim continuously when the flood water level together with rain intensity reached certain level of hazard. For the user or victim that always used social media, this system was very useful as it can send the alert via Twitter so they will keep updating with the latest condition of flood at their place. At the lowest part of the interface shows a Super-chart widget which could display the graph of flood level in real time condition. All the widgets kept updating between each other that lead to the combination of very useful system to warn and monitor current flood condition at place with high prone of flood in Selangor State.

### 3. Results and Discussion

To test whether the prototype works accordingly, an experiment was conducted to test the measurement of water detected by wireless sensor node. Buzzer and LED started to trigger when the water level reached 10cm until it reach critical level (30cm) away from the ground, a notification sent to victim through Blynk and email. Rain sensor detects the rain intensity and sends an alert when rain heavily started. Based on flood level detected, it can be viewed in the database that was sent to the email. Figure 6 shows the flood level for every minute. The x-axis is corresponding to the time, while y-axis is corresponding to the flood level monitoring. Whereas Figure 7 shows the Flood level on Blynk application that can be viewed on the user's smartphone. In this information, x-axis represents for time, and y-axis represents for flood level. Figure 7 provides an easy access for the user to get an accurate reading on flood level in real time condition. The graph shows the flood level reading for every second.




Figure 6. Schematic Diagram of Steps to Build Blynk Interface




Figure 7. Flood Level Monitoring for Every Seconds in Blynk Apps

Figure 8 shows the reading of data sense from the ultrasonic sensors from the system in Blynk application. There are three mode displays on the screen of the smartphone. It displayed level of water either in safety, warning or critical level to alert victims in a high prone area of flood. The distance of the water is also displayed on the widgets which used LED as the indicator (green for safety, yellow for warning and red for critical). This history graph can be used to track the flood level in real time condition. There will be three states which are level 1, level 2 and level 3 to give alarm to the people. The data sensed by the sensor was displayed on the Blynk’s interface reflecting the level indicator as well as the distance.

Once the data being received, green LED and buzzer started to trigger when level 1 of flood level detected. Then, level 2 yellow LED will blink and buzzer triggered and lastly, at level 3 red LED turn on, as well as the buzzer. Once the water level reached 31cm, the system will send the alert notification to the user via email and Blynk push notification. Table 1 tabulates the range of level indicator that indicates the distance of sensor for safety purposes.



Figure 8. Flood Level Detection Monitoring in Blynk Apps

Table 1. Flood Level Categories based on Flood Detection

Flood Level (cm)	Level Indicator	Warning Signage
11 - 20	1	Safety
21 - 30	2	Warning
31 and above	3	Critical

### 3.1 Rain Sensor Data on Blynk’s Interface

Figure 9 shows the condition when the rain started to fall at the particular place. The level of rain intensity which is in green colour shows that the rain just started to fall. This indicates that the people who live nearby should alert as

they know their place will get a very disastrous disaster if the rain started heavily. "Rain Warning!!" notification is sent to the user for alerting purposes.

As stated in Figure 10, the rain intensity have reach a certain point that need to be consider by the victim who tend to face flood at their area. This is because, when the rain started to fall heavily, a higher tendency that a flood will occur at any time at that place. The system sends the notification "Raining Heavily, Please be Aware!!" as an alert purpose so that the victim will get notified at any times and anywhere when the rain started to fall heavily.



Figure 9. Low Rain Intensity Display




Figure 10. High Rain Intensity Display

Figure 11 shows the notifications sent to the victim's email regarding the water level which has reached a critical level. Therefore, victims will get to know the status of flood level precisely. Figure 12 (a) shows the side view of the prototype. From the above figure, a black box is used to place the microcontroller of the system which is NodeMCU integrated with sensors. An external 5V of power supply is used to power on the system. Figure 12 (b) shows an ultrasonic sensors is placed 50cm from the ground to detect the flood level in centimetre. Figure 12 (c) shows the top view of the prototype. From the above figure, rain sensor module is placed at the top of the system. This is because the rain sensor will detect the rain intensity that fall on it. Besides, three different LEDs are used to indicate the different of flood levels warning signage. A buzzer which is placed near the LEDs will trigger with different frequencies based on multiple warning signage and colours of LEDs.

Figure 13 shows the PC and smartphone for monitoring purposes. Users could get the data of the flood water level from ultrasonic sensors for every minute via email. Then, users could monitor the Blynk interface which is designed for monitoring purposes. A graph plotted the flood level in centimeter in Excel format. The data plotted are important for future work of the system especially in flood forecasting and other improvement of the system.




Figure 11. Notification Alert and Warning Sent by Blynk App




Figure 12. Low-Cost Prototype of Flood Warning and Monitoring System. (a) Side View, (b) Bottom View, (c) Top View




Figure 13. Monitoring Desk of Flood Warning System

#### 4. Conclusion

This study based on the development of a smart flood monitoring system using ultrasonic sensors with NodeMCU and Blynk application. The results offer flexibility, efficiency and low cost. Wireless sensor node based on Blynk platform is an ideal platform to monitor flash floods and also as early warnings. The working of a low-cost ultrasonic sensors and rain sensor integrated with NodeMCU are able to detect and provide efficient and accurate sensing data for monitoring and alerting purposes. Through the experiment conducted, it shows that this system can be used for detecting, monitoring and alerting the community in Selangor in case of flash flood.

In this study, the prototype is only uses a small scale of sensor detection within 50cm. In actual world, the system needs to detect the flood for about 1 to 2 meter if the system is placed at the riverside to detect flood. Besides, this prototype needs to be improved on the water resistant features so that when the rain started to fall, it cannot damage the sensor node. A proper installation need to be done so that the system can be put at any kind of surfaces to avoid it being fall down when water level rise up. Therefore, the system could help a huge number of victim's life whenever the future work could be done on it.

#### References

- [1] N. Weng Chan, "Increasing Flood Risk In Malaysia: Causes and Solutions," *Disaster Prev. Manag.*, Vol. 6, No. 2, Pp. 72–86, 1997. <https://doi.org/10.1108/09653569710164035>
- [2] A. H. Bin Sulaiman, "Flood Management in Malaysia," *Department of Irrigation and Drainage Systems*, 2009.
- [3] S. G. Durumin Iya, M. B. Gasim, M. E. Toriman, and M. G. Abdullahi, "Floods In Malaysia Historical Reviews, Causes, Effects and Mitigations Approach," *Int. J. Interdiscip. Res. Innov.*, Vol. 2, No. 4, Pp. 59–65, 2014.
- [4] I. Ruin, S. Anquetin, J. D. Creutin, E. Grunfest, and C. Lutoff, "Human Vulnerability to Flash Floods: Addressing Physical Exposure and Behavioural Questions," *London: Taylor & Francis Group*, 2009.

- [5] M. S. Khalid et al., "Failure to React Positively to Flood Early Warning Systems: Lessons Learned by Flood Victims from Flash Flood Disasters: The Malaysia Experience," *Int. J. Educ. Pedagog. Sci.*, Vol. 9, No. 5, Pp. 1406–1410, 2015.
- [6] Mary Anne M. Sahagun, J. C. Dela Cruz, and Ramon G. Garcia, "Wireless Sensor Nodes For Flood Forecasting Using Artificial Neural Network," in *International Conference on Humanoid, Nanotechnology, Information Technology, Communication and Control, Environment and Management (HNICEM)*, Pp. 1–6, 2017. <https://doi.org/10.1109/HNICEM.2017.8269462>
- [7] S. K. Subramaniam, V. R. Gannapathy, S. Subramonian, and A. H. Hamidon, "Flood Level Indicator and Risk Warning System for Remote Location Monitoring Using Flood Observatory System," *WSEAS Trans. Syst. Control*, Vol. 5, No. 3, Pp. 153–163, 2010.
- [8] J. G. Natividad and J. M. Mendez, "Flood Monitoring and Early Warning System Using Ultrasonic sensor," *IOP Conf. Ser. Mater. Sci. Eng.*, Vol. 325, No. 1, 2018. <https://doi.org/10.1088/1757-899X/325/1/012020>
- [9] M. I. K. Alfahadiwy and A. Suliman, "Flood Detection using Sensor Network and Notification Via SMS and Public Network," in *Student Conference On Research And Development (SCOReD 2011)*, 2011, Pp. 1–7.
- [10] A. R. A. Mohamed and W. G. Wei, "Real Time Wireless Flood Monitoring System Using Ultrasonic Waves," *Int. J. Sci. Res.*, Vol. 3, No. 8, Pp. 100–103, 2014.
- [11] P. Damor and K. J. Sharma, "IoT based Water Monitoring System: A Review," *Int. J. Adv. Eng. Res. Dev.*, Vol. 4, No. 6, Pp. 1–6, 2017.
- [12] D. Swathi, S. Snehaa, R. Ragapriya, and P. Priyanka, "IoT Based Flood Monitoring Using Artificial Neural Network," *Int. J. Innov. Res. Technol.*, Vol. 4, No. 9, Pp. 348–353, 2018.
- [13] R. K. Kodali and S. Mandal, "IoT Based Weather Station," in *International Conference on Control, Instrumentation, Communication and Computational Technologies*, Pp. 680–683, 2016. <https://doi.org/10.1109/ICCICCT.2016.7988038>
- [14] E. S. Manolakos, E. Logaras, and F. Paschos, "Wireless Sensor Network Application for Fire Hazard Detection and Monitoring," in *International Conference on Sensor Applications, Experimentation and Logistics*, Pp. 1–15, 2009. [https://doi.org/10.1007/978-3-642-11870-8\\_1](https://doi.org/10.1007/978-3-642-11870-8_1)
- [15] T. Perumal, M. N. Sulaiman, and C. Y. Leong, "Internet of Things (IoT) enabled Water Monitoring System," in *Global Conference on Consumer Electronics*, Pp. 86–87, 2015. <https://doi.org/10.1109/GCCE.2015.7398710>
- [16] P. J and S. Chekuri, "Water Level Monitoring System Using IoT," *Int. Res. J. Eng. Technol.*, Vol. 4, No. 12, Pp. 1813–1817, 2017.
- [17] M. Selvan, A. Roy, K. P. Singh, and A. Kumar, "Automatic Water Level Indicator Using Ultrasonic sensor and GSM Module," *Int. J. Adv. Res. Innov. Ideas Educ.*, Vol. 4, No. 5, Pp. 261–269, 2018.
- [18] P. Jesani, T. J. Raval, and karishma A. Chaudhary, "A Review On IoT Based Smart Home Using Blynk Framework," *Int. J. Adv. Res. Innov. Ideas Educ.*, Vol. 3, No. 5, Pp. 624–632, 2017.
- [19] N. A. Z. M. Noar and M. M. Kamal, "The Development of Smart Flood Monitoring System Using Ultrasonic sensor with Blynk Applications," in *International Conference on Smart Instrumentation, Measurement and Application*, Pp. 1–6, 2017. <https://doi.org/10.1109/ICSIMA.2017.8312009>
- [20] B. V. Raju, "An Automatic Form Monitoring System Using Arduino and Wireless Sensor Networks," *Int. J. Innov. Res. Sci. Eng. Technol.*, Vol. 6, No. 7, Pp. 14777–14785, 2017. <http://dx.doi.org/10.15680/IJRSET.2017.0607318>

