

A large synoptic dataset of coastal *in situ* observations

Francken Frederic¹, Michael Fettweis¹, Dries Van den Eynde¹, Matthias Baeye¹, Vera Van Lancker¹, Joan Backers², Kevin Hindryckx² and Lieven Naudts²

Management Unit of the North Sea Mathematical Model (MUMM), Royal Belgian Institute of Natural Sciences (RBINS)

¹ MUMM-SUMO group, Gulledele 100, 1200 Brussels, Belgium
E-mail: F.Francken@mumm.ac.be

² MUMM-Measuring Services, 3de en 23ste Linierregimentsplein, 8400 Ostend, Belgium

Since the beginning of 2004 MUMM has performed a series of moorings in the Belgian Coastal Zone with a tripod or benthic lander, equipped with a series of oceanographic sensors. Current meters such as an Acoustic Doppler Profiler (ADP) and an Acoustic Doppler Velocimeter (ADV), a CT-sensor capable of measuring temperature and salinity, optical (OBS) and acoustic backscatter sensors (ADP and ADV) to measure suspended sediment concentration, a LISST 100 suspended particle sizer, a passive Cetacean monitoring device (C- PoD, Haelters *et al.*, 2012) and a passive sampling device for chemical monitoring (Monteyne *et al.*, 2013) have ever since been moored for more than 1750 days. From autumn 2009 a permanent coastal observatory has been installed at MOW1, located to the west of the entrance to the Zeebrugge harbor (Backers *et al.*, 2013). Other moorings have been carried out at more offshore locations, such as the Kwintebank, Gootebank, MOW0 and the offshore windmill farms and a very nearshore location (Blankenberge). The data collected have increased our understanding of cohesive sediment dynamics in response to tidal and wind-driven flow and this during both good and bad weather conditions and from short (turbulence) to long-term scales (seasonal variations).

The instruments have already recorded several GB worth of data files, but the data need to be processed before they can lead to a large synoptic dataset. This processing includes the transformation from a binary file to a readable ASCII format and is done by proprietary software. The subsequent step consists of the actual processing of the data, the quality control to identify instrument failure or biofouling and calculation of derivative parameters (such as bottom shear stress, turbulent kinetic energy and settling velocity). For this goal a series of MatLab scripts have been created which automate the task. Datasets will be made available through the BMDC website: <http://www.mumm.ac.be/datacentre/>.

References

- Backers J., K. Hindryckx, L. Naudts, M. Fettweis, M. Baeye, F. Francken, D. Van den Eynde and V. Van Lancker. 2013. The coastal observatory near MOW1: Technical aspects. Book of Abstracts VLIZ Young Marine Scientists' Day, 15 February 2013, BruggeVLIZ Special Publication 63:11.
- Haelters J., W. Van Roy, L. Vigin and S. Degraer. 2012. The effect of pile driving on harbour porpoises in Belgian waters. p. 127-143; *In*: Degraer S, R. Brabant & B. Rumes (Eds). Offshore wind farms in the Belgian part of the North Sea. RBINS-MUMM.
- Monteyne E, P. Roose and C. Janssen. Application of a silicone rubber passive sampling technique for monitoring PAHs and PCBs at three Belgian coastal harbours. *Chemosphere*. (in press).