



La Science à l'œuvre pour le
at work for Canada

NRC Publications Archive Archives des publications du CNRC

Polypropylene fibers nanocomposite: Properties, Structure and Process Parameters

Trudel-Boucher, David; Aji, Abdellah; Denault, Johanne

NRC Publications Record / Notice d'Archives des publications de CNRC:

<http://nparc.cisti-icist.nrc-cnrc.gc.ca/npsi/ctrl?action=rtdoc&an=11708240&lang=en>

<http://nparc.cisti-icist.nrc-cnrc.gc.ca/npsi/ctrl?action=rtdoc&an=11708240&lang=fr>

Access and use of this website and the material on it are subject to the Terms and Conditions set forth at

http://nparc.cisti-icist.nrc-cnrc.gc.ca/npsi/jsp/nparc_cp.jsp?lang=en

READ THESE TERMS AND CONDITIONS CAREFULLY BEFORE USING THIS WEBSITE.

L'accès à ce site Web et l'utilisation de son contenu sont assujettis aux conditions présentées dans le site

http://nparc.cisti-icist.nrc-cnrc.gc.ca/npsi/jsp/nparc_cp.jsp?lang=fr

LISEZ CES CONDITIONS ATTENTIVEMENT AVANT D'UTILISER CE SITE WEB.

Contact us / Contactez nous: nparc.cisti@nrc-cnrc.gc.ca.





National Research
Council Canada


Conseil national
de recherches Canada

Canada

IMI 2009-119936-G
CNRC 52351




Objectives



Overview

- **Experimental Procedure**
 - Material
 - Nanocomposite formulation
 - Fibers fabrication
 - Consolidation
- **Results**
 - Fibers characterization
 - Clay distribution
 - Consolidation
 - Voids distribution
 - Mechanical properties
- **Conclusions**



Overview

- **Experimental Procedure**
 - Material
 - Nanocomposite formulation
 - Fibers fabrication
 - Consolidation
- **Results**
 - Fibers characterization
 - Clay distribution
 - Consolidation
 - Voids distribution
 - Mechanical properties
- **Conclusions**




Nanocomposite formulation and fiber fabrication

Formulation:

Polypropylene
+
Clay platelets
+
Maleic anhydride grafted polypropylene
↓
Nanocomposite



Fiber extrusion:



- Fibers extruded at 220°C
- Draw ratio was defined as the ratio of collecting speed and feeding speed of the fibre

Consolidation principle

- **Partially melt the oriented fibers to create a matrix phase...**
 - One fraction of the material remain oriented to provide good mechanical properties
 - The melted fraction of the fibers becomes the matrix phase
- ↳ Good fiber/matrix interface property because of chain continuity
- ↳ Narrow temperature window



Consolidation

- **Two different procedures:**
 - Unidirectional laminates
 - Reference plates
- **Unidirectional laminates:**
 - Compression molding using aluminum tooling
 - Fibers aligned manually
 - 42 grams for 2-mm thick laminates
 - Parameters:
 - Pressure: 2.4 MPa (350 psi)
 - Temperatures: 160-167°C
 - Holding time: 5-15 minutes



Consolidation

- **Two different procedures:**


- Unidirectional laminates
- Reference plates



- **Reference plates:**

(Remove any possible orientation effect)

- Cut fibers (25.4 mm) randomly oriented
- Compression molding using a spacer frame to prevent excessive flowing
- Molding parameters:
 - Temperatures: 180°C
 - Holding time: 15 minutes



Overview


- **Experimental Procedure**

- Material
 - Nanocomposite formulation
 - Fibers fabrication
- Consolidation

- **Results**


- Fibers characterization
 - Clay distribution
- Consolidation
 - Voids distribution
 - Mechanical properties

- **Conclusions**




Clay distribution

- Preferential alignment of the clay platelets is observed
- Clay platelets not completely exfoliated \Rightarrow aggregates can be observed



Overview

- **Experimental Procedure**
 - Material
 - Nanocomposite formulation
 - Fibers fabrication
 - Consolidation
- **Results**
 - Fibers characterization
 - Clay distribution
 - Consolidation
 - Voids distribution
 - Mechanical properties
- **Conclusions**



Reference Plates


- **Consolidation**
 - Fiber pattern erase
 - Randomly distributed voids

- **Mechanical properties**

	Flexural Modulus (GPa)	Maximum Flexural Stress (MPa)
PP	1.84	60.1
PPNC	1.84	61.5


Flexural modulus: up 12% for PPNC

Maximum Flexural stress: no change




Void Distribution

- Consolidation temperature of 165°C
 - Holding time: 5 minutes
 - Large porosities between the fibers
 - ⇒ Insufficient resin melting
 - Holding time: 15 minutes
 - Small voids between the fibers
 - ⇒ significant improvement of the consolidation




Mechanical Properties

- **Flexural Modulus**
 - **Nanocomposite:**
 - Longitudinal direction:
 - Up 40% compared to randomly oriented
 - Up 12% compared to oriented PP




Mechanical Properties

- **Flexural Modulus**
 - **Nanocomposite:**
 - Longitudinal direction:
 - Up 40% compared to randomly oriented
 - Up 12% compared to oriented PP
- ⇒ Orientation and nanoparticles yield better results



Mechanical Properties


- **Maximum Flexural Stress**
 - **Nanocomposite:**
 - Longitudinal direction:
 - Up 30% compared to randomly oriented
 - Similar to oriented PP



Mechanical Properties

- **Maximum Flexural Stress**
 - **Nanocomposite:**
 - Longitudinal direction:
 - Up 40% compared to randomly oriented
 - Similar to oriented PP

- ⇒ Orientation gives better results
- ⇒ Addition of nanoparticles did not result in significant improvement



Conclusions and Future works

- **Polymer Fibers**
 - Significant improvement in mechanical properties
 - Better formulation will be used
 - Should high performance polymer be used?
- **Consolidation**
 - Very narrow processing window
 - Void content should be reduced
 - Promising mechanical properties
 - 40% improvement compared to randomly oriented fibers